

07.ISBI19_notebook

January 6, 2021

1 Non cartesian sampling: SPARKLING imaging

We explore the performance of SPARKLING (*Spreading projection Algorithm for Rapid K-space sampLING*) as non-Cartesian imaging technique. We do not actually provide the code of this algorithm but instead upload result files containing trajectories generated from the previous *radial in-out* initialization. For details, see the recently published paper: Lazarus et al, “SPARKLING: variable-density k-space filling curves for accelerated T_2^* -weighted MRI”, Magn Reson Med 2019; 81:3643:3661.

- Authors: Philippe Ciuciu (philippe.ciuciu@cea.fr)
- Date: 04/02/2019
- Target: [ISBI'19 tutorial](#) on **Recent advances in acquisition and reconstruction for Compressed Sensing MRI**
- **Revision:** 01/06/2021 for ATSI MSc hands-on session at Paris-Saclay University.

```
[6]: #DISPLAY T2* MR IMAGE
%matplotlib inline

import numpy as np
import os.path as op
import os
import math ; import cmath
import matplotlib
import matplotlib.pyplot as plt
import sys

from mri.operators import NonCartesianFFT
from mri.operators.utils import convert_locations_to_mask, \
    gridded_inverse_fourier_transform_nd
from pysap.data import get_sample_data

from skimage import data, img_as_float, io, filters
from modopt.math.metrics import ssim

mri_img = get_sample_data('2d-mri')
img_size = mri_img.shape[0]
```

```
plt.figure()
plt.title("T2* axial slice, size = {}".format(img_size))
if mri_img.ndim == 2:
    plt.imshow(mri_img, cmap=plt.cm.gray)
else:
    plt.imshow(mri_img)
plt.show()
```

<IPython.core.display.Javascript object>

<IPython.core.display.HTML object>

```
[7]: from scipy.io import loadmat

cwd = os.getcwd()
dirmg_2d = op.join(cwd, "..", "data")

k_spark = loadmat(op.join(cwd, "..", "
    ↳ "data", "samples_SPARKLING_N512_nc34x3073_OS1.mat"))

k_spark_vec = k_spark['samples']

Kmax = np.amax(k_spark_vec)
#print(Kmax)

k_spark_vec = k_spark_vec*1/(2*np.pi*Kmax)

#save in npz format in the outdir directory
outdir = op.join(cwd, "..", "output")
filename_traj = "sparkling_radial_N" + str(img_size) + ".npz"
outfile = op.join(outdir, filename_traj)
np.savez(outfile, k_spark_vec)

k_spark = plt.figure(figsize=(7,7))
plt.scatter(k_spark_vec[:,0], k_spark_vec[:,1], marker = '.', s=0.1)
plt.grid()
#Figure layout

unit = 1/4
tick = np.arange(-0.5, 0.5 + unit, unit)

label = [r"$-\frac{1}{2}$", r"$-\frac{1}{4}$", r"$0$", r"$+\frac{1}{4}$", "
    ↳ r"$+\frac{1}{2}$"]

plt.xticks(tick/np.pi, labels = label, fontsize = 16) ; plt.yticks(tick/np.
    ↳ pi, labels = label, fontsize = 16)
```

```
plt.xlabel(r"$k_x$", fontsize = 22) ; plt.ylabel(r"$k_y$", fontsize = 22)
plt.title("K-space sampling, spiral in-out initialization",fontsize = 18)
plt.show()
```

1280.0

```
<IPython.core.display.Javascript object>
```

```
<IPython.core.display.HTML object>
```

```
[9]: data=convert_locations_to_mask(k_spark_vec, mri_img.shape)
fourier_op = NonCartesianFFT(samples=k_spark_vec, shape=mri_img.shape,
                             implementation='cpu')
kspace_obs = fourier_op.op(mri_img.data)
```

```

NameError                                Traceback (most recent call
↳ last)

<ipython-input-9-46089bf0f5cd> in <module>
    1 data=convert_locations_to_mask(k_spark_vec, mri_img.shape)
    2 fourier_op = NonCartesianFFT(samples=k_spark_vec, shape=mri_img.
↳ shape,
----> 3                                implementation='cpu')
    4 kspace_obs = fourier_op.op(mri_img.data)

~/work/code/git/pysap-mri/mri/operators/fourier/non_cartesian.py in
↳ __init__(self, samples, shape, implementation, n_coils, **kwargs)
    550         if implementation == 'cpu':
    551             self.implementation = NFFT(samples=samples, shape=shape,
--> 552                                     n_coils=self.n_coils)
    553         elif implementation == 'cuda' or implementation == 'opencl':
    554             self.implementation = NUFFT(samples=samples, shape=shape,

~/work/code/git/pysap-mri/mri/operators/fourier/non_cartesian.py in
↳ __init__(self, samples, shape, n_coils)
    105         # TODO Parallelize this if possible
    106         self.nb_coils = n_coils

```

```
--> 107         self.plan = pynfft.NFFT(N=shape, M=len(samples))
      108         self.plan.x = self.samples
      109         self.plan.precompute()
```

NameError: name 'pynfft' is not defined

```
[10]: grid_space = np.linspace(-0.5, 0.5, num=mri_img.shape[0])
      grid2D = np.meshgrid(grid_space, grid_space)
      grid_soln = gridded_inverse_fourier_transform_nd(k_spark_vec, kspace_obs,
                                                         tuple(grid2D), 'linear')

      plt.imshow(np.abs(grid_soln), cmap='gray')
      # Calculate SSIM
      base_ssim = ssim(grid_soln, mri_img)
      plt.title('Gridded Solution\nSSIM = ' + str(base_ssim))
      plt.show()
```

```

      □
      ↪ -----
      ↪
      NameError                                Traceback (most recent call
      ↪ last)

      <ipython-input-10-336799777e9e> in <module>
          1 grid_space = np.linspace(-0.5, 0.5, num=mri_img.shape[0])
          2 grid2D = np.meshgrid(grid_space, grid_space)
      ----> 3 grid_soln = gridded_inverse_fourier_transform_nd(k_spark_vec,
      ↪ kspace_obs,
          4
      ↪ 'linear')
          5 plt.imshow(np.abs(grid_soln), cmap='gray')
```

NameError: name 'kspace_obs' is not defined

```
[11]: # fista rec using PySAP (branch pogm_addition: https://github.com/
      ↪ zaccharieramzi/pysap/tree/pogm\_addition)

      from modopt.opt.linear import Identity
      from modopt.opt.proximity import SparseThreshold, LinearCompositionProx
      from mri.numerics.fourier import NFFT
      from pysap import Image
      from mri.numerics.gradient import GradAnalysis2
      from mri.numerics.linear import WaveletN
```

```

from mri.numerics.reconstruct import sparse_rec_pogm
from mri.numerics.utils import convert_mask_to_locations
from modopt.math.metrics import ssim

## ops init
kspace_loc = convert_mask_to_locations(k_spark_vec)
linear_op = WaveletN(
    nb_scale=4,
    wavelet_name="db4",
    padding_mode="periodization",
)


fourier_op = NFFT(
    samples= k_spark_vec * np.pi,
    shape= mri_img.shape,
)

##compute the kspace data
kspace_data_nfft = fourier_op.op(mri_img)

## now back to ops
gradient_op = GradAnalysis2(
    data=kspace_data_nfft,
    fourier_op=fourier_op,
)

# define the proximity operator
prox_op = LinearCompositionProx(
    linear_op=linear_op,
    prox_op=SparseThreshold(Identity(), 0.05, thresh_type="soft"),
)

if 1:
    ## run pogm' (ie POGM with restart)
    x_final, costs, metrics = sparse_rec_pogm(prox_op=prox_op,
    ↪linear_op=Identity(), gradient_op=gradient_op,
    max_nb_of_iter=100, metric_call_period=20)

pogm_rec = np.abs(x_final)
img_rec = Image(data=pogm_rec)





ssim_pogm = ssim(mri_img, pogm_rec)
ssim_pogm = float(round(abs(ssim_pogm),3))

```

```
plt.figure()
plt.title('Restored image (POGM) : SSIM = ' + str(ssim_pogm))
plt.imshow(pogm_rec, cmap='gray')
plt.show()
```

WARNING: Making input data immutable.

100% (100 of 100) |#####| Elapsed Time: 0:00:34 Time: 0:00:34

<IPython.core.display.Javascript object>

<IPython.core.display.HTML object>