

Warm-up: Basic deterministic under-sampling

In this first notebook, we start with simple deterministic under-sampling using low-freq and high-freq only masks. Hence we want to generate a sampling mask $\Omega \in \{0,1\}^N$ such that $y = F_{\Omega}x$ where $x \in \mathbb{R}^N$ is the original image. The data y is then corrupted by additive noise b :

$$y = F_{\Omega}x + b$$

where b is a complex-valued circular Gaussian noise of variance σ^2 and $F_{\Omega} = QF$ in this Cartesian setting (i.e. sampling on the grid). We consider:

1. a low-frequency Cartesian mask Ω is defined by the central lines of k -space.
2. a low-frequency Cartesian mask Ω is defined by a square box in k -space centered at $(k_x, k_y) = (0, 0)$.
3. a high-frequency Cartesian mask Ω is defined as the complementary set of the lines defined in 1)
4. a high-frequency Cartesian mask Ω is defined as the complementary set of the box defined in 2)

Based on these masks we generate the corresponding measured data from a reference MR image and finally perform Cartesian image reconstruction \hat{x} from the under-sampled data y as follows:

$$\hat{x} = \hat{F}^* y$$

where \hat{F}^* is the zero-filled inverse Fourier transform (ifft).

- Author: Philippe Ciucci (philippe.ciucci@cea.fr)
- Date: 04/01/2019
- Target: [ISBI'18 tutorial](#) on Recent advances in acquisition and reconstruction for Compressed Sensing MRI
- Revision: 01/05/2021 for ATST MSC hands-on session at Paris-Saclay University.

```
In [70]: %DISPLAY BRAIN PHANTOM
%matplotlib inline
import sys
import os.path as op
import os
import math
import cmath
import numpy as np


import matplotlib.pyplot as plt

from skimage import data, io

# get current working dir
cwd = os.getcwd()
#cwd= "/P"
dirimg_2d = op.join(cwd, ".../data")
img_size = 512 #256
FOV = 0.2 #field of view in m
pixelSize = FOV/img_size


# load data file corresponding to the target resolution
filename = "BrainPhantom6.png" % img_size
mri_filename = op.join(dirimg_2d, filename)
mri_img = io.imread(mri_filename)

plt.figure()
plt.title("Brain Phantom, size = %s" % img_size)
if mri_img.ndim == 2:
    plt.imshow(mri_img, cmap=plt.cm.gray)
else:
    plt.imshow(mri_img)
plt.title("Original brain image")
plt.show()
#plt.close()
```



```
In [71]: # Plot Noisy image
new_img = np.copy(mri_img.astype('float64'))
new_img += np.random.randn(*mri_img.shape) * 10.
#print(mri_img.shape)

if 1:
    plt.figure()
    plt.imshow(new_img, cmap='Greys_r')
    plt.title("Noisy image")
    plt.show()
```



- To start up, the objective is to construct a low-frequency sampling mask that consists of the central k -space lines
- Fourier transform the reference MR image to compute k -space data, add zero-mean Gaussian complex-valued noise
- Mask the data using the above defined mask
- Next, perform zero-filled MR image reconstruction from masked k -space data
- Study the impact of the number of lines in the mask on the final image quality

```
In [72]: # Generate trivial Cartesian sampling masks
img_size = 512

mask="low_res"
factor_ctr = 8

#Objective: construct a k-space mask that consists of the central lines
# 0 entries: points not sampled, 1 entries: points to be sampled
# Initialize k-space with 0 everywhere and then place the "1" appropriately
kspace_masklines = np.zeros((img_size,img_size), dtype="float64")

low_res_size = img_size // factor_ctr + 1
idx_vec = np.linspace(img_size // 2 - low_res_size // 2, img_size // 2 + low_res_size // 2, low_res_size)
idx_vec_ = idx_vec.astype("int")
#print(idx_vec_)

#Use fancy indexing to select low frequency lines only
kspace_masklines[idx_vec_, ] = 1

#if 0: # to debug
#    vec = np.array([idx_vec_.astype("int")])
#    zero_vfill = np.zeros((1, (img_size-low_res_size) // 2), dtype="int")
#    line_vec = np.concatenate((zero_vfill, vec, zero_vfill), axis=1)
#    center_lines = np.tile(line_vec, (low_res_size, 1))
#    kspace_mask[center_lines] =1.

if 0:
    plt.figure()
    plt.imshow(kspace_masklines, cmap='Greys_r')
    plt.title("sampling mask")
    plt.show()

norm = "ortho"
#norm = None


def fft(x):
    return np.fft.fft2(x, norm=norm)

def ifft(x):
    return np.fft.ifft2(x, norm=norm)

# Generate the kspace data: first Fourier transform the image
kspace_data = np.fft.fftshift(fft(mri_img))
#add Gaussian complex-valued random noise
signoise = 10
kspace_data += np.random.randn(*mri_img.shape) * signoise * (1+1j)
# Mask data to perform subsampling
kspace_data *= kspace_masklines

# Zero order solution
image_rec0 = ifft(np.fft.ifftshift(kspace_data)) # get back to the convention

fig, axs = plt.subplots(2, 2, figsize=(10, 10))
axs[0, 0].imshow(mri_img, cmap='Greys_r')
axs[0, 0].set_title("True image")
axs[0, 1].imshow(kspace_masklines, cmap='Greys_r')
axs[0, 1].set_title("Low frequency sampling mask")
axs[1, 0].imshow(np.abs(kspace_data), cmap='gray', vmax=0.01*np.abs(kspace_data).max())
#axs[1, 0].imshow(np.abs(np.fft.ifftshift(kspace_data)), cmap='Greys_r')
#axs[1, 0].set_title("k-space noisy data")
axs[1, 1].imshow(np.abs(image_rec0), cmap='Greys_r')
axs[1, 1].set_title("Zero-order recon")
plt.show()
```



- Question: based on the previous example, try to construct a low-frequency sampling mask defined by a squared box centered around $(k_x, k_y) = (0, 0)$.
- Then, replicate the same steps:
 1. Generate noisy masked data
 2. P zero-filled MR image recon
 3. Visualize results and study the impact of both the noise level and the mask size

```
In [73]: #Objective: construct a k-space mask consisting of a central box

# Initialize k-space with 0 everywhere and then place the "1" appropriately
kspace_maskbox = np.zeros((img_size,img_size), dtype="float64")
# use fancy indexing along rows
kspace_maskbox[idx_vec_, ] = 1

list_img_size = np.arange(0, img_size).tolist()
filtered_center = [x for x in list_img_size if x not in idx_vec_]
array_idx_center = np.array(filtered_center)
array_idx_center_ = array_idx_center.astype("int")
# use fancy indexing along coils
kspace_maskbox[:, array_idx_center_] = 0

# Note that the combination of these two fancy indexing replaces the poor code below
#for i in idx_vec_:
#    for j in idx_vec_:
#        kspace_mask[i, j] = 1.

if 0:
    plt.figure()
    plt.imshow(kspace_maskbox, cmap='Greys_r')
    plt.title("Sampling mask")
    plt.show()

# Generate the kspace data: first Fourier transform the image
kspace_data = np.fft.fftshift(fft(mri_img))
#add Gaussian complex-valued random noise
signoise = 10
kspace_data += np.random.randn(*mri_img.shape) * signoise * (1+1j)
# Mask data to perform subsampling
kspace_data *= kspace_maskbox

fig, axs = plt.subplots(2, 2, figsize=(10, 10))
axs[0, 0].imshow(mri_img, cmap='Greys_r')
axs[0, 0].set_title("True image")
axs[0, 1].set_title("True image")
axs[0, 1].set_title("Low frequency sampling mask")
axs[1, 0].imshow(np.abs(kspace_data), cmap='gray', vmax=0.01*np.abs(kspace_data).max())
#axs[1, 0].imshow(np.abs(np.fft.ifftshift(kspace_data)), cmap='Greys_r')
#axs[1, 0].set_title("k-space noisy data")
axs[1, 1].imshow(np.abs(image_rec0), cmap='Greys_r')
axs[1, 1].set_title("Zero-order recon")
plt.show()
```



- Next question: Construct a k -space sampling mask that consists of the high-frequency lines, just discard the central lines
- Study the impact of the number of lines removed

```
In [74]: # 0 entries: points not sampled, 1 entries: points to be sampled
# Initialize k-space with "1" everywhere and then place the "0" appropriately
kspace_masklines = np.ones((img_size,img_size), dtype="float64")
# use fancy indexing along rows
kspace_maskbox[idx_vec_, ] = 0


list_img_size = np.arange(0, img_size).tolist()
filtered_center = [x for x in list_img_size if x not in idx_vec_]
array_idx_center = np.array(filtered_center)
array_idx_center_ = array_idx_center.astype("int")
# use fancy indexing along coils
kspace_maskbox[:, array_idx_center_] = 1

# Note that the combination of these two fancy indexing replaces the poor code below
#for i in idx_vec_:
#    for j in idx_vec_:
#        kspace_mask[i, j]=0.

# Generate the kspace data: first Fourier transform the image
kspace_data = np.fft.fftshift(fft(mri_img))
#add Gaussian complex-valued random noise
signoise = 10
kspace_data += np.random.randn(*mri_img.shape) * signoise * (1+1j)
# Mask data to perform subsampling
kspace_data *= kspace_masklines

# Zero order solution
image_rec0 = ifft(np.fft.ifftshift(kspace_data)) # get back to the convention

fig, axs = plt.subplots(2, 2, figsize=(10, 10))
axs[0, 0].imshow(mri_img, cmap='Greys_r')
axs[0, 0].set_title("True image")
axs[0, 1].set_title("True image")
axs[0, 1].set_title("High frequency sampling mask")
axs[1, 0].imshow(np.abs(kspace_data), cmap='gray', vmax=1*np.abs(kspace_data).max())
#axs[1, 0].imshow(np.abs(np.fft.ifftshift(kspace_data)), cmap='Greys_r')
#axs[1, 0].set_title("k-space noisy data")
axs[1, 1].imshow(np.abs(image_rec0), cmap='Greys_r')
axs[1, 1].set_title("Zero-order recon")
plt.show()
```



- Question: Based on the previous example, try to construct a k -space mask that consists of the removing the central box centered in $(k_x, k_y) = (0, 0)$.
- Then, replicate the same steps:
 1. Generate noisy masked data
 2. Perform zero-filled MR image recon
 3. Visualize results and study the impact of both the noise level and the mask size

```
In [75]: # 0 entries: points not sampled, 1 entries: points to be sampled
# Initialize k-space with "1" everywhere and then place the "0" appropriately
kspace_masklines = np.ones((img_size,img_size), dtype="float64")
# use fancy indexing along rows
kspace_maskbox[idx_vec_, ] = 0

list_img_size = np.arange(0, img_size).tolist()
filtered_center = [x for x in list_img_size if x not in idx_vec_]
array_idx_center = np.array(filtered_center)
array_idx_center_ = array_idx_center.astype("int")
# use fancy indexing along coils
kspace_maskbox[:, array_idx_center_] = 1

# Note that the combination of these two fancy indexing replaces the poor code below
#for i in idx_vec_:
#    for j in idx_vec_:
#        kspace_mask[i, j]=0.

# Generate the kspace data: first Fourier transform the image
kspace_data = np.fft.fftshift(fft(mri_img))
#add Gaussian complex-valued random noise
signoise = 10
kspace_data += np.random.randn(*mri_img.shape) * signoise * (1+1j)
# Mask data to perform subsampling
kspace_data *= kspace_masklines

# Zero order solution
image_rec0 = ifft(np.fft.ifftshift(kspace_data)) # get back to the convention

fig, axs = plt.subplots(2, 2, figsize=(10, 10))
axs[0, 0].imshow(mri_img, cmap='Greys_r')
axs[0, 0].set_title("True image")
axs[0, 1].set_title("True image")
axs[0, 1].set_title("High frequency box sampling mask")
axs[1, 0].imshow(np.abs(kspace_data), cmap='gray', vmax=1*np.abs(kspace_data).max())
#axs[1, 0].set_title("k-space noisy data")
axs[1, 1].imshow(np.abs(image_rec0), cmap='Greys_r')
axs[1, 1].set_title("Zero-order recon")
plt.show()
```

