

Ex no : 18

High level programming extensions -cursor

```
MySQL 8.0 Command Line Cli: x + v

mysql> delimiter //
mysql> CREATE PROCEDURE ShowEmployeeNames()
-> BEGIN
-> DECLARE emp_name VARCHAR(50);
-> DECLARE done INT DEFAULT 0;
-> DECLARE employee_cursor CURSOR FOR
-> SELECT Name FROM Employee;
-> DECLARE CONTINUE HANDLER FOR NOT FOUND SET done = 1;
-> OPEN employee_cursor;
-> read_loop: LOOP
-> FETCH employee_cursor INTO emp_name;
-> IF done = 1 THEN
-> LEAVE read_loop;
-> END IF;
-> SELECT emp_name AS EmployeeName;
-> END LOOP;
-> CLOSE employee_cursor;
-> end //
Query OK, 0 rows affected (0.03 sec)

mysql> delimiter ;
mysql> CALL ShowEmployeeNames();
+-----+
| EmployeeName |
+-----+
| Alice        |
+-----+
1 row in set (0.02 sec)

+-----+
| EmployeeName |
+-----+
| Bob          |
+-----+
1 row in set (0.02 sec)

+-----+
| EmployeeName |
+-----+
| Charlie      |
+-----+
```