

# 쿠버네티스를 활용한 멀티클라우드 도입과 운영전략

## - AWS, Azure, GCP 비교와 실습

2020년 3월  
아인인텔리전스  
권재원, Ph.D.

# **Lab: Introduction to Kubernetes**

## **- Using GCP CloudShell**

# 실습 : CloudShell 시작하기

Google Cloud Platform project2020

DASHBOARD ACTIVITY CUSTOMIZE

**Project info**

Project name  
project2020

Project ID  
project2020-270412

Project number  
631278269945

[ADD PEOPLE TO THIS PROJECT](#)

[Go to project settings](#)

**Compute Engine**

CPU (%)

No data is available for the selected time frame.

8:45 9 AM 9:15 9:30

**Google Cloud Platform status**

All services normal

[Go to Cloud status dashboard](#)

**Billing**

Estimated charges  
For the billing period Mar 1 - 21, 2020

USD \$0.06

[View detailed charges](#)

# 실습 : Introduction to Docker

- Setup and Requirements (GCP CloudShell)

```
$ gcloud auth list  
$ gcloud config set project {project_name}  
$ gcloud config list project  
$ gcloud config set compute/zone asia-northeast1-c  
$ export PROJECT_ID={project_name}  
$ echo $PROJECT_ID
```

*\* Google Cloud gcloud Overview - <https://cloud.google.com/sdk/gcloud>*

- Cluster Creation & Get-Credentials

```
$ gcloud container clusters create [CLUSTER-NAME]  
$ gcloud container clusters get-credentials [CLUSTER-NAME]
```

*\* <https://cloud.google.com/kubernetes-engine/docs/how-to/cluster-access-for-kubectl>*

# Kubernetes Lab

## - Orchestrating the Cloud with Kubernetes

- Provision a complete Kubernetes cluster using Kubernetes Engine.
- Deploy and manage Docker containers using kubectl.
- Break an application into microservices using Kubernetes' Deployments and Services.

# 실습 : Orchestrating the Cloud with Kubernetes

- <https://github.com/googlecode labs/orchestrate-with-kubernetes>

The screenshot shows the GitHub repository page for 'googlecode labs / orchestrate-with-kubernetes'. The repository has 23 watches and 132 forks. The 'Code' tab is selected, showing a list of files and folders. A banner at the top encourages joining GitHub today. The repository statistics show 9 commits, 1 branch, 0 packages, 0 releases, 3 contributors, and the Apache-2.0 license. The file list includes 'kubernetes', 'labs', 'CONTRIBUTING.md', 'LICENSE', and 'README.md'.

Why GitHub? ▾ Enterprise Explore ▾ Marketplace Pricing ▾ Search / Sign in Sign up

googlecode labs / orchestrate-with-kubernetes Watch 23 Fork 132

<> Code Issues 2 Pull requests 4 Actions Projects 0 Security Insights

Join GitHub today  
GitHub is home to over 40 million developers working together to host and review code, manage projects, and build software together.  
Sign up Dismiss

Orchestrating the Cloud with Kubernetes <https://codelabs.developers.google.co...>

9 commits 1 branch 0 packages 0 releases 3 contributors Apache-2.0

Branch: master ▾ New pull request Find file Clone or download ▾

askcarter Merge pull request #2 from IanLewis/blue-green ... Latest commit 6f5f3d1 on 3 Mar 2017

kubernetes	Updated to fix blue-green deployment	3 years ago
labs	Initial import	4 years ago
CONTRIBUTING.md	Initial import	4 years ago
LICENSE	Initial import	4 years ago
README.md	Updated README.md	4 years ago

## 실습 : Orchestrating the Cloud with Kubernetes

- [App](#) is hosted on GitHub and provides an example 12-Factor application. During this lab you will be working with the following Docker images:
- [kelseyhightower/monolith](#) - Monolith includes auth and hello services.
- [kelseyhightower/auth](#) - Auth microservice. Generates JWT tokens for authenticated users.
- [kelseyhightower/hello](#) - Hello microservice. Greets authenticated users.
- [nginx](#) - Frontend to the auth and hello services.

**Get the sample code**



# 실습 : Orchestrating the Cloud with Kubernetes

```
$ gcloud config set compute/zone asia-northeast1-c
```

```
$ gcloud container clusters create io
```

```
To inspect the contents of your cluster, go to: https://console.cloud.google.com/kubernetes/workload\_/gcloud/asia-northeast1-c/io?project=project2020-270412
```

```
kubeconfig entry generated for io.
```

NAME	LOCATION	MASTER_VERSION	MASTER_IP	MACHINE_TYPE	NODE_VERSION	NUM_NODES	STATUS
io	asia-northeast1-c	1.14.10-gke.24	35.194.111.122	n1-standard-1	1.14.10-gke.24	3	RUNNING

```
$ git clone https://github.com/googlecodelabs/orchestrate-with-kubernetes.git
```

```
$ cd orchestrate-with-kubernetes/kubernetes
```

```
$ ls -la
```

```
chaiwonkwon@cloudshell:~/Lab_k8s/lab03-1_orchestrate-with-kubernetes/kubernetes (project2020-270412)$ ls -la
total 32
drwxr-xr-x 7 chaiwonkwon chaiwonkwon 4096 Mar 22 16:26 .
drwxr-xr-x 5 chaiwonkwon chaiwonkwon 4096 Mar 22 16:26 ..
-rw-r--r-- 1 chaiwonkwon chaiwonkwon 283 Mar 22 16:26 cleanup.sh
drwxr-xr-x 2 chaiwonkwon chaiwonkwon 4096 Mar 22 16:26 deployments
drwxr-xr-x 2 chaiwonkwon chaiwonkwon 4096 Mar 22 16:26 nginx
drwxr-xr-x 2 chaiwonkwon chaiwonkwon 4096 Mar 22 16:26 pods
drwxr-xr-x 2 chaiwonkwon chaiwonkwon 4096 Mar 22 16:26 services
drwxr-xr-x 2 chaiwonkwon chaiwonkwon 4096 Mar 22 16:26 tls
```

# **Quick Kubernetes Demo**


# 실습 : Orchestrating the Cloud with Kubernetes

```
$ kubectl create deployment nginx --image=nginx:1.10.0  
$ kubectl get pods  
$ kubectl expose deployment nginx --port 80 --type LoadBalancer  
$ kubectl get services
```

```
chaiwonkwon@cloudshell:~/Lab_k8s/lab03-1_orchestrate-with-kubernetes (project2020-270412) $ kubectl create deployment  
nginx --image=nginx:1.10.0  
deployment.apps/nginx created  
chaiwonkwon@cloudshell:~/Lab_k8s/lab03-1_orchestrate-with-kubernetes (project2020-270412) $ kubectl get pods  
NAME                                READY   STATUS    RESTARTS   AGE  
nginx-574c99d7c8-slrh5              1/1     Running   0           38s  
chaiwonkwon@cloudshell:~/Lab_k8s/lab03-1_orchestrate-with-kubernetes (project2020-270412) $ kubectl expose deployment  
nginx --port 80 --type LoadBalancer  
service/nginx exposed  
chaiwonkwon@cloudshell:~/Lab_k8s/lab03-1_orchestrate-with-kubernetes (project2020-270412) $ kubectl get services  
NAME      TYPE           CLUSTER-IP    EXTERNAL-IP   PORT(S)          AGE  
kubernetes ClusterIP    10.51.240.1   <none>        443/TCP       8m1s  
nginx     LoadBalancer  10.51.245.155 <pending>     80:30137/TCP     8s  
chaiwonkwon@cloudshell:~/Lab_k8s/lab03-1_orchestrate-with-kubernetes (project2020-270412) $ kubectl get services  
NAME      TYPE           CLUSTER-IP    EXTERNAL-IP   PORT(S)          AGE  
kubernetes ClusterIP    10.51.240.1   <none>        443/TCP       8m27s  
nginx     LoadBalancer  10.51.245.155 <pending>     80:30137/TCP     34s  
chaiwonkwon@cloudshell:~/Lab_k8s/lab03-1_orchestrate-with-kubernetes (project2020-270412) $ kubectl get services  
NAME      TYPE           CLUSTER-IP    EXTERNAL-IP   PORT(S)          AGE  
kubernetes ClusterIP    10.51.240.1   <none>        443/TCP       8m50s  
nginx     LoadBalancer  10.51.245.155 35.200.101.136 80:30137/TCP     57s
```

# 실습 : Orchestrating the Cloud with Kubernetes

`http://<External_IP>:80`



## Welcome to nginx!

If you see this page, the nginx web server is successfully installed and working. Further configuration is required.

For online documentation and support please refer to [nginx.org](http://nginx.org).  
Commercial support is available at [nginx.com](http://nginx.com).

*Thank you for using nginx.*

# Pods


# 실습 : Orchestrating the Cloud with Kubernetes

```
$ cat pods/monolith.yaml
$ kubectl create -f pods/monolith.yaml
$ kubectl get pods
```

## Pods

Logical Application

- One or more containers and volumes
- Shared namespaces
- One IP per pod



```
chaiwonkwon@cloudshell:~/Lab_k8s/lab03-1_orchestrate-with-kubernetes/kubernetes (project2020-270412)$ kubectl create
-f pods/monolith.yaml
pod/monolith created
chaiwonkwon@cloudshell:~/Lab_k8s/lab03-1_orchestrate-with-kubernetes/kubernetes (project2020-270412)$ kubectl get pod
s
NAME                                READY   STATUS    RESTARTS   AGE
monolith                            1/1     Running   0           33s
nginx-574c99d7c8-slrh5              1/1     Running   0           12m
```

```
$ kubectl describe pods monolith
```

## 실습 : Orchestrating the Cloud with Kubernetes

- In the 2nd terminal, run this command to set up port-forwarding:

```
$ kubectl port-forward monolith 10080:80
```

- Now in the 1st terminal start talking to your pod using curl:

```
$ curl http://127.0.0.1:10080  
$ curl http://127.0.0.1:10080/secure  
$ curl -u user http://127.0.0.1:10080/login
```

Password = password

```
chaiwonkwon@cloudshell:~/Lab_k8s/lab03-1_orchestrate-with-kubernetes/kubernetes (project2020-270412) $ curl http://127.0.0.1:10080  
{"message":"Hello"}  
chaiwonkwon@cloudshell:~/Lab_k8s/lab03-1_orchestrate-with-kubernetes/kubernetes (project2020-270412) $ curl http://127.0.0.1:10080/secure  
authorization failed  
chaiwonkwon@cloudshell:~/Lab_k8s/lab03-1_orchestrate-with-kubernetes/kubernetes (project2020-270412) $ curl -u user http://127.0.0.1:10080/login  
Enter host password for user 'user':  
{"token":"eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJ1bmVzZXJAZXhhbXBsZS5jb20iLCJleHAiOiJlODUxMjI1NjUsImVudCI6MTU4NDg2MzZMNSwiaXNzIjoiYXV0aC5zZXJ2aWNlIiwic3ViIjoidXNlciJ9.Mgio2jue0S6kfRRuoqmvbrTH38aMiR-7A-EMFjS8WXc"}
```

```
$ TOKEN=$(curl http://127.0.0.1:10080/login -u user|jq -r '.token')
```

## 실습 : Orchestrating the Cloud with Kubernetes

- In the 2nd terminal, run this command to set up port-forwarding:

```
$ curl -H "Authorization: Bearer $TOKEN" http://127.0.0.1:10080/secure  
$ kubectl logs monolith
```

```
chaiwonkwon@cloudshell:~/Lab_k8s/lab03-1_orchestrate-with-kubernetes/kubernetes (project2020-270412)$ curl -H "Author  
ization: Bearer $TOKEN" http://127.0.0.1:10080/secure  
{"message":"Hello"}  
chaiwonkwon@cloudshell:~/Lab_k8s/lab03-1_orchestrate-with-kubernetes/kubernetes (project2020-270412)$ kubectl logs mo  
nolith  
  
2020/03/22 07:41:20 Starting server...  
2020/03/22 07:41:20 Health service listening on 0.0.0.0:81  
2020/03/22 07:41:20 HTTP service listening on 0.0.0.0:80  
127.0.0.1:59282 - - [Sun, 22 Mar 2020 07:47:49 UTC] "GET / HTTP/1.1" curl/7.52.1  
127.0.0.1:59338 - - [Sun, 22 Mar 2020 07:48:33 UTC] "GET /secure HTTP/1.1" curl/7.52.1  
127.0.0.1:59412 - - [Sun, 22 Mar 2020 07:49:25 UTC] "GET /login HTTP/1.1" curl/7.52.1  
127.0.0.1:59696 - - [Sun, 22 Mar 2020 07:53:03 UTC] "GET /login HTTP/1.1" curl/7.52.1  
127.0.0.1:59802 - - [Sun, 22 Mar 2020 07:54:24 UTC] "GET /secure HTTP/1.1" curl/7.52.1
```



# 실습 : Orchestrating the Cloud with Kubernetes

- Open a 3rd terminal and use the -f flag to get a stream of the logs happening in real-time:

```
$ kubectl logs -f monolith
```

- Now if you use curl in the 1st terminal to interact with the monolith, you can see the logs updating (in the 3rd terminal):

```
$ curl http://127.0.0.1:10080
```

```
$ kubectl exec monolith --stdin --tty -c monolith /bin/sh
```

```
/ # ping -c 3 google.com
```

```
/ # exit
```

```
chaiwonkwon@cloudshell:~/Lab_k8s/lab03-1_orchestrate-with-kubernetes/kubernetes (project2020-270412) $ kubectl logs monolith
2020/03/22 07:41:20 Starting server...
2020/03/22 07:41:20 Health service listening on 0.0.0.0:81
2020/03/22 07:41:20 HTTP service listening on 0.0.0.0:80
127.0.0.1:59282 - - [Sun, 22 Mar 2020 07:47:49 UTC] "GET / HTTP/1.1" curl/7.52.1
127.0.0.1:59338 - - [Sun, 22 Mar 2020 07:48:33 UTC] "GET /secure HTTP/1.1" curl/7.52.1
127.0.0.1:59412 - - [Sun, 22 Mar 2020 07:49:25 UTC] "GET /login HTTP/1.1" curl/7.52.1
127.0.0.1:59696 - - [Sun, 22 Mar 2020 07:53:03 UTC] "GET /login HTTP/1.1" curl/7.52.1
127.0.0.1:59802 - - [Sun, 22 Mar 2020 07:54:24 UTC] "GET /secure HTTP/1.1" curl/7.52.1
chaiwonkwon@cloudshell:~/Lab_k8s/lab03-1_orchestrate-with-kubernetes/kubernetes (project2020-270412) $
chaiwonkwon@cloudshell:~/Lab_k8s/lab03-1_orchestrate-with-kubernetes/kubernetes (project2020-270412) $ curl http://127.0.0.1:10080
{"message":"Hello"}
chaiwonkwon@cloudshell:~/Lab_k8s/lab03-1_orchestrate-with-kubernetes/kubernetes (project2020-270412) $ curl http://127.0.0.1:10080
{"message":"Hello"}
chaiwonkwon@cloudshell:~/Lab_k8s/lab03-1_orchestrate-with-kubernetes/kubernetes (project2020-270412) $ kubectl exec monolith --stdin --tty -c monolith /bin/sh
/ # ping -c 3 google.com
PING google.com (172.217.175.110): 56 data bytes
64 bytes from 172.217.175.110: seq=0 ttl=62 time=1.170 ms
64 bytes from 172.217.175.110: seq=1 ttl=62 time=1.337 ms
64 bytes from 172.217.175.110: seq=2 ttl=62 time=1.196 ms

--- google.com ping statistics ---
3 packets transmitted, 3 packets received, 0% packet loss
round-trip min/avg/max = 1.170/1.234/1.337 ms
/ # exit
chaiwonkwon@cloudshell:~/Lab_k8s/lab03-1_orchestrate-with-kubernetes/kubernetes (project2020-270412) $
```

# Services

# 실습 : Orchestrating the Cloud with Kubernetes


## Three Service's type

- ClusterIP (internal) -- the default type means that this Service is only visible inside of the cluster
- NodePort gives each node in the cluster an externally accessible IP
- LoadBalancer adds a load balancer from the cloud provider which forwards traffic from the service to Nodes within it.

## Services

Persistent Endpoint for Pods

- Use Labels to Select Pods
- Internal or External IPs



## 실습 : Orchestrating the Cloud with Kubernetes

```
$ cd ~/orchestrate-with-kubernetes/kubernetes  
$ cat pods/secure-monolith.yaml  
$ kubectl create secret generic tls-certs --from-file tls/  
$ kubectl create configmap nginx-proxy-conf --from-file nginx/proxy.conf  
$ kubectl create -f pods/secure-monolith.yaml
```

```
chaiwonkwon@cloudshell:~/Lab_k8s/lab03-1_orchestrate-with-kubernetes/kubernetes (project2020-270412)$ kubectl create secret g  
eneric tls-certs --from-file tls/  
secret/tls-certs created  
chaiwonkwon@cloudshell:~/Lab_k8s/lab03-1_orchestrate-with-kubernetes/kubernetes (project2020-270412)$ kubectl create configmap  
nginx-proxy-conf --from-file nginx/proxy.conf  
configmap/nginx-proxy-conf created  
chaiwonkwon@cloudshell:~/Lab_k8s/lab03-1_orchestrate-with-kubernetes/kubernetes (project2020-270412)$ kubectl create -f pods/s  
ecure-monolith.yaml  
pod/secure-monolith created
```

# 실습 : Orchestrating the Cloud with Kubernetes

```
$ cat services/monolith.yaml
```


```
$ kubectl create -f services/monolith.yaml
```

```
$ gcloud compute firewall-rules create allow-monolith-nodeport --allow=tcp:31000
```

```
chaiwonkwon@cloudshell:~/Lab_k8s/lab03-1_orchestrate-with-kubernetes/kubernetes (project2020-270412) $ cat services/monolith.yaml
kind: Service
apiVersion: v1
metadata:
  name: "monolith"
spec:
  selector:
    app: "monolith"
    secure: "enabled"
  ports:
    - protocol: "TCP"
      port: 443
      targetPort: 443
      nodePort: 31000
  type: NodePort
chaiwonkwon@cloudshell:~/Lab_k8s/lab03-1_orchestrate-with-kubernetes/kubernetes (project2020-270412) $ kubectl create -f services/monolith.yaml
service/monolith created
chaiwonkwon@cloudshell:~/Lab_k8s/lab03-1_orchestrate-with-kubernetes/kubernetes (project2020-270412) $
chaiwonkwon@cloudshell:~/Lab_k8s/lab03-1_orchestrate-with-kubernetes/kubernetes (project2020-270412) $ gcloud compute firewall-rules create allow-monolith-nodeport \
> --allow=tcp:31000

Creating firewall...:Created [https://www.googleapis.com/compute/v1/projects/project2020-270412/global/firewalls/allow-monolith-nodeport].
Creating firewall...done.
NAME                                NETWORK    DIRECTION    PRIORITY    ALLOW          DENY    DISABLED
allow-monolith-nodeport             default    INGRESS      1000        tcp:31000      False
```

# **Adding Labels to Pods**



## 실습 : Orchestrating the Cloud with Kubernetes

```
$ kubectl get pods -l "app=monolith"
```

```
$ kubectl get pods -l "app=monolith,secure=enabled"
```

```
$ kubectl label pods secure-monolith 'secure=enabled'
```

```
$ kubectl get pods secure-monolith --show-labels
```

```
chaiwonkwon@cloudshell:~/Lab_k8s/lab03-1_orchestrate-with-kubernetes/kubernetes (project2020-270412)$ kubectl get pods -l "app=monolith"
```

NAME	READY	STATUS	RESTARTS	AGE
monolith	1/1	Running	0	4h35m
secure-monolith	2/2	Running	0	27m

```
chaiwonkwon@cloudshell:~/Lab_k8s/lab03-1_orchestrate-with-kubernetes/kubernetes (project2020-270412)$ kubectl get pods -l "app=monolith,secure=enabled"
```

No resources found.

```
chaiwonkwon@cloudshell:~/Lab_k8s/lab03-1_orchestrate-with-kubernetes/kubernetes (project2020-270412)$ kubectl label pods secure-monolith 'secure=enabled'
```

pod/secure-monolith labeled

```
chaiwonkwon@cloudshell:~/Lab_k8s/lab03-1_orchestrate-with-kubernetes/kubernetes (project2020-270412)$ kubectl get pods secure-monolith --show-labels
```

NAME	READY	STATUS	RESTARTS	AGE	LABELS
secure-monolith	2/2	Running	0	29m	app=monolith,secure=enabled



# 실습 : Orchestrating the Cloud with Kubernetes

```
$ kubectl describe services monolith | grep Endpoints
```

```
chaiwonkwon@cloudshell:~/Lab_k8s/lab03-1_orchestrate-with-kubernetes/kubernetes (project2020-270412)$ kubectl describe services monolith | grep Endpoints  
Endpoints:          10.48.0.11:443
```

```
$ kubectl get nodes -o wide
```

```
$ curl -k https://<External_IP>:31000
```

```
chaiwonkwon@cloudshell:~/Lab_k8s/lab03-1_orchestrate-with-kubernetes/kubernetes (project2020-270412)$ kubectl get nodes -o wide
```

NAME	STATUS	ROLES	AGE	VERSION	INTERNAL-IP	EXTERNAL-IP	OS-IMAGE
gke-io-default-pool-a3b23fa7-2911	Ready	<none>	5h58m	v1.14.10-gke.24	10.146.0.8	35.194.105.203	Container-Optimized OS from Google
gke-io-default-pool-a3b23fa7-847k	Ready	<none>	5h58m	v1.14.10-gke.24	10.146.0.7	34.84.216.30	Container-Optimized OS from Google
gke-io-default-pool-a3b23fa7-njw8	Ready	<none>	5h58m	v1.14.10-gke.24	10.146.0.9	34.84.51.138	Container-Optimized OS from Google

```
chaiwonkwon@cloudshell:~/Lab_k8s/lab03-1_orchestrate-with-kubernetes/kubernetes (project2020-270412)$ curl -k https://35.194.105.203:31000  
{ "message": "Hello" }
```

```
chaiwonkwon@cloudshell:~/Lab_k8s/lab03-1_orchestrate-with-kubernetes/kubernetes (project2020-270412)$ curl -k https://34.84.216.30:31000  
{ "message": "Hello" }
```

```
chaiwonkwon@cloudshell:~/Lab_k8s/lab03-1_orchestrate-with-kubernetes/kubernetes (project2020-270412)$ curl -k https://34.84.51.138:31000  
{ "message": "Hello" }
```

# **Deploying Applications with Kubernetes**

## Deployments

Drive current state towards desired state


app: hello  
replicas: 3



## Deployments

Drive current state towards desired state

app: hello  
replicas: 3



# 실습 : Orchestrating the Cloud with Kubernetes

**We're going to break the monolith app into three separate pieces:**

- auth - Generates JWT tokens for authenticated users.
- hello - Greet authenticated users.
- frontend - Routes traffic to the auth and hello services.

```
$ cat deployments/auth.yaml  
$ kubectl create -f deployments/auth.yaml  
$ kubectl create -f services/auth.yaml  
$ kubectl create -f deployments/hello.yaml  
$ kubectl create -f services/hello.yaml
```

```
$ kubectl create configmap nginx-frontend-conf --from-file=nginx/frontend.conf  
$ kubectl create -f deployments/frontend.yaml  
$ kubectl create -f services/frontend.yaml
```

```
$ kubectl get services frontend  
$ curl -k https://<EXTERNAL-IP>
```

# 실습 : Orchestrating the Cloud with Kubernetes

```
$ kubectl describe services monolith | grep Endpoints
```

```
chaiwonkwon@cloudshell:~/Lab_k8s/lab03-1_orchestrate-with-kubernetes/kubernetes (project2020-270412)$ kubectl describe  
services monolith | grep Endpoints  
Endpoints:           10.48.0.11:443
```

```
$ kubectl get nodes -o wide
```

```
$ curl -k https://<External_IP>:31000
```