

# L<sup>A</sup>T<sub>E</sub>X class and style files for my own local use

Dominik Wujastyk

Draft of April 11, 2024

## Contents

1	XeLaTeX stuff	2
2	Used at different times	2
3	Multilingual macros	2
4	Packages that Polyglossia now auto-loads	3
5	Sanskrit hyphenation	5
6	Misc.	5
7	Marginal note hacks	5
8	Stacked diacritics	6
9	Private abbreviations	6
10	Nice hanging-indent footnotes	7
11	Normal LaTeX settings now	7
12	From article.cls	8
13	BibL <sup>A</sup> T <sub>E</sub> X	10
	Index of macro definitions	17

This file started to look like this in about 2016-04-01

## 1 XeLaTeX stuff

Normalize any residual Unicode combining accents, and write out error messages, if any:

XeLaTeX internals

```
1 \XeTeXinputnormalization=1
2 \tracinglostchars=1
3 \tracingonline=1
4 \XeTeXgenerateactualtext=1
```

## 2 Used at different times

Commented out.

hyperref

```
pdfx 5%\usepackage[final=true]{hyperref}
      6%\usepackage[a-1b]{pdfx} % get an archival PDF
```

## 3 Multilingual macros

from: [Stackexchange](#).

etex Not used

```
7%\usepackage{etex}
8%\reserveinserts{28}
9%\usepackage{xcolor}
```

polyglossia Set up various fonts and languages.

```
10 \usepackage{polyglossia}
11 %% work around a bug in polyglossia
12 %% from https://github.com/reutenauer/polyglossia/issues/626
13 \%makeatletter
14 \%ExplSyntaxOn
15 \%pretocmd\xpg@set@alias@values{%
16   \prop_if_exist:cF { xpg@alias@keyvals@#1@#4 }
17   { \prop_new:c {xpg@alias@keyvals@#1@#4} }
18 \%}\-{}
19 \%ExplSyntaxOff
```

```

20%\makeatother
21%% end of workaround
22
23\defaultfontfeatures{%
24  Mapping=tex-text,
25  %Color=red,
26  Numbers=OldStyle,
27}
28
29\setmainlanguage[variant=british]{english}

Main document font:
30% \setmainfont[AutoFakeBold=1.5]{EB Garamond 12}
31\setmainfont[BoldFont = * Bold] % t1pretest 2019
32% (See https://tug.org/pipermail/tex-live/2019-March/043211.html)
33% {Linux Libertine 0} % lovely, but use Libertinus
34% {fbb} % also lovely - Bembo, but no underdot
35% {Tinos} % a croscore font; good diacritics
36{TeX Gyre Pagella}
37% {IndUni-P}
38% {Lucida Sans Unicode}
39% {Libertinus Serif} % something funny with overlapping chars in bold 2019-05

```

## 4 Packages that Polyglossia now auto-loads

polyglossia automatically loads: fixltx2e, etex, xunicode, fontspec. But we still need metalogo for the definitions of logos like `\XeLaTeX`.

```

40\usepackage{metalogo}
41% \usepackage{xunicode} % get unicode encoding in PDF even when using
42% \= etc. Not needed at present.

```

Getting properly-hyphenated Sanskrit:

```

43\setotherlanguage{sanskrit} % for transliterated Sanskrit
44\newfontfamily\sanskritfont
45 [Script=Latin]
46% [Script=Devanagari]
47% {Linux Libertine 0} %Transliteration only in this font
48{TeX Gyre Pagella} %Transliteration only in this font
49% {IndUni-P} %Transliteration only in this font
50% {Brill} %Transliteration only in this font
51% {Sanskrit 2003} % Roman and Devanagari

```

Define `\sansk{}` which is the same as `\emph{}`, except that it causes appropriate hyphenation for Sanskrit words. Use `\sansk{}` for Sanskrit and

\emph{ } for English.

```
52 \newcommand{\sansk}[1]{\emph{\textsanskrit{#1}}}  
53 \let\iast=\sansk %better name for it  
54 \let\rsan=\sansk
```

Now define the Devanagari font: input using standard IAST transliteration

```
55 \newfontfamily\devanagarifont  
56 [Script=Devanagari,  
57 % FakeStretch=1.05,  
58 Mapping=RomDev, %prefer slightly to iast  
59 ]  
60 % {Sahadeva}  
61 % {Sanskrit 2003}  
62 {Tiro Devanagari Sanskrit}  
  
63 % \newcommand{\dev}[1]{\textdevanagari{#1}} % test this 2018-10  
64 \newcommand{\dev}[1]{\textsanskrit{\devanagarifont #1}} % test this 2020-01  
65 \let\dsan=\devanagarifont  
66 \let\dn=\devanagarifont  
67  
68 \setotherlanguage{bengali}  
69 \newfontfamily\bengalifont  
70 [Script=Bengali]  
71 % {Sahadeva}  
72 % {Noto Serif Bengali}  
73 {Tiro Bangla}
```

Use: \textbengali{ }

And other languages

```
74 \setotherlanguage{german}  
75 \setotherlanguage{french}
```

will call appropriate hyphenation.

Chinese, Japanese, Korean

```
76 \newfontfamily\cjkkfont{Noto Sans CJK SC} %  
77 % [Script=CJK,Mapping=tex-text,Scale=MatchLowercase]  
78 % {IPAexMincho}  
79 % {TakaoPGothic}  
80 \let\cjk\cjkkfont
```

<https://tex.stackexchange.com/questions/376420/>

[include-chinese-characters-into-article-in-xelatex](#)

Classical Greek:

```
81 \setotherlanguage{greek}
```

```

82 \newfontfamily\greekfont[Script=Greek,Mapping=tex-text]{GFS Didot}
83 % {GFS Porson}
84 % {GFS Philostratos}

```

End of polyglossia stuff.

## 5 Sanskrit hyphenation

hyphenations A cumulative hyphenation exception file, `sanskrit-hyphenations.tex`, adds numerous hand-tuned hyphenation points to the default Polyglossia hyphenation rules for Sanskrit. This file needs to be `\input` after the start of the document. Normally, we'd do this with `\AtBeginDocument`, but for obscure reasons, that doesn't work. So we have to add the `\input` statement by hand at the start of every document, immediately after `\begin{document}`.

```

85 % \AtBeginDocument{\input{sanskrit-hyphenations.tex}} % this doesn't work :- (

```

## 6 Misc.

```

csquotes
graphicx 86 \usepackage[style=british]{csquotes} % error in log if not included
          87 \usepackage{graphicx}

```

## 7 Marginal note hacks

Not used:

```

88 % \usepackage{marginfix}
      simple marginal query, now superseded:
89 % \newcommand{\q}[1]{%
90 %     \marginpar{%
91 %         \rlap{%
92 %             \fbox{\vtop{\hsize 0.2\textwidth\raggedright\tiny#1}}}}
93 %     %}

```

Actually, `todonotes` makes nicer marginal comments:

```

todonotes
94 \usepackage{colorinlistoftodos,
95 %     disable,
96 textsize=tiny,
97 obeyDraft,

```

```

98 textwidth=.11\textwidth,
99 loadshadowlibrary,
100 shadow,
101 backgroundcolor=yellow
102 ]{todonotes}
103     \setuptodonotes{fancyline}
104
105 % Now renew the \q command to use \todo:
106 \newcommand{\q}[1]{\todo{#1}}
107 % \AtEndDocument{\newpage\listoftodos } %print the todo list
108 % at the end,
109 % when in draft mode

```

## 8 Stacked diacritics

\diatop \diatop, by Christina Thiele, used for r underdot overbar (ṝ, F6, 246) See *TeXniques: Conference Proceedings* 1987, no.5, p.11. (<https://tug.org/texniques/>)

```

110 \def\diatop[#1|#2]{\leavevmode{\setbox1=\hbox{#1}}\setbox2=\hbox{#2}}}%
111     \dimen0=\ifdim\wd1>\wd2\wd1\else\wd2\fi%
112     \dimen1=\ht2\advance\dimen1by-1ex%
113     \setbox1=\hbox to1\dimen0{\hss#1\hss}%
114     \rlap{\raise1\dimen1\box1}%
115     \hbox to1\dimen0{\hss#2\hss}}}%

```

E.g. of use: \diatop[\ 'ō] gives u macron acute

## 9 Private abbreviations

```

\AD
etc. 116 \newcommand{\AD}{\textsc{ce}{}}
117 \newcommand{\BC}{\textsc{bce}{}}
118 \newcommand{\BCE}{\textsc{bce}{}}
119 \newcommand{\CE}{\textsc{ce}{}}
120 \providecommand{\Cs}{\emph{Caraka\ -saṃ\ -hitā}}
121 \providecommand{\Ss}{\emph{Suśruta\ -saṃ\ -hitā}}
122 \let\CS\Cs
123 \let\SS\Ss
124 \providecommand{\AH}{\emph{Aṣṭāṅga\ -hṛdaya\ -saṃ\ -hitā}}
125 % \newcommand{\saneng}[2]{#2 (\sansk{#1})} % now in
126 % xelatex-indexing-xindex.sty
127 \newcommand{\PYS}{PYŚ} % {Pātañjala\ -yoga\ -śāstra}
128 \newcommand{\YSV}{\sansk{Yogasūtravivaraṇa}}

```

```
129 \newcommand{\sutra}[1]{\textbf{\large #1}\par}
```

## 10 Nice hanging-indent footnotes

`\hangfootnotes` LaTeX Companion, p.73. Not used.

```
130 % \def\hangfootnotes{%
131 % \renewcommand{\@makefnmark}[1]{\setlength{\parindent}{0pt}%
132 % \begin{list}{}{\setlength{\labelwidth}{1.5em}%
133 % \setlength{\leftmargin}{\labelwidth}%
134 % \setlength{\labelsep}{3pt}\setlength{\itemsep}{0pt}%
135 % \setlength{\parsep}{0pt}\setlength{\topsep}{0pt}%
136 % \footnotesize\item[\hfill\@makefnmark]##1%
137 % \end{list}}%
138 %}
```

But the above is broken by bigfoot (too much vertical space)

Footnotes with hanging indents adapted from <http://www.ceus-now.com/raggedright-in-footnotes-with-hanging-indent/>

```
139 \newcommand\hangfootnotes{%
140 \long\def\@makefnmark##1{\leftskip=1.8em\hskip-1.8em\hb@xt@1.8em
141 {\@thefnmark\hss}##1}}
```

## 11 Normal LaTeX settings now

```
142 \setcounter{secnumdepth}{0}
```

`enumitem`

```
143 \usepackage[inline]{enumitem} % supersedes mdwlist: does it globally
144 \setlist{itemsep=.5em,
145 %labelindent=\parindent,
146 %leftmargin=*,
147 }
```

```
148 % \usepackage{makeidx} % leave this to xelatex-indexing.sty
```

`multicol (env.)`

`longtable (env.)` 149 \usepackage{multicol}

`array (env.)` 150 % \multicolsep = 12pt plus 4pt minus 3pt % default

```
151 \multicolsep = 1pt plus .25ex % like the starred environments
```

```
152 \usepackage{longtable}
```

```
153 \usepackage{array}
```

```
154 % \usepackage{index} % multiple indexes. Doesn't play well with Beamer
```

```
155 \widowpenalty 4000
```

```

156 \clubpenalty 300
157 \brokenpenalty 5000
158 \interfootnotelinepenalty 10 % lets notes break more easily
159 \vfuzz2pt % Don't report over-full v-boxes if over-edge is small
160 \hfuzz2pt % Don't report over-full h-boxes if over-edge is small
161 \emergencystretch .1\textwidth

162 \hyphenation{dharam-pal wuj-as-tyk never-the-less nutri-tive
163 asoka kerala Aristotle Alex-ander Majno manu-script manu-scripts}

```

Command to draw a box where the pictures will go:

```

164 \newcommand{\pretendpicture}
165 { {\centering \fbox{\vrule width0pt height 2.5in depth0pt
166 \vrule width 4in height0pt depth0pt }\par }}

```

use as follows:

```

\begin{figure}[htp]
\begin{center}
\pretendpicture
\end{center}
\caption{}
\label{fig: }
\end{figure}

```

## 12 From article.cls

This isn't used.

```

167% \typeout{Wujastyk: NB: Modified maketitle command, flush
168% left and no array for authors.}

169% \providecommand\@maketitle{%
170% \newpage
171% \null
172% \vskip 2em%
173%% \begin{center}%
174% \let \footnote \thanks
175% \noindent{\LARGE \@title \par}%
176% \vskip 1.5em%
177% \noindent {\large
178% \lineskip .5em%
179%% \noindent
180%% \begin{tabular}[t]{l} %DW
181% \@author
182%% \end{tabular}\par %DW

```



```

183%    }%
184%    \vskip 1em%
185%    \noindent {\large \@date}%
186%%    \end{center}%
187%    \par
188%    \vskip 3em} %DW was 1.5em

```

sloka See <http://cs.wlu.edu/~necaise/refs/latex2e/env-list.4.html> Not used:

```

189% \newenvironment{sloka} % based on {verse}, from book.cls
190%     {\let\\\@centercr
191%     \list{}\itemsep \z@
192%         \topsep .1\baselineskip
193%         \parsep .25\baselineskip
194%         \itemindent -1.5em%
195%         \listparindent\itemindent
196%         \rightmargin \z@
197%         \leftmargin 3pc % = CUP's \SFB@indent
198%         \advance\leftmargin 1.5em}%
199%     \item\itshape\relax}
200%     {\endlist}

```

Here's another version from book.cls, based on the quote environment

```

201 \newenvironment{sloka}
202 {\list{}\rightmargin\leftmargin}%
203 \item\itshape\relax}
204 {\endlist}

```

\PreliminaryNote Preliminary numberless "footnote" for abbreviations, grant references, and other general initial statements.

```

205 \newcommand{\PreliminaryNote}[1]{%
206 {\def\thefootnote{\relax }%
207 \footnotetext{\hspace*{-2.3em} %only if not using \hangfootnotes
208 #1}}}

209 \newcommand{\doublespacing}{%
210 \renewcommand{\baselinestretch}{1.5}
211 \addtolength{\footnotesep}{0.5\footnotesep}}

```

The following not used.

```

212% \usepackage{ccllicenses}
213% \let\DWolddate\date
214% \renewcommand{\date}[1]{\DWolddate{#1\\ \cc \ccby \ccnc \ccsa }}

```

## 13 BibLaTeX

BibLaTeX Load the BibLaTeX package and the oxyear style, and set the various options.

```
215 \usepackage[%
216 backend=biber,
217 %style=authoryear-icomp,
218 % Make idem and ibidem behave appropriately:
219 \url{https://tex.stackexchange.com/questions/61717/biblatex-strictly-identical-footnote-c
220 % (and see \newbibmacro*{cite:ibid} below).
221 %ibidpage,
222 %idemtracker=false,
223 %style=authoryear,
224 %uniquename=false,
225 % oxref:
226 style=oxyear,
227 dashed=true,
228 % end oxref
229 %bibstyle=publist,
230 %marginyear=true,
231 %style=verbose-trad1,
232 %
233 % I finally worked out how to sort cites by year and bibliography by name
234 %
235 \url{https://cikitsa.blogspot.ca/2017/07/biblatex-citations-and-bibliography.html}
236 sorting=ynt, %ynt for the citations in date order; nyt otherwise
237 sortcites=true,
238 %sortlocale=en-GB,
239 backref=false,
240 date=comp,
241 datecirca=true,
242 dateuncertain=true,
243 bibencoding=auto,
244 hyperref=auto,
245 isbn=true,
246 doi=true,
247 language=auto,
248 natbib=true,
249 texencoding=auto,
250 url=true,
251 urldate=short,
252 usetranslator=true,
253 useprefix=true,% van Nooten
254 giveninits=false, % Give first names in the bibliography. See
255 \url{https://github.com/alex-ball/biblatex-oxref/issues/17#issuecomment-843383550}
```

```

256 %maxnames=1, % before "et al."
257 %uniquelist=false,
258 %refsection=section,
259 ]{biblatex}
260
261 \ExecuteBibliographyOptions[% for biblatex-oxyear
262 article,
263 book,
264 mvbook,
265 mvcollection,
266 inbook,
267 incollection,
268 inreference,
269 collection,
270 reference,
271 mvreference]{useeditor=true,
272   usetranslator=true,
273 %   uniquename=full
274 }

```

compyear Patch so that date-abbreviations aren't just one digit. Kindly supplied by Alex Ball, <https://github.com/alex-ball/biblatex-oxref/issues/19>

```

275 \renewcommand{\blx@ox@compyear}[2]{%
276   \def\num@one{#1}%
277   \def\num@two{#2}%
278   \StrLen{\num@one}[\num@one@len]%
279   \StrLen{\num@two}[\num@two@len]%
280   \ifboolexpr{
281     test {\ifnumequal{\num@one@len}{\num@two@len}}
282     and
283     test {\ifnumless{\num@one}{\num@two}}
284   }{%
285     \StrCompare{\num@one}{\num@two}[\Result]%
286     \ifnum\num@two@len>3%
287     \IfStrEq{\Result}{2}{\def\Result{1}}{}%
288     \fi
289     %% Extend the legal date compression behaviour to all entries
290     \IfStrEq{\Result}{4}{\def\Result{3}}{}%
291     %% End of changes
292     \StrGobbleLeft{0\num@two}{\Result}%
293   }{\num@two}}

```

bookeditor I don't use this, now. patch of Sept 2019  
<https://mail.google.com/mail/u/0/#inbox/>

```

FMfcgxwDrHpMnGSkkqjMqHwCCdJqBLkC
294 %\makeatletter
295 %\xpatchbibmacro{bookeditor}{\global\undef\bbx@lasthash}{\}{\}{%
296 %    \wlog{INFO: oxyyear fix no longer needed!}}
297 %\makeatother

assignrefcontextentries I finally discovered how to sort citations by year and bibliography entries
by name (and see sorting, above).
https://cikitsa.blogspot.ca/2017/07/
biblatex-citations-and-bibliography.html
298 \AtBeginDocument{\assignrefcontextentries[]{*}}
But this isn't working 2021-05 :-()

comma Following sections 3.10 and 4.7.5 of the BibLATEX manual, put the comma
inside the quotation marks of the title.
299 \DefineBibliographyExtras{british}{\DeclareQuotePunctuation{.,}}

printbibliography To avoid saying \newrefcontext[sorting=nyt] before
\printbibliography in every document redefine \printbibliography
(from biblatex.sty):
300 \renewrobustcmd*{\printbibliography}{%
301 \newrefcontext[sorting=nyt] % added this line
302 \begingroup
303 \delimcontext{bib}%
304 \edef\on@line{\on@line}%
305 \@ifnextchar[%]
306 {\blx@printbibliography}
307 {\blx@printbibliography[]}}

volcite no "p." or "pp." in, for example, \volcite:
308 \DefineBibliographyStrings{english}{%
309 page = {},
310 pages = {},
311 volume = {},
312 }

addbibresource This isn't used, because we load different bibliographies in different docu-
ments.
313 % \addbibresource
314 %% [datatype=bibtex]
315 % {biblio4-utf8.bib}

```

urls biblatex documentation 4.11.2 and macros from biblatex.def Enable hot  
URLs for PDFs at Archive.org and Academia.edu

```
316 \newif\ifBibHiddenURLs
317 %
318 \ifBibHiddenURLs
319   \relax
320 \else
321 %
322 \DeclareFieldFormat{url}{%
323   \ifhyperref
324     {\textsc{url: }}\href{#1}{#1}} % added a newline to help with long URLs in PDFs
325   {\textsc{url: }}\nolinkurl{#1}} %DW bug here
326 %
327 % Buddhist Digital Resource Center:
328 \DeclareFieldFormat{eprint:tbrc}{%
329   \textsc{TBRC}\space
330   \ifhyperref
331     {\href{https://www.tbrc.org/\#!rid=#1}{\nolinkurl{#1}}}
332     {\nolinkurl{#1}}}
333 %
334 \DeclareFieldFormat{eprint:ark}{%
335   \textsc{ark:}\space
336   \ifhyperref
337     {\href{https://n2t.net/#1}{\nolinkurl{#1}}}
338     {\nolinkurl{#1}}}
339 %
340 \DeclareFieldFormat{eprint:archive}{%
341 %   Internet Archive\addcolon\space
342   \ifhyperref
343 %     {\href{http://archive.org/details/#1}{\nolinkurl{#1}}}
344 %     {\href{http://archive.org/details/#1}{\small Internet Archive}}}
345 %     {\nolinkurl{#1}}}
346 \DeclareFieldAlias{eprint:archive.org}{eprint:archive}
347 \DeclareFieldAlias{eprint:Archive.org}{eprint:archive}
348
349 \DeclareFieldFormat{eprint:academia}{%
350 %   Academia.edu\addcolon\space
351   \ifhyperref
352     {\href{http://www.academia.edu/#1}{\small Academia.edu}}}
353     {\nolinkurl{#1}}}
354 \DeclareFieldAlias{eprint:academia.edu}{eprint:academia}
355
356 \DeclareFieldFormat{eprint:dli}{%
357 %   DLI\addcolon\space
```

```

358 \ifhyperref
359 {\href{http://www.dli.gov.in/cgi-bin/DBscripts/allmetainfo.cgi?barcode=#1/}{\small
360 Digital Library of India}}
361 {\nolinkurl{#1}}}
362 \DeclareFieldAlias{eprint:DLI}{eprint:dli}
363 \DeclareFieldFormat{eprint:jstor}{%
364 \ifhyperref
365 {\href{http://www.jstor.org/stable/#1}{\small JSTOR}}}
366 {\nolinkurl{#1}}}
367
368 \DeclareFieldFormat{eprint:google}{%
369 \ifhyperref
370 {\href{http://books.google.com/books?id=#1}{\small Google books}}}
371 {\nolinkurl{#1}}}
372 %
373 \DeclareFieldFormat{doi}{%
374 \textsc{doi}\addcolon\space
375 \ifhyperref
376 {\href{https://doi.org/#1}{\nolinkurl{#1}}}
377 {\nolinkurl{#1}}}
378 %
379 \fi
380 \BibHiddenURLsfalse

```

citealias Not used. Better done in individual documents.

```

381 %\defcitealias{meul-hist}{HIML}
382 %\defcitealias{ncc}{NCC}
383 %\defcitealias{bisw-bibl}{BSIMC}

```

note To make Bib<sub>La</sub>T<sub>E</sub>X notes print last, like addendums  
from [http://tex.stackexchange.com/questions/138913/  
how-to-move-the-field-note-at-the-end-of-the-reference](http://tex.stackexchange.com/questions/138913/how-to-move-the-field-note-at-the-end-of-the-reference)

```

384 \DeclareSourcemap{
385 \maps[datatype=bibtex]{
386 \map{
387 \step[fieldsource=note, final]
388 \step[fieldset=addendum, origfieldval, final]
389 \step[fieldset=note, null]
390 }
391 }
392 }

```

DeclareFieldFormat Tweaks to make the citation form:- Author date: page

```

393 \DeclareFieldFormat{postnote}{#1}

```

```

394 \renewcommand{\postnotedelim}{:\,}
395 \renewcommand{\nameyear delim}{ }

clearfield Suppress shorthands: http://tex.stackexchange.com/questions/57041/
    Once again, I don't use this at present.
396 % \AtEveryCitekey{\clearfield{shorthand}}

csquotes
397 \usepackage{csquotes}
398 \setquotestyle{american} % american = double quotes

DeclareLabeldate BibLaTEX hacks to get pubstate (?forthcoming? etc.) behaving as it should
BibLaTEX manual 4.5.10
399 \DeclareLabeldate{%
400   \field{date}
401   \field{year}
402   \field{pubstate}
403   \field{eventdate}
404   \field{origdate}
405   \field{urldate}
406   \literal{nodate}
407 }

shorthandwidth Some magic from "moewe" at https://tex.stackexchange.com/questions/442749/biblatex-have-hyperref-links-point-to-the-shorthand-list that
makes hyperlinks work from citations to a list of abbreviations.
408 \DeclareFieldFormat{shorthandwidth}{%
409   \bibhypertarget{shorthand:\thefield{entrykey}}
410   {#1}}
411
412 \DeclareFieldFormat{bibhyperref}{%
413   \iffieldundef{shorthand}
414   {\bibhyperref{#1}}
415   {\bibhyperlink{shorthand:\thefield{entrykey}}{#1}}}

penalties Penalty settings to make URLs format better. From xurl documentation.
    Currently not used.
416 %\usepackage{xurl}
417 %\setcounter{biburllcpenalty}{1}
418 %\setcounter{biburlucpenalty}{1}
419 %\setcounter{biburlnumpenalty}{1}
420 %% but BibLaTEX has this built in to it.

```

volcite No "pp." or "pages" in \volcite etc.

```
421 \DefineBibliographyStrings{english}{%
422     page          = {},
423     pages          = {},
424 }
```

literal Create a new data type in bibtex, @literal, which just prints the content of the title field.

Thanks to emilianoehyans at <https://forums.zotero.org/discussion/110863/biblatex-both-langid-and-language-are-needed>

```
425 \DeclareBibliographyDriver{literal}{%
426     \newunit\newblock
427     \printfield{title}%
428     \finentry}
```

DeclareSourcemap It turns out that it's the langid field that controls language-switching in bibliography entries, not language. Since I've always used language, this code will just write the content of the language field to the langid field, on the fly.

```
429 \DeclareSourcemap{
430     \maps[datatype=bibtex]{
431         \map{
432             \step[fieldsource=language,fieldtarget=langid]
433         }
434     }
435 }
```

That's all, folks!



## Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in *roman* refer to the code lines where the entry is used.

<b>Symbols</b>			
\# ..... 331	\BCE ..... 118	\DeclareFieldAlias	
\, ..... 394	\begin ... 132, 173, 180		346, 347, 354, 362
\- .. 120, 121, 124, 127	\begingroup .... 302	\DeclareFieldFormat	
\= ..... 42	\bengalifont ..... 69		. 322, 328, 334,
\@author ..... 181	\BibHiddenURLsfalse		340, 349, 356,
\@centercr ..... 190	..... 380		363, 368, 373,
\@date ..... 185	\bibhyperlink ... 415		<u>393</u> , 393, 408, 412
\@ifnextchar .... 305	\bibhyperref .... 414	\DeclareLabeldate	
\@makefnmark .... 136	\bibhypertarget . 409		..... 399, 399
\@makefntext . 131, 140	\BibLaTeX ..... <u>215</u>	\DeclareQuotePunctuation	
\@maketitle .... 169	\blx@ox@compyear 275		..... 299
\@thefnmark .... 141	\blx@printbibliography	\DeclareSourcemap	
\@title ..... 175	..... 306, 307		.... 384, <u>429</u> , 429
\\ ..... 190, 214, 324	\bookeditor .... <u>294</u>	\def ..... 110,	
\_ ..... 420	\box ..... 114		130, 140, 206,
	\brokenpenalty .. 157		276, 277, 287, 290
		\defaultfontfeatures	
			..... 23
<b>A</b>	<b>C</b>	\defcitealias ....	
\AD ..... <u>116</u>	\cc ..... 214		.... 381, 382, 383
\addbibresource ..	\ccby ..... 214	\DefineBibliographyExtras	
..... <u>313</u> , 313	\ccnc ..... 214		..... 299
\addcolon ..... 341, 350, 357, 374	\ccsa ..... 214	\DefineBibliographyStrings	
\addtolength .... 211	\CE ..... 119		..... 308, 421
\advance .... 112, 198	\centering .... 165	\delimcontext ... 303	
\AH ..... 124	\citealias ..... <u>381</u>	\dev ..... 63, 64	
array (env.) ..... <u>149</u>	\CJK ..... 76, 80	\devanagarifont ..	
\assignrefcontextentries	\clearfield . <u>396</u> , 396		.... 55, 64, 65, 66
..... <u>298</u> , 298	\clubpenalty .... 156	\diatop ..... <u>110</u>	
\AtBeginDocument .	\comma ..... <u>299</u>	\dimen ..... 111,	
..... 85, 298	\compyear ..... <u>275</u>		112, 113, 114, 115
\AtEndDocument .. 107	\CS ..... 122	\dn ..... 66	
\AtEveryCitekey . 396	\Cs ..... 120, <u>122</u>	\doublespacing .. 209	
	\csquotes .... <u>86</u> , <u>397</u>	\dsan ..... 65	
<b>B</b>	<b>D</b>	\DWolddate .. 213, 214	
\baselineskip 192, 193	\date ..... 213, 214	<b>E</b>	
\baselinestretch 210	\DeclareBibliographyDriver	\edef ..... 304	
\bbx@lasthash ... 295	..... 425		
\BC ..... 117			

<code>\else</code> . . . . .	<a href="#">111</a> , <a href="#">320</a>	<code>\hss</code> . . . . .	<a href="#">113</a> , <a href="#">115</a> , <a href="#">141</a>	<code>\literal</code> . . . .	<a href="#">406</a> , <a href="#">425</a>
<code>\emergencystretch</code>	<a href="#">161</a>	<code>\ht</code> . . . . .	<a href="#">112</a>	<code>\long</code> . . . . .	<a href="#">140</a>
<code>\emph</code> .	<a href="#">52</a> , <a href="#">120</a> , <a href="#">121</a> , <a href="#">124</a>	<code>\hyperref</code> . . . . .	<a href="#">5</a>	<code>longtable</code> (env.)	<a href="#">149</a>
<code>\end</code> . . . . .	<a href="#">137</a> , <a href="#">182</a> , <a href="#">186</a>	<code>\hyphenation</code> . . . .	<a href="#">162</a>		
<code>\endlist</code> . . . .	<a href="#">200</a> , <a href="#">204</a>	<code>\hyphenations</code> . . . .	<a href="#">85</a>		
<code>\enumitem</code> . . . . .	<a href="#">143</a>			<b>M</b>	
environments:		<b>I</b>		<code>\makeatletter</code> .	<a href="#">13</a> , <a href="#">294</a>
<code>array</code> . . . . .	<a href="#">149</a>	<code>\iast</code> . . . . .	<a href="#">53</a>	<code>\makeatother</code> . .	<a href="#">20</a> , <a href="#">297</a>
<code>longtable</code> . . . .	<a href="#">149</a>	<code>\ifBibHiddenURLs</code> .		<code>\map</code> . . . . .	<a href="#">386</a> , <a href="#">431</a>
<code>multicol</code> . . . . .	<a href="#">149</a>	. . . . .	<a href="#">316</a> , <a href="#">318</a>	<code>\maps</code> . . . . .	<a href="#">385</a> , <a href="#">430</a>
<code>\etc</code> . . . . .	<a href="#">116</a>	<code>\ifboolexpr</code> . . . .	<a href="#">280</a>	<code>\marginpar</code> . . . . .	<a href="#">90</a>
<code>\etex</code> . . . . .	<a href="#">7</a>	<code>\ifdim</code> . . . . .	<a href="#">111</a>	<code>multicol</code> (env.) . .	<a href="#">149</a>
<code>\ExecuteBibliographyOptions</code>		<code>\iffieldundef</code> . . .	<a href="#">413</a>	<code>\multicolsep</code> .	<a href="#">150</a> , <a href="#">151</a>
. . . . .	<a href="#">261</a>	<code>\ifhyperref</code> <a href="#">323</a> , <a href="#">330</a> ,		<b>N</b>	
<code>\ExplSyntaxOff</code> . . .	<a href="#">19</a>	<a href="#">336</a> , <a href="#">342</a> , <a href="#">351</a> ,		<code>\nameyear delim</code> . .	<a href="#">395</a>
<code>\ExplSyntaxOn</code> . . . .	<a href="#">14</a>	<a href="#">358</a> , <a href="#">364</a> , <a href="#">369</a> , <a href="#">375</a>		<code>\newbibmacro</code> . . . .	<a href="#">220</a>
		<code>\ifnum</code> . . . . .	<a href="#">286</a>	<code>\newblock</code> . . . . .	<a href="#">426</a>
		<code>\ifnumequal</code> . . . .	<a href="#">281</a>	<code>\newcommand</code> . . . .	
<b>F</b>		<code>\ifnumless</code> . . . . .	<a href="#">283</a>	. . . . .	<a href="#">52</a> , <a href="#">63</a> , <a href="#">64</a> , <a href="#">89</a> ,
<code>\fbox</code> . . . . .	<a href="#">92</a> , <a href="#">165</a>	<code>\IfStrEq</code> . . . .	<a href="#">287</a> , <a href="#">290</a>	. . . . .	<a href="#">106</a> , <a href="#">116</a> , <a href="#">117</a> ,
<code>\fi</code> . . . . .	<a href="#">111</a> , <a href="#">288</a> , <a href="#">379</a>	<code>\input</code> . . . . .	<a href="#">85</a>	. . . . .	<a href="#">118</a> , <a href="#">119</a> , <a href="#">125</a> ,
<code>\field</code> . . . .	<a href="#">400</a> , <a href="#">401</a> ,	<code>\interfootnotelinepenalty</code>		. . . . .	<a href="#">127</a> , <a href="#">128</a> , <a href="#">129</a> ,
<a href="#">402</a> , <a href="#">403</a> , <a href="#">404</a> , <a href="#">405</a>		. . . . .	<a href="#">158</a>	. . . . .	<a href="#">139</a> , <a href="#">164</a> , <a href="#">205</a> , <a href="#">209</a>
<code>\finentry</code> . . . . .	<a href="#">428</a>	<code>\item</code> . . . .	<a href="#">136</a> , <a href="#">199</a> , <a href="#">203</a>	<code>\newenvironment</code> . .	
<code>\footnote</code> . . . . .	<a href="#">174</a>	<code>\itemindent</code> .	<a href="#">194</a> , <a href="#">195</a>	. . . . .	<a href="#">189</a> , <a href="#">201</a>
<code>\footnotesep</code> . . . .	<a href="#">211</a>	<code>\itemsep</code> . . . .	<a href="#">134</a> , <a href="#">191</a>	<code>\newfontfamily</code> . . .	
<code>\footnotesize</code> . . .	<a href="#">136</a>	<code>\itshape</code> . . . .	<a href="#">199</a> , <a href="#">203</a>	. . . . .	<a href="#">44</a> , <a href="#">55</a> , <a href="#">69</a> , <a href="#">76</a> , <a href="#">82</a>
<code>\footnotetext</code> . . .	<a href="#">207</a>			<code>\newif</code> . . . . .	<a href="#">316</a>
		<b>L</b>		<code>\newpage</code> . . . .	<a href="#">107</a> , <a href="#">170</a>
<b>G</b>		<code>\labelsep</code> . . . . .	<a href="#">134</a>	<code>\newrefcontext</code> . .	<a href="#">301</a>
<code>\global</code> . . . . .	<a href="#">295</a>	<code>\labelwidth</code> .	<a href="#">132</a> , <a href="#">133</a>	<code>\newunit</code> . . . . .	<a href="#">426</a>
<code>\graphicx</code> . . . . .	<a href="#">86</a>	<code>\LARGE</code> . . . . .	<a href="#">175</a>	<code>\noindent</code> . . . . .	
<code>\greekfont</code> . . . . .	<a href="#">82</a>	<code>\large</code> . . . .	<a href="#">129</a> , <a href="#">177</a> , <a href="#">185</a>	. . . . .	<a href="#">175</a> , <a href="#">177</a> , <a href="#">179</a> , <a href="#">185</a>
		<code>\LaTeX</code> . . . . .	<a href="#">420</a>	<code>\nolinkurl</code> . . . . .	
<b>H</b>		<code>\leavevmode</code> . . . .	<a href="#">110</a>	. . . . .	<a href="#">325</a> , <a href="#">331</a> , <a href="#">332</a> ,
<code>\hangfootnotes</code>	<a href="#">130</a> , <a href="#">207</a>	<code>\leftmargin</code> . . . .		. . . . .	<a href="#">337</a> , <a href="#">338</a> , <a href="#">343</a> ,
<code>\hb@xt@</code> . . . . .	<a href="#">140</a>	. . . . .	<a href="#">133</a> , <a href="#">197</a> , <a href="#">198</a> , <a href="#">202</a>	. . . . .	<a href="#">345</a> , <a href="#">353</a> , <a href="#">361</a> ,
<code>\hbox</code> . . . .	<a href="#">110</a> , <a href="#">113</a> , <a href="#">115</a>	<code>\leftskip</code> . . . . .	<a href="#">140</a>	. . . . .	<a href="#">366</a> , <a href="#">371</a> , <a href="#">376</a> , <a href="#">377</a>
<code>\hfill</code> . . . . .	<a href="#">136</a>	<code>\let</code> . . . . .	<a href="#">53</a> , <a href="#">54</a> ,	<code>\note</code> . . . . .	<a href="#">384</a>
<code>\hfuzz</code> . . . . .	<a href="#">160</a>	. . . . .	<a href="#">65</a> , <a href="#">66</a> , <a href="#">80</a> , <a href="#">122</a> ,	<code>\null</code> . . . . .	<a href="#">171</a>
<code>\href</code> .	<a href="#">324</a> , <a href="#">331</a> , <a href="#">337</a> ,	. . . . .	<a href="#">123</a> , <a href="#">174</a> , <a href="#">190</a> , <a href="#">213</a>	<code>\num@one</code> . . . . .	
. . . . .	<a href="#">343</a> , <a href="#">344</a> ,				

\num@two@len . . . . .	\sansk 52, 53, 54, 125, 128	\topsep . . . . . 135, 192
. . . . . 279, 281, 286	\sanskritfont . . . . . 44	\tracinglostchars . . 2
<b>O</b>	\setbox . . . . . 110, 113	\tracingonline . . . . 3
\on@line . . . . . 304	\setcounter . . . . .	\typeout . . . . . 167
	142, 417, 418, 419	
<b>P</b>	\setlength . . . 131,	<b>U</b>
\par . . . . . 129,	132, 133, 134, 135	\undef . . . . . 295
166, 175, 182, 187	\setlist . . . . . 144	\url . . . . . 219, 235, 255
\parindent . . 131, 145	\setmainfont . . . 30, 31	\urls . . . . . 316
\parsep . . . . . 135, 193	\setmainlanguage . . 29	\usepackage . . 5, 6,
\pdfx . . . . . 5	\setotherlanguage	7, 9, 10, 40, 41,
\penalties . . . . . 416	. 43, 68, 74, 75, 81	86, 87, 88, 94,
\polyglossia . . . . . 10	\setquotestyle . . 398	143, 148, 149,
\postnotedelim . . 394	\setuptodonotes . . 103	152, 153, 154,
\PreliminaryNote 205	\SFB@indent . . . . 197	212, 215, 397, 416
\pretendpicture . 164	\shorthandwidth . 408	
\pretocmd . . . . . 15	\sloka . . . . . 189	<b>V</b>
\printbibliography	\small . . . . . 344,	\vfuzz . . . . . 159
. . . . . 300, 300	352, 359, 365, 370	\volcite . . . . 308, 421
\printfield . . . . 427	\space . . . 329, 335,	\vrule . . . . . 165, 166
\prop . . . . . 16, 17	341, 350, 357, 374	\vskip 172, 176, 184, 188
\providecommand . .	\SS . . . . . 123	\vtop . . . . . 92
120, 121, 124, 169	\Ss . . . . . 121, 123	
\PYS . . . . . 127	\step 387, 388, 389, 432	<b>W</b>
<b>Q</b>	\StrCompare . . . . 285	\wd . . . . . 111
\q . . . . . 89, 105, 106	\StrGobbleLeft . . 292	\widowpenalty . . . 155
	\StrLen . . . . . 278, 279	\wlog . . . . . 296
<b>R</b>	\sutra . . . . . 129	
\raggedright . . . . . 92	<b>T</b>	<b>X</b>
\raise . . . . . 114	\textbf . . . . . 129	\XeLaTeX <sub>U</sub> internals 1
\relax 199, 203, 206, 319	\textdevanagari . . 63	\XeTeXgenerateactualtext
\renewcommand . . .	\textsanskrit . . 52, 64	. . . . . 4
. . . . . 131, 210,	\textsc . . 116, 117,	\XeTeXinputnormalization
214, 275, 394, 395	118, 119, 324,	. . . . . 1
\renewrobustcmd . 300	325, 329, 335, 374	\xpatchbibmacro . . 295
\reserveinserts . . . 8	\textwidth 92, 98, 161	\xpg@set@alias@values
\Result 285, 287, 290, 292	\thanks . . . . . 174	. . . . . 15
\rightmargin . 196, 202	\thefield . . . 409, 415	
\rlap . . . . . 91, 114	\thefootnote . . . . 206	<b>Y</b>
\rsan . . . . . 54	\tiny . . . . . 92	\YSV . . . . . 128
<b>S</b>	\todo . . . . . 105, 106	<b>Z</b>
\saneng . . . . . 125	\todonotes . . . . . 94	\z@ . . . . . 191, 196