 **NetExam**
Sri Lanka Institute of Information Technology

Write a C program to input a word from the keyboard and store it in a character array called **myArray**. Replace all the letters that have odd numbers as ASCII values with "*".
Hint : ASCII value of **a** is 97 and z is 122.
ASCII value of **A** is 65 and Z is 90.

Sample Output


Input Array

S	c	h	o	o	l
---	---	---	---	---	---

ASCII values of S, c, h, o, l are 83, 99, 104, 111, 108

Output Array

*	*	h	*	*	l
---	---	---	---	---	---



Question 1

```
#include <stdio.h>
```

```
int main(void)
```

```
{
```

```
    int i;
```

```
    int upper = 0;
```

```
    char myArray[100];
```

```
    printf("input word : ");
```

```
    scanf("%s", myArray);
```

```
    for(i=0; myArray[i] != '\0'; i++){
```

```
        if(myArray[i] % 2 == 0)
```

```
        {
```

```
            printf("%c\t", myArray[i]);
```

```
        }
```

```

else
{
    printf("%*t");
}
}
return 0;
}

```

Following program is written by a student to display the result of factorial of n.

$n! = 1 * 2 * 3 * 4 * \dots * n$

The factorial of a negative number doesn't exist. And the factorial of 0 is 1.

There are **five errors** in the program. Find the errors and write down the **corrected statements** in given space.

1. #include <stdio.h>
2. int main()
3. {
4. int n, i;
5. int fact = 0;
- 6.
7. printf("Enter an integer: ");
8. scanf("%f", &n);
- 9.
10. #Display error message
11. if (n < 0)
12. printf("Error\n");
13. else
14. {
15. for (i = 1; i <= n; ++i)

```

15.   for (i = 1; i <= n; ++i)
16.   {
17.       fact *= n;
18.   }
19.   printf("Factorial of %d = %d", n, i);
20. }
21.
22. return 0;
23. }

```

Corrected Statement 01 :

Corrected Statement 02 :

Corrected Statement 03 :

Corrected Statement 04 :

Corrected Statement 05 :

Question 2

01 :- `scanf("%d", &n);`

02 :- `fact = 1;`

03 :- `//display error message`

04 :- `fact *= i;`

05 :- `printf("Factorial of %d = %d ", n, fact);`

Question 3

Not yet answered

Marked out of
5.00

Flag question

Following C program used to read five Item details (Item Code, Item Name, Item Price) of grocery store from keyboard and store them in text file called 'items.dat'. Fill the missing words/statements in following C program.

```
#include<stdio.h>

int main(void)
{
    int ItemCode;
    char ItemName[30];
    float ItemPrice;

    int i;
    FILE *fitem;
    fitem = fopen("items.dat",  );

    if (  == NULL)
    {
        printf("File cannot be open");
        return -1;
    }

    for(i = 1; i <= 5; ++i)
```

```
    for(i = 1; i <= 5; ++i)
    {
        printf("Input Item Code: ");
        scanf("%d", &ItemCode);
        printf("Input Item Name: ");
        scanf("%s", ItemName);
        printf("Input Item Price: ");
        scanf("%f", &ItemPrice);
         (fitem, "%d %s %.2f\n",  );
    }
     ;
    return 0;
}
```

Question 3

01 :- "w+"


02 :- fitem

03 :- fitem

04 :- fprintf

05 :- ItemCode , ItemName , ItemPrice

06 :- fclose (fitem)



Question 4

```
#include <stdio.h>
```

```
//function main program execution
```

```
int main (void )
```

```
{
```

```
    int i , sum ;
```

```
    int numArr[9] ;
```

```
    numArr[0] = 1 ;
```

```
    numArr[1] = 2 ;
```

```
    sum = numArr[0] + numArr[1] ;
```

```
    printf("%d %d ", numArr[0] , numArr[1]);
```

```
    for (i = 2 ; i < 8 ; i++)
```

```
    {
```

```
        numArr[i] = numArr[i-2] + numArr[i-1] ;
```

```
        printf("%d ", numArr[i]);
```

```
        sum += numArr[i] ;
```

```
    }
```

```
    numArr[8] = sum ;
```


```
    printf("%d" , numArr[8] );
```

```

return 0 ;

} //end function main

```



Question 5

Before the programming Create a vcard file and store the Question's details

```

#include <stdio.h>

int main (void)
{
    int num ;
    int dos1 = 0 , dos2 = 0 ;
    FILE *vcard ;
    vcard = fopen("vcard.dat" , "r+");

    if (vcard == NULL)
    {
        printf("File cannot open");
        return -1 ;
    }

    fscanf(vcard , "%*s %*s %d" , &num);

    while (!feof (vcard))
    {

```



```

        if (num == 1)
        {
            dos1 += 1 ;
        }
        else if (num == 2)
        {
            dos2 += 1 ;
        }
        fscanf(vcard , "%*s %*s %d" , &num);
    }

    printf("number of students with one dosages = %d\n" , dos1);
    printf("number of students with two dosages = %d\n" , dos2);

    fclose(vcard);
    return 0 ;
}

```

Question 6
Not yet answered
Marked out of 5.00
Flag question

Following C program contains the structure called "Pharmacy" to store medicinal product details.

```

productNo      integer
productName    char[50]
unitPrice      double
qty            integer

```

The program creates a variable called t1 using *Pharmacy* data type and store some data entered through keyboard. Next the program calculates the total price based on quantity and unit price, then print the details on the screen as shown in output below. **Complete the following C code by filling the missing statements.**

Input Values:

productNo	productName	unitPrice	qty
1001	AZITHROMYCIN	50.00	120

Output:

productNo	productName	Total Price
1001	AZITHROMYCIN	6000.00

#include<stdio.h>

```
#include<stdio.h>
int main(void)
{
    int productNo;
    char productName[30];
    double unitPrice;
    int qty;

    printf("Enter Product No: ");
    scanf("%d", &productNo);

    printf("Enter Product Name: ");
    scanf("%s", t1.productName);

    printf("Enter Product Price: ");
    scanf("%lf", &t1.unitPrice);

    printf("Enter Product Quantity: ");
    scanf("%d", &t1.qty);


    return 0;
}
```

Question 6


```

01 :- struct Pharmacy
02 :- struct Pharmacy
03 :- scanf( " %d " , &t1.productNo ) ;
04 :- total = t1.unitPrice * t1.qty ;
05 :- printf( " %d \t %s \t %.2f " , t1.productNo , t1.productName , total ) ;

```



Question 7

```
#include <stdio.h>
```

```
int main()
```

```
{
```

```
    char name[50];
```

```
    int amount , tax ;
```

```
    printf("Customer name : ");
```

```
    scanf("%s" , name);
```

```

printf("Fixed Diposit amount : " );
scanf("%d" , &amount);

if(amount < 10000)
{
    tax = amount * (2.0 / 100) ;
}

else if(amount >= 10000 && amount < 100000)
{
    tax = amount * (3.0 / 100) ;
}

else if(amount >= 100000 && amount < 500000)
{
    tax = amount * (5.0 / 100) ;
}
else if(amount >= 500000)
{
    tax = amount * (10.0 / 100) ;
}

if (tax > 100000)
{
    tax = tax - tax * (4.0 / 100) ;
}

printf("Interest : %d" , tax);
return 0;
}

```

Complete the following C statement to calculate the result of $\sqrt[2]{b * b - 4 * a * c}$
 Assume a, b and c variables are integers.

float answer = (((, 2) - 4 * a * c);

Question 8

01 :- sqrt
02 :- fabs
03 :- pow
04 :- b

Question 9
Not yet answered
Marked out of 1.00
Flag question

Write a C program to do the following.

- a) Create a 2D integer array called **twoD** with 3 rows and 3 columns.
- b) Input numbers from the keyboard and store in the array.
- c) Replace the lower triangular by value 0
- d) Find sum of rows and columns of the matrix.

Hint : You need to use repetition structures to manipulate the matrix

Test Data :

Input elements to the matrix :

element - [0],[0] : 5
element - [0],[1] : 6
element - [0],[2] : 9
element - [1],[0] : 7
.....
.....

Expected Output :

The 2D array is: 5 6 9
 7 8 4
 2 1 1

After setting 0 in lower triangular

The 2D array is: 5 6 9
 0 8 4
 0 0 1

The sum of rows : 20, 12, 1
The sum of columns : 5, 14, 14

Rich text editor toolbar: Bold, Italic, Underline, Bulleted list, Numbered list, Link, Unlink, Image

Question 9

```
#include <stdio.h>
```

```
int main (void)
{
    int twoD[3][3];
    int i , j ;
    int sum_row[3] = {0} ;
    int sum_columns[3] = {0};
```

```

printf("input element of matrix : \n");

for (i = 0 ; i < 3 ; i++)
{
    for(j = 0 ; j < 3 ; j++)
    {
        printf("element - [%d],[%d] : " , i , i);
        scanf("%d" , &twoD[i][j]);
    }
}

printf("\n2D array is : \n");

for (i = 0 ; i < 3 ; i++)
{
    for (j = 0 ; j < 3 ; j++)
    {
        printf("%d " , twoD[i][j]);
    }
    puts(" ");
}

printf("\nAfter setting 0 in lower triangular\n");

printf("\n2D array is : \n");

for (i = 0 ; i < 3 ; i++)
{
    for (j = 0 ; j < 3 ; j++)
    {
        if (i <= j)
        {
            printf("%d " , twoD[i][j]);
        }
        else
        {
            twoD[i][j] = 0 ;
            printf("%d " , twoD[i][j]);
        }
    }
    puts(" ");
}

```

```

    }

    printf("\nThe sum of rows : ");
    for (i = 0 ; i < 3 ; i++)
    {
        for (j = 0 ; j < 3 ; j++)
        {
            sum_row[i] += twoD[i][j];
        }
        printf("%d ",sum_row[i] );
    }

    printf("\nThe sum of columns : ");
    for (i = 0 ; i < 3 ; i++)
    {
        for (j = 0 ; j < 3 ; j++)
        {
            sum_columns[i] += twoD[j][i];
        }
        printf("%d ",sum_columns[i] );
    }

    return 0 ;
}

```

An event management company needs to implement a system to manage their online events. They want to create few functions to be integrated to the system such as register a user to the event, purchase event ticket, grant discounts based on each event.

To purchase tickets, one must submit the **ticket type**(tType) . 1- Gold, 2 - Silver, 3 - Bronze, **session** (session), (m- morning, a - afternoon, e -evening) and the **number of tickets to purchase** (ticketCount). Then the function should display the amount of the tickets purchased.

Ticket Type	Price
1 - Gold	5000/=
2 - Silver	2500/=
3 - Bronze	1000/=

Fill in the blanks to complete the function **purchase()**.

```

 purchase(  tType ,   , int ticketCount)
{
    float total = 0.0;
    if(tType == 1)
    {
        total = ticketCount * 5000.0;
    }
    else if(tType == 2)
    {
        total = ticketCount * 2500.0;
    }
    // ...
}

```

```

    else if(tType == 2)
    {
        total = ticketCount * 2500.0;
    }
    else if(tType == 3)
    {
        total = ticketCount * 1000.0;
    }
    switch(session)
    {
        case 'm': printf("Thank you for purchasing %d tickets for morning session\n", ticketCount);
                  break;
        case 'a': printf("Thank you for purchasing %d tickets for afternoon session\n", ticketCount);
                  break;
        case 'e': printf("Thank you for purchasing %d tickets for evening session\n", ticketCount);
                  break;
    }
    printf("The amount of the tickets purchased : %.2f\n", total);
}

```

Question 10

- 01 :- void
- 02 :- int
- 03 :- char
- 04 :- session
- 05 :- total

Write two assert statements to test the following function. This function will return Surface Area of Cylinder when it's radius(r) and height(h) are passed as parameters.

```

double cylinderSurfaceArea(double r, double h)
{
    double area;
    area = (2 * 22 / 7.0 * r * h) + (2 * 22 / 7.0 * r * r);
    return area;
}


```

Sample Data

radius(r)	height(h)	Area of cylinder surface (area)
5.0	8.0	408.41
7.0	10.0	747.7

Question 11


```
assert ( fabs ( double cylinderSurfaceArea ( 5.0 , 8.0 ) - 408.41 ) < 0.001 ) ;
assert ( fabs ( double cylinderSurfaceArea ( 7.0 , 10.0 ) - 747.7 ) < 0.001 ) ;
```



Question 12

Block 01 :- input sales

Block 02 :- Ture

Block 03 :- False

Block 04 :- $\text{comis} = 1000 * \text{sales}$

Block 05 :- $\text{comis} = 3000 * \text{sales}$

Question 5
Not yet answered
Marked out of 5.00
Flag question

Fill the blanks in the following C program so that it will print following pattern to the screen.
Note: you can only use the given functions and variables to fill the blanks.

output: first-first-first*

```
#include<stdio.h>
/* function declaration */
void func1(int num1 );
void func2();
int func3(char c);
char func4(int n1,int n2);
int main () {
    int n1=100;
    char c1='b';
    char c2='c';
    func1( );
    ( );
    printf("%c",func4(func3( ), ( ) ));
    return 0;
}
void func1(int num1 ){
    int i;
    if (num1 == 100)
```

```

int i;
if (num1 == 100)
    for (i=1; i < 3; ++i) {
        func2();
        printf("-");
    } else
        printf("Second");
}
void func2() {
    printf("first");
}
int func3(char c) {
    switch (c) {
        case 'a': return 1;
        case 'b': return 2;
        case 'c': return 3;
    }
}
char func4(int n1, int n2) {
    if (n1==2 && n2==3)
        return '*';
    else
        return '+';
}

```

Question 13

```

func1 ( n1 );
func2 ( );
printf( " %c ", func4( func3 ( c1 ), func3 ( c2 ) ) );


```

Fill the blanks in the following c program so that it will print following pattern to the screen. Note: you can only use the given functions and variables to fill the blanks.

Output: firstthird-firstthird-firstthird9

```
#include <stdio.h>
/* function declaration */
void func_a(int num1);
void func_b();
int func_d(char c);
char func_e(int n1,int n2);
int main ()
{
    int m1 = 100;
    char c1 = 'a';
    char c2 = 'c';
    func_a( );
    ( );
    printf("%c",func_e(func_d( ), ( ) ( )));
```

```
int i;
if (num1 == 100)
    for (i = 1; i < 3; ++i)
    {
        func_b();
        printf("-");
    }
else
    printf("Second");
}
void func_b()
{
    printf("first");
    printf("third");
}
int func_d(char c)
{
    switch (c)
    {
        case 'a': return 1;
        case 'b': return 2;
```





Question 14

```

func_a ( m1 );
func_b ( );
printf( " %c ", func_e( func_d ( c1 ), func_d ( c2 ) ) );

```



Question 15

```

#include <stdio.h>


int main (void)
{
    char num[100], l;


    while (1 )
    {
        printf("Enter the number : ");
        scanf("%s", &num);

        if (num[0] == '-')
        {
            return -1 ;
        }
        for (i = 0 ; num[i] != '\0' ; i++)
        {
            printf(" %c , ", num[i]);
        }

        puts(" ");
    }
    return 0 ;
}

```





Question 16

```
#include <stdio.h>

int main (void)
{
    int twoD[3][3];
    int i , j ;
    int sum_row[3] = {0} ;
    int sum_columns[3] = {0};

    printf("input element of matrix : \n");

    for (i = 0 ; i < 3 ; i++)
    {
        for(j = 0 ; j < 3 ; j++)
        {
            printf("element - [%d],[%d] : " , i , i);
            scanf("%d" , &twoD[i][j]);
        }
    }

    printf("\n2D array is : \n");

    for (i = 0 ; i < 3 ; i++)
```

```

{
    for (j = 0 ; j < 3 ; j++)
    {
        printf("%d ", twoD[i][j]);
    }
    puts(" ");
}

printf("\nAfter setting 0 in lower triangular\n");

printf("\n2D array is : \n");

for (i = 0 ; i < 3 ; i++)
{
    for (j = 0 ; j < 3 ; j++)
    {
        if (i <= j)
        {
            printf("%d ", twoD[i][j]);
        }
        else
        {
            twoD[i][j] = 0 ;
            printf("%d ", twoD[i][j]);
        }
    }
    puts(" ");
}

printf("\nThe sum of rows : ");
for (i = 0 ; i < 3 ; i++)
{
    for (j = 0 ; j < 3 ; j++)
    {
        sum_row[i] += twoD[i][j];
    }
    printf("%d ", sum_row[i] );
}

printf("\nThe sum of columns : ");
for (i = 0 ; i < 3 ; i++)
{


```

```

        for (j = 0 ; j < 3 ; j++)
        {
            sum_columns[i] += twoD[j][i];
        }
        printf("%d ",sum_columns[i] );
    }

    return 0 ;
}

```



Question 16

```
#include <stdio.h>
```

```
//function main program execution
```

```
int main (void )
```

```
{
```

```
    int i ,num;
```

```
    int myArr[8] ;
```

```
    printf("Enter the number : ");
```

```
    scanf("%d" , &num);
```



```

myArr[0] = num ;
printf("\n%d ", myArr[0]);

for (i = 1 ; i < 8 ; i++ )
{
    myArr[i] = myArr[i-1] - (i*i) ;
    printf("%d ", myArr[i]);
}

return 0 ;
} //end function main

```



Question 17

01 :- pow
02 :- fabs
03 :- b

04 :- pow

05 :- c

Question 5
yet answered
marked out of 100
Flag question

Complete the following C program to fill an integer array with following numbers. You must use at least 10 lines of code in your program.

1	2	3	5	8	13	21	34	87
---	---	---	---	---	----	----	----	----

element 1 = 1
element 2 = 2
element 3 = element 1 + element 2
element 4 = element 2 + element 3
.....
.....
element 8 = element 6 + element 7
element 9 (Last value) = total of element 1 to element 8

```
#include <stdio.h>
int main(void)
{
    int numArr[9];
    .....
    .....

    return 0;
}
```

Question 18

```
#include <stdio.h>
```

```
//function main program execution
```

```
int main (void )
```

```
{
```

```
    int i , sum ;
```

```
    int numArr[9] ;
```

```
    numArr[0] = 1 ;
```

```
    numArr[1] = 2 ;
```

```
    sum = numArr[0] + numArr[1] ;
```

```
    printf("%d %d ", numArr[0] , numArr[1]);
```

```
    for (i = 2 ; i < 8 ; i++)
```


```

    {
        numArr[i] = numArr[i-2] + numArr[i-1] ;
        printf("%d ", numArr[i]);
        sum += numArr[i] ;
    }
    numArr[8] = sum ;
    printf("%d", numArr[8] );

    return 0 ;

} //end function main

```




Question 19


```

8 line :- scanf("%d ", &base );
11 line :- scanf( "%d ", &exp );
13 line :- //get power of an integer
16 line :- result *= base ;
20 line :- printf( "Answer = %d ", result );

```



Question 20

```
#include <stdio.h>
```

```
int main (void)
{
```

```

int twoD[3][3];
int i , j ;
int sum_row[3] = {0} ;
int sum_columns[3] = {0};

printf("input element of matrix : \n");

for (i = 0 ; i < 3 ; i++)
{
    for(j = 0 ; j < 3 ; j++)
    {
        printf("element - [%d],[%d] : " , i , i);
        scanf("%d" , &twoD[i][j]);
    }
}

printf("\n2D array is : \n");

for (i = 0 ; i < 3 ; i++)
{
    for (j = 0 ; j < 3 ; j++)
    {
        printf("%d " , twoD[i][j]);
    }
    puts(" ");
}

printf("\nAfter settinf 1 in upper tringular\n");

printf("\n2D array is : \n");

for (i = 0 ; i < 3 ; i++)
{
    for (j = 0 ; j < 3 ; j++)
    {
        if (i >= j)
        {
            printf("%d " , twoD[i][j]);
        }
        else
        {
            twoD[i][j] = 1 ;
        }
    }
}

```

```

                printf("%d ", twoD[i][j]);
            }

        }
        puts(" ");
    }

    printf("\nThe sum of rows : ");
    for (i = 0 ; i < 3 ; i++)
    {
        for (j = 0 ; j < 3 ; j++)
        {
            sum_row[i] += twoD[i][j];
        }
        printf("%d ",sum_row[i] );
    }

    printf("\nThe sum of columns : ");
    for (i = 0 ; i < 3 ; i++)
    {
        for (j = 0 ; j < 3 ; j++)
        {
            sum_columns[i] += twoD[j][i];
        }
        printf("%d ",sum_columns[i] );
    }

    return 0 ;
}

```

9
answered
out of
question

Write a C program to calculate and print the yearly interest for a fixed deposit. The customer Id(4 digit) and fixed deposit amount should be obtained by the user from the keyboard and display the total interest to be paid for the customer. The interest rates are as follow

Balance	Interest Rate(%)
20000 or less	3
above 20000 but less than or equal to 200000	5
above 200000 but less than or equal to 1000000	7
above 1000000	10

If the interest exceeds 50000 then 3% of tax payment will be deducted.

Test Input Data :
1101
2000000

Sample Calculation:
 $2000000 * 10 / 100 = 200000$
 $Final\ interest\ payment = 200000 - 200000 * (3 / 100) = 194000$

Expected Output :
Customer ID : 1101
Fixed Deposit Amount : 2000000
Interest : 194000

Question 21

```
#include <stdio.h>
```

```
int main()
```

```
{
```

```
    char name[50];
```

```
    int amount , tax ;
```

```
    printf("Customer name : ");
```

```
    scanf("%s" , name);
```

```
    printf("Fixed Diposit amount : " );
```

```
    scanf("%d" , &amount);
```

```
    if(amount <= 20000)
```

```
    {
```

```
        tax = amount * (3.0 / 100) ;
```

```
    }
```

```
    else if(amount > 20000 && amount <= 200000)
```

```
    {
```

```
        tax = amount * (5.0 / 100) ;
```

```
    }
```

```

else if(amount > 200000 && amount <= 1000000)
{
    tax = amount * (7.0 / 100);
}
else if(amount > 1000000)
{
    tax = amount * (10.0 / 100);
}

if (tax > 50000)
{
    tax = tax - tax * (3.0 / 100);
}

printf("Interest : %d" , tax);
return 0;
}

```

Write a C program to read and display all content from file "studentcount.dat" that has the subject name, and the student count of several subjects offered by an institute. Also find and display the **most popular subject**.

studentCount file


Maths 5
Science 10
History 2
Geography 8
English 3

The output of the main program must be formatted as follows:

Subject Name	Student Count
Maths	5
Science	10
History	2
Geography	8
English	3

Most popular subject is : Science

Question 22



```
studentcount - Notepad
File Edit Format View Help
Math      5
science   10
History    2
Geography  8
English    3

Ln 1, Col 1    100%    Windows (CRLF)    UTF-8
```

```
#include <stdio.h>
#include <string.h>

int main (void)
{
    char sub[20];
    char m_sub[20];
    int count , most = 0 ;
    FILE *student ;
    student = fopen ("studentcount.dat" , "r+");

    if (student == NULL)
    {
        printf("File cannot open");
        return -1 ;
    }

    printf("Subject name \t\t student count\n");
    fscanf(student , "%s %d" , sub , &count);


    most = count ;
    while (!feof (student))
    {
        printf("%s \t \t \t %d \n" , sub , count );
        if (most < count)
        {
            strcpy (m_sub , sub);
            most = count ;
        }
        fscanf(student , "%s %d" , sub , &count);
    }
    printf("\nMost populay subject is : %s" , m_sub);
}
```



```

    fclose(student);
    return 0;
}

```



```

    if ((age < 8) || (age > 60))
    {
        if (size == 1)
            discount = 0 ;
        else if (size == 2)
            discount = price * size * 0.05;
        else if (size == 3)
            discount = price * size * 0.2;
        else if (size == 4)
            discount = price * size * 0.5;
        else if (size == 5)
            discount = price * size * 0.7;
    }
    else
    {
        if (size == 1) || (size == 2)
            discount = 0 ;
        else if (size == 3)
            discount = price * size * 0.05;
        else if (size == 4)
            discount = price * size * 0.1;
        else if (size == 5)
            discount = price * size * 0.2;
    }

    return discount ;
}

```

Question 23

- 01 :- float
- 02 :- int
- 03 :- int
- 04 :- char flavour
- 05:- discount ;

Book publishing house distributes books to bookstores. Book publishers records following book details before the distribution.

Book No integer
Book Name char[50]
Book Price float
Quantity integer

Following C program uses a structure called "Book" to store book details before the distribution. You need to enter the details of 3 books from keyboard and calculate the total price of each book based on the quantity ordered. Finally print the details as shown in second table. Complete the following C code by filling in the missing words/statements.

Input Values:

Book No	Book Name	Book Price	Quantity
1001	C Programming	1500.00	12
1002	Algorithms	1750.00	8
1003	Java	1200.00	10

Output:

Book No	Book Name	Total Price
1001	C Programming	18000.00
1002	Algorithms	14000.00
1003	Java	12000.00

```
#include<stdio.h>
```

```
{
    int bookNo;
    char bookName[50];
    double bookPrice;
    int qty;
```

```
};

int main(void){
    struct book[3];
    int i;
    float total[3]={0};
    for(i=0; i <= 3; i++){
        printf("Enter Book No: ");
        scanf("%d",&book[i].bookNo);
        printf("Enter Book Name: ");
        scanf("%s",&book[i].bookName);
        printf("Enter Book Price: ");
        scanf("%f",&book[i].bookPrice);
        printf("Enter Book Quantity: ");
        scanf("%d",&book[i].qty);


        total[i] = book[i].bookPrice * book[i].qty;
    }
    printf("Book No\tBook Name\tTotal Price\n");
    for(i=0;i<3;i++){
        printf("%d\t%s\t%.2f\n",
```

Question 24

```

01 :- struct Book
02 :- struct Book
03 :- scanf( " %s " , book[i] . bookName ) ;
04 :- total[ i ]
05 :- printf( " %d \t %s \t %.2f " , book[i].bookNo , book[i] . bookName , total[ i ] ) ;

```



Question 25

```

#include <stdio.h>
int main (void)
{
    int n , i ;
    float result = 0 ;

    printf("Enter the number : ");
    scanf("%d" , &n);

    for (i = 1 ; i <= n ; i++)
    {
        result += 1.0 / i ;
    }


    printf("\nanswer is = %.2f" , result);
}


```

A cafeteria that provides food parcels gets pre orders from customers. The following flowchart is drawn to calculate and display amount of a customer.

Write the relevant instructions (Block 01 - 05) in the given space.

Food Parcel Type	Price of a parcel(Rs.)
A	200.00
B	300.00





Question 26

Block 01 :- False

Block 02 :- True

Block 03 :- quantity * 200

Block 04 :- quantity * 300

Block 05 :- total price

Question 6
Not yet answered
Marked out of 5.00
Flag question

Write two assert statements to test the following function. This function will return area of trapezoid when it's short base and height(h) are passed as parameters.

```

double trapezoidArea(double b1, double b2, double h){
    double area;
    area = h * (b1 + b2) / 2.0;
    return area;
}
  
```

Sample Data

Short base(b1)	Long base(b2)	Height(h)	Area of trapezoid(area)
10.0	15.0	8.0	100.0
28.0	15.0	7.0	150.5

Question 27


```
assert ( fabs ( trapezoidArea ( 10.0 , 15.0 , 8.0 ) -100.0 ) < 0.0001 );  
assert ( fabs ( trapezoidArea ( 28.0 , 15.0 , 7.0 ) -150.5 ) < 0.0001 );
```

Question 4

Not yet answered

Marked out of 5.00

Flag question

Following C program is used to read numbers from a file called "number.dat" that is shown below.

number.dat

2 4 6 8

Furthermore, this program allows to enter another number from the key board and store it in the "number.dat" file, if the file does not already have that number and it is an even number. If the number exist in the file or if it is an odd number, display an error message. (Assume the new number is >0).

Fill the missing words/statements in following C program.

```
#include <stdio.h>  
int main( void)  
{  
    int number, newNumber;  
    printf("Enter Number: ");  
    scanf("%d", &newNumber);  
  
    FILE *numPtr;  
    numPtr = fopen("number.dat", );  
    if(numPtr == NULL)  
    {  
        printf("File could not be opened \n");  
        return -1;  
    }  
}
```

Quiz

Finish atten

Time left 0:5

1 2

9 10

FEEDBACK

15

```

int number, newNumber;
printf("Enter Number: ");
scanf("%d", &newNumber);

FILE *numPtr;
numPtr = fopen("number.dat", r+ );
if(numPtr == NULL)
{
    printf("File could not be opened \n");
    return -1;
}


fscanf(numPtr, "%d", &number);
while(!feof( numPtr ))
{
    if( (number == newNumber) || ( number % 2 == 1))
    {
        printf("Invalid Number.");
        return -1;
    }
    fscanf (numPtr, "%d", &number);
}

fprintf(numPtr, "%d ", number );
fclose(numPtr);
return 0;
}


```

Question 28


- 01 :- "a+ "
- 02 :- numPtr
- 03 :- newNumber
- 04 :- fscanf
- 05 :- newNumber




Question 29



Question 30



Question 31



Question 32

```

#include <stdio.h>

int main (void)
{
    int i , pass = 0 , fail = 0;
    float avg = 0 ;
    float marks[10] = {75.00,45.00,61.00,91.00,55.00,43.00,78.00,56.00,95.00,12.00};


    for (i = 0 ; i < 10 ; i++)
    {
        avg += marks[i] ;
    }
    avg = (float)avg / 10.0 ;

    for (i = 0 ; i < 10 ; i++)
    {
        if (avg <= marks[i])
        {
            pass += 1 ;
        }
        else
        {
            fail += 1 ;
        }
    }

    printf("no of pass students = %d\n" , pass);
    printf("no of fail students = %d" , fail);

    return 0 ;
}

```



Question 33

```
#include <stdio.h>
```

```
int main (void)
```

```
{
```

```
    int num[5] = {2,5,8,4,9};
```

```
    int reverse[5];
```

```
    int i , j = 0;
```

```
    printf("After reverse array values\n");
```

```
    for (i = 4 ; i >= 0 ; i--)
```

```
    {
```

```
        reverse[j] = num[i];
```

```
        printf("%d ", reverse[j]);
```

```
        j++;
```

```
    }
```

```
    return 0;
```

```
}
```


Sri Lanka Institute of Information Technology

Question 15

Not yet answered

Marked out of 5.00

Flag question

A 2D array called **att** is used to store the attendance of 4 students in a class. A sample dataset is shown below.

1	0	1	1	1
1	1	1	1	1
1	1	0	1	1
1	1	1	1	1

Complete the following C code to determine and display the students (row number) who has attended to the class all five days.

In this example the students numbers are 2, 4

```
#include <stdio.h>
int main(void)
{
    int att[5][5] = {{1, 0, 1, 1, 1}, {1, 1, 1, 1, 1}, {1, 1, 0, 1, 1}, {1, 1, 1, 1, 1}, {1, 1, 1, 1, 0}};
    .....
    .....
    .....
    return 0;
}
```

Quiz na

1

MCQ (2 MA

1 2

8 9

ESSAY (5 M

11 12

18 19

ESSAY (10

25

FEEDBACK

26

Question 34

```
#include <stdio.h>
```

```
int main (void)
```

```
{
```

```
    int att[5][5] = {{1,0,1,1,1},{1,1,1,1,1},{1,1,0,1,1},{1,1,1,1,1},{1,1,1,1,0}};
```

```
    int i, j, count ;
```

```
    printf("All five days attendance students = ");
```

```
    for (i = 0 ; i < 5 ; i++)
```

```
    {
```

```
        count = 0 ;
```

```
        for (j = 0 ; j < 5 ; j++)
```

```
        {
```

```
            if(att[i][j] == 1)
```

```
            {
```

```
                count += 1 ;
```

```
            }
```

```
        }
```

```
        if(count == 5)
```

```
        {
```


```
            printf("%d ", i+1 );
```

```

    }
}


return 0;
}

```



Question 35

Before the programming Create a file and store the Question's details



```
#include <stdio.h>
```

```
int main (void)
{
```

```

char code[10];
char discri[50];
float price ;

FILE *menu ;
menu = fopen("menu.dat" , "r+");

if (menu == NULL)
{
    printf("File cannot open");
    return -1 ;
}

fscanf(menu , "%s %s %f" , code , discri , &price);
printf("Item code \t description \t price \n");

while (! feof (menu))
{
    printf("%s \t\t %s \t %.2f\n" , code , discri , price);
    fscanf(menu , "%s %s %f" , code , discri , &price);
}
fclose (menu);
return 0 ;
}


```

```

C:\Users\Nimesh\OneDrive - Sri Lanka Institute of Information Technology\Desktop\ip final exam\ip final 1\Question 35.c.exe
Item code      description      price
S1             proawns        675.00
S2             Fishes         850.00
S3             Chicken        575.00

-----
Process exited after 0.03131 seconds with return value 0
Press any key to continue . . .

```



Question 36

Before the programming Create a file and store the Question's details



```
#include <stdio.h>
```

```
int main (void)
```

```
{
```

```
    char type ;
```

```
    float amount , deposit = 0 , withdraw = 0;
```

```
    FILE *bank ;
```

```
    bank = fopen ("bank.dat" , "r+");
```

```

if(bank == NULL)
{
    printf("File cannot open");
    return 0 ;
}


fscanf(bank , " %*d %c %f" , &type , &amount);

while (!feof (bank))
{
    if(type == 'D')
    {
        deposit += amount ;
    }
    else
    {
        withdraw += amount ;
    }
    fscanf(bank , " %*d %c %f" , &type , &amount);
}

printf("Total number of deposits = %.2f\n" , deposit);
printf("Total number of Withdrawals = %.2f" , withdraw);

return 0 ;
}


```



```

C:\Users\Nimesh\OneDrive - Sri Lanka Institute of Information Technology\Desktop\ip final exam\ip final 1\question 36.exe
Total number of deposits = 11000.00
Total number of Withdrawals = 12500.00
-----
Process exited after 0.03666 seconds with return value 0
Press any key to continue . . .

```



Question 37

```
#include<stdio.h>

int main (void)
{
    char itemCode[5] , description[50];
    float price;
    int i;

    FILE *shop;
    shop = fopen("menu.dat" , "a+");

    if (shop == NULL)
    {
        printf("File cannot open");
        return -1 ;
    }

    for (i = 0 ; i < 3 ; i ++ )
    {
        printf("Enter Item Code : ");
        scanf("%s" , itemCode);

        printf("Enter Description : ");
        scanf("%s" , description);
```



```


printf("Enter Price : ");
scanf("%f" , &price);

fprintf(shop , "%s %s %.2f\n" , itemCode , description , price);
}

fclose(shop);

return 0;
}

```



Question 38

.....Here have function implement part only.....

```

newBalance ( float amount , float balance , char type)
{
    float newBlance ;


    if (type == 'w')
    {
        newBalance = balnce - amount ;
        return newBalance ;
    }
}

```

```

    }
    else if (type == 'd')
    {
        newBalance = balnce + amount ;
        return newBalance ;
    }
}

```



Question 39

.....Here used #include <stdio.h> header file only.....

```
#include <stdio.h>
```

```
//function main program execution
```

```
int main (void)
```

```
{
```

```
    char password[100] ;
```

```
    int check[4] = {0};
```

```
    int len , i ;
```

```
    printf("Enter the password :") ;
```

```
    scanf("%s" , password);
```

```

for (i = 0 ; password[i] != '\0' ; i++)
{
    if(password[i] >= 65 && password[i] <= 90)
    {
        check[0] += 1 ;
        continue ;
    }

    else if(password[i] >= 97 && password[i] <= 122)
    {
        check[1] += 1 ;
        continue ;
    }

    else if(password[i] >= 48 && password[i] <= 57)
    {
        check[2] += 1 ;
        continue ;
    }

    else if(password[i] == '@' || password[i] == '&' || password[i] == '$')
    {
        check[3] += 1 ;
        continue ;
    }
    else
    {
        printf("\n invalid password");
        return -1 ;
    }
}

if (i < 10)
{
    printf("\n invalid password");
    return -1 ;
}

for (i = 0 ; i < 4 ; i++)
{
    if (check[i] == 0)
    {
        printf("\n invalid password");
    }
}

```

```

        return -1 ;
    }
}

printf("\n valid password");

return 0 ;
} //end function main

```

SLIT Sri Lanka Institute of Information Technology

Question 17
Not yet answered
Marked out of 5.00
Flag question

Consider the following table having two columns. First column has line numbers and the second has different expressions. Write the line numbers of the relevant statements in correct order to obtain the following output.

No	Supportive components for program writing
1	{
2	}
3	for(int j=0;j<=6;j++)
4	printf("* ");
5	for(int j=1;j<=6;j++)
6	printf("\n ");
7	for(int j=0;j<=16;j++);
8	for(int j=1;j == 6;j++)
9	for(int k=1;k<=6;k++)
10	for(int k=j;k<=6;k++)
11	if (j == k)
12	else

Output

```

*****
*****
*****
*****
*****
*****

```

Question 40

5 --> 1 --> 9 --> 1 --> 4 --> 2 --> 6 --> 2

Sri Lanka Institute of Information Technology

Question 15
Not yet answered
Marked out of 5.00
Flag question

Consider the following table having two columns. First column has line numbers and the second has different programing statements and expressions. Write the line numbers of the relevant statements in correct order to obtain the following output.

No	Supportive components for program writing
1	{
2	}
3	for(int j=0;j<=6;j++)
4	printf("%d ",j);
5	for(int j=1;j<=6;j++)
6	printf("\n ");
7	for(int j=0;j<=16;j++);
8	for(int j=1;j == 6;j++)
9	for(int k=1;k<=6;k++)
10	for(int k=j;k<=6;k++)
11	if (j == k)
12	else

Output

```

*****
*****
****
***
**
*

```

Quiz navigation

MCQ (2 MARKS)

1 2 3

9 10

ESSAY (5 MARKS)

11 12 13

19 20 21

ESSAY (10 MARKS)

25

FEEDBACK

26

Finish attempt ...

Time left 0:43:22

Question 41

5 --> 1 --> 9 --> 1 --> 4 --> 2 --> 6 --> 2

Ice Cream Discount		
Age	container size	discount
children less than 8 years old and senior citizens	1L	No discount
	2L	5%
	3L	20%
	4L	50%
	5L	70%
For others	1L	No discount
	2L	No discount
	3L	5%
	4L	10%
	5L	20%

and the prices are as follows

Ice Cream Price	
Flavour	Price per liter
Vanilla	250/=
Strawberry	500/=
Chocolate	600/=
Butterscotch	800/=

Complete the following function implementation of `calcDiscount()` that takes the size of the ice cream container (`size`), the flavour of the ice cream (`flavour`), and age (`age`) as parameters, which then calculates the discount to be deducted from the total amount. Complete the function by filling the missing statements to run the code properly.

...adding the missing statements to run the code properly.

```
float calcDiscount(int age, int size, char flavour)
{
    float discount = 0, price;
    if(flavour == 'v' || flavour == 'V')
        price = 250.00;
    else if(flavour == 's' || flavour == 'S')
        price = 500.00;
    else if(flavour == 'c' || flavour == 'C')
        price = 600.00;
    else if(flavour == 'b' || flavour == 'B')
        price = 800.00;
    if ((age < 8) || (age > 60))
    {
        if (size == 1)
            discount = 0;
        else if (size == 2)
            discount = price * size * 0.05;
        else if (size == 3)
            discount = price * size * 0.2;
        else if (size == 4)
            discount = price * size * 0.5;
        else if (size == 5)
            discount = price * size * 0.7;
    }
    else
    {
        if (size == 1) || (size == 2)
            discount = 0;
        else if (size == 3)
            discount = price * size * 0.05;
        else if (size == 4)
            discount = price * size * 0.1;
        else if (size == 5)
            discount = price * size * 0.2;
    }
    return discount;
}
```

Question 42

- 01 :- float
- 01 :- int
- 03 :- int
- 04 :- char flavour
- 05 :- discount