

Class 9: Structural Bioinformatics

Challana Tea

What is in the PDB database?

```
pdbstats <- read.csv('pdb.csv', row.names = 1)
knitr::kable(pdbstats)
```

	X.ray	EM	NMR	Multiple.methods	Neutron	Other	Total
Protein (only)	152,809	9,421	12,117	191	72	32	174,642
Protein/Oligosaccharide	9,008	1,654	32	7	1	0	10,702
Protein/NA	8,061	2,944	281	6	0	0	11,292
Nucleic acid (only)	2,602	77	1,433	12	2	1	4,127
Other	163	9	31	0	0	0	203
Oligosaccharide (only)	11	0	6	1	0	4	22

Q1: What percentage of structures in the PDB are solved by X-Ray and Electron Microscopy.

```
pdbstats$X.ray
```

```
[1] "152,809" "9,008" "8,061" "2,602" "163" "11"
```

```
as.numeric(pdbstats$X.ray)
```

Warning: NAs introduced by coercion

```
[1] NA NA NA NA 163 11
```

The commas are converting values containing them to NA values

```
n.xray <- sum(as.numeric(gsub(",", "", pdbstats$X.ray)))
n.xray
```

[1] 172654

```
n.em <- sum(as.numeric(gsub(",", "", pdbstats$EM)))
n.total <- sum(as.numeric(gsub(",", "", pdbstats$Total)))

round(((n.xray + n.em)/n.total), 2)
```

[1] 0.93

```
rm_comma_sum <- function(filecolumn) {
  sum(as.numeric(gsub(",", "", filecolumn)))
}
```

```
rm_comma_sum(pdbstats$X.ray)/rm_comma_sum(pdbstats$Total)
```

[1] 0.8590264

```
round(n.xray/n.total, 2)
```

[1] 0.86

Q2: What proportion of structures in the PDB are protein?

```
round((rm_comma_sum(pdbstats$Total[1])/n.total), 2)
```

[1] 0.87

Q3: Type HIV in the PDB website search box on the home page and determine how many HIV-1 protease structures are in the current PDB?

Using the Molstar viewer

Q4: Water molecules normally have 3 atoms. Why do we see just one atom per water molecule in this structure?

The structure has only been resolved to 2 Å, which is above the resolution needed to see hydrogen.

Q5: There is a critical “conserved” water molecule in the binding site. Can you identify this water molecule? What residue number does this water molecule have

H 308

Q6: Generate and save a figure clearly showing the two distinct chains of HIV-protease along with the ligand. You might also consider showing the catalytic residues ASP 25 in each chain and the critical water (we recommend “Ball & Stick” for these side-chains). Add this figure to your Quarto document.

Let's do some bioinformatics

Use the bio3D package for structural bioinformatics.

```
library(bio3d)
p <- read.pdb("1hsg")
```

Note: Accessing on-line PDB file

p

Call: read.pdb(file = "1hsg")

```
Total Models#: 1
Total Atoms#: 1686, XYZs#: 5058 Chains#: 2 (values: A B)

Protein Atoms#: 1514 (residues/Calpha atoms#: 198)
Nucleic acid Atoms#: 0 (residues/phosphate atoms#: 0)

Non-protein/nucleic Atoms#: 172 (residues: 128)
Non-protein/nucleic resid values: [ HOH (127), MK1 (1) ]
```




Figure 1: Fig. 1: A rendering of HIV-1 Pr active site with a bound ligand

Protein sequence:

```
PQITLWQRPLVTIKIGGQLKEALLDTGADDTVLEEMSLPGRWKPKMIGGIGGFIKVRQYD
QILIEICGHKAIGTVLVGPTPVNIIGRNLLTQIGCTLNFPQITLWQRPLVTIKIGGQLKE
ALLDTGADDTVLEEMSLPGRWKPKMIGGIGGFIKVRQYDQILIEICGHKAIGTVLVGPTP
VNIIGRNLLTQIGCTLNF
```

```
+ attr: atom, xyz, seqres, helix, sheet,
      calpha, remark, call
```

```
head(p$atom)
```

	type	eleno	elety	alt	resid	chain	resno	insert	x	y	z	o	b
1	ATOM	1	N	<NA>	PRO	A	1	<NA>	29.361	39.686	5.862	1	38.10
2	ATOM	2	CA	<NA>	PRO	A	1	<NA>	30.307	38.663	5.319	1	40.62
3	ATOM	3	C	<NA>	PRO	A	1	<NA>	29.760	38.071	4.022	1	42.64
4	ATOM	4	O	<NA>	PRO	A	1	<NA>	28.600	38.302	3.676	1	43.40
5	ATOM	5	CB	<NA>	PRO	A	1	<NA>	30.508	37.541	6.342	1	37.87
6	ATOM	6	CG	<NA>	PRO	A	1	<NA>	29.296	37.591	7.162	1	38.40

	segid	elesy	charge
1	<NA>	N	<NA>
2	<NA>	C	<NA>
3	<NA>	C	<NA>
4	<NA>	O	<NA>
5	<NA>	C	<NA>
6	<NA>	C	<NA>

```
p$atom[1,'resid']
```

```
[1] "PRO"
```

```
p$atom$resid[1]
```

```
[1] "PRO"
```

```
aa321(p$atom$resid[1])
```

```
[1] "P"
```

Normal Mode Analysis (NMA)

```
#Read an input structure
adk <- read.pdb('6s36')
```

Note: Accessing on-line PDB file
PDB has ALT records, taking A only, rm.alt=TRUE

```
adk
```

```
Call: read.pdb(file = "6s36")
```

```
Total Models#: 1
  Total Atoms#: 1898, XYZs#: 5694 Chains#: 1 (values: A)

  Protein Atoms#: 1654 (residues/Calpha atoms#: 214)
  Nucleic acid Atoms#: 0 (residues/phosphate atoms#: 0)

  Non-protein/nucleic Atoms#: 244 (residues: 244)
  Non-protein/nucleic resid values: [ CL (3), HOH (238), MG (2), NA (1) ]
```


```
Protein sequence:
  MRIILLGAPGAGKGTQAQFIMEKYGIPQISTGDMLRAAVKSGSELGKQAKDIMDAGKLV
  TDELVIALVKERIAQEDCRNGFLLDGFPRTPQADAMKEAGINVDYVLEFDVPDELIVDKI
  VGRRVHAPSGRVYHVKFNPVKVEGKDDVTGEELTTRKDDQEETVRKRLVEYHQM
  TAPLIGYYSKEAEAGNTKYAKVDGTPVAEVRADLEKILG
```

```
+ attr: atom, xyz, seqres, helix, sheet,
      calpha, remark, call
```

```
#NMA
m <- nma(adk)
```

```
Building Hessian...      Done in 0.028 seconds.
Diagonalizing Hessian... Done in 0.371 seconds.
```

```
plot(m)
```



Make a video of this motion for Molstar

```
#Make a trajectory file  
mktrj(m, file="adk_m7.pdb")
```

PCA - Comparative structure analysis of Adenylate Kinase

First, extract the sequence

```
library(bio3d)  
aa <- get.seq("1ake_A")
```

Warning in get.seq("1ake_A"): Removing existing file: seqs.fasta

Fetching... Please wait. Done.

aa

```
      1      .      .      .      .      .      .      60
pdb|1AKE|A  MRIILLGAPGAGKGTQAQFIMEKYGIPQISTGDMRLRAAVKSGSELGKQAKDIMDAGKLVT
      1      .      .      .      .      .      .      60

      61      .      .      .      .      .      .      120
pdb|1AKE|A  DELVIALVKERIAQEDCRNGFLLDGFRTIPQADAMKEAGINVDYVLEFDVPDELIVDRI
      61      .      .      .      .      .      .      120

      121      .      .      .      .      .      .      180
pdb|1AKE|A  VGRRVHAPSGRVYHVKNPPKVEGKDDVTGEELTTRKDDQEETVRKRLVEYHQMTAPLIG
      121      .      .      .      .      .      .      180

      181      .      .      .      214
pdb|1AKE|A  YYSKEAEAGNTKYAKVDGTPVAEVRADLEKILG
      181      .      .      .      214
```

Call:

```
read.fasta(file = outfile)
```

Class:

```
fasta
```

Alignment dimensions:

```
1 sequence rows; 214 position columns (214 non-gap, 0 gap)
```

+ attr: id, ali, call

```
#b <- blast.pdb(aa)
#hits <- plot(b)
# hits
```

```
hits <- NULL
```

```
hits$ pdb.id <- c('1AKE_A','6S36_A','6RZE_A','3HPR_A','1E4V_A','5EJE_A','1E4Y_A','3X2S_A',
```

```
files <- get.pdb(hits$ pdb.id, path="pdbs", split=TRUE, gzip=TRUE)
```

Warning in get.pdb(hits\$ pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/1AKE.pdb.gz exists. Skipping download

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/6S36.pdb.gz exists. Skipping download

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/6RZE.pdb.gz exists. Skipping download

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/3HPR.pdb.gz exists. Skipping download

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/1E4V.pdb.gz exists. Skipping download

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/5EJE.pdb.gz exists. Skipping download

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/1E4Y.pdb.gz exists. Skipping download

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/3X2S.pdb.gz exists. Skipping download


Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/6HAP.pdb.gz exists. Skipping download

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/6HAM.pdb.gz exists. Skipping download

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/4K46.pdb.gz exists. Skipping download

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/3GMT.pdb.gz exists. Skipping download

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/4PZL.pdb.gz exists. Skipping download



Align and Superimpose

```
#Align related pdbs
pdbs <- pdbaln(files, fit = TRUE, exefile='msa')
```

Reading PDB files:
 pdbs/split_chain/1AKE_A.pdb
 pdbs/split_chain/6S36_A.pdb
 pdbs/split_chain/6RZE_A.pdb
 pdbs/split_chain/3HPR_A.pdb

```

pdbs/split_chain/1E4V_A.pdb
pdbs/split_chain/5EJE_A.pdb
pdbs/split_chain/1E4Y_A.pdb
pdbs/split_chain/3X2S_A.pdb
pdbs/split_chain/6HAP_A.pdb
pdbs/split_chain/6HAM_A.pdb
pdbs/split_chain/4K46_A.pdb
pdbs/split_chain/3GMT_A.pdb
pdbs/split_chain/4PZL_A.pdb
    PDB has ALT records, taking A only, rm.alt=TRUE
.   PDB has ALT records, taking A only, rm.alt=TRUE
.   PDB has ALT records, taking A only, rm.alt=TRUE
.   PDB has ALT records, taking A only, rm.alt=TRUE
..  PDB has ALT records, taking A only, rm.alt=TRUE
.... PDB has ALT records, taking A only, rm.alt=TRUE
.   PDB has ALT records, taking A only, rm.alt=TRUE
...

```

Extracting sequences


```

pdb/seq: 1   name: pdbs/split_chain/1AKE_A.pdb
    PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 2   name: pdbs/split_chain/6S36_A.pdb
    PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 3   name: pdbs/split_chain/6RZE_A.pdb
    PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 4   name: pdbs/split_chain/3HPR_A.pdb
    PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 5   name: pdbs/split_chain/1E4V_A.pdb
pdb/seq: 6   name: pdbs/split_chain/5EJE_A.pdb
    PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 7   name: pdbs/split_chain/1E4Y_A.pdb
pdb/seq: 8   name: pdbs/split_chain/3X2S_A.pdb
pdb/seq: 9   name: pdbs/split_chain/6HAP_A.pdb
pdb/seq: 10  name: pdbs/split_chain/6HAM_A.pdb
    PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 11  name: pdbs/split_chain/4K46_A.pdb
    PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 12  name: pdbs/split_chain/3GMT_A.pdb
pdb/seq: 13  name: pdbs/split_chain/4PZL_A.pdb

```

```
ids <- basename.pdb(pdb$ids)
graphics.off()
par(mar=c(0.5,0.5,0.5,0))
plot(pdb, labels=ids, width = 5, height = 4)
```

```
#Run a PCA
pc.xray <- pca(pdb)
plot(pc.xray)
```



Make a trajectory of the displacements captured by PCA

```
mktrj(pc.xray, pc = 1, file = "pc_1.pdb")
```