

Ninja RMM Public API v2.0.5 Device Filter Syntax

Device filter (df) parameter is a URL encoded string with the following syntax

- Organization Filter:
 - o **org=<OrgID>** - single organization ID
 - o **org in (<OrgID1>, <OrgID2>, ...)** – list of organization IDs
 - o **org!=<OrgID>** - All organizations except specified organization ID
 - o **org nin (<OrgID1>, <OrgID2>, ...)** – All organizations except specified organization IDs
- Location filter
 - o **loc=<LocID>** - single location ID
 - o **loc in (<LocID1>, <LocID2>, ...)** – list of location IDs
 - o **loc!=<LocID>** - All locations except specified location ID
 - o **loc nin (<LocID1>, <LocID2>, ...)** – All locations except specified location IDs
- Device Role filter
 - o **role=<RoleID>** - single role ID
 - o **role in (<RoleID1>, <RoleID2>, ...)** – list of role IDs
 - o **role!=<RoleID>** - All roles except specified role ID
 - o **role nin (<RoleID1>, <RoleID2>, ...)** – All roles except specified role IDs
- Device ID filter
 - o **id=<DeviceID>** - Single device
 - o **id in (<DeviceID1>, <DeviceID2>, ...)** – List of Device Identifiers
- Device Class filter (enumeration)
 - o **class=<ClassName>**
 - o **class in (ClassName1, ClassName2, ...)**

Where *ClassNameX* is one of the predefined Node Classes:

- **WINDOWS_SERVER**
- **WINDOWS_WORKSTATION**
- **LINUX_WORKSTATION**
- **MAC**
- **VMWARE_VM_HOST**
- **VMWARE_VM_GUEST**
- **LINUX_SERVER**
- **MAC_SERVER**
- **CLOUD_MONITOR_TARGET**
- **NMS_SWITCH**
- **NMS_ROUTER**

- NMS_FIREWALL
 - NMS_PRIVATE_NETWORK_GATEWAY
 - NMS_PRINTER
 - NMS_SCANNER
 - NMS_DIAL_MANAGER
 - NMS_WAP
 - NMS_IPSLA
 - NMS_COMPUTER
 - NMS_VM_HOST
 - NMS_APPLIANCE
 - NMS_OTHER
 - NMS_SERVER
 - NMS_PHONE
 - NMS_VIRTUAL_MACHINE
 - NMS_NETWORK_MANAGEMENT_AGENT
- Device Approval Status filter (enumeration)
 - **status=PENDING** – return devices with awaiting Approval
 - **status=APPROVED** – return approved devices (Default)
 - Device online/offline status filter (Predicate)
 - **online** – return devices currently online
 - **offline** – return devices currently offline
 - Device creation date filter
 - **created after** YYYY-MM-DD – return devices created after specified date
 - **created before** YYYY-MM-DD – return devices created before specified date

Before and After filters can be specified together to filter results for devices created during specified date range.
 - Group membership filter
 - **group** <GroupID> - filter records for devices that are members of predefined groups/saved search

Filters can be combined with **AND** operator

Examples:

/v2/queries/logged-on-users?df=online	Last users on all devices that are currently online
/v2/queries/software?df=group%203&pageSize=100	Software inventory for devices in group #3
/v2/devices?df=class%3DWINDOWS_SERVER%20AND%20offline	List of offline Windows Servers