

root

[Go Up](#)

Name	GaussianProcessRegression
Version	1.0
Description	RFF-accelerated Gaussian Process Regression
License	SeeLICENSE.TXT
Copyright	Copyright (C) 2022 HPCC Systems
Authors	HPCCSystems
DependsOn	ML_Core
Platform	8.4.0

Table of Contents

GPRI.ecl
Types.ecl

GPRI

[Go Up](#)

IMPORTS

`python3 | ML_Core.Types | std.system.Thorlib | Types | Internal.rffGPR |`

DESCRIPTIONS

GPRI GPRI

	GPRI
--	------

No Documentation Found

Children

1. [GetSession](#) : Initialize GPR on all nodes and return a session ID to be used in the following process
2. [fit](#) : Train a RFF accelerated GPR model
3. [predict](#) : Predict using trained GPR model

GETSESSION GetSession

[GPRI \](#)

INTEGER	GetSession
<code>()</code>	

Initialize GPR on all nodes and return a session ID to be used in the following process. This function needs to be called before any other process.

RETURN **INTEGER8** — sessID session ID to identify this session.

FIT fit

GPRI \

<code>DATASET(Layout_model2)</code>	fit
<code>(INTEGER session, DATASET(NumericField) x, DATASET(NumericField) y, UNSIGNED4 rff_dim = 10, REAL sigma = 1)</code>	

Train a RFF accelerated GPR model

PARAMETER session ||| INTEGER8 — No Doc

PARAMETER x ||| TABLE (NumericField) — No Doc

PARAMETER y ||| TABLE (NumericField) — No Doc

PARAMETER rff_dim ||| UNSIGNED4 — No Doc

PARAMETER sigma ||| REAL8 — No Doc

RETURN TABLE (layout__model2) — Gaussian process regression model in Layout__model2 foramt.

PARAMS session session ID for the training process.

PARAMS x independent training data.

PARAMS y dependent training data.

PARAMS rff_dim dimesion of random fourier features.

PARAMS sigma squre root of the variance.

SEE ML_Core.Types.Layout_Model2

PREDICT predict

GPRI \

DATASET(NumericField)	predict
<pre>(INTEGER session, DATASET(Layout_model2) mod, DATASET(NumericField) x)</pre>	

Predict using trained GPR model

PARAMETER session ||| INTEGER8 — No Doc

PARAMETER mod ||| TABLE (layout_model2) — No Doc

PARAMETER x ||| TABLE (NumericField) — No Doc

RETURN TABLE (NumericField) — prediction result in NumericField format

PARAMS session session ID for the predicting process.

PARAMS mod trained GPR model.

PARAMS x input data for prediction.

SEE ML_Core.Types.NumericField

Types

[Go Up](#)

DESCRIPTIONS

TYPES Types

	Types
--	-------

No Documentation Found

Children

1. [initParams](#) : No Documentation Found
-

INITPARAMS initParams

[Types](#) \

	initParams
--	------------

No Documentation Found

FIELD nodeid ||| UNSIGNED4 — No Doc

FIELD nnodes ||| UNSIGNED4 — No Doc
