P3714

SEAT No.	:	
----------	---	--

[Total No. of Pages :2

Engg. - 28

T. E. (E & TC) (Semester - I)

MICROCONTROLLER AND APPLICATIONS (In Sem.)

		(2012 Pattern)	,
Time	e:1 H	lour]	[Max. Marks :30
Insti	ructio	ons to the candidates :	
	1)	Answer Q1 or Q2, Q3 or Q4, Q5 or Q6.	
	<i>2)</i>	Neat diagrams must be drawn wherever necessary.	
	3)	Figures to the right side indicate full marks.	
	4)	Assume suitable data if necessary.	
Q1)	a)	Explain selection criteria of microcontrollers for particu	lar application.[5]
	b)	Define Embedded system. Explain its characteristics.	[5]
		OR	
Q2)	a)	Compare Von Neumann and Harvard architecture.	[5]
	b)	What are limitations of 8 bit microcontroller?	[5]
Q 3)	a)	Explain structure of port 0 and port 1 of 8051.	[4]
	b)	Explain SCON register in detail. Also calculate the hex TH1 when the baud rate of the controller is 1200. OR	adecimal count in [6]
Q4)	a)	Calculate the hexadecimal values to be loaded in TH register for delay calculations of 1 msec using Time (Assume input frequency 12 MHz)	
	b)	Explain the interrupt structure of 8051 also list the vect priority can be changed?	or addresses.How [4]

- Q5) a) What are the various oscillator options? How they can be selected using config register.[5]
 - b) Draw and explain structure of Program Memory Map of PIC. [5]
 OR
- **Q6)** a) What are the features of PIC microcontroller? [4]
 - b) What is the function of WREG, Status Register in PIC microcontroller. Explain in detail. [6]

