New-Scale Security Operations Platform Release Notes

January 23, 2026

Have feedback on this guide? We'd love to hear from you!
Email us at docs@exabeam.com.

Disclaimer: Ensure you are viewing the most up-to-date version of this guide by visiting the Exabeam Documentation Portal.

Exabeam
1051 E. Hillsdale Blvd, 4th Floor
Foster City, CA 94404
650.209.8599

Copyright

All content in this document, including text, graphics, logos, icons, images, and video clips, is the exclusive property of Exabeam or its content suppliers and is protected by U.S. and international copyright laws. The compilation (meaning the collection, arrangement, and assembly) of all content in this document is the exclusive property of Exabeam and is also protected by U.S. and international copyright laws. The content in this document may be used as a resource. Any other use, including the reproduction, modification, distribution, transmission, republication, display, or performance, of the content in this document is strictly prohibited.

Copyright ©2026 Exabeam, Inc. All Rights Reserved.

Trademarks

Exabeam and the Exabeam logo are trademarks or registered trademarks of Exabeam. All third-party trademarks mentioned in this document are the property of their respective owners. The trademarks and logos displayed in this document may not be used without the prior written consent of Exabeam or their respective owners.

Products

Exabeam owns and retains all right, title and interest in and to the Exabeam's products and services and portions, features and/or functionality of Exabeam's products may be protected under Exabeam's patents, as well as patents pending.

Other Policies

For information regarding Exabeam's treatment of personally identifiable information, please review Exabeam's current privacy policy at www.exabeam.com/privacy.

Table of Contents

2026 Release Notes 7
January 2026 7
Cloud Collectors 7
Context Management 7
Log Stream 8
Site Collectors 2.16 9
Threat Detection Management 10
Resolved Issues 34
2025 Release Notes 35
December 2025 35
Attack Surface Insights 35
Cloud Collectors 36
Context Management 36
Correlation Rules 37
Log Sources 37
Log Stream 38
New-Scale Platform 38
Search 39
Threat Center 39
Threat Detection Management 40
November 2025 48
Attack Surface Insights 49
Automation Management 51
Cloud Collectors 53
Correlation Rules 54
Dashboards 55
Log Stream 56
New-Scale Platform 57
Search 58
Site Collectors 2.15 58
Threat Center 58
Threat Detection Management 59
Resolved Issues 69
October 2025 70
Attack Surface Insights 71
Automation Management 71
Cloud Collectors 71
Log Stream 72
New-Scale Platform 73
Outcomes Navigator 74
Search 75
Site Collectors 2.14 76
Threat Center 77
Threat Detection Management 78
Resolved Issues 82

September 2025 82
Automation Management 83
Cloud Collectors 83
Correlation Rules 84
Log Sources 86
Outcomes Navigator 87
Search 90
Site Collectors 2.13 90
Threat Center 91
Threat Detection Management 94
Resolved Issues 105
August 2025 105
Attack Surface Insights 105
Automation Management 107
Cloud Collectors 109
Context Management 110
Log Stream 111
Search 112
Site Collectors 2.12 113
Threat Center 114
Threat Detection Management 115
Resolved Issues 115
July 2025 116
Cloud Collectors 116
Context Management 117
Log Sources 117
New-Scale Platform 118
Outcomes Navigator 118
Site Collectors 2.11 (July 2025) 118
Threat Center 119
Threat Detection Management 120
Resolved Issues 122
June 2025 123
Attack Surface Insights 124
Cloud Collectors 127
Context Management 128
Correlation Rules 129
Dashboards 130
Log Stream 131
Multi-Org Management 131
Outcomes Navigator 132
Search 133
Service Health and Consumption 134
Site Collectors 2.10 135
Threat Detection Management 136
Resolved Issues 137
May 2025 137

Attack Surface Insights 138
Cloud Collectors 138
Context Management 138
Correlation Rules 140
Log Stream 141
New-Scale Platform 141
Outcomes Navigator 142
Threat Center 143
Threat Detection Management 146
Resolved Issues 147
April 2025 147
Attack Surface Insights 147
Cloud Collectors 148
Context Management 149
Dashboards 149
Log Sources 150
New-Scale Platform 150
Outcomes Navigator 151
Search 151
Service Health and Consumption 152
Site Collectors 2.8 152
Threat Center 153
Resolved Issues 153
March 2025 154
Cloud Collectors 154
Context Management 155
Dashboards 156
Multi-Org Management 156
New-Scale Platform 156
Outcomes Navigator 157
Search 159
Site Collectors 2.7 159
Threat Center 160
Threat Detection Management 162
Resolved Issues 162
February 2025 163
Automation Management 163
Cloud Collectors 163
Correlation Rules 164
Dashboards 167
Search 168
Service Health and Consumption 168
Site Collectors 2.6 168
Threat Center 169
Threat Detection Management 170
Resolved Issues 174
January 2025 175

Attack Surface Insights 175
Automation Management 176
Cloud Collectors 178
Context Management 179
Correlation Rules 179
Dashboards 179
Log Stream 180
New-Scale Platform 181
Outcomes Navigator 181
Search 182
Service Health and Consumption 183
Site Collectors 2.5 184
Threat Center 184
Threat Detection Management 188
Resolved Issues 188
Known Issues 190
Attack Surface Insights 190
Automation Management 190
Cloud Collectors 190
Context Management 190
Correlation Rules 190
Dashboards 191
Log Sources 191
Log Stream 191
New-Scale Platform 191
Outcomes Navigator 192
Search 196
Service Health and Consumption 197
Site Collectors 197
Threat Center 198
Threat Detection Management 198

2026 Release Notes

These release notes include information about new features, known issues, and resolved issues for the New-Scale Security Operations Platform in all 2026 New-Scale product releases.

- January 2026
- Known Issues


January 2026

The New-Scale Security Operations Platform includes the following addressed features and new features for January 2026.

Cloud Collectors

Feature	Description
Gmail BigQuery Cloud Collector	The Gmail BigQuery Cloud Collector is now available as part of Cloud Collectors to facilitate ingestion of the gmail logs.
Palo Alto Networks XDR Cloud Collector	The Palo Alto Networks XDR Cloud Collector is now available as part of Cloud Collectors to facilitate ingestion of the security alerts logs generated by Cortex XDR.
Early Access Collectors	
Mimecast Incydr Cloud Collector	The Mimecast Incydr cloud collector is now available as part of Cloud Collectors Early Access program, to facilitate ingestion of events from the File events data source. The early access program offers you an opportunity to gain access to the latest cloud collectors before their official release. To participate, see Sign Up for the Early Access Program.

Context Management

Feature	Description
Key Attribute Icon Added to Column Headers	Context Management now provides a visible indicator of which column in a custom context table (including filtered tables) represents the key attribute. The key icon (🔑) is displayed in the column header for the key attribute. The key indicator is also displayed in column headers for most types of pre-built context tables (all except the threat intelligence tables).  For more information about specific types of context tables, see Custom Context Tables or Pre-Built Context Tables in the *Context Management Guide*.

Feature	Description
New Pre-Built Context Tables	Two additional pre-built New-Scale detection context tables have been made available: • **Threat Unix Commands** – This context table is populated with a list of default Unix commands that are often used by attackers. • **Host To IP Excluded Hosts** – This context table is empty by default but can be populated with a list of domain controllers or other host servers that you want to exclude from host to IP mapping enrichment procedures. You can populate this context table manually or via an automated process as part of a Log Stream early access opportunity. For more information, see Pre-Built Detection Context Tables in the *Context Management Guide*.

Log Stream

Feature	Description
Enhanced Host to IP Enrichment	New-Scale Host to IP enrichment has been enhanced so that the default condition covers an expanded set of filters. It now includes all of the mapping functionality that was available in Advanced Analytics static mapping. In addition, early access opportunities are available to customize the enrichment condition or to exclude specific entities from the enrichment process. See the note below. For more information about this type of enrichment, see Host to IP Enrichment in the *Log Stream Guide*. **NOTE** **Early Access Opportunities** The following access opportunities are available to customize the host to IP enrichment functionality: • **Customize the Default Condition** – If you want to modify the default condition used to map hostnames and IP addresses, you can request access to a platform enrichment rule called `HostToIP`. When your access to this enricher is activated, you can view and edit the rule directly on the Log Stream **Enrichment** tab. • **Exclude Hosts from Enrichment** – If you want to exclude domain controllers or other specific host servers from the host to IP enrichment process, you can use an exclusion context table called **Host To IP Excluded Hosts**. This context table is a Pre-Built New-Scale Analytics table available in the Context Management application. It can be populated manually or via an automated process that loads domain controllers based on your Active Directory. If you would like to take advantage of either of the above early access opportunities, email the following group: logstream-ea@exabeam.com.

Site Collectors 2.16

Feature	Description
SELinux Precheck	Implemented a precheck that verifies if SELinux is set to enforcing mode during Site Collector installation. The CLI displays a warning indicating that SELinux may prevent Site Collector from functioning correctly. To eliminate errors, consider changing SELinux to permissive or disabled mode.
NiFi Upgrade	Upgraded Apache NiFi to version 2.7.2.
Enhancement for the Windows Active Directory Collector	Optimized performance for the Windows Active Directory collector for easy context onboarding and monitoring. The context tables are automatically created after the collector is configured. If you want, you can also create context tables manually.
SSL/TLS Certificate Lifetime Update	The default lifetime of SSL/TLS certificates has been reduced to 100 days to align with current best practices for security and certificate management. The shorter default period gives you greater control over certificate rotation, ensuring certificates are renewed and updated regularly without relying on long-term expiration dates.
Warning Message on Syslog Port Reuse	The user interface now displays a validation warning when you attempt to assign a port that is already in use by another Syslog collector within the same Site Collector instance. This prevents configuration conflicts by ensuring that each collector uses a unique protocol-and-port combination.

Threat Detection Management

Feature	Description
New and Updated Pre-Built Analytics Rules	You can now better detect threats with new and updated analytics rules. New pre-built analytics rules include: • **Cntx-PC-Critical-Crit** – Process is a known critical command: True\False • **Cntx-PC-Critical-Parent-Crit** – Parent process is a known critical command: True\False • **NumDCP-FWrite-AuditRule-U-DE** – An abnormal number of unique endpoints where this user modified the audit.rules file in Unix system. Pre-built analytics rules for which `description`, `applicable_events`, `supressScope`, `supressThreshold`, `severity`, and `detectionReason` were updated include: • **Fact-Web-TI-IOC** – An HTTP communication attempt has been made to a known malicious URL. These events may include both failed and successful traffic. • **Fact-Web-TI-RepDom** – An HTTP communication attempt has been made to a bad reputation domain. These events may include both failed and successful traffic. • **Fact-Web-TI-MalDom** – An HTTP communication attempt has been made to a malicious site category. These events may include both failed and successful traffic. Pre-built analytics rules for which `title`, `description`, `applicable_events`, `detectionReason`, and `mitre` were updated include: • **Prof-CA-DA-O-U** – This is the first time this user has successfully attached a volume to an instance. • **Prof-CA-DC-FromSnapshot-O-U** – This is the first time this user has successfully created a volume from a snapshot. Pre-built analytics rules for which `title`, `description`, `trainOnCondition`, `query`, and `detectionReason` were updated include: • **NumCP-PC-CritCmdC-O** – An abnormal number of critical command executions have been observed for the organization. Pre-built analytics rules for which `title`, `description`, `applicable_events`, and `detectionReason` were updated include: • **Prof-CA-IPM-AddMember-O-U** – This is the first time a user has successfully modified the attributes of a compute image in AWS and shared it with a user/group. • **Prof-Login-E-U-SZ** – This is the first time a successful login has been observed from this network zone for the this user. • **Prof-BPM-U-PBPolicy-O-U** – This is the first time this user has successful edited the IAM policy of a bucket in AWS. IAM bucket policies determine the access users and other identities have to the files and objects inside the storage bucket. • **Prof-CPM-Resource-U-R** – This is the first time an IAM policy of a resource in this directory has been successfully modified by this user in GCP. IAM policies determine the roles and permissions granted to users on a resource. • **Prof-CA-IC-O-U** – This is the first time this user has successfully created an image for compute instances. • **Prof-Web-WebDom-O-Tld** – This is the first time a successful HTTP communication to this top level domain has been observed for the organization. • **Prof-Login-E-O-SZ** – This is the first time a successful login has been observed from this network zone for the organization.

Feature	Description
	• **Prof-Login-E-DZ-SZ** – This is the first time a successful login has been observed from this source network zone to this destination network zone. • **Prof-Login-Plt-U-Plt** – This is the first time this user has attempted to log into this platform. These events do not include endpoint events and may include both failed and successful logins. • **Prof-DB-E-UDBN-SZ** – This is the first time a successful database event in this database has been observed for this user from this network zone. • **Prof-CPM-DestUT-U-DestUT** – This is the first time a member with this user type was successfully granted IAM permissions in a GCP policy. IAM policies determine the roles and permissions granted to users on a resource. • **Prof-BPM-U-PBACL-O-U** – This is the first time this user has successful edited the ACL policy of a bucket in AWS. • **Prof-Login-E-UD-DZ** – This is the first time a user in this department attempted to log into this network zone. These events may include both failed and successful logins. • **Prof-Login-E-SE-DZ** – This is the first time a user on this endpoint successful logged into this network zone. • **Prof-DB-E-UDBN-SIP** – This is the first time a database event in this database has been observed for this user from this IP address. • **Prof-CPM-Resource-O-R** – This is the first time an IAM policy of a resource in this directory has been successfully modified in GCP. IAM policies determine the roles and permissions granted to users on a resource. • **Prof-CPM-DestD-U-DestD** – This is the first time a user from this domain was successfully granted IAM permissions in a GCP policy. IAM policies determine the roles and permissions granted to users on a resource. • **Prof-Login-E-DE-SZ** – This is the first time a successful login has been observed from this network zone to the this endpoint. • **Prof-CA-IC-Publisher-O-Publisher** – This is the first time this image publisher has been observed in a successful virtual machine image creation for the organization. • **Prof-CPM-URevertAWS-O-U** – This is the first time this user has successfully changed the default policy version of a policy in AWS. Policies in AWS are the documents that dictate what permissions are granted to identities and resources. • **Prof-Login-E-U-DZ** – This is the first time this user successfully logged into this network zone. • **Prof-DB-E-UDBN-SE** – This is the first time a successful database event in this database has been observed for this user from this endpoint. • **Prof-Web-WebDom-O-U-WebDomIP** – This is the first time an HTTP communication attempt directly to an IP address has been observed for this user. These events may include both failed and successful traffic. Pre-built analytics rules for which `title`, `description`, `severity`, and `detectionReason` were updated include: • **Fact-Web-ShellUserAgent** – An HTTP communication attempt has been made with a user-agent associated with a command shell. These events may include both failed and successful traffic. • **Fact-EA-KerberosNotPreAuth** – A user has successfully authenticated against an endpoint via Kerberos authentication with preauthentication 0. Pre-built analytics rules for which `description`, `featureValue`, `trainOnCondition`, and `mitre` were updated include: • **Prof-PC-PN-PltUD-PN** – This is the first time this process has been executed in this platform for users in this department. This feature only models processes from - Windows and Unix commands, pentest tools, system enumeration, account enumeration and network sniffers.

Feature	Description
	• **Prof-PC-PN-PltSZ-PN** – This is the first time this process has been executed in this platform from this network zone. This feature only models processes from - Windows and Unix commands, pentest tools, system enumeration, account enumeration and network sniffers. • **Prof-PC-PN-DE-PN** – This is the first time this process has been executed on this endpoint. This feature only models processes from - Windows and Unix commands, pentest tools, system enumeration, account enumeration and network sniffers. • **Prof-PC-PN-Plt-PN** – This is the first time this process has been executed in this platform. This feature only models processes from - Windows and Unix commands, pentest tools, system enumeration, account enumeration and network sniffers. • **Prof-PC-PN-PltU-PN** – This is the first time this process has been executed in this platform for this user. This feature only models processes from - Windows and Unix commands, pentest tools, system enumeration, account enumeration and network sniffers. Pre-built analytics rules for which `description`, `severity`, `applicable_events`, and `mitre` were updated include: • **Fact-CPM-PCrit-GCPAdmin** – A cloud resource policy in GCP has been successfully modified and included critical administrative permissions. IAM policies determine the roles and permissions granted to users on a resource. Pre-built analytics rules for which `description`, `severity`, `applicable_events`, and `detectionReason` were updated include: • **Fact-Web-TITOR-Dom** – An HTTP communication attempt has been made to a known TOR web proxy domain. These events may include both failed and successful traffic. Pre-built analytics rules for which `featureValue`, `scopeValue`, `trainOnCondition`, and `mitre` were updated include: • **Prof-PC-PPN-PPN-PN** – This is the first time this child process has been observed for this matured parent process. • **Prof-PC-PPN-PN-PPN** – This is the first time this parent process has been observed for this matured child process. Pre-built analytics rules for which `title`, `description`, and `detectionReason` were updated include: • **Prof-Login-EmD-Plt-EmD** – This is the first time this email domain has been used to successfully log into this platform. • **Prof-CA-SPM-AddMember-O-U** – This is the first time this user has successfully modified the attributes of a compute snapshot in AWS and shared it with a user/group. • **Prof-CA-SC-O-U** – This is the first time this user has successfully created a snapshot of a compute instance. • **Prof-Web-TI-U-WebDom-Malicious** – This is the first time an HTTP communication attempt to this malicious web domain has been observed for this user. These events may include both failed and successful traffic. • **Prof-DB-U-DBN-UD** – This is the first time a database event in this database has been observed for a user in this department. A database event consists of any event or operation performed on a database. These events may include both failed and successful operations. • **Prof-BC-U-O-U** – This is the first time this user has successfully created a cloud storage bucket. Pre-built analytics rules for which `description`, `applicable_events`, and `severity` include: • **Prof-DBQ-RS-SZ-RS** – An abnormal successful database query response size has been observed for this source network zone.

Feature	Description
	• **Fact-BPM-Public-Policy** – The IAM policy or the ACL of an AWS bucket has been successfully modified to make it public to all users. • **Fact-BPM-Public-AccessBlock** – The public access block of a bucket or an account in AWS has been successfully modified to remove public access prevention. This activity enables the bucket or the entire account to become public to all users. • **Fact-CPM-PCrit-AWSAdmin** – A policy with critical administrative permissions was created or attached to an identity in AWS. Policies in AWS are the documents that dictates what permissions are granted to identities and resources. • **Fact-CPM-PCrit-GCPPublic** – A policy has been successfully modified to allow public access to a GCP resource. This activity should be noted since public resources can be read or downloaded by everyone. Pre-built analytics rules for which `description`, `severity`, and `detectionReason` were updated include: • **Fact-Web-TITOR-Url** – An HTTP communication attempt has been made to a URL containing '/tor/server'. These events may include both failed and successful traffic. • **Fact-Web-TIPhish-PhishDom** – An HTTP communication attempt has been made to a phishing associated domain. These events may include both failed and successful traffic. • **Fact-Web-TIRansomware** – An HTTP communication attempt has been made to a ransomware associated domain. These events may include both failed and successful traffic. Pre-built analytics rules for which `description`, `query`, and `mitre` include: • **NumDCP-CA-DAC-U-Disks** – An abnormal number of volumes were observed attached to instances for this user. Pre-built analytics rules for which `description`, `mitre`, and `detectionReason` were updated include: • **Prof-CA-IKM-KeyCreateGCP-O-U** – This is the first time this user added or modified an SSH key of an instance in GCP. These events may include both failed and successful modifications. Pre-built analytics rules for which `title` and `detectionReason` were updated include: • **Fact-CA-IPM-PublicAWS** – A compute image resource in AWS has been made public, granting access to all users. Pre-built analytics rules for which `description` and `applicable_events` were updated include: • **Prof-DBQ-RS-U-RS** – An abnormal successful database query response size has been observed in this database for this user. Pre-built analytics rules for which `description` and `query` were updated include: • **NumDCP-Login-DZC-UD-DZ** – An abnormal number of unique destination network zones have been observed in login events for users in this department. These events may include both failed and successful logins. • **NumDCP-Login-DZC-U-DZ** – An abnormal number of unique destination network zones have been observed in login events for this user. These events may include both failed and successful logins. • **NumSP-DBQ-RS-U-RS** – An abnormal database query response size has been observed for this user. These events may include both failed and successful queries. • **NumCP-DB-DBOpC-U** – An abnormal number of database operation events were observed for this user - this can include both unique and non-unique operations. A database operation consists of any action in a database query (i.e. SELECT, DROP, UPDATE, etc...). These events may include both failed and successful operations.

Feature	Description
	Pre-built analytics rules for which `description` and `detectionReason` were updated include: • **Prof-DB-U-DBN-U** – This is the first time a database event in this database has been observed for this user. A database event consists of any event or operation performed on a database. These events may include both failed and successful operations. • **Prof-CA-IRC-O-U** – This is the first time this user executed a remote command on an instance. These events may include both failed and successful executions. • **Prof-AuditPolicyMod-U-O-U** – This is the first time this user has performed an audit policy modification. These events may include both failed and successful modifications. • **Prof-CPM-UAttachAWS-O-U** – This is the first time this user attached a policy to an identity (user, group and role) in AWS. Policies in AWS are the documents that dictate what permissions are granted to identities and resources. These events may include both failed and successful attachments. • **Prof-Web-BinURL-O-U** – This is the first time an executable file was downloaded during an HTTP session for this user. • **Prof-CPM-UCreate-O-U** – This is the first time this user created or modified an IAM policy on this cloud platform. IAM policies determine the roles and permissions granted to users on a resource. These events may include both failed and successful creations\modifications. • **Prof-BPM-Public-O-U** – This is the first time this user has attempte to modify the IAM policy or the ACL of an AWS bucket to make it public to all users. These events may include both failed and successful modifications. • **Prof-AuditPolicyMod-E-O-SE** – This is the first time an audit policy modification has been observed from this endpoint. These events may include both failed and successful modifications. Pre-built analytics rules for which `applicable_events` and `query` were updated include: • **NumSP-Web-Bytes-U-BytesInPost** – An abnormal amount of bytes have been uploaded to the web with POST requests for this user. • **NumSP-Web-Bytes-U-BytesStorageIn** – An abnormal amount of bytes have been downloaded from file sharing websites for this user. Pre-built analytics rules for which `applicable_events` and `mitre` were updated include: • **Cntx-Web-WDCrit-FS** – Web domain is a file sharing domain: True\False Pre-built analytics rules for which `mitre` and `query` were updated include: • **NumSP-Network-BytesIn-SZ-Bytes** – An abnormal amount of bytes have been sent in inbound communication from this network zone. • **NumSP-SADLP-Bytes-U-Bytes** – An abnormal amount of outgoing bytes have been recorded in DLP alerts for this user. • **NumSP-Network-BytesOut-SZ-Bytes** – An abnormal amount of bytes have been sent in outbound communication from this network zone. • **NumCP-FDnld-EC-UD** – An abnormal amount of file download events have been observed for users in this department. • **NumCP-Git-EC-U** – An abnormal amount of GitHub API access events have been observed for this user. • **NumDC-Git-RepoC-U-Object** – An abnormal number of unique repository endpoints where secrets are generally stored, which may indicate unauthorized enumeration or insider reconnaissance activity. Repository name is parsed into the object field which is being counted here. • **NumCP-FDnld-EC-O** – An abnormal amount of file download events have been observed for the organization.

Feature	Description
	• **NumSP-NetworkF-BytesOut-SE-Bytes** – An abnormal amount of bytes have failed to be sent in outbound communication from this endpoint. • **NumSP-Network-BytesOut-SE-Bytes** – An abnormal amount of bytes have been sent in outbound communication from this endpoint. • **NumCP-AI-U-Guardrail-Block** – An abnormal amount of AI guardrail violations have been observed for a user. • **NumDCP-SADLP-ProtoC-U-Proto** – An abnormal number of unique protocols have been observed in DLP alerts for this user. • **NumCP-FDnld-EC-U** – An abnormal amount of file download events have been observed for this user. Pre-built analytics rules for which `mitre` and `severity` were updated include: • **Fact-FWrite-2018APT** – The 'ds7002.lnk', which is related to a known attack, was written to. Pre-built analytics rules for which `severity` and `detectionReason` were updated include: • **Fact-Login-PenTT** – A domain associated with known hacking tools has been observed in a login event. Pre-built analytics rules for which `description` was updated include: • **Prof-ShA-SZ-SN** – This is the first time this network share has been successfully accessed from this network zone. Pre-built analytics rules for which `mitre` was updated include: • **Cntx-PCplink-Exfil** – Process is 'plink.exe': True\False • **Cntx-ShA-AdminShare** – Share is an admin share: True\False • **Fact-AI-Guardrail-Block** – An AI guardrail violation has been observed. • **Cntx-EL-UCrit-ADomain** – User is a domain account: True\False • **Cntx-AuditPolicyMod-ECrit** – Endpoint is critical: True\False • **Cntx-PCquser-ADisc** – Local accounts enumerated using quser.exe: True\False • **Cntx-PC-Critical-Sniffer** – Process is a sniffing tool: True\False • **Cntx-Login-LType** – Login type • **Cntx-PCwmic-ADisc** – Local accounts enumerated using wmic.exe in on endpoint: True\False • **Cntx-PC-Critical-Parent-Shell** – Parent process is a shell process • **Cntx-ELF-LF-BadCred** – Login failed due to bad credentials: True\False • **Cntx-PC-Critical-Parent-Pentest** – Parent process is a known pentesting tool • **Cntx-FRead-Repo** – File is located in a repository: True\False • **Prof-SADLP-TId-Proto-TId** – This is the first time a DLP alert triggered on this domain for this protocol. • **Cntx-VPNIn-UCrit-Vendor** – User is a vendor: True\False • **Cntx-EL-UCrit-UPriv** – User is privileged: True\False • **Cntx-GMA-GCrit-Admin** – Security group is privileged: True\False • **Cntx-Network-Protocol** – Network protocol • **Prof-SA-PN-U-PN** – This is the first time an alert triggered on this process for this user. • **Cntx-PC-Critical-Parent-SystemEnum** – Parent process is a system enumeration tool: True\False • **Cntx-PCapplocker-UAC** – Process is a known Applocker bypass process: True\False

Feature	Description
	• **Cntx-PCwhoami-ADisc** – Local accounts enumerated using whoami.exe on endpoint: True\False • **Cntx-PC-Critical-CredEnum** – Process is a credential enumeration tool: True\False • **Cntx-GA-TI-SIP** – Source IP is marked by threat intelligence: True\False • **Cntx-EL-UCrit-Exec** – User is an executive: True\False • **Cntx-GA-TIRansomware-SIP** – Source IP is marked as a ransomware by threat intelligence: True\False • **Cntx-GA-TIRansomware-DIP** – Destination IP is marked as a ransomware by threat intelligence: True\False • **Cntx-LogCI-ECrit-CS** – Endpoint is critical: True\False • **Prof-GA-Country-SZ-DCountry** – This is the first time an activity has been observed to this country for this network zone, determined by geolocation lookup. • **Cntx-NetworkF-ATF** – Network activity failed: True\False • **Cntx-PC-FC-SusDir** – Process executed from a known suspicious folder: True\False • **Cntx-Web-WDCrit-IP** – Web domain is an IP address: True\False • **Cntx-UCreate-UCrit** – User is local: True\False • **Cntx-PC-Critical-Parent-Webserver** – Parent process is a web server process: True\False • **Cntx-EL-ECrit-CS** – Destination endpoint is critical: True\False • **Cntx-PCwsmprovhost-RP-PN** – Process is 'wsmprovhost.exe': True\False • **Prof-AI-UD-Guardrail-Block** – This is the first time a user in this department has triggered an AI guardrail violation. • **Cntx-PC-Critical-Pentest** – Process is a known pentesting tool • **Prof-SA-PN-UD-PN** – This is the first time an alert triggered on this process for users in this department. • **Prof-GA-Country-DZ-SCountry** – This is the first time an activity has been observed from this country to this network zone, determined by geolocation lookup. • **Cntx-FA-FCrit-SrcExecutable** – Source file is an executable: True\False • **Prof-Auth-U-Okta-AnonVPN** – This is the first time an Okta user has used an anonymous VPN to authenticate. • **Cntx-GA-TI-DIP** – Destination IP is marked by threat intelligence: True\False • **Cntx-PC-Critical-Parent-CredEnum** – Parent process is a credential enumeration tool: True\False • **Cntx-PC-ECrit-Server** – Endpoint is a server: True\False • **Cntx-USwtch-UCrit** – User is privileged: True\False • **Cntx-GA-SA** – User is a service account: True\False • **Cntx-EL-ECrit-DC** – Destination endpoint is a Domain Controller: True\False • **Cntx-PLA-Outcome** – Physical access failed: True\False • **Cntx-GMA-ULocal** – User is local: True\False • **Cntx-ShA-NamedPipe** – Share is a known named pipe: True\False • **Cntx-PC-FC-PDir** – Process executed from a temporary directory: True\False • **Cntx-FUSB-Outlook** – File has a .pst/.ost extension: True\False • **Cntx-Web-UCrit-Exec** – User is an executive: True\False • **Cntx-PC-Critical-SystemEnum** – Process is a system enumeration tool: True\False • **Cntx-ShA-PrivU** – User is privileged: True\False

Feature	Description
	• **Cntx-Web-ECrit-DC** – Endpoint is a Domain Controller: True\False • **Cntx-PC-Critical-Parent-MSOffice** – Parent process is a Microsoft Office process: True\False • **Prof-GA-Country-O-DCountry** – This is the first time an activity has been observed to this country, determined by geolocation lookup. • **Prof-PCIOC-IOCPenT-U-PenT** – This is the first time a process execution of a known pentesting tool has been observed for this user. • **Cntx-GA-UDisabled** – User owns a disabled account: True\False • **Cntx-EL-ET-Wrkstn** – Destination endpoint is a workstation: True\False • **Cntx-PCqwinsta-ADisc** – Local accounts enumerated using qwinsta.exe on endpoint: True\False • **Cntx-Web-UCrit-Priv** – User is privileged: True\False • **Prof-Network-SEPN-DE** – This is the first time this process has accessed this destination endpoint from this source endpoint. • **Cntx-GMA-SelfAdd** – User added themselves to a security group: True\False • **Cntx-GA-AF** – Activity failed: True\False • **Prof-SADLP-Proto-U-Proto** – This is the first time a DLP alert triggered on this protocol for this user. • **Cntx-VPNIn-UCrit-Exec** – User is an executive: True\False • **Cntx-EL-UCrit-SA** – User is a service account: True\False • **Cntx-PC-Critical-Shell** – Process is a shell process • **Prof-AI-O-Guardrail-Block** – This is the first time a user in the organization has triggered an AI guardrail violation. • **Cntx-EMS-Outcome** – Email sent outcome • **Cntx-VPNIn-UCrit-SA** – User is a service account: True\False • **Cntx-PC-ECrit-CS** – Endpoint is critical or a Domain Controller: True\False • **Cntx-VPNIn-UCrit-Contractor** – User is a contractor : True\False • **Cntx-USwtch-DUCrit** – Dest user is privileged: True\False • **Cntx-PCwsmprovhost-RP-PPN** – Parent process is 'wsmprovhost.exe': True\False • **Prof-AI-U-Guardrail-Block** – This is the first time this user has triggered an AI guardrail violation. Pre-built analytics rules for which `severity` was updated include: • **Fact-PCwindump-NetSniff** – The WinDump process (a process dumping tool) has been executed. This sigma rule is authored by Timur Zinniatullin, oscd.community, Nasreddine Bencherchali (Nextron Systems) and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_network_sniffing.yml • **Fact-PCcmdkey-UDisc** – The CMDKey (Credential Manager Command Line) process has been used to enumerate cached credentials. This sigma rule is authored by jmallette, Florian Roth (Nextron Systems), Nasreddine Bencherchali (Nextron Systems) and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_cmdkey_recon.yml • **Fact-PCesentutl-CDbC** – The Esentutl (Extensible Storage Engine Utility) process has been used to copy files with credentials data. This sigma rule is authored by Teymur Kheirkhabarov, Daniil Yugoslavskiy, oscd.community and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_copying_sensitive_files_with_credential_data.yml

Feature	Description
	• **Fact-PCstunnel-Exfil** – The 'stunnel.exe' (a data exfiltration tool) process has been executed. This sigma rule is authored by Daniil Yugoslavskiy, oscd.community and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_exfiltration_and_tunneling_tools_execution.yml • **Fact-PCcsi-AP** – The CSI (C# Interactive Console) process has been spawned by the PowerShell process. This sigma rule is authored by Michael R. (@nahamike01) and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_susp_use_of_csharp_console.yml • **Fact-PCnwp-NWP** – A Windows system process has been executed from a folder it shouldn't normally execute from. This sigma rule is authored by Florian Roth (Nextron Systems), Patrick Bareiss, Anton Kutepov, oscd.community, Nasreddine Bencherchali and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_susp_system_exe_anomaly.yml • **Fact-PCpwrshell-SCC** – The PowerShell process has been used to create a shadow copy. This sigma rule is authored by Teymur Kheirkhabarov, Daniil Yugoslavskiy, oscd.community and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_shadow_copies_creation.yml • **Fact-PCcsws-AP** – A Windows Script Host process ('cscript.exe' or 'wscript.exe') has been spawned by the RegSvr (Register Server) process. This sigma rule is authored by Florian Roth (Nextron Systems), oscd.community, Tim Shelton and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_regsvr32_anomalies.yml • **Fact-PCbcdedit-DisRec** – The BCDEdit (Boot Configuration Data Edit) process has been used to disable Windows recovery mode. This sigma rule is authored by E.M. Anhaus (originally from Atomic Blue Detections, Endgame), oscd.community and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_bcdedit_boot_conf_tamper.yml • **Fact-SEPwrshell-EnumNetworkAdapter** – A PowerShell script that enumerate network adapters using wmi object has been executed. • **Fact-RA-WDigest** – The WDigest authentication protocol, which uses clear-text credential caching, has been enabled via the registry. • **Fact-PCforfiles-IC** – The 'forfiles.exe' process has spawned a child process. This sigma rule is authored by E.M. Anhaus (originally from Atomic Blue Detections, Endgame), oscd.community and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_lolbin_forfiles.yml • **Fact-PCpcalua-IC** – The PCALUA (Program Compatibility Assistant Service) process has been used to execute an indirect command. This sigma rule is authored by E.M. Anhaus (originally from Atomic Blue Detections, Endgame), oscd.community and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/deprecated/windows/proc_creation_win_indirect_cmd.yml • **Fact-PCjava-JavaRD** – The Java process has been executed with remote debugging allowed for more than just the localhost. This sigma rule is authored by Florian Roth (Nextron Systems) and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_vul_java_remote_debugging.yml • **Fact-PCnltest-DomDisc** – The NLTest (Network Location Test) process has been used to discover domain trusts. This sigma rule is authored by E.M. Anhaus, Tony Lambert, oscd.community, omkar72 and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/

Feature	Description
	master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_dsquery_domain_trust_discovery.yml • **Fact-PCwsreset-UAC** – The WSReset (Windows Store Reset) process has spawned a child process that it shouldn't normally spawn. This sigma rule is authored by E.M. Anhaus (originally from Atomic Blue Detections, Tony Lambert), oscd.community, Florian Roth and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_uac_bypass_wsreset.yml • **Fact-PCSplashtop-InstalledAgent** – The Splashtop remote desktop access agent has been installed. • **Fact-PCcsws-SExec-PP** – The 'wscript.exe' or 'cscript.exe' processes (Windows Script Host) were used to execute a script from the user directory or the program data directory. This sigma rule is authored by Margaritis Dimitrios (idea), Florian Roth (Nextron Systems), oscd.community and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_malware_script_dropper.yml • **Fact-PC-MshtaScriptExecution** – The MsHTA (Microsoft HTML Application) process has been used to execute a script code. • **Fact-FCopy-Outlook-FExt** – A file ending in a '.pst'/'.ost' extension has been copied. • **Fact-PCsharphound-BloodHound** – The 'sharphound.exe' (a network domain enumeration tool) process has been executed. • **Fact-PCTeamViewer-StartedService** – The TeamViewer remote desktop access service has been started. • **Fact-PCscrcons-WMI** – The 'scrcons.exe' process (WMI script event consumer) has been executed. This sigma rule is authored by Thomas Patzke and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_wmi_persistence_script_event_consumer.yml • **Fact-PCsocat-Exfil** – The 'socat.exe' (a data exfiltration tool) process has been executed. This sigma rule is authored by Daniil Yugoslavskiy, oscd.community and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_exfiltration_and_tunneling_tools_execution.yml • **Fact-ELF-SA** – A service account failed to log into an endpoint using an interactive Windows logon type. A service account is a user account that belongs to an application rather than an end user. • **Fact-PCtaskmgr-SysPerm** – The task manager process has been executed by the system user. This sigma rule is authored by Florian Roth (Nextron Systems) and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_taskmgr_localsystem.yml • **Fact-PCschtasks-TM** – The SchTasks (Scheduled Tasks) process has been used to modify the user account configuration of a scheduled task. • **Fact-PCschtasks-TC** – The SchTasks (Scheduled Tasks) process has been spawned by a command associated with the 'PowerSploit' or 'Empire' attack tools. This sigma rule is authored by Markus Neis, @Karneades and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_hktl_powersploit_empire_default_schtasks.yml • **Fact-PCGoToMyPC-StartedService** – The GoToMyPC remote desktop access service has been started. • **Fact-EMS-Competition** – An email has been sent to an email domain belonging to a competitor. • **Fact-PCmklink-SCA** – The 'mklink.exe' process has been used to create a symbolic link to a shadow copy. This sigma rule is authored by Teymur Kheirkhabarov, oscd.community and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/

Feature	Description
	master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_shadow_copies_access_symlink.yml • **Fact-PCbcdedit-ESP** – The BCDEdit (Boot Configuration Data Edit) process has been used to enable test signing. • **Fact-PCpwrshell-AD** – The PowerShell process has executed a 'ps1' script from the AppData folder. This sigma rule is authored by Florian Roth (Nextron Systems), Jonhnathan Ribeiro, oscd.community and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_powershell_susp_ps_appdata.yml • **Fact-PCAnyDesk-InstalledAgent** – The AnyDesk remote desktop access service has been installed. • **Fact-PCwhoami-SysPerm** – The 'whoami.exe' process has been executed by the system user. • **Fact-PC-SysP** – The 'rundll32.exe' process has been used to execute a command associated with CVE-2023-23397. • **Fact-PCfsutil-JDel** – The FSUtil (File System Utility) process has been used to create or delete a journal. This sigma rule is authored by Ecco, E.M. Anhaus, oscd.community and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_fsutil_usage.yml • **Fact-PCappcmd-ModIns** – The 'appcmd.exe' (IIS Application Command Line) process has been used to install an IIS native-code module. • **Fact-PCcsc-AP** – The CSC (C# Compiler) process has been spawned by a command line executable or a Microsoft Office process. This sigma rule is authored by Florian Roth (Nextron Systems), Nasreddine Bencherchali (Nextron Systems) and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_csc_susp_parent.yml • **Fact-PCping-HexEn** – The 'ping.exe' process has been used to ping a hex encoded IP address. This sigma rule is authored by Florian Roth (Nextron Systems) and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_susp_ping_hex_ip.yml • **Fact-PCpwrshell-HidExec** – The PowerShell process has been executed with a hidden or non-interactive console window. This sigma rule is authored by Florian Roth (Nextron Systems), Daniel Bohannon (idea), Roberto Rodriguez (Fix) and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_powershell_susp_parameter_variation.yml • **Fact-PCoffice-Regsvr32** – A Microsoft Office process has spawned the RegSvr (Registration Service) process. This sigma rule is authored by Florian Roth (Nextron Systems), oscd.community, Tim Shelton and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_regsvr32_anomalies.yml • **Fact-PCAnyDesk-StartedAgent** – The AnyDesk remote desktop access service has been started. • **Fact-PCpwrshell-ELT** – The PowerShell process has been used to clear or delete an event log. This sigma rule is authored by Ecco, Daniil Yugoslavskiy, oscd.community, D3F7A5105 and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_susp_eventlog_clear.yml • **Fact-PCpwrshell-En-SuspEnc** – The PowerShell process has been used to execute a command associated with the ChromeLoader malware. This sigma rule is authored by Florian Roth (Nextron Systems), Markus Neis, Jonhnathan Ribeiro, Daniil Yugoslavskiy, Anton Kutepov, oscd.community and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/

Feature	Description
	master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_powershell_base64_encoded_cmd.yml • **Fact-PCrundll32-ProcMemDump-1** – The 'rundll32.exe' process has been used to dump process memory using the 'minidump' exported function in 'comsvcs.dll'. This sigma rule is authored by Florian Roth (Nextron Systems), Modexp, Nasreddine Bencherchali (Nextron Systems) and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_rundll32_process_dump_via_comsvcs.yml • **Fact-PCDotNet-CommandLine** – This .NET supporting process was created with an URL in the commandline. • **Fact-GA-TITOR** – An IP address associated with TOR has been observed. • **Fact-UModify-UACPreAuthDisable** – UAC pre-authentication has been disabled for a user account. • **Fact-PCLogMeIn-InstalledAgent** – The LogMeIn remote desktop access agent has been installed. • **Fact-PCLsass-Lsass** – The WERFault (Windows Error Reporting Fault) process has been used to dump the LSASS process. This sigma rule is authored by sigma and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_lsass_dump.yml • **Fact-PCpsr-Screenshot** – The PSR (Problem Steps Recorder) process has been used to take a screenshot. This is a benign event that is still useful to keep track of. This sigma rule is authored by Beyu Denis, oscd.community and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_susp_psr_capture_screenshots.yml • **Fact-U-PrivMM** – A non-privileged user has been observed accessing an attribute of a privileged directory service user account. • **Fact-PCcsws-SExec** – The 'wscript.exe' or 'cscript.exe' processes (Windows Script Host) have been used to execute a VBScript shell. These programs can be used to aid in fileless malware execution, a technique that can help evade detection. This sigma rule is authored by Florian Roth (Nextron Systems) and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_apt_cloudhopper.yml • **Fact-PCsdbinst-SI** – The SDBInst (Application Compatibility Database Installer) process has been used to register a shim database. This event is notable as shims can be used to intercept API calls and load malicious DLLs enabling an attacker to run malicious software. This sigma rule is authored by Markus Neis and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_sdbinst_shim_persistence.yml • **Fact-PCappcmd-IIS** – The 'appcmd.exe' (IIS Application Command Line) process has been used to disable IIS HTTP logging . • **Fact-PCrundll32-Cpl** – The Windows control panel process has spawned the 'rundll32.exe' process. This sigma rule is authored by Florian Roth (Nextron Systems) and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_rundll32_susp_control_dll_load.yml • **Fact-PCschtasks-DA** – The SchTasks (Scheduled Tasks) process has been used to deactivate a scheduled defragmentation task. This sigma rule is authored by Florian Roth (Nextron Systems), Bartlomiej Czyz (@bczyz1) and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_apt_slingshot.yml • **Fact-PCwmic-SCD** – The WMIC (WMI Command Line) process has been used to delete a shadow copy. This sigma rule is authored by Florian Roth (Nextron Systems), Michael Haag, Teymur Kheirkhabarov, Daniil Yugoslavskiy, oscd.community, Andreas Hunkeler (@Karneades) and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/

Feature	Description
	master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_susp_shadow_copies_deletion.yml • **Fact-PCcmstp-UAC** – The CMSTP (Connection Manager Profile Installer) has been used to silently install a service profile for all users on an endpoint. This sigma rule is authored by E.M. Anhaus (originally from Atomic Blue Detections, Endgame), oscd.community and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_uac_bypass_cmstp.yml • **Fact-PCLogMeIn-InstalledService** – The LogMeIn remote desktop access service has been installed. • **Fact-PCbitsadmin-AbP** – The 'bitsadmin.exe' process has been spawned by a command line executable. This sigma rule is authored by Florian Roth (Nextron Systems), Tim Shelton and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_susp_shell_spawn_susp_program.yml • **Fact-FRead-Lssas** – A process has directly read from the memory space of 'lsass.exe'. • **Fact-PCsvchost-DCOMLaunch** – Remote DCOM activation under DcomLaunch service. • **Fact-PCdir-UDisc** – The 'dir.exe' process has been used to list users by enumerating the users folder. • **Fact-PCbginfo-VBExec** – The BgInfo (Background Information) process has used a .bgi file to bypass application whitelisting. This is notable as this method allows blindly trusted signed binaries to write code which can be leveraged to run malicious actions. This sigma rule is authored by Beyu Denis, oscd.community and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_susp_bginfo.yml • **Fact-PCnwp-NWP-PPP** – A Windows system process has been spawned by a parent process that's in a folder it shouldn't normally execute from. This sigma rule is authored by vburov and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_susp_proc_wrong_parent.yml • **Fact-PCsc-SvcMod-Ingt** – The SC (Service Controller) process has been used to change a service binary path or failure command configuration with medium integrity level executed. This sigma rule is authored by Teymur Kheirkhabarov and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_sc_change_sevice_image_path_by_non_admin.yml • **Fact-PCiexplorer-IHttp** – The 'consent.exe' (Windows UAC consent dialogue) process has spawned the 'iexplorer.exe' (Internet Explorer) process with system permissions. This sigma rule is authored by Florian Roth (Nextron Systems) and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_exploit_cve_2019_1388.yml • **Fact-PCsc-SuspSP** – The SC (Service Controller) process has been executed with suspicious command line parameters. • **Fact-PCsr-AC** – The Sound Recorder process was used to record external audio. This sigma rule is authored by E.M. Anhaus (originally from Atomic Blue Detections, Endgame), oscd.community and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_soundrecorder_audio_capture.yml • **Fact-PCcertutil-AP** – The CertUtil (Certification Utility) process has been spawned by a command line executable. This sigma rule is authored by Florian Roth (Nextron Systems), Tim Shelton and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_susp_shell_spawn_susp_program.yml • **Fact-MPermMod-UCrit** – A user has modified the mailbox permissions of an executive user.

Feature	Description
	• **Fact-PCbitsadmin-FDnld** – The BITSAdmin (Background Intelligent Transfer Service Admin) process has been used to download a file. This sigma rule is authored by Michael Haag, FPT.EagleEye and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_bitsadmin_download.yml • **Fact-DllLoadWmiprvse-Exe** – The 'wmiprvse.exe' (WMI Provider Service) process has been observed loading a 'cmd.exe' or a 'powershell.exe' image. • **Fact-PCcdb-DSE** – The CDB (Console Debugger) process has been used to execute a script. This sigma rule is authored by Beyu Denis, oscd.community, Nasreddine Bencherchali and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_lolbin_cdb.yml • **Fact-PCrundll32-PwrshellDll-PPN** – The PowerShell process has been used to spawn 'rundll32.exe' and execute a DLL from a temporary folder. • **Fact-PCwmic-SCC** – The WMIC (WMI Command Line) process has been used to create a shadow copy. This sigma rule is authored by Teymur Kheirkhabarov, Daniil Yugoslavskiy, oscd.community and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_shadow_copies_creation.yml • **Fact-PCassoc-FAssocCh** – The Assoc (File Association) process has been used to change the association of an extension to execution. This sigma rule is authored by Nasreddine Bencherchali (Nextron Systems) and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_change_default_file_association.yml • **Fact-PCpwrshell-Base64En-Hidden** – The PowerShell has been used to execute a known malicious encoded command. This sigma rule is authored by John Lambert (rule) and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_powershell_hidden_b64_cmd.yml • **Fact-PCIOC-Mimikatz** – The PowerShell process has been used to execute a Mimikatz command. • **Fact-PCsetspn-SPNDisc** – The 'setspn.exe' process has been used to query service principal names. This sigma rule is authored by Markus Neis, keepwatch and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_setspn_spn_enumeration.yml • **Fact-PC-RemoteExecAdminShare** – A remote process has been executed and redirected to an admin share. This activity can be related to the execution of Impacket. • **Fact-PCfltmc-SysmonDU** – The FltMC (Filter Manager Control) process has been used to unload the Sysmon driver. This sigma rule is authored by Kirill Kiryanov, oscd.community and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_sysmon_driver_unload.yml • **Fact-PC-TsconRDPRedirection** – The 'tscon.exe' has been used to redirect RDP traffic. • **Fact-PCLsass-ProcDumpLsass** – The 'procdump.exe' process has been used to dump the LSASS process. This sigma rule is authored by Florian Roth (Nextron Systems) and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_sysinternals_procdump_lsass.yml • **Fact-PCwbadmin-CD** – The WBAdmin (Windows Backup Admin) process has been used to delete a backup catalog. • **Fact-PCcertutil-SuspCmd** – The CertUtil (Certification Utility) process has been executed with suspicious command line parameters. This sigma rule is authored by Florian Roth (Nextron Systems), juju4, keepwatch and is licensed under Detection

Feature	Description
	Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_certutil_decode.yml, https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_certutil_download.yml, https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_certutil_encode.yml. • **Fact-PCdllhost-UACCOM** – The 'dllhost.exe' process has been used to bypass UAC using COM objects. This sigma rule is authored by Nik Seetharaman, Christian Burkard (Nextron Systems) and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_cmstp_com_object_access.yml • **Fact-PCreg-WDigest** – The 'reg.exe' has been used to enable WDigest authentication through the registry. • **Fact-PCGoToMyPC-InstalledAgent** – The GoToMyPC remote desktop access agent has been installed. • **Fact-PCdns-SIGRed** – The DNS process has spawned a child process that it shouldn't normally spawn. • **Fact-PCmshta-JsExec** – The MsHTA (Microsoft HTML Application) process has been used to execute javascript. This sigma rule is authored by E.M. Anhaus (originally from Atomic Blue Detections, Endgame), oscd.community and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_mshta_javascript.yml • **Fact-DNS-DomQ-Sunburst** – A DNS query has been observed requesting a domain associated with the SUNBURST malware. • **Fact-PCSplashtop-InstalledService** – The Splashtop remote desktop access service has been installed. • **Fact-PCGoToMyPC-InstalledService** – The GoToMyPC remote desktop access service has been installed. • **Fact-PChh-HtmlExec** – The HH (HTML Help) process has loaded a '.chm' (Compiled HTML) file. This sigma rule is authored by E.M. Anhaus (originally from Atomic Blue Detections, Dan Beavin), oscd.community and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_hh_chm_execution.yml • **Fact-PCcontrol-CPLFExec** – The Windows control panel process has loaded control panel items outside of the folders they are loaded from by default. This sigma rule is authored by Kyaw Min Thein, Furkan Caliskan (@caliskanfurkan_) and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_control_panel_item.yml • **Fact-EMS-SrcCode** – An email containing a source code file attachment has been sent. • **Fact-PC-TempF-Outlook** – A process have been executed from an Outlook temporary folder. This sigma rule is authored by Florian Roth (Nextron Systems) and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_office_outlook_execution_from_temp.yml • **Fact-PCIOC-Mimikatz-PN** – The Mimikatz process has been executed. • **Fact-FCopy-Outlook-FDir** – A file from the Outlook folder has been copied to a non-Outlook folder. • **Fact-PCicacls-FPermMod-Everyone** – The ICACLs (Integrity Control Access Control Lists) process has been used to grant global permissions on a file. • **Fact-PCcopy-TFE** – The 'copy.exe' process has been used to perform task folder evasion. This sigma rule is authored by Sreeman and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_task_folder_evasion.yml

Feature	Description
	• **Fact-LogCl-LogClear-AT** – An audit log has been cleared. • **Fact-PCiodine-PExec** – The 'iodine.exe' (a DNS tunneling tool) process has been executed. This sigma rule is authored by Daniil Yugoslavskiy, oscd.community and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_dns_exfiltration_tools_execution.yml • **Fact-PCntdsutil-NTDS** – The 'ntdsutil.exe' (NT Directory Service Utility) process has been executed. This sigma rule is authored by Thomas Patzke and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_susp_ntdsutil_usage.yml • **Fact-PCtshark-NetSniff** – The TShark process (a network sniffing tool) has been executed. This sigma rule is authored by Timur Zinniatullin, oscd.community, Nasreddine Bencherchali (Nextron Systems) and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_network_sniffing.yml • **Fact-PCat-IJob** – The 'at.exe' process has been used to execute an interactive scheduled task. This sigma rule is authored by E.M. Anhaus (originally from Atomic Blue Detections, Endgame), oscd.community, and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/62d4fd26b05f4d81973e7c8e80d7c1a0c6a29d0e/rules/windows/process_creation/proc_creation_win_at_interactive_execution.yml • **Fact-PCgup-AF** – The Notepad++ updater has been executed from a folder it shouldn't normally execute from. This sigma rule is authored by Florian Roth (Nextron Systems) and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_susp_gup.yml • **Fact-PCvssadmin-SCD** – The VSSAdmin (Volume Shadow Copy Service Admin) process has been used to delete a shadow copy. This sigma rule is authored by Florian Roth (Nextron Systems), Michael Haag, Teymur Kheirkhabarov, Daniil Yugoslavskiy, oscd.community, Andreas Hunkeler (@Karneades) and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_susp_shadow_copies_deletion.yml • **Fact-PCrundll32-PwrshellDll-PCL** – The 'rundll32.exe' process has been used to execute a PowerShell command. This sigma rule is authored by Markus Neis, Nasreddine Bencherchali and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_powershell_dll_execution.yml • **Fact-PCdctask64-Zoho** – The ZOHO 'dctask64.exe' process has been used to perform process injection. This sigma rule is authored by Florian Roth (Nextron Systems) and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_susp_dctask64_proc_inject.yml • **Fact-PCTeamViewer-InstalledService** – The TeamViewer remote desktop access service has been installed. • **Fact-PCregsvr32-SuspExec** – The RegSvr (Registration Service) process has been used to download/install/register a new DLL that is hosted on web, on this endpoint. This sigma rule is authored by Florian Roth (Nextron Systems), oscd.community, Tim Shelton and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_regsvr32_anomalies.yml • **Fact-WinSC-SuspSC-Param** – A service has been created with suspicious execution command parameters. • **Fact-PCrundll32-ADllLoad-Susp** – The 'rundll32.exe' process has executed an exported module function using an ordinal number. This sigma rule is authored by Florian Roth (Nextron Systems)

Feature	Description
	and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_susp_rundll32_by_ordinal.yml • **Fact-PCLogMeIn-StartedService** – The LogMeIn remote desktop access service has been started. • **Fact-PCnetsh-FD** – The NetSh (Network Shell) process has been used to disable the Windows firewall. This sigma rule is authored by Fatih Sirin and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_netsh_fw_disable.yml • **Fact-PCbcdedit-DisRec-BootSP** – The BCDEdit (Boot Configuration Data Edit) process has been used to Windows error recovery. This sigma rule is authored by E.M. Anhaus (originally from Atomic Blue Detections, Endgame), oscd.community and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_bcdedit_boot_conf_tamper.yml • **Fact-PCSplashtop-StartedService** – The Splashtop remote desktop access service has been started. • **Fact-PCIOC-Archer** – The 'rundll32.exe' process has executed a command associated with the Archer malware service. This sigma rule is authored by Florian Roth (Nextron Systems) and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_malware_fireball.yml • **Fact-PCecho-TFE** – The 'echo.exe' process has been used to perform task folder evasion. This sigma rule is authored by Sreeman and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_task_folder_evasion.yml • **Fact-WebMtgM-RmPwd** – A meeting has been modified to remove the meeting password. • **Fact-PCwmic-WebExec** – The WMIC (WMI Command Line) process has been used to invoke a remote XSL script. This sigma rule is authored by Markus Neis, Florian Roth and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_wmic_squiblytwo_bypass.yml • **Fact-EMRC-FwR-ExtDom** – An inbox rule has been configured to forward emails to an email address that's in a different domain than the rule's creator. • **Fact-PCpwrshell-Base64En** – The PowerShell process has been used to decode a Base64 string using 'frombase64string'. This sigma rule is authored by Florian Roth (Nextron Systems) and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_powershell_frombase64string.yml • **Fact-PCTeamViewer-InstalledAgent** – The TeamViewer remote desktop access agent has been installed. • **Fact-PCmsiexec-WebExec** – The MsiExec process (Windows Installer) has been used to execute a remote script using a web addresses parameter. This sigma rule is authored by Florian Roth (Nextron Systems) and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_msiexec_web_install.yml • **Fact-PCcrackmapexec-CrackMapExecWin** – The 'crackmapexec.exe' (a penetration testing tool) process has been executed. This sigma rule is authored by Markus Neis and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_apt_dragonfly.yml • **Fact-PCpwrshell-AC** – The PowerShell process has been used to record external audio. This sigma rule is authored by E.M. Anhaus (originally from Atomic Blue Detections, Endgame), oscd.community, Nasreddine Bencherchali (Nextron Systems) and

Feature	Description
	is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_powershell_audio_capture.yml • **Fact-PCsc-SvcMod-PCL** – The SC (Service Controller) process has been used to configure a PowerShell service. This sigma rule is authored by Victor Sergeev, oscd.community, Nasreddine Bencherchali (Nextron Systems) and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_sc_service_path_modification.yml • **Fact-PCwmiprvse-FireEye** – The WMIPrvSe (WMI Provider Host) process has been used to execute a command associated with FireEye Pentesting. • **Fact-SA-ET-RN** – A correlation rule has been triggered • **Fact-PCeqnedt32-EE** – The 'eqnedt32.exe' (EquationEditor) process has been executed. This is a known built in tool used by attackers due to its ability for exploitation. This sigma rule is authored by Florian Roth (Nextron Systems) and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_exploit_cve_2017_11882.yml • **Fact-PCrundll32-Meterpreter** – The 'rundll32.exe' process has been used to execute a known Meterpreter/Cobalt Strike module. This sigma rule is authored by Teymur Kheirkhabarov, Ecco, Florian Roth and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/builtin/security/win_security_meterpreter_or_cobaltstrike_getsystem_service_install.yml • **Fact-FWrite-DExt** – A file with an '.exe' extension following a non-executable extension was written to. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_susp_double_extension.yml • **Fact-PCpwrshell-BitsJob** – The PowerShell process has been used to execute a BITS (Background Intelligent Transfer Service) transfer. This sigma rule is authored by Endgame, JHasenbusch (ported to sigma for oscd.community) and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules-deprecated/windows/proc_creation_win_powershell_bitsjob.yml • **Fact-PCpwrshell-ADS** – The PowerShell process has been used to execute a PowerShell script from an ADS (Alternate Data Stream). This sigma rule is authored by Sergey Soldatov, Kaspersky Lab, oscd.community and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_powershell_run_script_from_ads.yml • **Fact-WinSC-SuspSC-Temp** – A service has been created from a temporary internet files directory. • **Fact-PCpassworddump-SecurityXploded** – The 'passworddump.exe' process (a password dumping tool from the 'SecurityXploded' toolkit) has been executed. This sigma rule is authored by Florian Roth (Nextron Systems) and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_hktl_secutyxploded.yml • **Fact-STC-SP** – A scheduled task has been configured to execute the PowerShell process. • **Fact-PCrundll32-ADllLoad-Trojan** – The 'rundll32.exe' process has loaded a module from the AppData folder. This sigma rule is authored by Florian Roth (Nextron Systems), Jonhnathan Ribeiro, oscd.community and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_apt_sofacy.yml • **Fact-PCmwc-mstsc** – The MSTSC (Microsoft Terminal Services Client) process has been used to shadow an existing remote desktop session. This sigma rule is authored by Florian Roth (Nextron Systems) and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/

Feature	Description
	sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_mstsc_rdp_hijack_shadowing.yml • **Fact-PCdevtool-BinExec** – The DevToolsLauncher process has deployed a process. This sigma rule is authored by Beyu Denis, oscd.community (rule), @_felamos (idea) and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_susp_devtoolslauncher.yml • **Fact-PChttptunnel-ExfilTExec** – The 'httptunnel.exe' (a data exfiltration tool) process has been executed. This sigma rule is authored by Daniil Yugoslavskiy, oscd.community and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_exfiltration_and_tunneling_tools_execution.yml • **Fact-PCsvchost-NoArg** – The SvcHost (Service Host) process has been executed without any command line arguments. This sigma rule is authored by David Burkett, @signalblur and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_svchost_execution_with_no_cli_flags.yml • **Fact-PCcreateminidump-ProcMemDump** – The CreateMiniDump process (a memory dumping tool) has been executed. This tool is used to dump the LSASS process memory for credential extraction on the attacker's machine. This sigma rule is authored by Florian Roth (Nextron Systems) and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_hktl_createminidump.yml • **Fact-PCnetsniff-SniffT** – A network sniffing tool has been executed. • **Fact-PCtakeown-FO** – The 'takeown.exe' process has been used to take ownership of a file or a folder. • **Fact-PCtype-TFE** – The 'type.exe' process has been used to perform task folder evasion. This sigma rule is authored by Sreeman and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_task_folder_evasion.yml • **Fact-PCreg-AutorunMod** – The 'reg.exe' process has been used to modify an AutoRun registry key. This sigma rule is authored by Victor Sergeev, Daniil Yugoslavskiy, oscd.community and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_reg_direct_asep_registry_keys_modification.yml • **Fact-PCpwrshell-AMSI** – The PowerShell process has been used to disable AMSI (Anti Malware Scan Interface) Scanning using AmsiInitFailed. This sigma rule is authored by Markus Neis, @Kostastsale and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_powershell_amsi_init_failed_bypass.yml • **Fact-PCIOC-ZxShell** – The 'rundll32.exe' process has been used to execute a known 'ZxShell' backdooring software module. This sigma rule is authored by Florian Roth (Nextron Systems), oscd.community, Jonhnathan Ribeiro and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules-emerging-threats/2014/TA/Axiom/proc_creation_win_apt_zxshell.yml • **Fact-PCecho-EchoP** – The 'echo.exe' process has been used to execute a command associated with Meterpreter and Cobalt Strike's GetSystem system privilege escalation function. • **Fact-PCreg-SRH** – The 'reg.exe' process has been used to dump the security/sam/system registry hives. This sigma rule is authored by Teymur Kheirkhabarov, Endgame, JHasenbusch, Daniil Yugoslavskiy, oscd.community, frack113 and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_reg_dumping_sensitive_hives.yml

Feature	Description
	• **Fact-PCdnscat-DNSExfil** – The DNScat (a DNS tunneling tool) process has been executed. This sigma rule is authored by Daniil Yugoslavskiy, oscd.community and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_dns_exfiltration_tools_execution.yml • **Fact-PCmwc-PExec** – The Microsoft Workflow Compiler process has been executed. Microsoft Workflow Compiler may permit the execution of arbitrary unsigned code. This sigma rule is authored by Nik Seetharaman, frack113 and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_lolbin_workflow_compiler.yml • **Fact-PCopenwith-Exec** – The OpenWith process has been used to execute a program. This sigma rule is authored by Beyu Denis, oscd.community (rule), @harr0ey (idea) and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_susp_openwith.yml • **Fact-PCpwrshell-Empire** – The PowerShell process has been used to execute a command associated with an Empire module. • **Fact-PCbcdedit-BootEM** – The BCDEdit (Boot Configuration Data Edit) process has been used to delete or import boot entry data. This sigma rule is authored by @neu5ro and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_bcdedit_susp_execution.yml • **Fact-PCfodhelper-UAC** – The 'fodhelper.exe' has spawned a child process. This sigma rule is authored by E.M. Anhaus (originally from Atomic Blue Detections, Tony Lambert), oscd.community and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_uac_bypass_fodhelper.yml • **Fact-PCwmic-ELT** – The WMIC (WMI Command Line) process has been used to clear or delete an event log. This sigma rule is authored by Ecco, Daniil Yugoslavskiy, oscd.community, D3F7A5105 and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_susp_eventlog_clear.yml • **Fact-PC-DExt** – A process with an '.exe' extension following a non-executable extension has been executed. This sigma rule is authored by Florian Roth (Nextron Systems), @blu3_team (idea), Nasreddine Bencherchali (Nextron Systems) and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_susp_double_extension.yml Pre-built analytics rules for which `query` was updated include: • **NumCP-SEPwrshell-CmdInvC-O-InvC** – An abnormal number of PowerShell command invocations have been observed for the organization. • **NumCP-RegD-EC-DE** – An abnormal number of registry deletion events have been observed on this device. • **NumSP-EMR-Bytes-DU-Bytes** – An abnormal amount of bytes have been received in incoming emails for this user. • **NumCP-ELF-EC-U-RDP** – An abnormal number of failed RDP (remote desktop protocol) logins to this endpoint have been observed for this user. • **NumCP-AppAuthF-EC-U** – An abnormal number of application authentication failures have been observed for this user. • **NumSP-DNSReq-Bytes-O-Bytes** – An abnormal amount of bytes were sent in DNS queries from endpoints in the organization.

Feature	Description
	• **NumCP-PC-InsmodCmdC-DE** – An abnormal number of 'insmod' (Install Module) process executions have been observed on this endpoint. • **NumCP-PC-ChownCount-U** – An abnormal number of 'chown' (Change Owner) process executions have been observed for this user. • **NumCP-PC-KextloadCmdC-U** – An abnormal number of 'kextload' (Kernel Extention Load) process executions have been observed for this user. • **NumSP-FRead-FS-SA-Bytes** – An abnormal amount of file bytes have been read in this storage account for this user. • **NumSP-Web-Bytes-UD-BytesStorageOut** – An abnormal amount of bytes have been uploaded to file sharing websites for users in this department. • **NumCP-FDel-LogFileCount-U** – An abnormal number of log file deletion events have been observed for this user. • **NumDCP-FRead-EC-UP-FP** – An abnormal number of unique files have been read in this platform for this user. • **NumCP-AppLF-EC-U** – An abnormal number of application login failures have been observed for this user. • **NumSP-Web-Bytes-O-BytesStorageOut** – An abnormal amount of bytes have been uploaded to file sharing websites for the organization. • **NumSP-DNSReq-Bytes-SE-Bytes** – An abnormal amount of bytes were sent in DNS queries from this endpoint. • **NumDCP-FRead-EC-B-FP** – An abnormal number of unique files have been read in this bucket for this user. • **NumCP-WebF-EC-U-Id** – An abnormal number of failed HTTP events have been observed for this user. • **NumCP-PC-SudoCount-U** – An abnormal number of 'sudo' (Superuser Do) process executions have been observed for this user. • **NumSP-VPNOut-Bytes-U-Bytes** – An abnormal amount of bytes have been uploaded in VPN session for this user. • **NumCP-PCpwrshell-EC-U** – An abnormal number of PowerShell process executions have been observed for this user. • **NumCP-DNSResp-NXC-O-NX** – An abnormal number of DNS queries to NX domains have been observed for the organization. • **NumDCP-FRead-FS-U-DE** – An abnormal number of unique destination endpoints have been observed in file read events for this user. • **NumSP-FRead-FS-B-Bytes** – An abnormal amount of file bytes have been read in this bucket for this user. • **NumDCP-PCCEnum-TC-U-CEnum** – An abnormal number of unique credential enumeration tools have been executed for this user. • **NumDCP-FRead-EC-SA-FP** – An abnormal number of unique files have been read in this storage account for this user. • **NumCP-PwdChkout-EC-U-SC** – An abnormal number of password retrievals have been observed for this user. • **NumCP-PC-ModprobeCmdC-U** – An abnormal number of 'modprobe' (Module Probe, a kernel module managment tool) process executions have been observed for this user. • **NumCP-DSOW-EC-O** – An abnormal number of directory service write events have been observed for the organization. Directory services typically manage various types of objects to organize and administer resources within a network environment. • **NumDCP-RegW-RPC-ServicesStop-DE-RP** – An abnormal number of unique services have been stoped by modifying the registry on this endpoint.

Feature	Description
	• **NumCP-DNSResp-NXC-SE-NX** – An abnormal number of DNS queries to NX domains from this endpoint have been observed. • **NumCP-RegD-Services-EC-U** – An abnormal number of unique service configurations have been deleted from the registry for this user. • **NumSP-EMS-Bytes-U-Bytes** – An abnormal amount of bytes have been sent in outgoing emails for this user. • **NumCP-DSOW-EC-U** – An abnormal number of directory service events have been observed for this user. Directory services typically manage various types of objects to organize and administer resources within a network environment. • **NumDCP-RegW-RPC-ServicesStop-U-RP** – An abnormal number of unique services have been stoped by modifying the registry for this user. • **NumSP-FUSB-Bytes-U-Bytes** – An abnormal amount of file bytes have been written to peripheral storage devices for this user. • **NumCP-DL-EC-SE** – An abnormal number of kernel module or drivers have been loaded on this endpoint. • **NumCP-RegD-EC-U** – An abnormal number of registry deletion events have been observed for this user. • **NumSP-DNSReq-Bytes-SZ-Bytes** – An abnormal amount of bytes were sent in DNS queries from this network zone. • **NumDCP-SA-ANC-UD-AN** – An abnormal number of unique alerts have triggered for users in this department. • **NumCP-VPNInF-EC-U** – An abnormal number of vpn login failures have been observed for this user. • **NumCP-PCpwrshell-EC-UD** – An abnormal number of PowerShell process executions have been observed for users in this department. • **NumCP-FUpld-EC-U** – An abnormal amount of file upload events have been observed for this user. • **NumCP-DL-EC-UPlt** – An abnormal number of kernel module or drivers have been loaded for this user. • **NumSP-FRead-FS-UP-Bytes** – An abnormal amount of file bytes have been read in this platform for this user. • **NumCP-ELF-EC-U-SE** – An abnormal number of failed endpoint logins from this endpoint have been observed for this user. • **NumDCP-ELF-SEC-DE-SE** – An abnormal number of unique endpoints have been observed failing to log into this endpoint. • **NumCP-EMS-EC-U-Id** – An abnormal number of outgoing emails have been observed for this user. • **NumDCP-RegR-RPC-Cert-U-RP** – An abnormal number of unique certificates and private keys related registry values have been read by this user. • **NumCP-SEPwrshell-WebReq-O-WebReq** – An abnormal number of PowerShell web requests have been observed for the organization. • **NumCP-RuleDel-EC-U** – An abnormal number of security rules deletion events have been observed for this user. • **NumDCP-GA-OpC-UPlt-FOp** – An abnormal number of unique failed operations have been observed in this platform for this user. • **NumSP-Web-Bytes-U-BytesStorageOut** – An abnormal amount of bytes have been uploaded to file sharing websites for this user. • **NumCP-FUpld-EC-O** – An abnormal amount of file upload events have been observed for the organization. • **NumDCP-FDel-U-DE** – An abnormal number of unique remote destination endpoints have been observed in file deletion events on this endpoint for this user.

Feature	Description
	• **NumDCP-SA-ANC-SE-AN** – An abnormal number of unique alerts have triggered from this endpoint. • **NumCP-RegD-Services-EC-DE** – An abnormal number of unique service configurations have been deleted from the registry on this device. • **NumDCP-PCHEnum-TC-U-HEnum** – An abnormal number of unique host enumeration tools have been executed for this user. • **NumDCP-PwdChkout-SVC-U-SV** – An abnormal number of unique safes have been observed in passwords retrieval events for this user. • **NumDCP-PLA-LocC-U-LocDoor** – An abnormal number of unique doors have been observed in physical access events for this user. • **NumDCP-EL-DEC-O-DE** – An abnormal number of unique destination endpoints have been observed in endpoint login events for the organization. These events may include interactive Window logins and other (interactive or not) OS logins, both failed as successful. • **NumDCP-WebF-WebDomC-U-WebDom** – An abnormal number of unique domains have been observed in failed HTTP events for this user. • **NumCP-FUpld-EC-UD** – An abnormal amount of file upload events have been observed for users in this department. • **NumCP-PwdChkout-EC-UD-SC** – An abnormal number of password retrievals have been observed for users in this department. • **NumSP-Network-BytesOut-SEDP-Bytes** – An abnormal amount of bytes have been sent using SSH, Telnet, SMTP, DNS, FTP, HTTP or HTTPS protocols in outbound communication from this endpoint to this port. • **NumCP-FDel-EC-U** – An abnormal number of file deletion events have been observed for this user. • **NumDCP-PLA-LocC-U-LocCity** – An abnormal number of unique cities have been observed in physical access events for this user. • **NumCP-WebReqF-EC-U-Id** – An abnormal number of failed HTTP requests have been observed for this user. • **NumCP-MPermMod-EC-U** – An abnormal number of mailbox permission modifications have been observed for this user. • **NumCP-Auth-MfaEC-U** – An abnormal number of Multi-Factor Authentication (MFA) authentication events for this user have been observed. These events may include both failed and successful authentications to an MFA service. • **NumCP-PrivUse-EC-U-APC** – An abnormal number of administrative privilege access events have been observed for this user. • **NumDC-ShA-ShareC-U-DS** – An abnormal number of unique network shares have been accessed for this user. • **NumCP-EScrn-EC-U** – An abnormal number of screenshot events have been observed for this user. • **NumCP-ELF-EC-U-DZ** – An abnormal number of failed logins to endpoints in this network zone have been observed for this user. • **NumCP-PC-DirSearchCount-U** – An abnormal number of unix file search process executions have been observed for this user. • **NumDCP-Auth-TgsEC-U-Sn** – An abnormal number of Ticket Granting Services (TGS) were observed for this user. In Kerberos authentication, a Ticket Granting Ticket (TGT) is a user authentication token issued by the Key Distribution Center (KDC) to be used to request from the Ticket Granting Service (TGS) access tokens for specific resources/systems joined to the domain. This event is notable since it may indicate use of stolen credentials. • **NumCP-EMR-EC-DU** – An abnormal number of incoming emails have been observed for this user. • **NumCP-UPwdMod-O** – An abnormal amount of password reset events were observed for this user.

Feature	Description
	• **NumDCP-EL-DEC-SE-DE** – An abnormal number of unique destination endpoints have been observed in successful endpoint login events from this endpoint. These events may include interactive Window logins and other (interactive or not) OS logins. • **NumDCP-Network-DIPC-SE-DIP** – An abnormal number of unique destination IPs have been accessed from this source endpoint. • **NumCP-PC-ChmodCount-U** – An abnormal number of 'chmod' (Change Mode) process executions have been observed for this user. • **NumCP-PwdChkout-EC-O-SC** – An abnormal number of password retrievals have been observed for the organization. • **NumDCP-FWrite-EC-U-FP** – An abnormal number of unique files have been written for this user. • **NumDCP-SA-ANC-U-AN** – An abnormal number of unique alerts have triggered for this user. • **NumCP-ELF-EC-U-DE** – An abnormal number of failed endpoint logins to this endpoint have been observed for this user. • **NumCP-PC-ModprobeCmdC-DE** – An abnormal number of 'modprobe' (Module Probe, a kernel module managment tool) process executions have been observed on this endpoint. • **NumCP-PCpwrshell-EC-O** – An abnormal number of PowerShell process executions have been observed for the organization. • **NumDCP-FUSB-FPC-U-FP** – An abnormal number of unique files has been written to peripheral storage devices for this user. • **NumDC-RA-U-RAC** – An abnormal number of role-assume requests have been observed for this user. These events can include both successful and failed assumed roles. • **NumDCP-EL-DEC-U-DE** – An abnormal number of unique destination endpoints have been observed in endpoint login events for this user. These events may include interactive Window logins and other (interactive or not) OS logins, both failed as successful. • **NumCP-PC-InsmodCmdC-U** – An abnormal number of 'insmod' (Install Module) process executions have been observed for this user. • **NumCP-DSOW-EC-UD** – An abnormal number of directory service write events have been observed for users in this department. Directory services typically manage various types of objects to organize and administer resources within a network environment. Pre-built analytics rules for which `trainOnCondition` was updated include: • **Prof-GA-E-U-SE** – This is the first time an activity from this endpoint has been observed for this user. Pre-built analytics rules for which `scoreUnless` was updated include: • **Prof-ELF-E-U-DE** – This is the first time this user has failed to log into this endpoint. The user might have logged in successfully before, but this is the first time a failed login event was observed on the endpoint. Pre-built analytics rules for which `detectionReason` was updated include: • **Fact-CA-Startup-StartupScriptAWS** – A startup script was added or modified in an instance in AWS. • **Fact-CA-SPM-PublicAWS** – A compute snapshot resource in AWS has been made public, granting access to all users. • **Fact-CA-Startup-StartupScriptGCP** – A startup or shutdown script have been added or modified in a instance in GCP. Removed obsolete pre-built analytics include: • **Cntx-PC-Critical-Parent-CritWindows** – Parent process is a known critical Windows command: True\False

Feature	Description
	• **Cntx-PC-Critical-CritWindows** – Process is a known critical Windows command: True\False

Resolved Issues

Log Stream Resolved Issues

Issue ID	Description
ENG-73916	To resolve an issue during parsing of raw logs to events, Log Stream now drops fields when the field value is a literal dash ("-"). This resolution avoids incorrect rule triggering when fields with only a dash value are parsed.

Site Collector 2.16: Resolved Issues

Release Number	Description
ENG-83398	Fixed vulnerailities for commons-fileupload, bcprov-jdk15o, c-ares, commons-beanutils.
ENG-79756	Fixed an issue for the Linux File Collector in which the collector installation on a Red Hat server failed because the Site Collector instance used to reset the connection, even though the server can reach it on all required ports. The Linux File Collector installation now completes successfully on the a Red Hat server.

Site Collector 2.16: Security Vulnerabilities Remediations

The Site Collectors 2.16 (January 2026) release includes remediated security vulnerabilities. For more information about Exabeam's commitment to remediating vulnerabilities for Site Collector, see the Vulnerability Remediation Policy.

There are no open known CVEs in any container image (Nifi). Toolkit has been deprecated and is no longer in use hence no security vulnerabilities update is available for that.

The following table lists the CVEs remediated for the Nifi container and their severity.

Critical	High	Medium	Low
Total: 0	Total: 2	Total: 13	Total: 0
–	• CVE-2025-66418 • CVE-2025-66471	• CVE-2025-11226 • CVE-2025-11412 • CVE-2025-11413 • CVE-2025-11414 • CVE-2025-11494 • CVE-2025-11839 • CVE-2025-11840 • CVE-2025-6075 • CVE-2025-64505 • CVE-2025-64506 • CVE-2025-64720 • CVE-2025-65018 • CVE-2025-8291	–

2025 Release Notes

These release notes include information about new features, known issues, and resolved issues for the New-Scale Security Operations Platform in all 2025 New-Scale product releases.

- December 2025
- November 2025
- October 2025
- September 2025
- August 2025
- July 2025
- June 2025
- May 2025
- April 2025
- March 2025
- February 2025
- January 2025
- Known Issues

December 2025

The New-Scale Security Operations Platform includes the following addressed features and new features for December 2025.

Attack Surface Insights

Feature	Description
User Entity Linking Using Custom Context Tables	To ensure related identities are accurately unified under a single user entity, you can now control how Attack Surface Insights links identities to entities by defining relationships in a new customizable pre-built context table, the User Entity Links context table. By default, the User Entity Links context table has four columns: KeyType1, Key1, KeyType2, and Key2. You can configure these columns and add data to the context table, either programmatically using APIs or manually. Attack Surface Insights prioritizes enriching user entities with context data from the User Entity Links context data first, alongside Microsoft Active Directory and before any other context source.
Extended Entity Deletion Window	To more easily maintain entities over the long term, you now have a larger window to delete obsolete entities. You can now delete entities created in the past 1,000 days.


Cloud Collectors

Feature	Description
Azure Blob Storage Cloud Collector	The Azure Blob Storage Cloud Collector is now available as part of Cloud Collectors to facilitate ingestion of the logs from Azure data sources such as threat detections, security alerts, and defender OTP logs.
Azure Virtual Network Flow Cloud Collector	The Azure Virtual Network Flow Cloud Collector is now available as part of Cloud Collectors to facilitate ingestion of the virtual network flow logs.
Gemini Enterprise Cloud Collector	The Gemini Enterprise Cloud Collector is now available as part of Cloud Collectors to facilitate ingestion of the Model Armor prompts logs of Gemini Enterprise Apps via GCP Pub/Sub topic.
Early Access Collectors	
Gmail BigQuery Cloud Collector	The Gmail BigQuery Cloud Collector is now available as part of Cloud Collectors Early Access program, to facilitate ingestion of the gmail logs. The early access program offers you an opportunity to gain access to the latest cloud collectors before their official release. To participate, see Sign Up for the Early Access Program.

Context Management

Feature	Description
New Attack Surface Insights Context Table	Context Management now provides a new pre-built Attack Surface Insights context table. The new table is the **User Entity Links** context table. It supports the detection and enrichment rule activities of of the Attack Surface Insights application by providing mapping information for custom user entities. For more information about Attack Surface Insights context tables, see Pre-Built Detection Context Tables in the *Context Management Guide*.
New Condition Operators Available for Filtered Tables	Additional condition options have been made available for creating a custom filtered context table in Context Management. Previously, data could only be filtered based on whether is was equal to or contained in a specific value. Now the set of available filtering operators are expanded to include all of the following: • Equals • Contains • Equals Ignoring Case • Starts With • Not Starts With • Not Equals For more information about filtered context tables, see Working with Filtered Context Tables in the *Context Management Guide*.

Correlation Rules

Feature	Description
Granular Correlation Rule Detection Grouping by Detection ID	You can now create a unique case for each correlation rule detection using a detection grouping rule. Detection grouping rules can now group correlation rule detections into a case by their detection ID, a unique identifier assigned to a detection when it's created.  If you're grouping detections by detection ID, the only additional field by which you can group detections is rule name.

Log Sources

Feature	Description
Enhancements to the Log Source Policy	You can now use the following enhancements for Log Source policies: • Editable Log Source Policy Conditions – You can now edit the log source policy conditions in the existing log source polices. • Date Filter – You can now apply a filter to the last seen log sources of a particular log source policy. You can select a date range to view the log sources for a specific time or clear the filter to view the records that were visible before. • Duration of Log Source Retention – You can now set the Time-to-live (TTL) value while creating a log source policy to ensure optimal storage and performance.

Log Stream

Feature	Description
Enhanced Host to IP Enrichment	New-Scale Host to IP enrichment has been enhanced so that the default condition covers an expanded set of filters. It now includes all of the mapping functionality that was available in Advanced Analytics static mapping. In addition, early access opportunities are available to customize the enrichment condition or to exclude specific entities from the enrichment process. See the note below. For more information about this type of enrichment, see Host to IP Enrichment in the *Log Stream Guide*. **NOTE** **Early Access Opportunity** An early access opportunity is available to customize the host to IP enrichment functionality. You may want to take advantage of this opportunity if any of the following reasons apply to your environment: • You want to limit host to IP enrichment to specific scenarios. You can work with Exabeam to develop a custom condition for deciding which logs to enrich. Instead of using the default set of activity types listed above, you can condition the enrichment to be implemented on a more limited set of activity types, in combination with specific outcomes, vendors, or other fields. • You want to exclude domain controllers or other specific servers from the host to IP enrichment process. To implement the exclusion process, contact the Log Stream early access team for help. If you would like to take advantage of this early access customization, email the following group: logstream-ea@exabeam.com.


New-Scale Platform

Feature	Description
Global Token Revocation	When editing or adding a new identity provider, you can now enable Global Token Revocation (Universal Logout) when using Auth0 with Okta Workforce Identity. With Global Token Revocation, if a user is logged out with the identity provider, such as during an admin-initiated logout or a security event, they will also be logged out of all applications, including Exabeam. For more information, see Set up Okta as your Identity Provider in the *New-Scale Security Operations Platform Administration Guide*.
Webhook View Details	When viewing the details of a webhook with a large amount of recent calls, the dialog could take a long time to load or fail to load the responses entirely. Now, only the 10 most recent responses are displayed over the last 48 hours to ensure no issues with loading the View Details dialogue for webhooks. For more information, see View Details/Edit a Webhook in the *New-Scale Security Operations Platform Administration Guide*.



Search


Feature	Description
Improvements to the Timeline View of Search Results	The layout and functional behavior of the Timeline view of search results has been enhanced to both reduce visual noise and make the investigational workflow more intuitive. For easier scanning and to provide a more streamlined view of events, the display of parsed fields can be toggled on and off from an option at the top of the results list. In addition, fewer clicks are now needed to drill into events and detection when looking for detailed information. For more information, see Timeline View of Search Results in the *Search Guide*.
Increased in Storage Retention for Some Licenses	Default search retention has been extended from 31 days to 45 days for customers using New-Scale Analytics and New-Scale Fusion licenses. For information about the storage capacity available for your specific license, see Exabeam Product Entitlements. For more information about different types of storage, see Log Retention in the *Search Guide*.



Threat Center


Feature	Description
Granular Correlation Rule Detection Grouping by Detection ID	You can now create a unique case for each correlation rule detection using a detection grouping rule. Detection grouping rules can now group correlation rule detections into a case by their detection ID, a unique identifier assigned to a detection when it's created.  If you're grouping detections by detection ID, the only additional field by which you can group detections is rule name.
New Case Global Notification Enhancement	To ensure you can immediately access important case information from anywhere, you can now get more detailed Threat Center global notifications when a case is created. Global notifications sent when a case is created now include: • Case name • Exabeam Nova Investigation Summary • Risk score • Classification • Threat vector

Threat Detection Management

Feature	Description
Analytics Rules Insights	To troubleshoot over-triggering analytics rules, you can now view suggestions for exclusion expressions that reduce noise for the analytics engine and prevent them from over-triggering. The analytics engine automatically generates the suggestions during training. The **COMPATIBILITY** column has been renamed the **RULE INSIGHTS** column. Under the **RULE INSIGHTS** column, an analytics rule that is most likely to generate false positives is marked as having **Insights**.  To view suggested exclusion expressions for the analytics rule, click **Insights**. You can then copy the exclusion expression and use it to create an exclusion for the analytics rule. If there are no suggested exclusions available, a message suggests that you review the analytics rule. 

Feature	Description
JSON Configuration in Analytics Rule Details	To copy or reference the JSON configuration of an analytics rule, you can now view the JSON configuration under the **JSON** tab in the analytics rule details. 

Feature	Description
Required Event Fields in Analytics Rule Details	To determine if events have the necessary fields for an analytics rule to trigger, you can now review those required fields under **REQUIRED EVENT FIELDS** in the analytics rule details. This list of fields is automatically generated and used by Outcomes Navigator to calculate coverage scores. 
Prerequisite for Enabling and Deleting Exclusions	To prevent changes to exclusions from inadvertently retraining analytics rules, you can no longer enable or delete exclusions while you have pending analytics rule changes. You must apply or revert the pending changes first. If there are any pending changes, you receive an error. 

Feature	Description
Granular Correlation Rule Detection Grouping by Detection ID	You can now create a unique case for each correlation rule detection using a detection grouping rule. Detection grouping rules can now group correlation rule detections into a case by their detection ID, a unique identifier assigned to a detection when it's created.  If you're grouping detections by detection ID, the only additional field by which you can group detections is rule name.

Feature	Description
New and Updated Pre-Built Analytics Rules	You can now better detect defense evasion, persistence, privilege escalation, and reconnaissance with new and updated analytics rules. New pre-built analytics rules include: • **Fact-PCwevtutil-EventTracingClear** – The WEvtUtil (Windows Event Utility) process has been used to clear an ETW (Event Tracing for Windows). This sigma rule is authored by @neu5ron, Florian Roth (Nextron Systems), Jonhnathan Ribeiro, oscd.community and is licensed under Detection Rule License (DRL), https://github.com/SigmaHQ/sigma/blob/master/LICENSE.Detection.Rules.md. Reference: https://github.com/SigmaHQ/sigma/blob/master/rules/windows/process_creation/proc_creation_win_etw_trace_evasion.yml • **NumDC-Git-RepoC-U-Object** – An abnormal number of unique repository endpoints where secrets are generally stored, which may indicate unauthorized enumeration or insider reconnaissance activity. Repository name is parsed into the object field which is being counted here. • **Prof-Fwrite-E-O-DE-Xdg** – This is the first time a XDG autostart file was created on this endpoint. • **Prof-RegW-COM-U-CLSID** – This is the first time this user has modified the registry path to a COM class with this CLSID. • **Fact-CA-Startup-StartupScriptGCP** – A startup or shutdown script have been added or modified in a instance in GCP. • **Fact-FWrite-SELinuxConfigFile** – The SELinux (Security-Enhanced Linux) configuration file was written to. • **Fact-FWrite-SystemCADirs** – A file was written in a System CA (Certificate Authority) directory. • **Prof-AI-U-Guardrail-Block** – This is the first time this user has triggered an AI guardrail violation. • **Prof-Auth-U-Okta-AnomVPN** – This is the first time an Okta user has used an anonymous VPN to authenticate. • **Prof-CA-IPM-AddMember-O-U** – This is the first time a user modified the attributes of a compute image in AWS and shared it with a user/group. • **Prof-PCnet-U-O-U-netuser** – This is the first time a user account has been enabled or disabled using 'net.exe' for this user. • **Prof-CA-IKM-KeyCreateGCP-O-U** – This is the first time this user added or modified an SSH key of an instance in GCP. • **Prof-FWrite-AuthorizedKeys-O-U** – This is the first time an 'authorized_keys' file has been modified by this user. • **Prof-Fwrite-AuditRule-O-U** – This is the first time an audit rule file has been modified by this user. • **Prof-CA-DC-FromSnapshot-O-U** – This is the first time this user created a volume from a snapshot. • **NumCP-Git-EC-U** – An abnormal amount of GitHub API access events have been observed for this user. • **Fact-FWrite-SSHConfigFile** – The sshd_config file was written to. • **Prof-AI-O-Guardrail-Block** – This is the first time a user in the organization has triggered an AI guardrail violation. • **Fact-CA-Startup-StartupScriptAWS** – A startup script was added or modified in an instance in AWS. • **Fact-PCspctl-DisableGatekeeper** – The 'spctl' command has been used to disable the Gatekeeper. • **NumCP-AI-U-Guardrail-Block** – An abnormal amount of AI guardrail violations have been observed for a user. • **Fact-PCauditctl-DeleteRules** – The 'auditctl' command has been used to delete the audit rules.

Feature	Description
	• **Cntx-FA-FCrit-SrcExecutable** – Source file is an executable: True/False • **NumDCP-CA-DAC-U-Disks** – An abnormal number of unique volumes were observed attached to instances for this user. • **Prof-FWrite-AuthorizedKeys-O-UD** – This is the first time an 'authorized_keys' file has been modified by users in this department. • **Prof-PCnet-U-O-U-netuserdel** – This is the first time a user account has been deleted using 'net.exe' for this user. • **Prof-CA-DA-O-U** – This is the first time this user attached a volume to an instance. • **Prof-Fwrite-SystemdService-O-U** – This is the first time a systemd service file has been modified by this user. • **Prof-PCca-U-O-U** – This is the first time root certificate has been installed on a Linux machine using 'update-ca-certificates' or 'update-ca-trust' for this user. • **Fact-PC-DisableAuditd** – Auditd service was disabled. • **Fact-CA-IPM-PublicAWS** – A compute image resource in AWS has been made public, granting access to all users. • **Fact-PCwevtutil-EventTracingDisable** – The WEvtUtil (Windows Event Utility) process has been used to disable an ETW (Event Tracing for Windows). This sigma rule is authored by @neu5ron, Florian Roth (Nextron Systems), Jonhnathan Ribeiro, oscd.community and is licensed under Detection Rule License (DRL). • **Prof-CA-SC-O-U** – This is the first time this user created a snapshot of a compute instance. • **Fact-PCsetenforce-DisableSELinux** – The 'setenforce' command has been used to disable the SELinux (Security-Enhanced Linux). • **Prof-PCnet-U-O-U-netlocalgroup** – This is the first time a user account has been added to a group using 'net.exe' for this user. • **Prof-PCnet-U-O-U-netlocalgroupadmin** – This is the first time a user account has been added to the administrators group using 'net.exe' for this user. • **Prof-CA-IC-Publisher-O-Publisher** – This is the first time this image publisher has been observed in a virtual machine image creation for the organization. • **Prof-PCwmic-IR-O-U-grp** – This is the first time a group has been renamed using 'wmic.exe' for this user. • **Prof-RegW-COM-O-CLSID** – This is the first time the registry path to a COM class with this CLSID has been modified. • **Prof-AI-UD-Guardrail-Block** – This is the first time a user in this department has triggered an AI guardrail violation. • **Prof-CA-SPM-AddMember-O-U** – This is the first time this user modified the attributes of a compute snapshot in AWS and shared it with a user/group. • **Fact-CA-SPM-PublicAWS** – A compute snapshot resource in AWS has been made public, granting access to all users. • **Prof-CA-IC-O-U** – This is the first time this user created an image for compute instances. • **Prof-CA-IRC-O-U** – This is the first time this user executed a remote command on an instance. • **Fact-AI-Guardrail-Block** – An AI guardrail violation has been observed. • **Prof-PCwmic-IR-O-U-usr** – This is the first time a user account has been renamed using 'wmic.exe' for this user. Pre-built analytics rules for which `trainOnCondition` was updated include: • **Prof-EL-HT-U-HT** – This is the first time this user has attempted to log into an endpoint of this type (server, workstation...). These events may include both failed and successful logins.

Feature	Description
	• **Prof-ELF-E-U-DE** – This is the first time this user has failed to log into this endpoint. The user might have logged in successfully before, but this is the first time a failed login event was observed on the endpoint. • **Prof-EL-EDC-U-SZ** –This is the first time an endpoint login event to a domain controller has been observed originating from this network zone for this user. These events may include both failed and successful logins. • **NumCP-ELF-EC-U-SE** – An abnormal number of failed endpoint logins from this endpoint have been observed for this user. • **Prof-Login-EmD-Plt-EmD** – This is the first time this email domain has been used to log into this platform. • **Prof-GA-Op-Plt-Op** – This is the first time this operation has been observed for this platform. Operations can include function types, APIs, application activities and more. • **Prof-EL-EDC-O-SZ** – This is the first time an endpoint login event to a domain controller has been observed originating from this network zone for the organization. These events may include both failed and successful logins. • **Fact-ELF-SA** – A service account failed to log into an endpoint using an interactive Windows logon type. A service account is a user account that belongs to an application rather than an end user. • **NumDCP-ELF-SEC-DE-SE** – An abnormal number of unique endpoints have been observed failing to log into this endpoint. • **Prof-EL-E-U-DE** – This is the first time this user attempted to log into this endpoint. These events may include both failed and successful logins. • **NumCP-ELF-EC-U-DE** – An abnormal number of failed endpoint logins to this endpoint have been observed for this user. • **Prof-EL-E-U-SE** – This is the first time this user attempted to login from this endpoint. These events may include both failed and successful logins. • **NumCP-ELF-EC-U-DZ** – An abnormal number of failed logins to endpoints in this network zone have been observed for this user. • **Prof-EL-E-UD-DE** – This is the first time a user from this department attempted to log into this endpoint. These events may include both failed and successful logins. Pre-built analytics rules for which `description` was updated include: • **Prof-PC-U-O-U-Kextload** – his is the first time a process execution of a 'kextload' (Kernel Extension Load) command has been observed for this user. • **NumCP-PC-KextloadCmdC-U** – An abnormal number of 'kextload' (Kernel Extension Load) process executions have been observed for this user. Pre-built analytics rules for which `title` was updated include: • **NumCP-PC-DirSearchCount-U** – An abnormal number of unix file search process executions have been observed for this user. Pre-built analytics rules for which `value` and `actOnCondition` were updated include: • **Fact-Fwrite-HiddenFile** – Createing a file that starts with ".". File that starts with "." is a hidden file. An attacker can create hidden file to evade detection. • **Fact-Fwrite-RCScripts** – Adversaries can establish persistence by adding a malicious binary path or shell commands to rc.local, rc.common, and other RC scripts specific to the Unix-like distribution.


Feature	Description
	• **Fact-Fwrite-LoginHookFile** – Adversaries may use a Login Hook to establish persistence executed upon user logon. They can add or insert a path to a malicious script in the com.apple.loginwindow.plist file, using the LoginHook or LogoutHook key-value pair. • **Fact-PC-DisableHistoryCol** – History collection can be disabled in unix shells by modifying the history environment variables. This can help the attacker ot evade detection. • **Fact-PC-ClearComHistory** – This can help the attacker ot evade detection. • **Fact-PC-LoginHookFile** – Adversaries may use a Login Hook to establish persistence executed upon user logon. The plist can be modified using the defaults command-line utility. This behavior is the same for logout hooks where a script can be executed upon user logout. • **Fact-PC-Chflags-HiddenFile** – The "setfile" unix process can be used to make files hidden by modifying their attributes, making sure they remain undetected by users. An attacker can create hidden file to evade detection. Pre-built analytics rules for which `applicable_events` and `trainOnCondition` were updated include: • **NumSP-NetworkF-BytesOut-SE-Bytes** – An abnormal amount of bytes have failed to be sent in outbound communication from this endpoint. Pre-built analytics rules for which `value`, `actOnCondition`, and `maturityThreshold` were updated include: • **Fact-FRead-Passwd** – The passwd file is a plain text file in Unix-based operating systems, including Linux and macOS, that stores essential user account information. An attacker can try to read it to get information about the users include the passwords • **Fact-PC-Visudo** – The /etc/sudoers file is typically edited using the visudo command, which provides a safe way to make changes to the file and prevents multiple simultaneous edits, reducing the risk of syntax errors that could lock users out of administrative access. An attacker can try to read this file to know what user he should get access to, or he can try to write to this file and give a user he have access to these privileges. • **Fact-FA-Sudoers** – The /etc/sudoers file is a critical configuration file in Unix-based operating systems. It controls the access and privileges granted to users and groups to execute commands with elevated privileges (root or superuser privileges) using the sudo command. An attacker can try to read this file to know what user he should get access to, or he can try to write to this file and give a user he have access to these privileges. • **Fact-PC-SuspFind** – Adversaries may enumerate files and directories or may search in specific locations of a host or network share for certain information within a file system. This command searches for files with the setuid (SUID) permission set for the owner. • **Fact-PC-Shell-Base64** – Identifies base64 being decoded and passed to a Linux shell • **Fact-FWrite-EtcLldSo** – The /etc/ld.so.preload file, if present, allows users to add additional shared libraries that will be loaded before the standard libraries. This can be useful for various purposes, such as implementing custom libraries, applying system-wide modifications, or debugging and profiling applications. Attackers could use this file to force the loading of their own malicious libraries, enabling them to modify system behavior, escalate privileges, or intercept sensitive data. Pre-built analytics rules for which `title`, `description`, and `detectionReason` were updated include: • **NumDCP-RegW-RPC-ServicesStop-DE-RP** – An abnormal number of unique services have been stopped by modifying the registry on this endpoint. Pre-built analytics rules for which `value`, `supressThreshold`, `supressScope`, `actOnCondition`,and `maturityThreshold` were updated include:




Feature	Description
	• **Fact-PC-Chmod-Setgid** – An adversary may change the setgid bits set in order to get code running in a different (and possibly more privileged) user's context • **Fact-PC-Chmod-Setuid** – An adversary may change the setuid bits set in order to get code running in a different (and possibly more privileged) user's context Removed obsolete pre-built analytics include: • **Prof-CDA-UCreateFromSnapshot-O-U** – This is the first time this user created a volume from a snapshot. • **ProfCIA-Publisher-O-Publisher** – This is the first time this image publisher has been observed in a virtual machine image creation for the organization. • **Fact-CIA-PublicAWS** – A compute image resource in AWS has been made public, granting access to all users. • **Prof-CVMA-RemoteCommand-O-U** – This is the first time this user executed a remote command on an instance. • **NumDCP-CDA-EC-U-Disks** – An abnormal number of volumes were observed attached to instances for this user. • **Fact-CVMA-Startup-StartupScriptAWS** – A startup script was added or modified in an instance in AWS. • **Prof-CVMA-KeyCreateGCP-O-U** – This is the first time this user added or modified an SSH key of an instance in GCP. • **Prof-CIA-UCreate-O-U** – This is the first time this user created an image for compute instances. • **Prof-EL-Acct-U-Acct** – This is the first time this user has attempted to log into an endpoint using this domain account. These events may include both failed and successful logins. • **Prof-CSA-UCreate-O-U** – This is the first time this user created a snapshot of a compute instance. • **Prof-CDA-UAttach-O-U** – This is the first time this user attached a volume to an instance. • **Prof-CIA-UAddMemberAWS-O-U** – This is the first time a user modified the attributes of a compute image in AWS and shared it with a user/group. • **Prof-CSA-UAddMemberAWS-O-U** – This is the first time this user modified the attributes of a compute snapshot in AWS and shared it with a user/group. • **Fact-CSA-PublicAWS** – A compute snapshot resource in AWS has been made public, granting access to all users. • **Fact-PCwevtutil-ELT** – The WEvtUtil (Windows Event Utility) process has been used to disable or clear an ETW (Event Tracing for Windows). This sigma rule is authored by @neu5ron, Florian Roth (Nextron Systems), Jonhnathan Ribeiro, oscd.community and is licensed under Detection Rule License (DRL). • **Fact-FDnld-ExeFile** – An file with an executable extension has been downloaded. • **Fact-CVMA-Startup-StartupScriptGCP** – A startup or shutdown script have been added or modified in a instance in GCP.

November 2025




The New-Scale Security Operations Platform includes the following addressed features and new features for November 2025.



Attack Surface Insights



Feature	Description
Attack Surface Insights Rules for Entity Types	To simplify and better manage your Attack Surface Insight rules, rule management is now separated by entity type. You now manage rules for user entities on the Users tab and rules for device entities on the Devices tab.
Pre-Built Attack Surface Insights Rule Security Criticality Editing	To better customize pre-built Attack Surface Insight rules, you can now edit the security criticality of a pre-built Attack Surface Insights Rule.
Entity Details Organized By Source	To clarify from where attributes are derived, entity details are now organized by source. You can now view attributes derived from context tables under **Context Data** and attributes derived from events under **Event Data**. 

Feature	Description
Default View Enhancement	To help you get started searching for entities, you can now view a list of example queries in the default view of the **Users** and **Devices** tabs. When you click on an example, the query automatically populates the search bar.  
Security Criticality Tiers	To improve clarity and align with standard tier models, the values for security critical now include a corresponding tier number. The updated values are High (1), Medium (2), and Low (3). 

Automation Management

Feature	Description
Service and Action Deletion	To organize and maintain your automation tools, you can now delete custom services and actions. Before you delete a service or action, you must remove it from all existing playbooks.   

Feature	Description
Increased Playbook Name Character Limit	To allow you to create more detailed and descriptive playbook names, you can now enter up to 205 characters for the playbook name. 
Increased No Trigger Playbook Creation Limit	To build a more comprehensive library of manual, on-demand playbooks, you can now create up to 20 advanced playbooks without a trigger. 



Feature	Description
Service Created By Filter	To find a specific service, you can now filter services by creator. The searchthen applies only to those filtered results. 
Pre-Built Service Created By Enhancement	To better distinguish between pre-built and custom services, the Exabeam name and logo is now displayed under the **CREATED BY** column for pre-built services. 

Cloud Collectors

Feature	Description
Broadcom Carbon Black Cloud Collector	The Broadcom Carbon Black Cloud Collector is now available as part of Cloud Collectors, to facilitate ingestion of Alerts, Events, and Audit Logs from the storage bucket used by the data forwarder.
Cylance Protect (now Arctic Wolf) Cloud Collector	The Cylance Protect (now Arctic Wolf) Cloud Collector is now available as part of Cloud Collectors, to facilitate ingestion of logs from the following data sources: **Memory Protection**, to collect threats related to memory vulnerabilities, **Threats**, to collect threat detection alerts and related information, or both.
GitHub Cloud Collector	The GitHub Cloud Collector is now available as part of Cloud Collectors to facilitate ingestion of GitHub enterprise audit logs that include events such as repository access, authentication attempts, permission changes, and more from the GitHub Enterprise Audit API endpoint to monitor your enterprise GitHub server or cloud-based GitHub service.
Early Access Collectors	
Azure Blob Storage Cloud Collector	The Azure Blob Storage Cloud Collector is now available as part of Cloud Collectors Early Access program, to facilitate ingestion of the logs from Azure data sources such as threat detections, security alerts, and defender OTP logs. The early access program offers you an opportunity to gain access to the latest cloud collectors before their official release. To participate, see Sign Up for the Early Access Program.
Azure Virtual Network Flow Cloud Collector	The Azure Virtual Network Flow Cloud Collector is now available as part of Cloud Collectors Early Access program, to facilitate ingestion of the virtual network flow logs. The early access program offers you an opportunity to gain access to the latest cloud collectors before their official release. To participate, see Sign Up for the Early Access Program.

Feature	Description
Palo Alto Networks XDR Cloud Collector	The Palo Alto Networks XDR Cloud Collector is now available as part of Cloud Collectors early access program to facilitate ingestion of the security alerts logs generated by Cortex XDR. The early access program offers you an opportunity to gain access to the latest cloud collectors before their official release. To participate, see Sign Up for the Early Access Program.

Correlation Rules

Feature	Description
Trigger Schedules	To address specific use cases and improve correlation rule accuracy, you can schedule correlation rules to trigger on specific days or during specific periods only. When you create or edit a correlation rule, you can schedule a correlation rule to trigger daily, weekly, monthly, or during a custom time period with specific start and end times.  

Feature	Description
New Correlation Rule Templates	You can now better detect adversary reconnaissance techniques with new correlation rule templates: • **Fsutil Peripheral Device Discovery Command** – Detects use of the fsutil command to enumerate drives, which may indicate reconnaissance or preparation for data exfiltration. • **Password Policy Discovery Commands** – Detects use of commands used to access information about password policies. • **System Language Discovery Commands** – Detects use of commands used to gather information about the system language of a victim to potentially infer the geographical location of that host. • **Log Enumeration Commands** – Detects the use of commands used to enumerate system and service logs.


Dashboards

Feature	Description
Auto-Creating an Anomaly Fields Visualization from a Natural Language Prompt	As part of Exabeam Nova and its set of AI-driven capabilities, the use of the natural language prompt for auto-creating a dashboard visualization has been expanded to an additional data model. You can now use the natural language prompt for the **Anomaly Fields** data model. This enhancement means that you can leverage the natural language prompt in the Dashboard application to describe, in plain language, the **Anomaly Fields** data you want to visualize. Based on this plain language prompt, the measures, dimensions, filters, and even the chart type can be configured automatically. **NOTE** This auto-create option is also currently available to create visualizations for the **Event** and **Alerts** data models. (You must be using Threat Center to access the **Alerts** data model.) If the automatically generated visualization does not produce the data you want to visualize, you can modify the visualization settings manually to produce exactly the desired results. For more information about auto-creating visualizations, see Auto-Create a Visualization from a Natural Language Prompt in the *Dashboards Guide*.

Log Stream

Feature	Description
Planned Removal of Custom Default Parsers	The **Custom Default** category of parsers will be discontinued in favor of a simpler, more streamlined approach to customizing default parsers. In January of 2026, Exabeam will begin, one region at a time, removing the custom default parsers from Log Stream. As these parsers are removed, the corresponding default parsers will become enabled. Exabeam will provide notifications in each region before beginning to remove the custom default parsers. The **Custom Default** category is a specific set of customized parsers that were migrated from legacy products. These parsers were originally created for use in your legacy product environments when a customization was needed. Once migrated to Log Stream, custom default parsers were treated like default parsers, except they were not updated by the regular Exabeam content packages. As a result, these parsers have become out-of-date and stale but continue to be enabled and active in Log Stream. Parsers in this category have higher priority ratings than their corresponding default parsers and cause the more up-to-date default parsers to be disabled. Discontinuing the **Custom Default** category will help resolve these issues and simplify the overall categorization of parsers. If you rely on any of the custom default parsers in your Log Stream environment and you want to retain the customizations they contain, you need to identify them and manually add the same customizations to the corresponding default parser. For more information about this change to parser customization, and for the steps necessary to retain customizations you rely on, see Parser Types in the *Log Stream Guide*.
Filtering Live Tail by Source Collectors	The filtering capabilities in Live Tail have been enhanced with an additional option. In addition to being able to filter for all logs parsed by a specific parser, you can now opt to filter the Live Tail stream based on the source collector the logs are being ingested from. For more information about filtering the Live Tail stream, see View and Filter Data in the Live Tail section of the *Log Stream Guide*.

New-Scale Platform

Feature	Description
Multi-factor Authentication for Local Accounts	To reduce downtime in the event of SSO interruption, you can now require Multi-factor Authentication (MFA) for all local accounts.  To activate MFA, enable it on the Single Sign-On/MFA settings page. When enabled, local accounts will require registration of a MFA token on the next login and then to authenticate on each subsequent login using a compatible TOTP authenticator. Reset a token anytime through the Users settings page, which will force new MFA on a local account. 
Improved Query Building for Secured Resources	The query building functionality available to define secured resources has been updated to include the improved capabilities already available in the Search application. These include the option to build queries using either Basic or Advanced search modes. The Basic mode allows you to select fields from pre-built options for fast, accurate query building. The Advanced mode provides the flexibility to manually build a query and includes the following upgrades: • Improved suggestions as you enter query syntax • Options to search in any column of a context table • Server-side parsing of Exabeam Query Language For more information, see Secured Resources in the *New-Scale Security Operations Platform Administration Guide*.

Search

Feature	Description
Improvements to the Timeline View of Search Results	The layout and functional behavior of the Timeline view of search results has been enhanced to both reduce visual noise and make the investigational workflow more intuitive. To better represent the sometimes confusing relationships between events and detections distinct **Events** and **Detections** columns have been labeled and the associations between events and detections in these columns have been clarified. For more information, see Timeline View of Search Results in the *Search Guide*.



Site Collectors 2.15




Feature	Description
Custom Installation Folder	Site Collector now creates a custom installation folder during the Site Collector installation process. • If the default folders **/tmp** and **/opt** do not exist, they will be created automatically. • If the you specify a custom folder instead of the default **/opt**, for example, /opt123, the specified folder is created if it does not already exist, for Site Collector installation. • If you specify a custom folder instead of the default **/tmp**, for example, /tmp123, the specified folder is created if it does not already exist, for Site Collector installation.
Enhancement for the Splunk Collector	Optimized performance for the Splunk collector for processing time-based conditions.
Precheck Implementation	Implemented a precheck that verifies that only valid SSL certificate files are stored in the **/opt/exabeam_prep/ssl** folder, and no other files such as certificate bundles or non-certificate items are included.



Threat Center

Feature	Description
Webhook Payload Enhancements	You can now get more context for automation and better track events with enhanced webhook payloads. When case or alert information is sent to a webhook, the payload now includes key timestamps: • `alert_created_time`, `case_created_time`, and `case_closed_time` are now included in the case webhook payload. • `alert_created_time` is now included in the alert webhook payload.

Threat Detection Management

Feature	Description
Correlation Rule Trigger Schedules	To address specific use cases and improve correlation rule accuracy, you can schedule correlation rules to trigger on specific days or during specific periods only. When you create or edit a correlation rule, you can schedule a correlation rule to trigger daily, weekly, monthly, or during a custom time period with specific start and end times.  

Feature	Description
Pre-Built Analytics Rule Update Enhancement	In pre-built analytics rule details, you can now more quickly identify and understand what's changed with an analytics rule update: • If an analytics rule has an available update, you can view an **UPDATE AVAILABLE** status in the analytics rule details.  • You can view a streamlined summary of the specific fields and values that have been changed with the update. 
Additional Analytics Rule Details Actions	To streamline rule management, you can now edit, export, and adjust severity from the analytics rule details. 

Feature	Description
Analytics Rule Details Summary Enhancement	To make the configuration of an analytics rules easier to understand, you can now view its key components in a human-readable format under **Summary** in the analytics rule details. 
Analytics Rules Last Modified Column	You can now quickly identify and sort analytics rules by when they were last modified using the **Last Modified** column. 

Feature	Description
New and Updated Pre-Built Analytics Rules	You can now better detect adversary techniques, from initial reconnaissance and privilege escalation to defense evasion and data exfiltration, with new and updated analytics rules. New pre-built analytics rules include: • **NumCP-Git-EC-U** – An abnormal amount of GitHub API access events have been observed for this user. • **NumDC-Git-RepoC-U-Object** – An abnormal number of unique repository endpoints where secrets are generally stored, which may indicate unauthorized enumeration or insider reconnaissance activity. Repository name is parsed into the object field which is being counted here. • **Prof-Auth-U-Okta-AnonVPN** – This is the first time an Okta user has used an anonymous VPN to authenticate. • **NumCP-FDel-LogFileCount-U** – An abnormal number of log file deletion events have been observed for this user. • **NumCP-PC-InsmodCmdC-DE** – An abnormal number of 'insmod' (Install Module) process executions have been observed on this endpoint. • **Prof-DL-U-O-Upit** – This is the first time a kernel module/driver was loaded for this user. • **NumCP-DL-EC-SE** – An abnormal number of kernel module or drivers have been loaded on this endpoint. • **Prof-PC-U-O-U-Modprobe** – This is the first time a process execution of a 'modprobe' (Module Probe, a kernel module management tool) command has been observed for this user. • **Fact-PC-Visudo** – The /etc/sudoers file is typically edited using the visudo command, which provides a safe way to make changes to the file and prevents multiple simultaneous edits, reducing the risk of syntax errors that could lock users out of administrative access. An attacker can try to read this file to know what user he should get access to, or he can try to write to this file and give a user he have access to these privileges. • **NumCP-PC-ModprobeCmdC-U** – An abnormal number of 'modprobe' (Module Probe, a kernel module management tool) process executions have been observed for this user. • **Fact-PC-Chmod-Setuid** – An adversary may change the setuid bits set in order to get code running in a different (and possibly more privileged) user's context. • **Fact-FRead-Shadow** – The shadow file is a file in Unix-based operating systems, including Linux and macOS, that stores password-related information for user accounts. It is a crucial component of the system's security as it helps protect user passwords from unauthorized access. An attacker can try to read it to get the passwords of the users. • **Fact-PC-DisableHistoryCol** – History collection can be disabled in unix shells by modifying the history environment variables. This can help the attacker to evade detection. • **Fact-FA-Sudoers** – The /etc/sudoers file is a critical configuration file in Unix-based operating systems. It controls the access and privileges granted to users and groups to execute commands with elevated privileges (root or superuser privileges) using the sudo command. An attacker can try to read this file to know what user he should get access to, or he can try to write to this file and give a user he have access to these privileges. • **Fact-PC-Setfile-HiddenFile** – The "setfile" unix process can be used to make files hidden by modifying their attributes, making sure they remain undetected by users. An attacker can create hidden file to evade detection. • **Fact-Fwrite-HiddenFile** – Creating a file that starts with ".". File that starts with "." is a hidden file. An attacker can create hidden file to evade detection. • **NumCP-DL-EC-UPIt** – An abnormal number of kernel module or drivers have been loaded for this user. • **Prof-DL-E-O-SE** – This is the first time a kernel module/driver was loaded on this endpoint. • **Cntx-EL-UCrit-ADomain** – User is a domain account: True/False.

Feature	Description
	• **Fact-PC-SuspFind** – Adversaries may enumerate files and directories or may search in specific locations of a host or network share for certain information within a file system. This command searches for files with the setuid (SUID) permission set for the owner. • **NumCP-PC-ChmodCount-U** – An abnormal number of 'chmod' (Change Mode) process executions have been observed for this user. • **Prof-PC-E-O-SE-Modprobe** – This is the first time a process execution of a 'modprobe' (Module Probe, a kernel module management tool) command has been observed on this endpoint. • **NumCP-PC-ChownCount-U** – An abnormal number of 'chown' (Change Owner) process executions have been observed for this user. • **Prof-PC-E-O-SE-Insmod** – This is the first time a process execution of a 'insmod' (Install Module) command has been observed on this endpoint. • **NumCP-PC-KextloadCmdC-U** – An abnormal number of 'kextload' (Kernel Extension Load) process executions have been observed for this user. • **Fact-PC-Chmod-Setgid** – An adversary may change the setgid bits set in order to get code running in a different (and possibly more privileged) user's context. • **Fact-PC-LoginHookFile** – Adversaries may use a Login Hook to establish persistence executed upon user logon. The plist can be modified using the defaults command-line utility. This behavior is the same for logout hooks where a script can be executed upon user logout. • **NumCP-PC-SudoCount-U** – An abnormal number of 'sudo' (Superuser Do) process executions have been observed for this user. • **Prof-Fwrite-U-O-U-KernelExtExt** – This is the first time a kernel extension file was created on MacOS system by this user. • **Prof-PC-U-O-U-Insmod** – This is the first time a process execution of a 'insmod' (Install Module) command has been observed for this user. • **NumCP-PC-InsmodCmdC-U** – An abnormal number of 'insmod' (Install Module) process executions have been observed for this user. • **Fact-Fwrite-LoginHookFile** – Adversaries may use a Login Hook to establish persistence executed upon user logon. They can add or insert a path to a malicious script in the com.apple.loginwindow.plist file, using the LoginHook or LogoutHook key-value pair. • **Prof-FDel-U-O-U-LogFile** – This is the first time a log file has been deleted by this user. • **NumCP-PC-ModprobeCmdC-DE** – An abnormal number of 'modprobe' (Module Probe, a kernel module management tool) process executions have been observed on this endpoint. • **Prof-PC-U-O-U-Kextload** – This is the first time a process execution of a 'kextload' (Kernel Extension Load) command has been observed for this user. • **NumCP-PC-DirSearchCount-U** – An abnormal number of unix file search process executions have been observed for this user. • **Fact-PC-Chflags-HiddenFile** – The "setfile" unix process can be used to make files hidden by modifying their attributes, making sure they remain undetected by users. An attacker can create hidden file to evade detection. • **Prof-PC-U-O-USudo** – This is the first time a process execution of a 'sudo' (Superuser Do) command has been observed for this user. • **Fact-FRead-Passwd** – The passwd file is a plain text file in Unix-based operating systems, including Linux and macOS, that stores essential user account information. An attacker can try to read it to get information about the users including the passwords. • **Fact-PC-ClearComHistory** – This can help the attacker to evade detection. • **Fact-FWrite-EtcLldSo** – The /etc/ld.so.preload file, if present, allows users to add additional shared libraries that will be loaded before the standard libraries. This can be useful for various purposes, such as implementing custom libraries, applying system-wide modifications, or debugging and profiling applications. Attackers could use this file to force the loading of

Feature	Description
	their own malicious libraries, enabling them to modify system behavior, escalate privileges, or intercept sensitive data. • **Fact-PC-Shell-Base64** – Identifies base64 being decoded and passed to a Linux shell. • **Fact-Fwrite-RCScripts** – Adversaries can establish persistence by adding a malicious binary path or shell commands to rc.local, rc.common, and other RC scripts specific to the Unix-like distribution. • **Prof-Fwrite-U-O-U-Plist** – This is the first time a plist file was created by this user. Pre-built analytics rules for which `featureValue` was updated include: • **Prof-STC-O-PN** – This is the first time a scheduled task has been created and configured to execute this process for the organization. • **NumDCP-FWrite-EC-U-FP** – An abnormal number of unique files have been written for this user. • **NumDCP-PCCEnum-TC-U-CEnum** – An abnormal number of unique credential enumeration tools have been executed for this user. • **Prof-PCipconfig-NetDisc-U-PN** – This is the first time a process execution of 'ipconfig.exe' has been observed for this user. • **Prof-PCpwrshell-En-O-PP** – This is the first time a process execution of 'powershell.exe' with an encrypted command has been observed for this parent process. • **Prof-FPM-PublicCloud-B-U** – This is the first time a cloud storage object was modified to become public in this bucket. By manipulating file permissions to make the object public, attackers can expose the data of important or sensitive files, making them available to read, download or even modify by everyone. • **Prof-PC-PN-PltUD-PN** – This is the first time this process has been executed in this platform for users in this department. This feature only models processes from - Windows commands, pentest tools, system enumeration, account enumeration and network sniffers. • **Prof-PCIOC-IOCPenT-U-PenT** – This is the first time a process execution of a known pentesting tool has been observed for this user. • **Prof-DllLoad-Dir-O-FD** – This is the first time a DLL image file was loaded from this folder for the organization. • **Prof-PC-PN-PltSZ-PN** – This is the first time this process has been executed in this platform from this network zone. This feature only models processes from - Windows commands, pentest tools, system enumeration, account enumeration and network sniffers. • **Prof-DllLoad-Dll-O-FN** – This is the first time this DLL image file was loaded in the organization. • **Prof-PC-PN-Plt-PN** – This is the first time this process has been executed in this platform. This feature only models processes from - Windows commands, pentest tools, system enumeration, account enumeration and network sniffers. • **NumDCP-PCHEnum-TC-U-HEnum** – An abnormal number of unique host enumeration tools have been executed for this user. • **Prof-CPM-Resource-O-R** – This is the first time an IAM policy of a resource in this directory has been modified in GCP. IAM policies determine the roles and permissions granted to users on a resource. • **Prof-RegR-Certs-U-RP** – This is the first time this user has read this certificate\private key related registry value. • **NumDCP-FRead-EC-B-FP** – An abnormal number of unique files have been read in this bucket for this user. • **Prof-CPM-Resource-U-R** – This is the first time an IAM policy of a resource in this directory has been modified by this user in GCP. IAM policies determine the roles and permissions granted to users on a resource.

Feature	Description
	• **Prof-PC-PN-DE-PN** – This is the first time this process has been executed on this endpoint. This feature only models processes from - Windows commands, pentest tools, system enumeration, account enumeration and network sniffers. • **Prof-RegA-PP-O-PP** – This is the first time this process has performed a registry activity. • **NumDCP-RegR-RPC-Cert-U-RP** – An abnormal number of unique certificates and private keys related registry values have been read by this user. • **Prof-SA-PN-UD-PN** – This is the first time an alert triggered on this process for users in this department. • **NumDCP-FRead-EC-UP-FP** – An abnormal number of unique files have been read in this platform for this user. • **NumDCP-FRead-EC-SA-FP** – An abnormal number of unique files have been read in this storage account for this user. • **Prof-STC-U-PN** – This is the first time a scheduled task has been created and configured to execute this process for this user. • **Prof-SA-PN-U-PN** – This is the first time an alert triggered on this process for this user. • **Prof-STC-TN-UD-TN** – This is the first time a scheduled task with this name has been created for users in this department. • **Prof-PC-PN-PltU-PN** – This is the first time this process has been executed in this platform for this user. This feature only models processes from - Windows commands, pentest tools, system enumeration, account enumeration and network sniffers. • **Prof-PCroute-NetDisc-U-PN** – This is the first time a process execution of 'route.exe' has been observed for this user. • **Prof-SA-PN-O-PN** – This is the first time a security alert triggered on this process for the organization. • **NumDCP-FUSB-FPC-U-FP** – An abnormal number of unique files has been written to peripheral storage devices for this user. • **Prof-PC-O-Pdir** – This is the first time a process execution has been observed from this directory. • **Prof-STC-TN-O-TN** – This is the first time a scheduled task with this name has been created. • **Prof-WinSC-PP-SN-PP** – This is the first time this service was created with this command process path. • **Prof-PC-PN-Pdir** – This is the first time a process execution has been observed from this directory for this process. Pre-built analytics rules for which `scoreUnless` was updated include: • **Prof-RegW-UAC-O-U** – This is the first time this user has modified or created a registry key\value under the UAC configuration key 'HKLM\SOFTWARE\Microsoft\Windows\CurrentVersion\Policies\System'. • **Prof-RegW-U-DetailsLen** – An abnormal registry details length has been observed for this user. • **Fact-RegW-TrustProvider** – A trust provider component has been modified via the registry. • **Prof-RegW-IFEO-O-U** – This is the first time this user has modified or created the Image File Execution Options of a process by writing to the registry value 'Debugger' under the key 'HKLM\SOFTWARE{\Wow6432Node}\Microsoft\Windows NT\CurrentVersion\Image File Execution Options\<executable>'. • **Prof-RegW-EnvVarPath-O-U** – This is the first time this user has modified the PATH environment variable by writing to the registry value 'HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Control\Session Manager\Environment\Path'.

Feature	Description
	• **Fact-RegE-SAM** –The registry key 'HKLM\SAM' or 'HKLM\SYSTEM' has been exported from the registry. • **Fact-RegW-RunService** – Run Services registry keys have been modified. • **Prof-RegW-CORPROFILER-O-U** – This is the first time this user has modified or created a registry value for an environment variable associated with the COR_PROFILER. • **Prof-RegW-Services-O-UD** – This is the first time users in this department have modified or created a service by writing a registry key\value under the key 'HKLM\SYSTEM\CurrentControlSet\Services'. • **Fact-RegE-Certs** – Registry values related to certificates and private keys have been exported. • **Fact-RegW-AppCert** – An AppCert DLL registry configuration has been modified or created under the registry key 'HKEY_LOCAL_MACHINE\System\CurrentControlSet\Control\Session Manager' • **Prof-RegW-SafeBoot-O-U** – This is the first time this user has modifed the safe mode boot configuration by writing to a registry value/key under the registry key HKLM\SYSTEM\CurrentControlSet\Control\SafeBoot\Minimal. • **Prof-RegR-LSA-O-UD** – This is the first time users in this department read have read a LSA secret from the registry. • **Fact-RegW-AppShim** – A registry key/value has been created under the Shim database registry key 'HKLM\SOFTWARE\Microsoft\Windows NT\CurrentVersion\AppCompatFlags\Custom' or 'HKLM\SOFTWARE\Microsoft\Windows NT\CurrentVersion\AppCompatFlags\InstalledSDB • **Fact-RegW-ChromeExt** – A Chrome extension has been installed via the registry. • **Fact-RegW-OfficeTest** – An Office test file has been modified by writing to the registry key HKCU\Software\Microsoft\Office test\Special\Perf. • **Fact-RegW-SIP** – A SIP component has been modified via the registry. • **Fact-RegE-LSA** – The registry key 'HKLM\SECURITY\Policy\Secrets' has been exported from the registry. • **Fact-RegW-ControlPanel** – A control panel item has been registered by writing to a registry key/value under HKCU\Software\Microsoft\Windows\CurrentVersion\Control Panel\Cpls. • **Fact-RegW-RootCert** – A root certificate has been installed via the registry. • **Prof-RegD-Services-O-UD** – This is the first time users in this department have deleted a service by deleting a registry key\value under the key 'HKLM\SYSTEM\CurrentControlSet\Services'. • **Prof-RegR-SAM-O-UD** – This is the first time users in this department have read a registry value under the SAM registry key. • **Fact-RegW-GlobalDotName** – The registry value GlobalDotName has been created. • **Fact-RegW-AppInit** – An AppInit DLL registry configuration has been modified or created under the registry key 'HKEY_LOCAL_MACHINE\Software\Microsoft\Windows NT\CurrentVersion\Windows' or 'HKEY_LOCAL_MACHINE\Software\Wow6432Node\Microsoft\Windows NT\CurrentVersion\Windows' • **Prof-RegW-AppPaths-O-U** – This is the first time this user has modified a registry key\value under the App Paths key '[HKLM/HKCU]\Software\Microsoft\Windows\CurrentVersion\App Paths'. • **Prof-RegW-FileAssoc-O-U** – This is the first time this user has modified a command of a file assocation handler by modifing its registry configuration. • **Fact-RegW-CodeSigningPolicy** – A code signing policy has been modified by writing to the registry key HKCU\Software\Policies\Microsoft\Windows NT\Driver Signing. • **Fact-RegD-RDPCon** – The RDP connection history has been cleared via the registry.

Feature	Description
	• **Prof-RegW-SilentExitMon-O-U** – This is the first time this user has modified or created the silent exit configuration of a process by writing a registry key\value under the key 'HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Windows NT\CurrentVersion\SilentProcessExit'. • **Fact-RegW-EventLogDisabled** – The Event Log service has been disabled via the registry. • **Fact-RegW-Netshell** – A NetShell helper DLL has been registered or modified by writing the registry key 'HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\NetSh'. • **Prof-RegA-PP-O-PP** – This is the first time this process has performed a registry activity. • **NumCP-RegD-EC-U** – An abnormal number of registry deletion events have been observed for this user. • **NumCP-RegD-Services-EC-DE** – An abnormal number of unique service configurations have been deleted from the registry on this device. • **NumDCP-RegR-RPC-Cert-U-RP** – An abnormal number of unique certificates and private keys related registry values have been read by this user. • **NumDCP-RegW-RPC-ServicesStop-DE-RP** – An abnormal number of unique services have been stoped by modifying the registry on this endpoint. • **NumCP-RegD-Services-EC-U** – An abnormal number of unique service configurations have been deleted from the registry for this user. • **Prof-RegR-Certs-U-RP** – This is the first time this user has read this certificate\private key related registry value. • **NumDCP-RegW-RPC-ServicesStop-U-RP** – An abnormal number of unique services have been stoped by modifying the registry for this user. • **NumCP-RegD-EC-DE** – An abnormal number of registry deletion events have been observed on this device. Pre-built analytics rules for which `query` was updated include: • **NumSP-SADLP-Bytes-U-Bytes** – An abnormal amount of outgoing bytes have been recorded in DLP alerts for this user. • **NumCP-DSOW-EC-U** – An abnormal number of directory service events have been observed for this user. Directory services typically manage various types of objects to organize and administer resources within a network environment. • **NumDCP-FRead-EC-UP-FP** – An abnormal number of unique files have been read in this platform for this user. • **NumCP-DSOW-EC-UD** – An abnormal number of directory service write events have been observed for users in this department. Directory services typically manage various types of objects to organize and administer resources within a network environment. • **NumCP-DSOW-EC-O** – An abnormal number of directory service write events have been observed for the organization. Directory services typically manage various types of objects to organize and administer resources within a network environment. • **NumDCP-EL-DEC-SE-DE** – An abnormal number of unique destination endpoints have been observed in successful endpoint login events from this endpoint. These events may include interactive Window logins and other (interactive or not) OS logins. • **NumDC-ShA-ShareC-U-DS** – An abnormal number of unique network shares have been accessed for this user. • **NumCP-EMR-EC-DU** – An abnormal number of incoming emails have been observed for this user. • **NumDCP-EL-DEC-U-DE** – An abnormal number of unique destination endpoints have been observed in endpoint login events for this user. These events may include interactive Window logins and other (interactive or not) OS logins, both failed as successful.

Feature	Description
	• **NumCP-PCpwrshell-EC-U** – An abnormal number of PowerShell process executions have been observed for this user. • **NumDCP-EL-DEC-O-DE** – An abnormal number of unique destination endpoints have been observed in endpoint login events for the organization. These events may include interactive Window logins and other (interactive or not) OS logins, both failed as successful. • **NumSP-EMR-Bytes-DU-Bytes** – An abnormal amount of bytes have been received in incoming emails for this user. • **NumDCP-Network-DIPC-SE-DIP** – An abnormal number of unique destination IPs have been accessed from this source endpoint. • **NumCP-FDnld-EC-U** – An abnormal amount of file download events have been observed for this user. • **NumCP-FUpld-EC-O** – An abnormal amount of file upload events have been observed for the organization. • **NumCP-FDnld-EC-O** – An abnormal amount of file download events have been observed for the organization. • **NumCP-FUpld-EC-U** – An abnormal amount of file upload events have been observed for this user. • **NumCP-FUpld-EC-UD** – An abnormal amount of file upload events have been observed for users in this department. • **NumCP-FDnld-EC-UD** – An abnormal amount of file download events have been observed for users in this department. • **NumCP-RegD-EC-U** – An abnormal number of registry deletion events have been observed for this user. • **NumCP-RegD-Services-EC-DE** – An abnormal number of unique service configurations have been deleted from the registry on this device. • **NumDCP-RegR-RPC-Cert-U-RP** – An abnormal number of unique certificates and private keys related registry values have been read by this user. • **NumDCP-RegW-RPC-ServicesStop-DE-RP** – An abnormal number of unique services have been stoped by modifying the registry on this endpoint. • **NumCP-RegD-Services-EC-U** – An abnormal number of unique service configurations have been deleted from the registry for this user. • **NumDCP-RegW-RPC-ServicesStop-U-RP** – An abnormal number of unique services have been stoped by modifying the registry for this user. • **NumCP-RegD-EC-DE** – An abnormal number of registry deletion events have been observed on this device. Pre-built analytics rules for which `trainOnCondition` was updated include: • **Prof-DllLoad-Dir-O-FD** – First DLL image loaded from this folder for the organization. • **Prof-DllLoad-Dll-O-FN** – First DLL image with this name loaded for the organization. Pre-built analytics rules for which `scopeValue` was updated include: • **NumSP-FRead-FS-B-Bytes** – An abnormal amount of file bytes have been read in this bucket for this user. • **Prof-DllLoad-Ext-PN-FileExt** – This is the first time a DLL image file with this extension was loaded for this process. • **Prof-Network-SEPN-DE** – This is the first time this process has accessed this destination endpoint from this source endpoint.

Feature	Description
	Pre-built analytics rules for which `featureValue` and `scopeValue` were updated include: • **Prof-FWrite-UMWorkerProcess-PN-FN** – This is the first time this file was created by the 'umworkerprocess.exe' process. • **Prof-STC-PP-TN-PP** – This is the first time a scheduled task has been created and configured to execute this process for this task name. • **NumDCP-FRead-EC-B-FP** – An abnormal number of unique files have been read in this bucket for this user. Pre-built analytics rules for which `applicable_events` and `actOnCondition` were updated include: • **Fact-SA-ET-RN** – A correlation rule has been triggered • **Cntx-SA-AC-RSev** – Correlation rule severity `description` was updated for the following pre-built analytics rule: • **Prof-ShA-SE-SN** – This is the first time this network share has been accessed from this endpoint. `scopeValue`, `featureValue`, and `trainOnCondition` were updated for the following pre-built analytics rule: • **Prof-PC-PPN-PPN-PN** – First child process for this known parent process. `title`, `description`, and `detectionReason` were updated for the following pre-built analytics rule: • **Fact-PCecho-EchoP** – The 'echo.exe' process has been used to execute a command associated with Meterpreter and Cobalt Strike's GetSystem system privilege escalation function. Removed obsolete pre-built analytics rules include: • **Prof-GA-E-UP-SE** – This is the first time an activity from this endpoint has been observed for this user on this platform. • **Cntx-EL-UCrit-APriv** – Domain account is privileged: True\False
New Correlation Rule Templates	You can now better detect adversary reconnaissance techniques with new correlation rule templates: • **Fsutil Peripheral Device Discovery Command** – Detects use of the fsutil command to enumerate drives, which may indicate reconnaissance or preparation for data exfiltration. • **Password Policy Discovery Commands** – Detects use of commands used to access information about password policies. • **System Language Discovery Commands** – Detects use of commands used to gather information about the system language of a victim to potentially infer the geographical location of that host. • **Log Enumeration Commands** – Detects the use of commands used to enumerate system and service logs.

Resolved Issues

Attack Surface Insights Resolved Issues

Issue ID	Description
ENG-69014	If you used a Windows operating system, country flags for user entities did not display correctly because the flag icons were based on an emoji library not supported by Windows. The flag rendering library has been updated, and country flags now display correctly.

Search Resolved Issues

ID	Description
ENG-79511	Previously, when search results were exported, the `approxLogTime` field was not included in the export. This issue is resolved so that `approxLogTime` is included in exported results.

Site Collector 2.15: Resolved Issues

Release Number	Description
ENG-67509	Fixed an issue in which the user interface incorrectly displayed an error—'certificate rotation failed'—meant to indicate an automatic certificate generation failure, even after the certificate is regenerated manually. After you manually regenerate the certificate using the ngsccli commands, the error— 'certificate rotation failed' automatically disappears after approximately 3 to 6 hours.

Site Collector 2.15: Security Vulnerabilities Remediations

The Site Collectors 2.15 (November 2025) release includes remediated security vulnerabilities. For more information about Exabeam's commitment to remediating vulnerabilities for Site Collector, see the Vulnerability Remediation Policy.

Known CVE - CVE-2025-11226

Toolkit has been deprecated and is no longer in use hence no security vulnerabilities update is available for that.


The following table lists the CVEs remediated for the Nifi container and their severity.

Critical	High	Medium	Low
Total: 0	Total: 0	Total: 1	Total: 0
–	–	CVE-2025-7425	–

October 2025

The New-Scale Security Operations Platform includes the following addressed features and new features for October 2025.

Attack Surface Insights

Feature	Description
Device Entity Details IP Address Label Enhancement	**This feature was released on November 4, 2025.** To distinguish between static IP addresses from context and IP addresses from events, the IP address-related labels in device entity details are now updated for clarity. The **IP Address** field displays the static IP addresses defined in your context tables, while the **IP Address History observed in events** section displays the IP addresses observed in events. 

Automation Management

Feature	Description
Comments for Predefined Case Closed Reasons in Rule-Based Playbooks	To add more context to automated case closures, you can now include a custom comment with all predefined case closed reasons when the playbook action is **Escalate to a case** and and stage to is **Closed**.

Cloud Collectors



Feature	Description
Salesforce EventLog Cloud Collector	The Salesforce EventLog Cloud Collector is now available as part of Cloud Collectors to facilitate ingestion of various event types from Salesforce cloud.
Snowflake Cloud Collector	The Snowflake Cloud Collector is now available as part of Cloud Collectors to facilitate ingestion of data from data sources **Login History**, **Others**, and **Query History**.
Early Access Collectors	

Feature	Description
Broadcom Carbon Black Cloud Collector	The Broadcom Carbon Black Cloud Collector is now available as part of Cloud Collectors Early Access program, to facilitate ingestion of Alerts, Events, and Audit Logs from the storage bucket used by the data forwarder. The early access program offers you an opportunity to gain access to the latest cloud collectors before their official release. To participate, see Sign Up for the Early Access Program.
Support for Importing and Exporting Configuration Settings for the REST API Cloud Collector	The REST API Cloud Collector now supports importing and exporting configuration settings. You can import the configuration details in JSON format while configuring a new collector instance and export the configuration details in JOSN format to use it later for backup, replication, or integration. This functionality is available as part of Cloud Collectors Early Access program. The early access program offers you an opportunity to gain access to the latest cloud collectors before their official release. To participate, see Sign Up for the Early Access Program.


Log Stream

Feature	Description
Host to IP Enrichment	Host to IP enrichment ensures that hostnames and IP addresses can be mapped to each other in order to enrich events with whichever of those fields is missing in the raw log. The system uses a dynamic host-IP mapping table to store those associations. Incoming logs are evaluated to determine if they meet the conditions necessary for host to IP enrichment. By default, host to IP enrichment takes place if the log includes one of a specific set of activity types. For more information about this type of enrichment, see Host to IP Enrichment in the *Log Stream Guide*. **NOTE** **Early Access Opportunity** An early access opportunity is available to customize the host to IP enrichment functionality. You may want to take advantage of this opportunity for either of the following reasons: • You find that the default enrichment condition is providing inaccurate host to IP mapping. The early access feature provides a different set of enrichment conditions that could result in more accurate mapping. • You want to limit host to IP enrichment to specific scenarios. You can work with Exabeam to develop a custom condition for deciding which logs to enrich. Instead of using the default set of activity types listed above, you can condition the enrichment to be implemented on a more limited set of activity types, in combination with specific outcomes, vendors, or other fields. If you would like to take advantage of this early access customization, email the following group: logstream-ea@exabeam.com.


New-Scale Platform



Feature	Description
Improved Panel to View Permissions Assigned to a User Role	A new panel has been implemented to facilitate easier viewing of all the permissions assigned to a given user role in the New-Scale Security Operations Platform **Settings**. If the list of permissions is long, you can use the **Search** field to quickly locate a specific permission. Alternately, you can filter the list by types of permissions. For custom user roles, **Edit** and **Delete** options are conveniently available from the permissions panel. You can use them to edit or delete the existing custom role. For more information, see View Permissions in a User Role. 
Duplicate Roles	To aid in faster role creation, you can now duplicate an existing role and modify it to make it easier to create new roles. 
UI and API Restriction by IP	A new **IP-Based Access** page has been added to the New-Scale Security Operations Platform **Settings**. On the new page, you can manage UI and public API access to New-Scale functionality on the basis of IP addresses. You can add new IP addresses, either individually or in ranges, to create an allowed list of access and restrictions. You can also edit access for IP addresses already on the list or delete IP addresses from the list. For more information, see Manage Access by IP Addresses.

Outcomes Navigator

Feature	Description
Unsupported Status for `session-end` Advanced Analytics Rules	To improve the accuracy of coverage calculations, Advanced Analytics whose rule expressions include `session-end` events are now excluded from coverage calculations and are now marked as *Unsupported*. 

Search


Feature	Description
Entity Details Information Available from Search Results	A new **Entities** tab is now available in the **Details** panel for viewing user entity information when search results return events associated with parsed user entity fields. This new tab provides multiple ways to explore the user entities that may be associated with security risks or anomalous behavior associated with the events in your search results: • When the **Entities** tab is displayed in the **Details** panel, it lists each user entity associated with a specific event in your search results. • For each entity listed in the **Entities** tab, you can opt to view the **User Entity Details** panel, which displays entity information that is stored in the Attack Surface Insights application. This option provides access to extensive user entity information without leaving the Search application results. For more information about what the **Entity Details** panel shows and how to use it, see View Entity Details in the *Attack Surface Insights Guide*. • For each entity listed in the Entities tab, you can use the User Entity Timeline option to open a new Search window that automatically populates and runs a search for activities related to the selected entity. This option pivots to a new Search window so you can drill down on the behavior of specific entities without closing the results you're already exploring. For more information about all of these Entities tab capabilities, see Entity Details in the *Search Guide*. 



Feature	Description
Expanded Context Table Information Displayed in Search Results	More context table information is now visible in search results when a field value is extracted from a context table record. To enhance the way context information is presented in search results, some new formats are in use: • In the List and Timeline views of search results, where parsed fields are displayed for an event, a field whose value is extracted from a context table record is shown with a new icon ( ) and in a purple chip. The chip includes the context table name, the column, and the extracted value.  • In the **Parsed Fields** list of an **Event** tab in the **Details** panel, even more information is available about the context table that a field value was extracted from. Using an expanded table, values are included from other columns in the same record of the context table. An arrow points to the specific column the value was extracted from.  For more information, see Context Tables in Search in the *Search Guide*.

Site Collectors 2.14


Feature	Description
Enhancements for the MySQL Collector	You can now enable SSL option while configuring the MySQL collector to establish a secure connection between MySQL collector and the MySQL server.



Threat Center

Feature	Description
Comments for All Predefined Case Closed Reasons	To add more context to case closures, you can now enter a comment for all predefined case closed reasons. 

Feature	Description
	 

Threat Detection Management

Feature	Description
Increased Analytics Rule Description Character Limit	To ensure you can communicate everything you want with the analytics rule description, you can now add up to 1,024 characters in the description when using the analytics rule builder. 

Feature	Description
Analytics Rule Configuration Enhancements	To simplify and improve the consistency of analytics rule configuration, several analytics rule fields and the analytics rule builder experience have been enhanced. For factFeature rules: • `actOnCondition` is now mandatory when creating a rule using JSON. • `trainOnCondition` is now mandatory and must always be `"true"` when creating a rule using JSON. When creating a rule using the analytics rule builder, `trainOnCondition` is set to true by default and is no longer configurable. • `value` is now optional.  For numericCountProfiledFeature, numericDistinctCountProfiledFeature, and numericSumProfiledFeature rules, the **Count per** field is now optional in the analytics rule builder. 

Feature	Description
New and Updated Pre-Built Analytics Rules	You can now better detect registry manipulations, anomalous user and endpoint activity, and suspicious network data transfers with new and updated pre-built analytics rules. New pre-built analytics rules include: • **NumDCP-RegW-RPC-ServicesStop-U-RP** – Abnormal number of unique services was stopped by modifying the registry for this user • **NumDCP-RegW-RPC-ServicesStop-DE-RP** – Abnormal number of unique services was stopped by modifying the registry on this endpoint • **Fact-RegW-GlobalDotName** – The registry value GlobalDotName was created • **NumCP-RegD-EC-U** – Abnormal number of registry deletion events for this user • **NumCP-RegD-EC-DE** – Abnormal number of registry deletion events on this endpoint • **NumCP-RegD-Services-EC-U** – Abnormal number of unique service configurations deleted from the registry for this user • **NumCP-RegD-Services-EC-DE** – Abnormal number of unique service configurations deleted from the registry on this endpoint • **Prof-RegD-Services-O-U** – First deletion of a service registry configuration for this user • **Prof-RegD-Services-O-UD** – First deletion of a service registry configuration for users in this department • **Prof-RegA-PP-O-PP** – First registry activity for this process • **Fact-RegD-RDPCon** – The RDP connection history was cleared via the registry • **Fact-RegE-SAM** – The SAM key was exported from the registry • **Fact-RegE-LSA** – The LSA secrets key was exported from the registry • **Fact-RegE-Certs** – System certificate keys were exported from the registry • **Prof-RegR-SAM-O-U** – First SAM registry value read for this user • **Prof-RegR-SAM-O-UD** – First SAM registry value read for this users in this department • **Prof-RegR-LSA-O-U** – First registry LSA secret read for this user • **Prof-RegR-LSA-O-UD** – First registry LSA secret read for users in this department • **Prof-RegR-Certs-U-RP** – First read of this certificate\private key registry value for this user • **NumDCP-RegR-RPC-Cert-U-RP** – Abnormal number of unique certificates\private keys registry values read for this user • **Fact-RegW-AppCert** – An AppCert DLL was registered or modified via registry • **Fact-RegW-AppInit** – An AppInit DLL was registered or modified via registry • **Fact-RegW-AppShim** – A Shim database was installed via the registry • **Fact-RegW-ChromeExt** – A Chrome extension was installed via the registry • **Fact-RegW-CodeSigningPolicy** – A code signing policy was modified via the registry • **Fact-RegW-ControlPanel** – A Control Panel item was registered via the registry • **Prof-RegW-UAC-O-U** – First modification of the UAC registry configuration for this user • **Prof-RegW-AppPaths-O-U** – First modification of the App Paths registry configuration for this user • **Prof-RegW-Services-O-U** – First modification or creation of a service via the registry for this user • **Prof-RegW-Services-O-UD** – First modification or creation of a service via the registry for users in this department

Feature	Description
	• **Prof-RegW-IFEO-O-U** – First modification of the Image File Execution Options registry configuration for this user • **Prof-RegW-SilentExitMon-O-U** –First modification of the SilentProcessExit registry configuration for this user • **Prof-RegW-EnvVarPath-O-U** – First modification of the PATH environment variable in the registry for this user • **Prof-RegW-CORPROFILER-O-U** – First modification of a COR_PROFILER environment variable in the registry for this user • **Prof-RegW-SafeBoot-O-U** – First modification of the safe mode registry configuration for this user • **Prof-RegW-FileAssoc-O-U** – First modification of a file assocation handler command's registry configuration for this user • **Prof-RegW-COM-O-CLSID** – First modification of this COM class registry path for the organization • **Prof-RegW-COM-U-CLSID** – First modification of this COM class registry path for this user • **Fact-RegW-EventLogDisabled** – The Event Log service was disabled via the registry • **Fact-RegW-Netshell** – A NetShell helper DLL was registered or modified via registry • **Fact-RegW-OfficeTest** – An Office test file was modified via the registry • **Fact-RegW-RootCert** – A root certificate was installed via the registry • **Fact-RegW-RunService** – Run Services registry keys were modified • **Fact-RegW-SIP** – A SIP component was modified via the registry • **Fact-RegW-TrustProvider** – A trust provider component was modified via the registry • **Prof-RegW-U-DetailsLen** – Abnormal registry details length for this user Pre-built analytics rules for which `trainOnCondition` was updated include: • **Prof-GA-PrivU-PltOp-PrivU** – First successful platform operation from a non-privileged user • **Prof-GA-Country-O-DCountry** – First activity to this country for the organization • **Prof-GA-Country-U-SCountry** – First activity from this country for this user • **Prof-EL-E-U-SE** – First endpoint login event from this endpoint for this user • **Prof-GA-Country-O-SCountry** – First activity from this country for the organization • **Prof-GA-E-Plt-SZ** – First activity from this network zone for this platform • **Prof-GA-E-UP-SE** – First activity from this endpoint on this platform for this user • **Prof-GA-Op-Plt-Op** – First operation for this platform • **Prof-GA-Plt-U-Plt** – First activity on this platform for this user • **Prof-GA-Plt-UD-Plt** – First activity on this platform for users in this department • **Prof-GA-RGN-O-RGN** – First cloud region for the organization • **Prof-Web-WebDom-O-Tld** – First HTTP communication to this top level domain for the organization `scopeValue` and `applicable_events` were updated for the following pre-built analytics rule: • **NumSP-Network-BytesOut-SEDP-Bytes** – Abnormal amount of bytes sent using SSH, Telnet, SMTP, DNS, FTP, HTTP or HTTPS protocols in outbound communication from this endpoint to this port

Resolved Issues

Site Collector 2.14: Security Vulnerabilities Remediations
The Site Collectors 2.14 (October 2025) release includes remediated security vulnerabilities. For more information about Exabeam's commitment to remediating vulnerabilities for Site Collector, see the Vulnerability Remediation Policy.

There are no open known CVEs in any container image (Nifi). Toolkit has been deprecated and is no longer in use hence no security vulnerabilities update is available for that.

The following table lists the CVEs remediated for the Nifi container and their severity.


Critical	High	Medium	Low
Total: 0	Total: 1	Total: 5	Total: 2
–	CVE-2025-9900 _	• CVE-2023-45803 • CVE-2024-3651 • CVE-2025-7709 • CVE-2025-8058 • CVE-2025-9230	• CVE-2025-6297 • CVE-2025-9165

September 2025

The New-Scale Security Operations Platform includes the following addressed features and new features for September 2025.

Automation Management

Feature	Description


Automation Agent Image Version 1.532.1 Upgrade	The automation agent image is now upgraded to version 1.532.1. With the upgrade:
	• If a playbook contains actions using an automation agent that is not running, the playbook is automatically stopped after one minute.
	• You can now quickly identify the health and availability of an automation agent when selecting automation agents for an action. A green dot indicates that an automation agent is running; a red dot indicates that an automation agent is not running.
	 
	To take advantage of this upgrade, download the upgraded automation agent image using the following command:
	`docker pull us-docker.pkg.dev/exa-cloud-utils/public/exabeam-automation-agent:2.0`
	When you create and run a container using the environment variables for your automation agent, use the following updated command:
	`docker run --env-file ./agentworkerconfig.env us-docker.pkg.dev/exa-cloud-utils/public/exabeam-automation-agent:2.0`

Cloud Collectors

Feature	Description
GCP Cloud Logging Cloud Collector	The GCP Cloud Logging Cloud Collector is now available as part of Cloud Collectors to facilitate ingestion of logs from Google Cloud services.
GCP Security Command Center Cloud Collector	The GCP Security Command Center Cloud Collector is now available as part of Cloud Collectors to facilitate ingestion of logs from GCP Security Command Center.
Progress ShareFile Cloud Collector	The Progress ShareFile Cloud Collector is now available as part of Cloud Collectors to facilitate ingestion of logs from the ShareFile endpoints: AccessChange, SharesSend, Activity, and SharesRequest.
Early Access Collectors	
Cylance Protect (now Arctic Wolf) Cloud Collector	The Cylance Protect (now Arctic Wolf) Cloud Collector is now available as part of Cloud Collectors Early Access program, to facilitate ingestion of logs from the following data sources: **Memory Protection**, to collect threats related to memory vulnerabilities, **Threats**, to collect threat detection alerts and related information, or both. The early access program offers you an opportunity to gain access to the latest cloud collectors before their official release. To participate, see Sign Up for the Early Access Program.

Feature	Description
Salesforce EventLog Cloud Collector	The Salesforce EventLog Cloud Collector is now available as part of Cloud Collectors Early Access program, to facilitate ingestion of various event types from Salesforce cloud. The early access program offers you an opportunity to gain access to the latest cloud collectors before their official release. To participate, see Sign Up for the Early Access Program.
Snowflake Cloud Collector	The Snowflake Cloud Collector is now available as part of Cloud Collectors Early Access program, to facilitate ingestion of data from data sources **Login History**, **Others**, and **Query History**. The early access program offers you an opportunity to gain access to the latest cloud collectors before their official release. To participate, see Sign Up for the Early Access Program.

Correlation Rules



Feature	Description
Standalone Case Creation from Correlation Rules	To quickly identify Threat Center cases created as the outcome of a correlation rule, you can now create a standalone case containing the correlation rule detection using a detection grouping rule. Detection grouping rules can now group correlation rule detections into a case by the correlation rule group by field. For Threat Center to create standalones case for correlation rule detections, you must create a detection grouping rule with specific conditions and actions, and the detection grouping rule must be ordered first in the list of detection grouping rules. 


Feature	Description
New and Updated Correlation Rule Templates	You can now better detect suspicious logins, exploitation of the Log4Shell vulnerability, suspicious use of system utilities, data exfiltration, firewall tampering, and common web application attacks with new correlation rule templates: • **Failed logins for a large number of users from this endpoint** – Failed logins have been observed to 10 or more different users from this endpoint in 10 minutes. • **An email subject associated with CVE-2021-44228 was observed** – An email activity containing an email subject with JNDI strings related to CVE-2021-44228 has been observed. • **Port forwarding configured using 'netsh.exe'** – Port forwarding has been configured using the Network Shell command line utility. • **DLL executed using 'odbcconf.exe'** – The Open Database Connectivity configuration utility ('odbcconfig.exe') has been used to register and execute an arbitrary DLL. • **HTA file executed using 'mshta.exe'** – The Microsoft HTML Applications ('mshta.exe') utility has been used to execute an HTML application script file ('.hta'). • **Web activity associated with CVE-2021-44228 was observed** – Web activity containing a URL, user agent, mime or referrer with JNDI strings related to CVE-2021-44228 has been observed. • **A process associated with CVE-2021-44228 was executed** – A process execution with JNDI command line strings related to CVE-2021-44228 has been observed. • **SUSEFireWall2 disabled** – The SUSEFireWall2 firewall script has been stopped. This enables potentially malicious network communications to be allowed into and out of the endpoint. • **Exchange mailbox exported using PowerShell** – An exchange mailbox has been exported using a PowerShell script. • **PowerCat downloaded using PowerShell** – The PowerCat tool has been downloaded using a PowerShell script. • **Insecure design remote JMX access** – Monitor for application behavior that exposes sensitive functionality without proper controls, such as debug endpoints or unprotected admin interfaces. • **Cross-site Scripting** – Monitor for web requests containing suspicious input patterns which may indicate cross-site scripting attempts • **Directory traversal** – Identify requests attempting to access unauthorized directories using traversal sequences • **SQL injection** – Detect inbound HTTP requests that suggest SQL injection activity • **Software and data integrity failures web root** – Detect unauthorized changes to critical files, unsigned software updates, or tampering with CI/CD pipelines. • **Failed logins for a large number of users to this endpoint** – Failed logins have been observed for 10 or more different users to this endpoint in 10 minutes. • **Service Stop** – Monitors for the stopping of services, which could indicate attempts to disrupt system operations or evade detection. • **Ransom Note Dropped** – Detects the creation of ransom notes indicative of internal system defacement by attackers. Removed obsolete correlation rule templates include: • **Sysmon driver was unloaded** – The Sysmon driver has been unloaded. This causes Sysmon to stop auditing logs which could be used by attackers to evade detection. • **Bruteforce: Large amount of failed logins to this endpoint for this user** – This user has failed to login to this endpoint 10 or more times in 1 minute. Fields have been modified in an additional 189 correlation rule templates.



Log Sources

Feature	Description
Support for Silent Log Source Detection —from 30 Minutes of Inactivity	You can now proactively detect silent log sources before they impact operations, using the Silent Monitoring Threshold feature. You can now set the Warn After Silent For duration from 30 minutes to 72 hours to automatically detect inactivity. When a log source goes silent beyond your defined window, you are instantly notified—helping you maintain visibility and control.

Outcomes Navigator


Feature	Description
Peer Comparison	To get a better sense of how your security posture compares to that of other organizations, you can now benchmark your coverage against industry peers. Under the MITRE ATT&CK Coverage and Use Case Coverage tabs, select the organizations against which you're comparing coverage by industry and organization size:  Under the overall coverage score charts, you can compare your overall coverage score against the average overall coverage score of other organizations:  For a specific MITRE ATT&CK® technique[a] or use case, you can also use the **Coverage Over Time** chart to compare your coverage score for a specific technique or use case against the average coverage score of other organizations, using the same criteria for organizations you defined in the overall coverage score:

Feature	Description
	 To view the relative change in the coverage score over the last month for organizations types you selected, hover over a point in the line chart:

Feature	Description
	 

[a.]MITRE ATT&CK and ATT&CK are trademarks of The MITRE Corporation ("MITRE"). Exabeam is not affiliated with or sponsored or endorsed by MITRE. Nothing herein is a representation of the views or opinions of MITRE or its personnel.


Search



Feature	Description
Support for Sort Order in Exported Search Results	The sort order selector is now available when exporting search results. It includes options to sort chronologically to show the most recent or the oldest results. For more information, see Export Search Results in the *Search Guide*.
Associated Events for Detections in the Timeline View	Search has been updated to support the display of all events associated with a detection in the Timeline view. A detection event can be triggered by multiple events and, to keep the display of results in the Timeline view simple and uncluttered, the detection is shown only on the row of the latest chronological event that triggered it. Now, a new **Show Associated Events** option in the detection box lets you expand a full list of all the events associated with the detection. The list of associated events expands below the original event row and you can interact with the listed events in all the ways you can interact with other events. Alternately, you can opt to open the expanded set of associated events in a new Search tab.  For more information, see Detections in the Timeline in the *Search Guide*.


Site Collectors 2.13

Feature	Description
Upgradation to NiFi 2.5	Based on the vulnerability remediation policy, the version of Apache NiFi is upgraded to the latest available version 2.5 for enhanced performance, security, stability, and integration capabilities.
Enhanced Template Update Process	The updated templates now improve how agent collectors receive the latest changes, making the update process more reliable and efficient. The template types include: Windows, Windows File, Linux File, Archive Windows, and Archive Linux. To avoid errors and improve stability during bulk operations, limits on quantity and frequency of updates are added. This solution ensures smooth, time-distributed delivery of actions, prevents system overload, and maintains full control over throttling.

Threat Center


Feature	Description
Analytics Rules Severity	**The ability of the *Critical* severity to automatically create a case was released on September 30, 2025** To manually tune Threat Center case or alert risk scores, you can now adjust the severity of analytics rules.  Analytics rule severity is now one of the business factors Threat Center uses when calculating a case or alert risk score. Each severity, from low to critical, has a corresponding weight that reduces or increases the risk score. The none severity doesn't affect risk scoring and can be used to test the analytics rule. When Threat Center calculates a risk score, it considers the highest severity of all analytics rule associated with detections grouped under the case or alert. You can assign an analytics rule the following severities: • **None** – Analytics rule is not used in risk scoring. Used for testing the analytics rule. • **Low** – Reduces risk score. • **Medium** – Doesn't adjust the risk score. • **High** – Increases risk score. • **Critical** – Significantly increases risk score and automatically creates a case. Analytics rule severity doesn't affect risk scores for existing cases and alerts. To revise risk scores for existing cases and alerts, ensure that you re-train the analytics engine on past events.


Feature	Description
Standalone Case Creation from Correlation Rules	To quickly identify Threat Center cases created as the outcome of a correlation rule, you can now create a standalone case containing the correlation rule detection using a detection grouping rule. Detection grouping rules can now group correlation rule detections into a case by the correlation rule group by field. For Threat Center to create standalones case for correlation rule detections, you must create a detection grouping rule with specific conditions and actions, and the detection grouping rule must be ordered first in the list of detection grouping rules. 
Case Opened in New Tab	To keep the case or alert list easily accessible while working on cases or alerts, you can now right-click on a case or alert and open it in a new browser tab. 


Feature	Description
Increased Case Notes Character Limit	To ensure you can communicate everything you want to with case notes, you can now add up to 10,000 characters in a single note. 
Increase Custom Case Closed Reason Character Limit	To ensure you can communicate everything you want to when entering a custom case closed reason, you can now add up to 10,000 characters in a custom case closed reason. 
Increased Attachment Size Limit	To ensure you can attach important evidence to a case, you can now attach a file of up to 15 MB. 


Threat Detection Management


Feature	Description
Custom Analytics Rule Builder	You can now create a custom analytics rule directly in Threat Detection Management with a point-and-click interface. The guided experience walks you through each step so you can easily create and edit analytics rules. After you create a custom analytics rule, you can also edit and delete it.


Feature	Description
	


Feature	Description
	

Feature	Description
	

Feature	Description
	

Feature	Description
	

Feature	Description
Analytics Rules Severity	**The ability of the *Critical* severity to automatically create a case was released on September 30, 2025** To manually tune Threat Center case or alert risk scores, you can now adjust the severity of analytics rules.  Analytics rule severity is now one of the business factors Threat Center uses when calculating a case or alert risk score. Each severity, from low to critical, has a corresponding weight that reduces or increases the risk score. The none severity doesn't affect risk scoring and can be used to test the analytics rule. When Threat Center calculates a risk score, it considers the highest severity of all analytics rule associated with detections grouped under the case or alert. You can assign an analytics rule the following severities: • **None** – Analytics rule is not used in risk scoring. Used for testing the analytics rule. • **Low** – Reduces risk score. • **Medium** – Doesn't adjust the risk score. • **High** – Increases risk score. • **Critical** – Significantly increases risk score and automatically creates a case. Analytics rule severity doesn't affect risk scores for existing cases and alerts. To revise risk scores for existing cases and alerts, ensure that you re-train the analytics engine on past events. When Exabeam delivers updates to pre-built analytics rules, the severity you assign to the pre-built analytics rule persists.

Feature	Description
Standalone Case Creation from Correlation Rules	To quickly identify Threat Center cases created as the outcome of a correlation rule, you can now create a standalone case containing the correlation rule detection using a detection grouping rule. Detection grouping rules can now group correlation rule detections into a case by the correlation rule group by field. For Threat Center to create standalones case for correlation rule detections, you must create a detection grouping rule with specific conditions and actions, and the detection grouping rule must be ordered first in the list of detection grouping rules. 

Feature	Description
New and Updated Pre-Built Analytics Rules	You can now better detect lateral movement, privilege escalation, suspicious command execution, unauthorized access, and data exfiltration with new pre-built analytics rules: • **Prof-Network-ERDP-DE-SE** – First successfull RDP connection from this source endpoint to this destination endpoint • **Prof-FA-FDir-DE-NTDSDir** – First NTDS access from this folder on this endpoint • **Prof-PC-CmdArgs-InstallUtil-O-DLLParam** – First execution of 'installutil.exe' with this DLL file parameter • **Prof-PC-CmdArgs-InstallUtil-O-EXEParam** – First execution of 'installutil.exe' with this EXE file parameter • **Prof-PC-CmdArgs-Msbuild-O-CsprojParam** – First execution of 'msbuild.exe' to build this C# project • **Prof-PC-CmdArgs-Msbuild-O-XMLParam** – First execution of 'msbuild.exe' to build a project with this xml file • **Cntx-PC-Critical-Parent-CritWindows** – Parent process is a known critical Windows command: True\False • **Prof-PC-CmdArgs-Regsvr32-O-SCTParam** – First execution of 'regsvr32.exe' with the this SCT file parameter • **Prof-ShA-SZ-SN** – First successful access to this network share from this network zone • **Fact-Web-ShellUserAgent** – HTTP communication was attempted using a shell user-agent • **Fact-PC-TsconRDPRedirection** – RDP traffic redirected using 'tscon.exe' • **Prof-PC-E-NetUserAdd-O-DE** – First user creation using 'net.exe' on this endpoint • **Prof-PC-E-NetUserAdd-O-DZ** – First user creation using 'net.exe' on this network zone • **Prof-GA-PrivU-PltOp-PrivU** – First successful platform operation from a non-privileged user • **Fact-UModify-UACPreAuthDisable** – UAC pre-authentication was disabled for a user account • **Fact-EA-KerberosNotPreAuth** – A user logged on via Kerberos authentication with preauthentication 0 • **NumSP-SADLP-Bytes-U-Bytes** – An abnormal amount of outgoing bytes have been recorded in DLP alerts for this user • **Prof-EW-DCShadow-SE-O-SE** – First failed MFA authentication with this failure reason for this user • **Prof-DS-A-UDSOT-A** – First directory service activity on this directory service object class for this user • **Prof-PC-PN-DE-PN** – First execution of this process on this endpoint • **Prof-Network-SEPN-DE** – First access to this destination endpoint for this process from this source endpoint • **Prof-SA-PN-U-PN** – First alert trigger on this process for this user • **Prof-SA-PN-O-PN** – First security alert trigger on this process for the organization • **Prof-SA-PN-UD-PN** – First alert trigger on this process for users in this department • **Cntx-FA-ECrit-CS** – Destination endpoint is critical: True\\False • **Prof-MFA-MFADevice-U-MFADevice** – First MFA authentication using this device for this user • **Prof-MFA-FailureReason-U-FailureReason** – First failed MFA authentication with this failure reason for this user • **Prof-MFA-AuthMethod-U-AuthMethod** – First MFA authentication with this authentication method for this user • **Prof-EL-AP-U-AP** – First remote Windows login or access with this authentication package for this user

Feature	Description
	• **Fact-SEPwrshell-EnumNetworkAdapter** – A PowerShell script enumerated network adapters using wmi objects Removed obsolete pre-built analytics rules include: • **Prof-PC-PN-SE-PN** – First execution of this process from this endpoint • **Prof-SADLP-PN-U-PN** – First DLP alert trigger on this process for this user • **Prof-SADLP-PN-O-PN** – First DLP alert trigger on this process for the organization • **Prof-SADLP-PN-UD-PN** – First DLP alert trigger on this process for users in this department

Feature	Description
New and Updated Correlation Rule Templates	You can now better detect suspicious logins, exploitation of the Log4Shell vulnerability, suspicious use of system utilities, data exfiltration, firewall tampering, and common web application attacks with new correlation rule templates: • **Failed logins for a large number of users from this endpoint** – Failed logins have been observed to 10 or more different users from this endpoint in 10 minutes. • **An email subject associated with CVE-2021-44228 was observed** – An email activity containing an email subject with JNDI strings related to CVE-2021-44228 has been observed. • **Port forwarding configured using 'netsh.exe'** – Port forwarding has been configured using the Network Shell command line utility. • **DLL executed using 'odbcconf.exe'** – The Open Database Connectivity configuration utility ('odbcconfig.exe') has been used to register and execute an arbitrary DLL. • **HTA file executed using 'mshta.exe'** – The Microsoft HTML Applications ('mshta.exe') utility has been used to execute an HTML application script file ('.hta'). • **Web activity associated with CVE-2021-44228 was observed** – Web activity containing a URL, user agent, mime or referrer with JNDI strings related to CVE-2021-44228 has been observed. • **A process associated with CVE-2021-44228 was executed** – A process execution with JNDI command line strings related to CVE-2021-44228 has been observed. • **SUSEFireWall2 disabled** – The SUSEFireWall2 firewall script has been stopped. This enables potentially malicious network communications to be allowed into and out of the endpoint. • **Exchange mailbox exported using PowerShell** – An exchange mailbox has been exported using a PowerShell script. • **PowerCat downloaded using PowerShell** – The PowerCat tool has been downloaded using a PowerShell script. • **Insecure design remote JMX access** – Monitor for application behavior that exposes sensitive functionality without proper controls, such as debug endpoints or unprotected admin interfaces. • **Cross-site Scripting** – Monitor for web requests containing suspicious input patterns which may indicate cross-site scripting attempts • **Directory traversal** – Identify requests attempting to access unauthorized directories using traversal sequences • **SQL injection** – Detect inbound HTTP requests that suggest SQL injection activity • **Software and data integrity failures web root** – Detect unauthorized changes to critical files, unsigned software updates, or tampering with CI/CD pipelines. • **Failed logins for a large number of users to this endpoint** – Failed logins have been observed for 10 or more different users to this endpoint in 10 minutes. • **Service Stop** – Monitors for the stopping of services, which could indicate attempts to disrupt system operations or evade detection. • **Ransom Note Dropped** – Detects the creation of ransom notes indicative of internal system defacement by attackers. Removed obsolete correlation rule templates include: • **Sysmon driver was unloaded** – The Sysmon driver has been unloaded. This causes Sysmon to stop auditing logs which could be used by attackers to evade detection. • **Bruteforce: Large amount of failed logins to this endpoint for this user** – This user has failed to login to this endpoint 10 or more times in 1 minute. Fields have been modified in an additional 189 correlation rule templates.

Feature	Description
Analytics Engine Custom Fields Support	To tailor detection logic to specific use cases, the analytics engine can now evaluate and trigger on custom event fields. You can now use custom event fields in analytics rule expressions.
Automated Sigma Rule Conversion	You can now easily convert Sigma rules to Exabeam analytics rules with Uncoder.io, a free, open-source marketplace for detection and investigation engineering. Uncoder.io uses artificial intelligence to automate the conversion of any Sigma and third-party SIEM rule in its comprehensive library of threat hunting content into Exabeam analytics rules.

Resolved Issues

Site Collector 2.13: Security Vulnerabilities Remediations
The Site Collectors 2.13 (September 2025) release includes remediated security vulnerabilities. For more information about Exabeam's commitment to remediating vulnerabilities for Site Collector, see the Vulnerability Remediation Policy.

There are no open known CVEs in any container image (Nifi). Toolkit has been deprecated and is no longer in use hence no security vulnerabilities update is available for that.

The following table lists the CVEs remediated for the Nifi container and their severity.



Critical	High	Medium	Low
Total: 0	Total: 0	Total: 8	Total: 1
–	–	• CVE-2025-6069 • CVE-2025-8194 • CVE-2025-8534 • CVE-2025-8851 • CVE-2025-49794 • CVE-2025-49796 • CVE-2025-6021 • CVE-2025-6170	• CVE-2025-8176


August 2025

The New-Scale Security Operations Platform includes the following addressed features and new features for August 2025.

Attack Surface Insights



Feature	Description
Pre-Built Attack Surface Insights Rules Criticality Enhancement	To prevent inflated risk scores for Threat Center cases and alerts, all pre-built Attack Surface Insights rules now automatically apply the *Low* criticality to entities. Review all pre-built rules and ensure they accurately reflect your environment. If not, disable the pre-built rule. You can then duplicate the pre-built rule and change the criticality it applies to entities or create a new rule that better reflects your needs.


Feature	Description
User Risk Trend Enhancement	You can now get more information about alerts and cases associated with a user entity with the User Risk Trend chart. In the minimized User Risk Trend chart, you can now view the number of open cases and alerts associated with a user entity during the selected time frame. To view details about the cases and alerts, click **<#> cases** or **<#> alerts**.   In the expanded User Risk Trend chart, you now view more detail about the case or alert with the highest risk score on a specific day when you hover over a point in the chart.

Feature	Description
	

Automation Management

These features were released on August 22, 2025.

Feature	Description
Automation Agents	You can now securely connect Automation Management to segmented networks using automation agents. An automation agent is a process that securely connects Automation Management to on-premises or network-segmented systems so you can run advanced playbooks and actions remotely on those systems. To connect Automation Management to a segmented network, you create an automation agent, then run the automation agent using Docker. When you run an automation agent, it's assigned a JSON Web Token (JWT) for authenticating HTTP requests to your network.The JWT is valid for 365 days, after which it expires. When the JWT is deleted, revoked, or expired, you can delete the automation agent. View all automation agents in the **Automation Agents** tab.  After you create an automation agent, you assign a given action the specific automation agent it uses to connect to your network. 

Feature	Description
Pre-Defined Case Closed Reasons in Rule-Based Playbooks	To better track and report Threat Center case closures, you can now select a pre-defined reason for why cases were closed if you use rule-based playbooks to change the case stage to Closed. You can select a pre-defined case closed reason when the playbook action is **Escalate to a case** and **and stage to** is **Closed**: 

Cloud Collectors

Feature	Description
AWS CloudWatch Alarms Cloud Collector	The AWS CloudWatch Alarms Cloud Collector now available as part of Cloud Collectors to facilitate ingestion of AWS CloudWatch alarms related events.
AWS GuardDuty Cloud Collector	The AWS GuardDuty Cloud Collector is now available as part of Cloud Collectors to facilitate ingestion of GuardDuty Findings from AWS S3 bucket.
AWS Security Lake Cloud Collector	The AWS Security Lake Cloud Collector is now available as part of Cloud Collectors to facilitate ingestion of security events from AWS S3 Security Lake bucket.
DataBahn Cloud Collector	The DataBahn Cloud Collector is now available as part of Cloud Collectors to facilitate ingestion of events from DataBahn sources.
Dropbox Cloud Collector	The Dropbox Cloud Collector is now available as part of Cloud Collectors to facilitate ingestion of team activity logs from Dropbox.
Qualys Cloud Collector	The Qualys Cloud Collector is now available as part of Cloud Collectors to facilitate ingestion of Activity Logs, and Vulnerabilities including VM host detection events from Qualys sources.
Slack Cloud Collector	The Slack Cloud Collector is now available as part of Cloud Collectors to facilitate ingestion of events from the Audit Logs API endpoints.

Feature	Description
Tenable Cloud Collector	The Tenable Cloud Collector is now available as part of Cloud Collectors to facilitate ingestion of vulnerability events from Tenable APIs.
Zoom Cloud Collector	The Zoom Cloud Collector is now available as part of Cloud Collectors to facilitate ingestion of events from the sign-in/sign-out activity and operational logs endpoints.
Early Access Collectors	
GitHub Cloud Collector	The GitHub Cloud Collector is now available as part of Cloud Collectors Early Access program, to facilitate ingestion of GitHub enterprise audit logs that include events such as repository access, authentication attempts, permission changes, and more from the GitHub Enterprise Audit API endpoint to monitor your enterprise GitHub server or cloud-based GitHub service. The early access program offers you an opportunity to gain access to the latest cloud collectors before their official release. To participate, see Sign Up for the Early Access Program.
GCP Cloud Logging Cloud Collector	The GCP Cloud Logging Cloud Collector is now available as part of Cloud Collectors Early Access program, to facilitate ingestion of logs from Google Cloud services. The early access program offers you an opportunity to gain access to the latest cloud collectors before their official release. To participate, see Sign Up for the Early Access Program.
GCP Security Command Center Cloud Collector	The GCP Security Command Center Cloud Collector is now available as part of Cloud Collectors Early Access program, to facilitate ingestion of logs from GCP Security Command Center. The early access program offers you an opportunity to gain access to the latest cloud collectors before their official release. To participate, see Sign Up for the Early Access Program.
Progress ShareFile Cloud Collector	The Progress ShareFile Cloud Collector is now available as part of Cloud Collectors Early Access program, to facilitate ingestion of logs from the ShareFile endpoints: AccessChange, SharesSend, Activity, and SharesRequest. The early access program offers you an opportunity to gain access to the latest cloud collectors before their official release. To participate, see Sign Up for the Early Access Program.




Context Management

Feature	Description
Pre-Built Vulnerability Scanners Context Table	Context Management now provides new pre-built correlation rules context tables. The first of these to be made available is the Vulnerability Scanners context table. The correlation rules context tables support the detection activities of correlation rules and are documented along with pre-built New-Scale Analytics and Attack Surface Insights context tables. For more information, see Pre-Built Detection Context Tables.

Log Stream

Feature	Description
Standardize Usage of bytes_in and bytes_out Fields	The definition of `bytes_in` and `bytes_out` fields will be standardized across all Exabeam content, including default parsers and rules, starting in the first week of September, 2025. The standardized fields will be defined as follows: • `bytes_in` – number of bytes received by the device or interface (data ingress) • `bytes_out` – number of bytes sent from the device or interface (data egress) These fields have become inconsistent in some cases because of an attempt to match vendor definitions, which may use reverse logic. Historically, enrichment rules have been created to handle exceptions, adding further confusion to the definitions. After a thorough content review, it has been decided to standardize the use of `bytes_in` and `bytes_out` across all parsers and any downstream content. Furthermore, these definitions will be independent of enrichment rules. You can, however, customize default parsers to use reverse logic if necessary for your business scenarios. It is recommended that you check any enrichment rules or downstream correlation rules that leverage the `bytes_in` and `bytes_out` fields, to ensure that they are still operating properly. Data coming from the following vendors and products may be affected: • Cisco - Cisco Network Security • Fortinet - FortiGate • Google - Google Cloud Platform , GCP CloudAudit • Microsoft - Azure Monitor

Search



Feature	Description
Improvements to Search Results Views and Detail Panels	Search includes the following improvements to certain aspects of the way search results are displayed: • In the Timeline view of search results, numbering has been introduced when multiple events are grouped. You can see the event numbering when you expand the event row in the Timeline view or when you view the **Event** tabs in the **Details** panel.  • In the Timeline view, numbering is also applied when multiple detections are associated with a single event. You can see the detection numbering in both the Timeline view of results and when you view the **Detection** tabs in the **Details** panel.  • To streamline the display of detection events in the Timeline view, information about use case and about MITRE tactics and techniques has been moved to the **Detection** tab in the **Details** panel. • The names of the **Details** panel and it's tabs have been updated for consistency: **Events**, **Detections**, **Data Insights**. • When you enter the **Details** panel from a grouped event in the Timeline view or from an event associated with multiple detections, the event and detection information is presented in a set of numbered tabs. The numbers correspond to the numbering in the Timeline view.  • A new **Rules** section has been added to the **Detection** tab of the **Details** panel. The **Rules** section lists the triggered rules that generated the detection event. You can expand each rule to view the rule fields and MITRE labels associated with each rule.  • The **Summary** view of fields returned in the search results has been improved so that it stays pinned to the top of the left-hand column in all views. Once the **Summary** panel is displayed, it no longer moves when you scroll through results on the Timeline, List, or Table views.

Feature	Description
	For more information about any of these views or Details panel tabs, see the Search Results section of the Search Guide.
Support for Sort Order in Saved and Exported Searches	The selected sort order information is now persisted in a new **Sorting** column for both recent and saved searches lists. The column shows which sort order options was selected when the search query ran. For more information, see Saved Searches in the *Search Guide*.
Improved Titles for Detection Events	The Search Timeline view is using new logic to display more meaningful titles for detection events. To make the detection titles more useful for understanding why a detection was triggered, the titles will now be derived from critical triggering logic. This change ensures that titles are not based on context rule information, which is less useful for understanding the cause of a detection. Rather they will be based on triggering rule information so the reason for the detection is more obvious.


Site Collectors 2.12

Feature	Description
Windows Event Log Collector Auto-Restart (version 2.11.0 +).	The Auto-Restart feature for the Windows Event Log Collector automatically restarts exabeam-welc-collector-service and exabeam-welc-management if they fail unexpectedly, except when stopped by you via the user interface (UI) or API. The Auto-Restart feature restores collectors, improves reliability, reduces downtime, and minimizes manual recovery.
Advance Configuration Settings for the Windows Template	For Windows Event Log Collector, while creating a Windows template, you can now use advanced configuration options. Using these options you can set the number of records to commit per batch, the number of events to read per batch, and the percentage for item substitution. You can enable or disable Security Identifiers (SID) lookup and caching SID.
Windows Event Log Collector Upgrade	Site Collector now provides improved stability, and speed for Windows Event Log Collector (WELC) upgrades. To take advantage of these improvements, upgrade to the latest Site Collector version 2.12. Then, upgrade the Windows Event Log Collector instances for the new WELC management service to finalize configuration. If you use Windows Event Log Collectors version 2.9 or earlier, after upgrading to Site Collector version 2.12, follow the two-step upgrade process. First, Windows Event Log Collector is upgraded to version 2.11.2 irrespective of your current version. The next upgrade provides you with an option to move to the latest version.

Threat Center

Feature	Description
Pre-Defined Case Closed Reasons	**This feature was released on August 22, 2025.** To better track and report case closures, you can now select a pre-defined reason for why a case was closed.  You can select between: • **Already mitigated/resolved** – The threat has been addressed or resolved. • **False positive or duplicate** – The threat was mistakenly identified as a threat and is actually normal, non-malicious activity. • **Low risk** – The threat is insignificant or unlikely to harm the system or data. • **Rule misconfiguration** – Monitoring or detection content was misconfigured. • **Policy or setup issue** – The activity described in the case occurred because of known operations in your environment, like scheduled maintenance, authorized testing, or temporary workarounds. • **Other** – The reason for closing the case isn't covered by the other predefined reasons. In the case **Overview** tab, review the reason why the case was closed, the queue and assignee assigned to the case when it was closed, and the date and time the case was closed under **Case Closed**. 

Threat Detection Management

Feature	Description
Analytics Rules Reduced anomalyThreshold Minimum	To track anomalies over smaller intervals, the minimum valid value for the anomalyThreshold field is now 1 day for the following analytics rule types: • profiledFeature • numericSumProfiledFeature • numericDistinctCountProfiledFeature • numericCountProfiledFeature
Analytics Rules Limit Chart Enhancement	To better track how many custom analytics rules have been created in your environment, you can now view the number of custom analytics rules enabled compared to the maximum your entitlement allows in the **Limit** chart under **Custom Rules**. 

Resolved Issues

Search Resolved Issues

ID	Description
ENG-74006	An issue has been fixed so that when you save a search with a relative time range, the time range remains relative when the saved search is run on subsequent days. Previously, if you defined a query with a relative time range from 10 days ago to now, and you ran the saved search two days later, it returned results from 12 to 2 days ago. This issue is resolved so that a relative search remains relative whenever you run it.

Site Collector 2.12: Security Vulnerabilities Remediations

The Site Collectors 2.12 (August 2025) release includes remediated security vulnerabilities. For more information about Exabeam's commitment to remediating vulnerabilities for Site Collector, see the Vulnerability Remediation Policy.

There are no open known CVEs in any container image (Nifi). Toolkit has been deprecated and is no longer in use hence no security vulnerabilities update is available for that.

The following table lists the CVEs remediated for the Nifi container and their severity.

Critical	High	Medium	Low
Total: 0	Total: 0	Total: 14	Total: 2
–	–	• CVE-2025-32988 • CVE-2025-32989 • CVE-2025-32990 • CVE-2025-40909 • CVE-2025-4877 • CVE-2025-4878 • CVE-2025-48924 • CVE-2025-5318 • CVE-2025-5351 • CVE-2025-5372 • CVE-2025-5702 • CVE-2025-5987 • CVE-2025-6395 • CVE-2025-6965	• CVE-2024-23337 • CVE-2024-53427

July 2025

The New-Scale Security Operations Platform includes the following addressed features and new features for July 2025.

Cloud Collectors

Feature	Description
Anomali Cloud Collector	The Anomali Cloud Collector is now available is now available, as part of Cloud Collectors to facilitate threat intelligence data collection from an Anomali source that supports the STIX/TAXII framework. You can opt to collect data about either IP addresses or domains. You can also opt to automatically generate a corresponding Anomali context table in the Context Management application that will process the data and map it to a standardized set of attributes. The context table will have the same name as the cloud collector.
Authentication Method options to Authenticate via Microsoft Entra ID for Azure EventHub Cloud Collector	In addition to the existing Shared Access Signature (SAS) based connection string authentication method, the Azure EventHub Cloud Collector now supports authentication via Microsoft Entra ID Account for more secure, and centralized identity and access management.
Early Access Collectors	

Feature	Description
Dropbox Cloud Collector	The Dropbox Cloud Collector is now available as part of Cloud Collectors Early Access program, to facilitate ingestion of team activity logs from Dropbox. The early access program offers you an opportunity to gain access to the latest cloud collectors before their official release. To participate, see Sign Up for the Early Access Program.
Qualys Cloud Collector	The Qualys Cloud Collector is now available as part of Cloud Collectors Early Access program, to facilitate ingestion of Activity Logs, and Vulnerabilities including VM host detection events from Qualys sources. The early access program offers you an opportunity to gain access to the latest cloud collectors before their official release. To participate, see Sign Up for the Early Access Program.
Slack Cloud Collector	The Slack Cloud Collector is now available as part of Cloud Collectors Early Access program, to facilitate ingestion of events from the Audit Logs API endpoints. The early access program offers you an opportunity to gain access to the latest cloud collectors before their official release. To participate, see Sign Up for the Early Access Program.

Context Management

Feature	Description
Anomali Context Tables	Context Management now supports a preconfigured onboarding experience for Anomali context tables. These tables process data that is ingested by a corresponding Anomali cloud collector that supports the STIX/TAXII framework. By default these context tables process a predetermined set of IP or domain attributes from the source collector and then map these attributes to a set of standardized Exabeam target attributes. For more information, see Anomali Context Tables in the *Context Management Guide*. For information about onboarding an Anomali context table via a cloud collector, see Anomali Cloud Collector in the *Cloud Collectors Administration Guide*.
Delete Records via a New Public API	You can now delete one or more records directly from a custom context table via a new public API. To indicate the records to be deleted, specify the values from the primary key column of the table in the API request body. Note that this API can be used to remove records only from custom context tables. For more information, see Context Management APIs and look for the following API: `DELETE /context-management/v1/ tables/{id}/deleteRecords`

Log Sources

Feature	Description
Log Source Monitoring	Using the Log Source service you can now detect and monitor active and inactive log sources. In addition to granular monitoring of log sources, the Log Source service offers log source policy configuration and discovery, log source status visibility, and export of log sources.
Support for New Log Source Identifiers	While creating a log source policy you can now select unique log source identifiers from a wide range of options to detect and monitor active and inactive log sources.

New-Scale Platform

Feature	Description
Global Email Notifications	To extend the ability of notifications for system events, you can now send email notifications to a specific user or a shared distribution list. For more information, see Manage Global Notifications Preferences in the *New-Scale Security Operations Platform Administration Guide*.




Outcomes Navigator

Feature	Description
Exabeam Nova Advisor Agent Renaming	The Exabeam Nova Analyst Assistant is now renamed Exabeam Nova Advisor Agent.

Site Collectors 2.11 (July 2025)

Feature	Description
Support for Additional Ports for Syslog Collector Configuration	In addition to the supported port range 1024 - 49151, the port numbers 514 and 515 of the Syslog server are now supported for configuration of Syslog and Fortinet Collectors.

Threat Center

Feature	Description
Enhanced Search Timeline Navigation	You can more easily navigate to the Search timeline view from Threat Center to view all detections related to the attribute or entity by which they are grouped. From the cases and alerts lists, you can now navigate directly to the Search timeline view by clicking :   In cases and alerts, you can now navigate directly to the Search timeline view by clicking **Timeline**:  The query automatically generated in Search has been enhanced to show detections only and in the same time range applied in Threat Center search.

Threat Detection Management

Feature	Description
Custom Analytics Rules	To detect unique security threats not addressed with pre-built analytics rules or correlation rules, you can now create your own analytics rule. To create an analytics rule, you define the analytics rule in JSON format, then import the JSON file into Threat Detection Management. An imported analytics rule is initially disabled. To activate it and allow it to trigger in your environment, you must enable it and apply the change to your environment. After you create a custom analytics rule, you can export and delete it. Custom analytics rules are available with an add-on to a New-Scale Security Operations porfolio license.

Feature	Description
New and Updated Pre-Built Analytics Rules	**This analytics rule update was released on July 23, 2025.** You can now better detect remote access abuse, suspicious process execution, and first time login activities with new and updated pre-built analytics rules. New pre-built analytics rules include: • **Fact-PCGoToMyPC-InstalledAgent** – The GoToMyPC remote desktop access agent has been installed. • **Fact-PCGoToMyPC-InstalledService** – The GoToMyPC remote desktop access service has been installed. • **Fact-PCGoToMyPC-StartedService** – The GoToMyPC remote desktop access service has been started. • **Fact-PCLogMeIn-InstalledService** – The LogMeIn remote desktop access service has been installed. • **Fact-PCLogMeIn-InstalledAgent** – The LogMeIn remote desktop access agent has been installed. • **Fact-PCLogMeIn-StartedService** – The LogMeIn remote desktop access service has been started. • **Fact-PC-MshtaScriptExecution** – The MsHTA (Microsoft HTML Application) process has been used to execute a script code. • **Fact-PCTeamViewer-InstalledService** – The TeamViewer remote desktop access service has been installed. • **Fact-PCTeamViewer-InstalledAgent** – The TeamViewer remote desktop access agent has been installed. • **Fact-PCTeamViewer-StartedService** – The TeamViewer remote desktop access service has been started. • **Fact-PCDotNet-CommandLine** – This .NET supporting process was created with an URL in the commandline. • **Prof-GA-Country-O-DCountry** – This is the first time an activity has been observed to this country, determined by geolocation lookup. • **Prof-FWrite-UMWorkerProcess-PN-FN** – This is the first time this file was created by the 'umworkerprocess.exe' process. • **Prof-EL-NTLM-O-SE** – This is the first time a successful NTLM login has been observed from this endpoint. • **Fact-PC-RemoteExecAdminShare** – A remote process has been executed and redirected to an admin share. This activity can be related to the execution of Impacket. • **Prof-GA-Country-DZ-SCountry** – This is the first time an activity has been observed from this country to this network zone, determined by geolocation lookup. • **Prof-GA-Country-SZ-DCountry** – This is the first time an activity has been observed to this country for this network zone, determined by geolocation lookup. • **Fact-PCsvchost-DCOMLaunch** – Remote DCOM activation under DcomLaunch service. • **Prof-PCMsbuild-E-O-DE** – This is the first time the 'msbuild.exe' process has been used to build and execute a project on this endpoint. • **Fact-PCSplashtop-InstalledService** – The Splashtop remote desktop access service has been installed. • **Fact-PCSplashtop-InstalledAgent** – The Splashtop remote desktop access agent has been installed. • **Fact-PCSplashtop-StartedService** – The Splashtop remote desktop access service has been started. Pre-built analytics rules for which `detectionReason` was updated include: • **Prof-ELNAC-Loc-U-Loc** – This is the first time this user has been observed logging into an endpoint using a network access control platform from this network location.

Feature	Description
	• **Prof-ELNAC-LT-UD-LT** – This is the first time a network access control login type has been observed in login events for users in this department. These events may include both failed and successful logins. • **Prof-ELNAC-LT-U-LT** – This is the first time this network access control login type has been observed in login events for this user. These events may include both failed and successful logins. • **Prof-ELNAC-LT-O-LT** – This is the first time this network access control login type has been observed in login events for the organization. These events may include both failed and successful logins. • **Prof-ELNAC-E-U-SMac** – This is the first a network access control login event has been observed coming from this MAC address for this user. These events may include both failed and successful logins. • **Prof-EL-HT-U-HT** – This is the first time this user has attempted to log into an endpoint of this type (server, workstation...). • **Prof-EL-EDC-O-SZ** – This is the first time an endpoint login event to a domain controller has been observed originating from this network zone for the organization. These events may include both failed and successful logins. • **Prof-EL-E-UD-DE** – This is the first time a user from this department attempted to log into this endpoint. These events may include both failed and successful logins. • **Prof-EL-E-U-SE** – This is the first time this user attempted to login from this endpoint. These events may include both failed and successful logins. • **Prof-EL-E-U-DE** – This is the first time this user attempted to log into this endpoint. These events may include both failed and successful logins. • **Prof-EL-Acct-U-Acct** – This is the first time this user has attempted to log into an endpoint using this domain account. These events may include both failed and successful logins. • **Prof-AL-E-U-SE** – This is the first time this user attempted to log into an application from this endpoint. These events may include both failed and successful logins. • **Prof-AL-E-O-SE** – This is the first time a user in the organization attempted to log into an application from this endpoint. These events may include both failed and successful logins. • **NumDCP-EL-DEC-O-DE** – An abnormal number of unique destination endpoints have been observed in endpoint login events for the organization. These events may include both failed and successful logins. • **NumDCP-EL-DEC-U-DE** – An abnormal number of unique destination endpoints have been observed in endpoint login events for this user. These events may include both failed and successful logins. • **Prof-EL-EDC-U-SZ** – This is the first time an endpoint login event to a domain controller has been observed originating from this network zone for this user. These events may include both failed and successful logins. Pre-built analytics for which `trainOnCondition` was updated include: • **Prof-PC-PPN-PPN-PN** – This is the first time this child process has been observed for this matured parent process. • **Prof-PC-PPN-PN-PPN** – This is the first time this parent process has been observed for this matured child process. Removed pre-built analytics rule include: • **Fact-DSOW-DCSyn-Attr** – The GC (global catalog) and DRS (directory replication service) service principal names have been added to an endpoint. These SPNs are required for the active directory replication process, and can be added to a rogue domain controller to execute a DCShadow attack.

Resolved Issues

Attack Surface Insights Resolved Issues

Issue ID	Description
ENG-73607	When you selected all entities matching a search query, the action to edit all selected entities was incorrectly made available. You could edit the entities displayed on the page only, not all entities matching the search query. Now, when you select all entities matching a search query, the ability to edit those entities is disabled.

Site Collector 2.11: Security Vulnerabilities Remediated in July 2025

The Site Collectors 2.11 (July 2025) release includes remediated security vulnerabilities. For more information about Exabeam's commitment to remediating vulnerabilities for Site Collector, see the Vulnerability Remediation Policy.

Known CVE - CVE-2025-48734. This is a NiFi CVE. Site Collector uses the latest NiFi version 2.4.0 and will update to the new version after NiFi provides a fix in an upcoming NiFi release.

Toolkit has been deprecated and is no longer in use hence no security vulnerabilities update is available for that.


The following table lists the CVEs remediated for the Nifi container and their severity.


Critical	High	Medium	Low
Total: 0	Total: 0	Total: 11	Total: 1
–	–	• CVE-2025-50181 • CVE-2025-6020 • CVE-2024-12718 • CVE-2025-4138 • CVE-2025-4330 • CVE-2025-4435 • CVE-2025-4516 • CVE-2025-4517 • CVE-2025-1795 • CVE-2025-50182 • CVE-2025-4598	CVE-2024-47081




June 2025

The New-Scale Security Operations Platform includes the following addressed features and new features for June 2025.

Attack Surface Insights

Feature	Description
User Risk Trend Chart	To understand a user entity's history and identify trends in their level of risk, you can now view a line chart of a user entity's risk score over time.  You can view the user entity's risk score over a time frame you specify: the past seven days, two weeks, one month, two months, or three months.  You can also navigate directly to the Threat Center case or alert associated with the risk score for a given day.

Feature	Description
Associated Open Threat Center Cases in User Entity Details	To start investigating a user entity from Attack Surface Insights, you can now view the number of open Threat Center cases whose detections are grouped by the user entity and created during the time frame selected in the User Risk Trend chart:  To navigate directly to those cases in the user entity details, click **<#> open cases**. If there are no open cases in the time frame, the information doesn't appear.

Feature	Description
Entity Deletion	To remove obsolete entities created due to parsing or enrichment issues, you can now delete entities.    

Cloud Collectors

Feature	Description
Cisco Secure Endpoint Cloud Collector	The Cisco Secure Endpoint Cloud Collector now available as part of Cloud Collectors to facilitate ingestion of security events from Cisco Secure Endpoint V1 APIs.
CrowdStrike Context Cloud Collector	The CrowdStrike Context Devices Cloud Collector is now available as part of Cloud Collectors to facilitate ingestion of data from a CrowdStrike source. The use of a cloud collector allows you to ingest CrowdStrike device data without the need for the **Exabeam Ingester for CrowdStrike** license add-on. The corresponding context table in the Context Management application will process the data and map it to a standardized set of attributes. **NOTE** If you opt to use the cloud collector method to ingest CrowdStrike data, the collector must be created ***before*** the context table. If you previously onboarded a CrowdStrike context table and you want to integrate with the cloud collector, you must delete the context table and recreate it after the CrowdStrike cloud collector is created and running. For information about creating the context table, see CrowdStrike Context Tables in the *Context Management Guide*.
Trellix Cloud Collector	The Trellix Endpoint Security Cloud Collector now available as part of Cloud Collectors to facilitate ingestion of security alerts from Trellix APIs.
Early Access Collectors	
Anomali Cloud Collector	The Anomali Cloud Collector is now available is now available, as part of Cloud Collectors Early Access program, to facilitate threat intelligence data collection from an Anomali source that supports the STIX/TAXII framework. You can opt to collect data about either IP addresses or domains. You can also opt to automatically generate a corresponding Anomali context table in the Context Management application that will process the data and map it to a standardized set of attributes. The context table will have the same name as the cloud collector. The early access program offers you an opportunity to gain access to the latest cloud collectors before their official release. To participate, see Sign Up for the Early Access Program.
AWS GuardDuty Cloud Collector	The AWS GuardDuty Cloud Collector is now available as part of Cloud Collectors Early Access program to facilitate ingestion of GuardDuty Findings from AWS S3 bucket. The early access program offers you an opportunity to gain access to the latest cloud collectors before their official release. To participate, see Sign Up for the Early Access Program.
AWS Security Lake Cloud Collector	The AWS Security Lake Cloud Collector is now available as part of Cloud Collectors Early Access program to facilitate ingestion of security events from AWS S3 Security Lake bucket. The early access program offers you an opportunity to gain access to the latest cloud collectors before their official release. To participate, see Sign Up for the Early Access Program.
Tenable Cloud Collector	The Tenable Cloud Collector is now available as part of Cloud Collectors Early Access program to facilitate ingestion of vulnerability events from Tenable APIs. The early access program offers you an opportunity to gain access to the latest cloud collectors before their official release. To participate, see Sign Up for the Early Access Program.

Feature	Description
Zoom Cloud Collector	The Zoom Cloud Collector is now available as part of Cloud Collectors Early Access program to facilitate ingestion of events from the sign-in/sign-out activity and operational logs endpoints. The early access program offers you an opportunity to gain access to the latest cloud collectors before their official release. To participate, see Sign Up for the Early Access Program.

Context Management

Feature	Description
Anomali Context Tables	Context Management now supports a preconfigured onboarding experience for Anomali context tables. These tables process data that is ingested by a corresponding Anomali cloud collector that supports the STIX/TAXII framework. By default these context tables process a predetermined set of IP or domain attributes from the source collector and then map these attributes to a set of standardized Exabeam target attributes. The Anomali context table onboarding via cloud collector is available as part of the Early Access program. The early access program offers you an opportunity to gain access to the latest cloud collectors before their official release. To participate, see Sign Up for the Early Access Program, in the *Cloud Collectors Administration Guide*. For more information, see Anomali Context Tables in the *Context Management Guide*.
CrowdStrike Device Context Table via Cloud Collector	Context Management now supports onboarding a CrowdStrike device context table with data ingested by a cloud collector, without the need for the **Exabeam Ingester for CrowdStrike** license add-on. The context table processes data that is ingested by a corresponding CrowdStrike Context cloud collector from a CrowdStrike source. By default the context table processes a predetermined set of device attributes from the source collector and maps them to a set of standardized Exabeam target attributes. For more information and prerequisites, see CrowdStrike Context Tables in the *Context Management Guide*. **NOTE** If you opt to use the cloud collector method to ingest CrowdStrike data, the collector must be created ***before*** the context table. If you previously onboarded a CrowdStrike context table and you want to integrate with the cloud collector, you must delete the context table and recreate it after the CrowdStrike cloud collector is created and running. For information about creating the cloud collector, see CrowdStrike Context Cloud Collector in the *Cloud Collectors Administration Guide*.

Correlation Rules

Feature	Description
New and Updated Correlation Rule Templates	You can now better identify insider threats with new and updated correlation templates. New correlation rule templates include: • **UBA: Large number of denied access events towards external domain** – A large number of denied outbound requests to external domains were detected from a single IP address, which indicates potential command and control or network discovery • **UBA: Account or Group or Privileges Modified** – Indicates when a user account was affected by an action which changes the user's effective privileges • **UBA: Anonymous User Accessed a Resource** – Detects an anonymous user accessing a resource • **UBA: External User Failed Mailbox Login** – Detects repeated failures to log in to mailbox from an external user • **UBA: Failed to Set Mailbox Audit Logging Bypass** – Detects when a user failed to correctly set mailbox audit logging bypass • **UBA: Sharing Link Sent to Guest** – Detects a sharing invitation being sent to a guest • **UBA: Sharing Policy Changed or Shared External (SharePoint/OneDrive)** – Detects when an item's sharing policy is changed to share with a guest user • **UBA: User Added to a Group on SharePoint or OneDrive by Site Admin** – Detects a user being added to a group in Sharepoint or OneDrive by a System Admin • **UBA: User Failed to be Added to Role** – Detects when an attempt to add a user to a role fails • **UBA: DPAPI Backup Master Key Recovery Attempted** – A recovery attempt of the DPAPI master key has been observed. • **UBA: Possible Directory Services Enumeration** – Detects reconnaissance attempts to Directory Service Enumeration. • **UBA: Possible SMB Session Enumeration on a Domain Controller** – 20 SMB access attempts have been observed from this user. • **UBA: Malware Activity - Registry Modified In Bulk** – Detects processes that create or modify the registry values in bulk within a shorter interval. • **UBA: Volume Shadow Copy Created** – Volume shadow copies have been created using vssadmin or wmic process • **Large amount of failed mailbox login events for this user** – 10 failed mailbox login events have been observed for a single user within 1 minute • **Multiple failed VPN logins from a single IP address** – 10 failed VPN logins have been observed from a single IP address within 1 minute • **Multiple VPN logins from a single IP address** – 10 successful VPN logins have been observed from a single IP address within 1 minute • **Server-side request forgery** – Identifies outbound HTTP requests from internal servers to internal IP ranges that may indicate SSRF exploitation • **Security logging and monitoring failures Syslogd** – Alert when syslogd logging services are stopped • **MFA request generation: repeated OKTA push denies** – Multi-Factor Authentication Request Generation Updated correlation rule templates include:

Feature	Description
	• **UBA: Suspicious Improbable Travel** – A user logs in from two or more geographically distant locations within a short timeframe, making it physically impossible to travel between those locations • **UBA: Multiple failed VPN login attempts from a single IP** – Multiple failed login attempts were detected from a single IP address within a specific time frame via VPN accounts, which indicates brute-force attack. • **UBA: Multiple VPN logins from single IP** – Multiple VPN accounts login attempts were detected from a single IP address within a specific time frame.

Dashboards

Feature	Description
Increased Count Maximum for the Anomalies Dashboard	The maximum end of the **Trigger Count** filter has been increased to a value of 10,000 in the pre-built Anomalies dashboard. This increase allows more accurate anomaly trigger rate reporting.  For more information, see Anomalies Dashboard in the *Dashboards Guide*.
New Compliance Dashboards Available	The following pre-built dashboards are available so that analysts and management can monitor compliance-focused activity on a recurring basis. These dashboards can be used to look for anomalous behavior, system health, and environmental trends. They can also be used to produce reports and provide evidence to assessors and auditors as needed. • CMMC – Analyst Dashboard / Management Dashboard • HIPAA – Analyst Dashboard / Management Dashboard • ISO 27001 – Analyst Dashboard / Management Dashboard • NIST 800-53 – Analyst Dashboard / Management Dashboard • NIST 800-171 – Analyst Dashboard / Management Dashboard • NIST CSF – Analyst Dashboard / Management Dashboard • PCI DSS – Analyst Dashboard / Management Dashboard For more information about the pre-built compliance dashboards, see Compliance Dashboards in the *Dashboards Guide*.
New Bulk Actions Available for Scheduled Reports	The following new bulk actions are now available for the **Scheduled Reports** tab: • **Send Now** – You can opt to send multiple scheduled reports immediately without waiting for their configured delivery times. • **Delete** – You can opt to delete multiple scheduled reports so they are removed from the Scheduled Reports tab. For more information, see Configure and Manage Scheduled Reports in the *Dashboards Guide*.


Log Stream


Feature	Description
Expanded Out-of-the-Box Access to Creating Custom Enrichment Rules	Access to creating custom rules has been expanded. Previously, this capability was available out-of-the-box only to those with the New-Scale Analytics license. Access is now available with any New-Scale license in the Exabeam portfolio: New-Scale SIEM, New-Scale Fusion, or New-Scale Analytics. The **Enrichments** tab provides access to define enrichment rules inside the Log Stream application. You can configure both the conditions an event must meet for a specific enrichment to be applied and the mapping that the enrichment rule will perform. This functionality provides access to do the following: • Create new custom enrichment rules • Edit existing custom enrichment rules • Duplicate existing custom enrichment rules For more information, see Enrichments in the *Log Stream Guide*.
Improvements to Defining Custom Enrichment Rules	The following new functionality has been added to the process of defining a custom enrichment rule: • A new operator has been added to the options for building conditions in an enrichment rule. The new operator, `is context key of`, allows you to include data found in the key column of a context table to your condition. • An option to create a new custom field on-the-fly has been added to the mapping section of the custom enrichment rule. You can define the the custom fields and use it to map a value from the conditions define in the rule. For more information about these capabilities, see Define an Enrichment Rule in the *Log Stream guide*.

Multi-Org Management

Feature	Description
Support for Custom User Roles in Multi-Org Management	You can now create custom user roles for Multi-Org Management. If the available default user roles do not provide the permissions you need, you can create custom roles and configure them with permissions tailored to your specific need. You can then assign the custom role to users in the parent or child organizations. For more information, see User Roles for Multi-Org Management.

Outcomes Navigator

Feature	Description
Exabeam Nova Analyst Assistant	You can now quickly learn and get answers to questions about your overall security posture using a security-trained AI assistant. Prompt Exabeam Nova Analyst Assistant with a message or query, and it interprets information from the MITRE ATT&CK Coverage Summary or Use Case Coverage Summary to generate a natural language response. 

Feature	Description
	

Search

Feature	Description
Expanded Access to Timeline View of Search Results	Exabeam has expanded access to the Timeline view of search results. Previously, this view of results was available only to those with one of the New-Scale licenses. Access is now available with any license in the Exabeam portfolio of licenses. The Timeline view brings the investigational timeline experience into the Search application. Analysts and threat hunters can use the Timeline view as a starting point for investigating risky or anomalous events while still leveraging the granular filtering capabilities of the Search application. The Timeline view is designed specifically with this task in mind. It's visually organized so that detection events are easy to spot and investigate. You can drill into the detections or the associated events to find detailed information and data insights. For more information, see Timeline View of Search Results in the *Search Guide*.

Feature	Description
Support for Sort Order Selection of Search Results	A configurable sort order option is now available for search results. The new sort order selector is located in the search bar for Basic, Advanced, and Natural Language modes. It includes options to sort chronologically to show the most recent or the oldest results. The sort happens on the server-side when you run your search, so results display the newest or oldest results from the entire set of results. For more information, see Search Bar in the *Search Guide*.
Updates to the Display of Detections in the Timeline View of Results	To enhance the chronological aspect of the Timeline view in Search, detections listed on the right-hand side of the view are now shown only on the row of the latest associated event. Detections can be triggered by multiple events and, previously, they were displayed in association with each triggering event. This led to a confusing view of the chronology of detections. To resolve this confusion and simplify the view, a detection is now displayed only on the chronologically latest associated event. For more information about the Timeline view, see Timeline View of Search Results in the *Search Guide*.
Improved Visibility for Site Tags in Search Results	Site tags are now more easily visible in both the Timeline View and the List View of search results. If you use unique site names to manage access to data from specific collector sources in your environment, tags with site names are now clearly visible on each event ingested by a tagged cloud or site collector. You can also toggle the display of the tags on or off in the search results. For more information, see either Timeline View of Search Results or List View of Search Results in the *Search Guide*.
Context Searching Using Any Table Type	When searching context values, you can now add any type of context table to a search query. You can search for data in collector-base context tables, in custom or filtered context tables, or in pre-built context tables. For more information, about adding context tables to Basic or Advanced search queries, see Context Tables in Search in the *Search Guide*.

Service Health and Consumption

Feature	Description
Notification for Exceeding Long Term Search Quota	The Long-Term Consumption Details page now displays notifications when you reach 100% of your long-term search quota or exceed the allowed quota, based on your Long Term Search and Long Term Storage licenses. The notifications inform you about following cases with the recommended action. • If you reach 100% of your long-term search quota, the data is moved to long-term storage. • If you exceed the 100% of your contracted long-term search quota, either reduce your usage or contact your account team to purchase more quota.
Enhancements for Public API	The new set of Public APIs are introduced for License Consumption endpoint to read license consumption information, including: • Current license level • Current and historical usage data, consistent with the UI history • Details for each license type (SIEM and NSA/AA, Long-term Search, Long-term Storage, API) • SIEM and AA/NSA consumption details

Site Collectors 2.10

Feature	Description
Upgradation to NiFi 2.4	Based on the vulnerability remediation policy, the version of Apache NiFi is upgraded to the latest available version 2.4.

Threat Detection Management

Feature	Description
New and Updated Correlation Rule Templates	You can now better identify insider threats with new and updated correlation templates. New correlation rule templates include: • **UBA: Large number of denied access events towards external domain** – A large number of denied outbound requests to external domains were detected from a single IP address, which indicates potential command and control or network discovery • **UBA: Account or Group or Privileges Modified** – Indicates when a user account was affected by an action which changes the user's effective privileges • **UBA: Anonymous User Accessed a Resource** – Detects an anonymous user accessing a resource • **UBA: External User Failed Mailbox Login** – Detects repeated failures to log in to mailbox from an external user • **UBA: Failed to Set Mailbox Audit Logging Bypass** – Detects when a user failed to correctly set mailbox audit logging bypass • **UBA: Sharing Link Sent to Guest** – Detects a sharing invitation being sent to a guest • **UBA: Sharing Policy Changed or Shared External (SharePoint/OneDrive)** – Detects when an item's sharing policy is changed to share with a guest user • **UBA: User Added to a Group on SharePoint or OneDrive by Site Admin** – Detects a user being added to a group in Sharepoint or OneDrive by a System Admin • **UBA: User Failed to be Added to Role** – Detects when an attempt to add a user to a role fails • **UBA: DPAPI Backup Master Key Recovery Attempted** – A recovery attempt of the DPAPI master key has been observed. • **UBA: Possible Directory Services Enumeration** – Detects reconnaissance attempts to Directory Service Enumeration. • **UBA: Possible SMB Session Enumeration on a Domain Controller** – 20 SMB access attempts have been observed from this user. • **UBA: Malware Activity - Registry Modified In Bulk** – Detects processes that create or modify the registry values in bulk within a shorter interval. • **UBA: Volume Shadow Copy Created** – Volume shadow copies have been created using vssadmin or wmic process • **Large amount of failed mailbox login events for this user** – 10 failed mailbox login events have been observed for a single user within 1 minute • **Multiple failed VPN logins from a single IP address** – 10 failed VPN logins have been observed from a single IP address within 1 minute • **Multiple VPN logins from a single IP address** – 10 successful VPN logins have been observed from a single IP address within 1 minute • **Server-side request forgery** – Identifies outbound HTTP requests from internal servers to internal IP ranges that may indicate SSRF exploitation • **Security logging and monitoring failures Syslogd** – Alert when syslogd logging services are stopped • **MFA request generation: repeated OKTA push denies** – Multi-Factor Authentication Request Generation Updated correlation rule templates include: • **UBA: Suspicious Improbable Travel** – A user logs in from two or more geographically distant locations within a short timeframe, making it physically impossible to travel between those locations

Feature	Description
	• **UBA: Multiple failed VPN login attempts from a single IP** – Multiple failed login attempts were detected from a single IP address within a specific time frame via VPN accounts, which indicates brute-force attack. • **UBA: Multiple VPN logins from single IP** – Multiple VPN accounts login attempts were detected from a single IP address within a specific time frame.

Resolved Issues

Site Collectors 2.10 Resolved Issues

ID	Description
ENG-68402	Implemented mandatory Kafka topic selection while configuring the Kafka Collector to enable log retrieval from the specified topic.

Site Collector 2.10: Security Vulnerabilities Remediated in June 2025

The Site Collectors 2.10 (June 2025) release includes remediated security vulnerabilities. For more information about Exabeam's commitment to remediating vulnerabilities for Site Collector, see the Vulnerability Remediation Policy.

Known CVE - CVE-2025-48734. This is a NiFi CVE. Site Collector uses the latest NiFi version 2.4.0 and will update to the new version after NiFi provides a fix in an upcoming NiFi release.

Toolkit has been deprecated and is no longer in use hence no security vulnerabilities update is available for that.

The following table lists the CVEs remediated for the Nifi container and their severity.

CVEs for NiFi

Critical	High	Medium	Low
Total: 0	Total: 0	Total: 9	Total: 1
–	–	• CVE-2024-47081 • CVE-2025-29087 • CVE-2025-29088 • CVE-2025-32414 • CVE-2025-32415 • CVE-2025-3277 • CVE-2025-3576 • CVE-2025-4598 • CVE-2025-47273	CVE-2024-58237

May 2025

The New-Scale Security Operations Platform includes the following addressed features and new features for May 2025.

Attack Surface Insights

Feature	Description
Attack Surface Insights Entity Tags in Threat Center	You can now find Threat Center cases or alerts related to groups of entities. When the detections of a case or alert are grouped by entity, the tags of that entity are automatically added to the tags of the case or alert. You can then use the tags to search for cases or alerts involving certain kinds of entities. Entity tags are copied to the case or alert. If you remove a tag from the entity, the tag remains in the case or alert. If you remove a tag from the case or alert, it remains in the entity.

Cloud Collectors




Feature	Description
CrowdStrike Context Devices Cloud Collector	The CrowdStrike Context Devices Cloud Collector is now available as part of Cloud Collectors Early Access program to facilitate ingestion of data from a CrowdStrike source. The use of a cloud collector to ingest CrowdStrike device data eliminates the need for the **Exabeam Ingester for CrowdStrike** license add-on. The early access program offers you an opportunity to gain access to the latest cloud collectors before their official release. To participate, see Sign Up for the Early Access Program.
STIX/TAXII Cloud Collector	The STIX/TAXII Cloud Collector is now available to facilitate threat intelligence data collection from external sources that support the STIX/TAXII framework. You can opt to collect data about either IP addresses or domains. You can also opt to automatically generate a corresponding context table in the Context Management application that will process the data and map it to a standardized set of attributes. The context table will have the same name as the cloud collector.
Recorded Future Context Cloud Collector	The Recorded Future Context Cloud Collector is now available to facilitate threat intelligence data collection from a Recorded Future Context source that supports the STIX/TAXII framework. You can opt to collect data about either IP addresses or domains. You can also opt to automatically generate a corresponding Recorded Future context table in the Context Management application that will process the data and map it to a standardized set of attributes. The context table will have the same name as the cloud collector.

Context Management

Feature	Description
STIX/TAXII Context Tables	Context Management now supports onboarding STIX/TAXII context tables. These tables process data that is ingested by a corresponding STIX/TAXII cloud collector from an external threat intelligence source that supports the STIX/TAXII framework. By default these context tables process a predetermined set of IP or domain attributes from the source collector and they map these attributes to a set of standardized Exabeam target attributes. For more information, see STIX/TAXII Context Tables in the *Context Management Guide*.
Recorded Future Context Tables	Context Management now supports a preconfigured onboarding experience for Recorded Future context tables. These tables process data that is ingested by a corresponding Recorded Future Context cloud collector that supports the STIX/TAXII framework. By default these context tables process a predetermined set of IP or domain attributes from the source collector and they map these attributes to a set of standardized Exabeam target attributes. For more information, see Recorded Future Context Tables in the *Context Management Guide*.

Feature	Description
CrowdStrike Device Context Table via Cloud Collector	Context Management now supports onboarding a CrowdStrike device context table via a cloud collector, without the need for the **Exabeam Ingester for CrowdStrike** license add-on. The context table process es data that is ingested by a corresponding CrowdStrike Context cloud collector from a CrowdStrike source. By default the context table processes a predetermined set of device attributes from the source collector and maps them to a set of standardized Exabeam target attributes. The CrowdStrike context table onboarding via cloud collector is available as part of the Early Access program. The early access program offers you an opportunity to gain access to the latest cloud collectors before their official release. To participate, see Sign Up for the Early Access Program, in the *Cloud Collectors Administration Guide*. For more information and prerequisites, see CrowdStrike Context Tables in the *Context Management Guide*.

Correlation Rules

Feature	Description
Correlation Rules Insights	To make informed decisions about authoring and tuning rules, you can now view insights about your correlation rules directly in Correlation Rules, including: • The total number of correlation rules in your environment and a pie chart of their statuses  • The number of created sequences  • A line chart of the number of correlation rules triggered in enabled and testing statuses over the past 30 days 


Log Stream

Feature	Description
Creating Custom Enrichment Rules	New workflows have been introduced for the **Enrichments** tab in Log Stream. The new functionality provides access to define enrichment rules inside the Log Stream application. You can configure both the conditions an event must meet for a specific enrichment to be applied and the mapping that the enrichment rule will perform. This functionality provides access to do the following: • Create new custom enrichment rules • Edit existing custom enrichment rules • Duplicate existing custom enrichment rules Currently, this feature is available out-of-the-box only if you have the New-Scale Analytics license. If you have another Exabeam license, this feature can be made available through an Early Access program. To sign up for this program, email the following group: logstream-ea@exabeam.com. For more information, see Enrichments in the *Log Stream Guide*.

New-Scale Platform



Feature	Description
Documentation of Supported Regions for Data Residency	A table of supported regions and their base URLs has been added to the New-Scale Security Operations Platform Guide and is available from the New-Scale landing page in the Exabeam Documentation portal. For more information, see Supported Regions for Data Residency.




Outcomes Navigator



Feature	Description
Exabeam Nova MITRE ATT&CK Coverage Summary	To get a high-level view of your overall security posture, you can now view an AI-generated summary of your overall MITRE ATT&CK® coverage.[a.]  The summary identifies: • The three ATT&CK techniques whose coverage score has increased the most • The three ATT&CK techniques whose coverage score has decreased the most • Recommendations for improving your coverage for those ATT&CK techniques whose coverage score has decreased

[a.]MITRE ATT&CK and ATT&CK are trademarks of The MITRE Corporation ("MITRE"). Exabeam is not affiliated with or sponsored or endorsed by MITRE. Nothing herein is a representation of the views or opinions of MITRE or its personnel.




Threat Center

Feature	Description
Watchlists	You can now monitor and quickly get an overview of entities of interest using watchlists.  Watchlists dynamically rank entities from highest to lowest risk score over a time frame you specify: the past day, two days, seven days, 14 days, 30 days, or 60 days.  There are five pre-built watchlists for notable users, notable assets, executive users, privileged users, and service accounts. You can also create your custom watchlists based on tags applied to entities in Attack Surface Insights. After you create a watchlist, you can edit and delete it.

Feature	Description
	 Watchlists are available only with a New-Scale Security Operations portfolio license.
Attack Surface Insights Entity Tags in Threat Center	You can now find Threat Center cases or alerts related to groups of entities. When the detections of a case or alert are grouped by entity, the tags of that entity are automatically added to the tags of the case or alert. You can then use the tags to search for cases or alerts involving certain kinds of entities. Entity tags are copied to the case or alert. If you remove a tag from the entity, the tag remains in the case or alert. If you remove a tag from the case or alert, it remains in the entity. This feature is available only with a New-Scale Security Operations portfolio license.
Alert Dismissal	To indicate that you reviewed an alert and other team members don't need to review it, you can now dismiss alerts. You can dismiss an individual alert or multiple alerts at once.  When an alert is dismissed, the dismissed reason, who dismissed the alert, and the date and time they dismissed the alert appears in the alert **Overview** tab. It is also recorded in the alert history.
Alert Read and Unread Statuses	To track your alert triage workflow, you can now mark an alert as read and unread. An alert is automatically marked as read when you open it. After an alert is read, you can manually mark it as unread.  Dismissed alerts are automatically reverted to unread status when their risk scores increase by a percentage you specify. By default, the percentage is 10 percent. Any time an alert is marked as read or unread, it is recorded in the alert history.

Feature	Description
Alert Status Column	You can now view whether an alert is read, unread, or dismissed in the **Alerts** tab, under the **STATUS** column.  You can also search for alerts by status. To filter dismissed alerts from the list, toggle **Hide Dismissed** on. 
Permission for Sending Information to Webhooks	To send case or alert information to a webhook, you must have the Manage webhooks: Read, Write and Delete permission.

Threat Detection Management

Feature	Description
Correlation Rules Insights	To make informed decisions about authoring and tuning rules, you can now view insights about your correlation rules directly in the **Correlation Rules** tab, including: • The total number of correlation rules in your environment and a pie chart of their statuses  • The number of created sequences  • A line chart of the number of correlation rules triggered in enabled and testing statuses over the past 30 days 

Feature	Description
Optional Exclusion Descriptions	When you create an exclusion, the description field is now optional.

Resolved Issues

Site Collectors 2.9 Hot Fixes

Release Number	Hot Fix Description
2.9.3	Fixed an issue for MySQL, MSSQL, Oracle, and QRadar collectors to ensure accurate initialization of collector setup.
2.9.2	Fixed an issue for ngscd health check for backward compatibility for operating systems.
2.9.1	Addressed an issue to ensure more robust and consistent observability in Site Collectors.

Site Collector 2.9: Security Vulnerabilities Remediated in May 2025

The Site Collectors 2.9 (May 2025) release includes remediated security vulnerabilities. For more information about Exabeam's commitment to remediating vulnerabilities for Site Collector, see the Vulnerability Remediation Policy.

There are no open known CVEs in any container image (Nifi). Toolkit has been deprecated and is no longer in use hence no security vulnerabilities update is available for that.

The following table lists the CVEs remediated for the Nifi container and their severity.

Critical	High	Medium	Low
Total: 0	Total: 0	Total: 3	Total: 0
–	–	• CVE-2025-32414 • CVE-2025-32415 • CVE-2024-56406	

April 2025

The New-Scale Security Operations Platform includes the following addressed features and new features for April 2025.

Attack Surface Insights

Feature	Description
Default Search Enhancement	To ensure you get a blank slate to define your own search query, there is no default search query for user and device entities when you open Attack Surface Insights.

Cloud Collectors


Feature	Description
Cloudflare Cloud Collector	The Cloudflare Cloud Collector is now available as part of Cloud Collectors to facilitate data collection from the account based and zone based data sources that include Audit logs, HTTP requests, and Gateway DNS events.
Google Workspace Cloud Collector	The Google Workspace Cloud Collector is now available as part of Cloud Collectors to facilitate data collection from the data sources: Admin, Calendar, Drive, Gplus, Groups, Login, Meet, Mobile, Rules, Saml, Token.
LastPass Cloud Collector	The LastPass Cloud Collector is now available as part of Cloud Collectors to facilitate data ingestion from LastPass report events.
ServiceNow Cloud Collector	The ServiceNow Cloud Collector is now available as part of Cloud Collectors to facilitate data ingestion from the data sources Sys Audit Role, Sys Attachment, Change Request, Change Task, Sys Audit, Sys Event, Syslog Transaction, Report View, Event, Request, Task, Incident, Interaction, and Problem.
Vectra Cloud Collector	The Vectra Cloud Collector is now available as part of Cloud Collectors to facilitate data ingestion from the data sources Audit Log Events, and Detections.
Refresh token feature for the REST API Cloud Collector	You can now set the Authentication Refresh Body Parameters, and specify JSON path expression to extract the refresh token attribute and expiry time attribute for configuring OAuth 2.0 authentication for the REST API Cloud Collector.
Regex Filtering for Cloud Collectors	You can now add filter conditions for the CrowdStrike Falcon (via FDR) Cloud Collector, AWS S3 Cloud Collector, AWS CloudTrail (via S3) Cloud Collector, SentinelOne CloudFunnel Cloud Collector, and Cisco Umbrella Cloud Collector in addition to the Azure Event Hub Cloud Collector, using regex syntax to include and exempt logs to be sent to the New-Scale Security Operations Platform. The cloud collector processes logs based on the conditions that you specify using the regex pattern.
Early Access Collectors	
AWS CloudWatch Alarms Collector	The AWS CloudWatch Alarms Cloud Collector now available as part of Cloud Collectors Early Access program to facilitate ingestion of AWS CloudWatch alarms related events. The early access program offers you an opportunity to gain access to the latest cloud collectors before their official release. To participate, see Sign Up for the Early Access Program.
Cisco Secure Endpoint Cloud Collector	The Cisco Secure Endpoint Cloud Collector now available as part of Cloud Collectors Early Access program to facilitate ingestion of security events from Cisco Secure Endpoint V1 APIs. The early access program offers you an opportunity to gain access to the latest cloud collectors before their official release. To participate, see Sign Up for the Early Access Program.
Trellix Endpoint Security Cloud Collector	The Trellix Endpoint Security Cloud Collector now available as part of Cloud Collectors Early Access program to facilitate ingestion of security alerts from Trellix APIs. The early access program offers you an opportunity to gain access to the latest cloud collectors before their official release. To participate, see Sign Up for the Early Access Program.

Context Management

Feature	Description
Expanded IOC Field Enrichment	You can now search for IOC data from both internal and external threat intelligence sources. This functionality is made possible because the Context Management service now provides threat intelligence data from both prebuilt, curated sources and from external log sources that support the STIX/TAXII framework. **NOTE** STIX/TAXII context tables are available as part of a Cloud Collector Early Access program. During the early access period, you can access this functionality for STIX/TAXII context tables only if you participate in the program. To participate, see Sign Up for the Early Access Program, in the *Cloud Collectors Administration Guide*. To facilitate this expanded functionality, a new `ioc_sources` attribute has been added to the enriched IOC fields you can use in the Search and Correlation Rules applications. Values in this field identity which log source a suspected IOC record was ingested by. For more information, see Context in Search and Correlation Rules in the *Context Management Guide*.

Dashboards

Feature	Description
Support for STIX/TAXII based Context Tables	You can now filter dashboard visualizations for threat intelligence data from both Exabeam-provided and STIX/TAXII-based sources. This functionality is made possible because the Context Management service now provides threat intelligence data from both prebuilt, curated sources and from external log sources that support the STIX/TAXII framework. **NOTE** STIX/TAXII context tables are available as part of a Cloud Collector Early Access program. During the early access period, you can access this functionality for STIX/TAXII context tables only if you participate in the program. To participate, see Sign Up for the Early Access Program, in the *Cloud Collectors Administration Guide* For more information, see Include Context Filtering in Visualizations in the *Dashboards Guide*.
Updates to AI/LLM Pre-built Dashboards	The following updates have been made to AI/LLM pre-built dashboards: • **Nightfall AI - AI/LLM Alerts** – This dashboard, and all of the visualizations it includes, have been reconfigured to visualize alert activity for any AI usage. The dashboard has been renamed as **AI/LLM Alerts**. • **Enterprise AI/LLM Usage - GCP** – This dashboard has been streamlined to contain just the following visualizations: **AI/LLM Operations in GCP** and **Operations Performed Against Models in GCP**. For more information about the AI/LLM pre-built dashboards, see AI/LLM Dashboards in the *Dashboards Guide*.

Feature	Description
Improve Filtering a Visualization on a Context Table	Filter behavior has been improved when selecting a context table as a query filter for a visualization. You can now select a context table that contains no records and add it to the visualization query filter. However, the visualization will not display any results until at least one record is added to the context table. A new message has been added to alert you when the context table you select contains no records.  For more information, see Include Context Filtering in Visualizations in the *Dashboards Guide*.

Log Sources

Feature	Description
Log Source Monitoring	Using the Log Sources service you can now detect and monitor active and inactive log sources. In addition to granular monitoring of log sources, the Log Source service offers log source policy configuration and discovery, log source status visibility, and export of log sources. This feature is available as a part of the early access program. To participate, see Sign Up for the Early Access Program.

New-Scale Platform


Feature	Description
New Access Control API Endpoints	You can now programmatically retrieve lists of users, roles, and API keys that are configured in your environment. Three new **Access Control** endpoints are available to view this information without the need to log into the New-Scale Security Operations Platform and navigate the **Settings** options. For more information, see Access Control APIs in the *New-Scale Security Operations Platform Administration Guide* or visit the the Exabeam API Reference Guide and use the left navigation panel to find the **Access Control** endpoints.

Outcomes Navigator

Feature	Description
Numeric Coverage Scores	To have a more representative coverage score, better understand how the coverage score is calculated, and better track trends over time, all coverage scores are now numeric values between 0 and 100. **Overall coverage scores** are the average individual coverage scores across all Exabeam use cases or MITRE ATT&CK® techniques.[a.] **Coverage scores for individual use cases or techniques** are the weighted average of coverage scores across Exabeam applications or features, like analytics rules, correlation rules, and Dashboards.

[a.]MITRE ATT&CK and ATT&CK are trademarks of The MITRE Corporation ("MITRE"). Exabeam is not affiliated with or sponsored or endorsed by MITRE. Nothing herein is a representation of the views or opinions of MITRE or its personnel.

Search

Feature	Description
Context Searching Using Non-key Columns	Until now, when searching for values in a context table, you could search for values only in the key column of the table. Now, the use of context tables in search includes the capability of searching in any column of a context table, including non-key columns. This expanded functionality is available in both the Basic and Advanced search modes. You can include up to two tables in a query, and a single column for each table. To facilitate the selection of non-key columns in Basic search, changes have been made in the UI for adding a context table to the query. When you choose a context table, a preview of the table is displayed. The key column is selected by default, but you can select any other column in the table.  In Advanced search, additional syntax is provided to indicate the selection of both a context table and a specific column. For backwards compatibility, you can still add a context table without specifying a column. If no column is indicated, the query searches for values in the key column by default. The new syntax takes the following form: `IN "table name"."column name"` For more information, about adding context tables to Basic or Advanced search queries, see Context Tables in Search in the *Search Guide*.

Feature	Description
Advanced Search Suggestion Improvements	In the Advanced search mode, automated suggestions have been improved to display a greater variety of possible syntax options and to make those suggestions with greater context-awareness. The automated suggestions can now include key words, logical operators, fields, field values, and functions. Suggestions are only displayed if they are appropriate for the clause or syntax you are entering. For visual clarity, each different type of suggestion is accompanied by an icon that indicates what type of syntax is represents. For more information about Advanced search suggestions, see Running an Advanced Search in the *Search Guide*.
Expanded IOC Field Enrichment	You can now search for IOC data from both Exabeam-provided and STIX/TAXII-based threat intelligence sources. This functionality is made possible because the Context Management service now provides threat intelligence data from both prebuilt, curated sources and from external log sources that support the STIX/TAXII framework. **NOTE** STIX/TAXII context tables are available as part of a Cloud Collector Early Access program. During the early access period, you can access this functionality for STIX/TAXII context tables only if you participate in the program. To participate, see Sign Up for the Early Access Program, in the *Cloud Collectors Administration Guide*. To facilitate this expanded functionality, a new `ioc_sources` attribute has been added to the enriched IOC fields you can query in the Search application. Values in this field identity which log source a suspected IOC record was ingested by. For more information, see Threat Intelligence Enrichment in the *Search Guide*.

Service Health and Consumption

Feature	Description
Public API	Exabeam Public API enables you to programmatically retrieve license information for Long Term Search, Long Term Storage, and Correlation Rules. With the new public API you can now: • Monitor and manage your license consumption by retrieving data about usage of Long Term Search and Storage • Authenticate securely using OAuth 2.0 client credentials • Review application health status including uptime and outage For more information, see the Exabeam API Reference Guide and use the left navigation panel to access the **Service Health Consumption** section. Additionally, navigate to the **Changelog** section for more details.

Site Collectors 2.8

Feature	Description
Region-specific Deployments	For Site Collector deployment, the regional endpoints will be utilized for communication with GCS instead of the generic GCS endpoints. Regional endpoints ensure that all requests and data in transit are processed and uploaded into the destination GCS only within the specified geographic region, maintaining data residency compliance.

Feature	Description
Automatic Scaling of Concurrency Settings for Site Collectors	Based on system load and hardware specifications such as CPU count, Site Collector is enhanced to dynamically scale its concurrency settings. This helps prevent event log accumulation in the queue and minimizes processing delays, especially when the repository disk is at full capacity.

Threat Center

Feature	Description
Exabeam Nova Case Name Enhancement	To ensure AI-generated case names help you quickly decide which cases to work on, the prompt used to generate case names has been refined to produce more concise case names.
Increased Case and Alert List Default View	By default, you now see more cases or alerts in the case and alert lists. By default, 50 cases or alerts are displayed per page. You can also adjust the list to display 10, 25, or 100 cases or alerts per page.

The following issues have been addressed from Threat Center in this release:

ID	Description
ENG-68306	Email notifications sent from Threat Center didn't display the case ID. Now, the case ID is displayed under the **Case Number** field.

Resolved Issues

Search Resolved Issues

ID	Description
ENG-67439	An issue has been resolved so that when running an aggregated search using Advanced Query Language operators, the applicable license entitlements are enforced. You will not be able to run aggregated searches beyond your licensed time period.
ENG-65001	When using CIDR notations are used in queries with `NOT` operators (example: `NOT dest_ip:[123.45.678.912/8]`), fields with null IP addresses are being excluded or included inconsistently in Search results. This issue has been resolved and the intended behavior restored. The intended behavior is that searches consistently include null IP addresses unless a condition is added to the query syntax to explicitly exclude them (example: `AND NOT dest_ip:NULL`).

Site Collectors 2.8 Hot Fixes

Release Number	Hot Fix Description
2.8.1	Fixed a CICD issue that was preventing successful deployment of updates for Site Collectors.

Site Collector 2.8: Security Vulnerabilities Remediations

The Site Collectors 2.8 (April 2025) release includes remediated security vulnerabilities. For more information about Exabeam's commitment to remediating vulnerabilities for Site Collector, see the Vulnerability Remediation Policy.

There are no open known CVEs in any container image (Nifi). Toolkit has been deprecated and is no longer in use hence no security vulnerabilities update is available for that.

The following table lists the CVEs remediated for the Nifi container and their severity.

Critical	High	Medium	Low
Total: 0	Total: 0	Total: 10	Total: 1
–	–	• CVE-2024-50032 • CVE-2024-55549 • CVE-2024-8176 • CVE-2025-1176 • CVE-2025-1178 • CVE-2025-1181 • CVE-2025-1182 • CVE-2025-24855 • CVE-2025-30258 • CVE-2025-31115	CVE-2025-1153

March 2025

The New-Scale Security Operations Platform includes the following addressed features and new features for March 2025.

Cloud Collectors

Feature	Description
Mimecast Cloud Collector	The Mimecast Cloud Collector is now available as part of Cloud Collectors to facilitate data collection from the data sources Archive Search Logs, TTP Attachment Protection Logs, TTP Impersonation Protect Logs, TTP URL Logs, SIEM Logs, Archive Message View Logs, and Audit Events.
REST API Cloud Collector	The REST API Cloud Collector is now available as part of Cloud Collectors to facilitate data collection from REST API endpoints from a broad range of vendors and products.
Sophos Cloud Collector	The Sophos Cloud Collector is now available as part of Cloud Collectors to facilitate data collection from the data sources alerts and events.
Event Exploration on Search via Cloud Collectors	Now with the Open in Search option, you can open the Search application in a new tab to view a prepopulated Search query that displays details of logs related to the selected Cloud Collector instance. You can modify the Search query with parameters and timeframe to filter logs to see details specific to a Collector instance.
Early Access Collectors	
Cloudflare Cloud Collector	The Cloudflare Cloud Collector is now available as part of Cloud Collectors Early Access program to facilitate data collection from the account based and zone based data sources that include Audit logs, HTTP requests, and Gateway DNS events. The early access program offers you an opportunity to gain access to the latest cloud collectors before their official release. To participate, see Sign Up for the Early Access Program.
Google Workspace Cloud Collector	The Google Workspace Cloud Collector is now available as part of Cloud Collectors Early Access program to facilitate data collection from the data sources: Admin, Calendar, Drive, Gplus, Groups, Login, Meet, Mobile, Rules, Saml, Token. The early access program offers you an opportunity to gain access to the latest cloud collectors before their official release. To participate, see Sign Up for the Early Access Program.

Feature	Description
LastPass Cloud Collector	The LastPass Cloud Collector is now available as part of Cloud Collectors Early Access program to facilitate data ingestion from LastPass report events. The early access program offers you an opportunity to gain access to the latest cloud collectors before their official release. To participate, see Sign Up for the Early Access Program.
Vectra Cloud Collector	The Vectra Cloud Collector is now available as part of Cloud Collectors Early Access program to facilitate data ingestion from the data sources Audit Log Events, and Detections. The early access program offers you an opportunity to gain access to the latest cloud collectors before their official release. To participate, see Sign Up for the Early Access Program.
STIX/TAXII Cloud Collector	The STIX/TAXII Cloud Collector is now available as part of Cloud Collectors Early Access program to facilitate threat intelligence data collection from external sources that support the STIX/TAXII framework. You can opt to collect data about either IP addresses or domains. You can also opt to automatically generate a corresponding context table in the Context Management application that will process the data and map it to a standardized set of attributes. The context table will have the same name as the cloud collector. The early access program offers you an opportunity to gain access to the latest cloud collectors before their official release. To participate, see Sign Up for the Early Access Program.
Recorded Future Context Cloud Collector	The Recorded Future Context Cloud Collector is now available as part of Cloud Collectors Early Access program to facilitate threat intelligence data collection from a Recorded Future Context source that supports the STIX/TAXII framework. You can opt to collect data about either IP addresses or domains. You can also opt to automatically generate a corresponding STIX/TAXII context table in the Context Management application that will process the data and map it to a standardized set of attributes. The context table will have the same name as the cloud collector. The early access program offers you an opportunity to gain access to the latest cloud collectors before their official release. To participate, see Sign Up for the Early Access Program.

Context Management

Feature	Description
STIX/TAXII Context Tables	Context Management now supports onboarding STIX/TAXII context tables. These tables process data that is ingested by a corresponding STIX/TAXII cloud collector from an external threat intelligence source that use the STIX/TAXII framework. By default these context tables process a predetermined set of IP or domain attributes from the source collector and maps them to a set of standardized Exabeam target attributes. The STIX/TAXII context tables are available as part of the Early Access program. During the early access period, STIX/TAXII context tables can be created from either a STIX/TAXII or a Recorded Future Context cloud collector. The early access program offers you an opportunity to gain access to the latest cloud collectors before their official release. To participate, see Sign Up for the Early Access Program, in the *Cloud Collectors Administration Guide*. For more information, see STIX/TAXII Context Tables in the *Context Management Guide*.

Dashboards

Feature	Description
New Scheduled Reports Tab	A new **Scheduled Reports** tab has been introduced in the Dashboards application. The new tab provides a centralized view of all the dashboard reports you have currently scheduled for delivery via email. From the new **Scheduled Reports** tab you can see which dashboards are scheduled for delivery, which recipients are scheduled to receive them, and on what schedule they will be delivered. You can also control the scheduled reports, with options to **Run Now**, **Edit**, **Duplicate**, or **Delete**. For more information about the new tab, see Navigate the Scheduled Reports Tab in the *Dashboards Guide*.



Multi-Org Management



Feature	Description
Add Descriptive Child Names in the Multi-Org Console	If you are managing multiple organizations in a Multi-Org console, you can now add descriptive banner names to your child organizations. You can enter user-friendly, identifiable names that help reflect the way you refer to your customers or environments. For more information, see the Get Started section of the *Multi-Org Management Guide*.

New-Scale Platform

Feature	Description
Introducing Exabeam Nova	Exabeam Nova, a transformative new agentic AI tool, is now available as part of the New-Scale Security Operations Platform. Exabeam Nova is built directly into the platform and requires no additional cost or extra complexity. Exabeam Nova is designed to augment SOC team efforts by automating routine investigative tasks. It can intelligently process vast amounts of event and alert data to provide targeted insights. And it is flexible enough to generate actionable investigation summaries for analysts of different experience levels. For more information, see Exabeam Nova in the *New-Scale Security Operations Platform Administration Guide*.


Outcomes Navigator

Feature	Description
Coverage Summaries	To get a high-level view of your overall security posture, you can now view a summary of your coverage across all MITRE ATT&CK® techniques and use cases.[a] To quickly understand your security posture at a glance, you can now view an overall Use Case Coverage Score and MITRE ATT&CK Coverage Score. The overall coverage scores represent the average coverage score across all use cases or ATT&CK techniques. It is calculated once per day.   To identify trends in the overall coverage score, you can view a bar chart depicting the overall coverage score over one month, three months, or six months. You can also view the relative change of the overall coverage score over the given period and the relative change since the last time the score was calculated. **Exabeam Nova Use Case Coverage Summary** is an AI-generated summary of your overall use case coverage.

Feature	Description
	 The summary identifies: • The three uses cases whose coverage score has increased the most • The three uses cases whose coverage score has decreased the most • Recommendations for improving your coverage for those use cases whose coverage score has decreased For ATT&CK techniques, this summary is under development and will be delivered in the coming months. 

[a.] MITRE ATT&CK and ATT&CK are trademarks of The MITRE Corporation ("MITRE"). Exabeam is not affiliated with or sponsored or endorsed by MITRE. Nothing herein is a representation of the views or opinions of MITRE or its personnel.

Search



Feature	Description
Data Insights	Data Insights functionality was previously only available to users with one of the New-Scale licenses. It is now also available to users with any Exabeam Security Operations licenses. The **Insights** tab is available in the **Event Details** panel for any search results that include parsed user or device information. The Insights tab provides a quick, easy way to drill into information related to events in your results. It lets you visualize what else is going on around a selected event, within specific time ranges. For example, if an event shows that a user triggered an alert, you can investigate which other assets the user has accessed in the past few days, which countries the user logged in from, or what files the user accessed. For more information, see Data Insights in the *Search Guide*.
Entity Search Enhancements	The **Entities** tab in the Basic Search mode has been enhanced for more intuitive use and to display an increased level of detail. As part of the Exabeam True Identity functionality, the User Entity search consolidates all of the identifiers associated with a user account in your environment. In this way you can efficiently search across all the user identifiers with a single query. The process has been improved so that you can search by a user's full name or by any username or email address associated with the user account. Tooltips have been added so that you can view all of the associated names and addresses that will be included in the search results.  Options are still available to search by specific user account identifiers, including username or email address. For more information, about user entity searching, see Pre-Built Basic Search Lists in the *Search Guide*. This feature is currently available only if you have either the New-Scale Analytics license or the New-Scale Fusion license. For more information about these licenses, see New-Scale Security Operations Portfolio Licenses. For more information about managing and viewing entities in your environment, see the Attack Surface Insights guide.



Site Collectors 2.7

Feature	Description
Performance Optimization for Windows and Linux File Collector	Implemented performance enhancements for Windows and Linux File Collector to facilitate processing of extra large files exceeding 20GB.
Site Collector Upgrade Options	After you upgrade to the Site Collector 2.7 version, the next releases will show options to upgrade the current Site Collector version to the latest and the most recent stable version.

Feature	Description
Windows Server 2025 and Windows Server 2025 Core Support for Agent Collectors	The Windows Event Log Collector, Windows File Collector and Windows Archive Collector now support the Windows Server 2025 and Windows Server 2025 Core operating system.

Threat Center

Feature	Description
Threat Center Exabeam Nova Enhancement	If you have a license that includes Advanced Analytics, Exabeam Nova Analyst Assistant and Exabeam Nova Threat Summary now have a better understanding of a case or alert, considering the 50 most recently grouped detections when generating a response.[a.] If you have a New-Scale Security Operations portfolio license, you can now get more accurate and trustworthy responses with minimal hallucinations from Exabeam Nova Analyst Assistant and Copilot Threat Summary. Exabeam Nova now has a better understanding of a case or alert, considering associated entity information and all associated detections when generating a response.
Created Column	To ensure you're investigating the right case or alert, you can now view the date and time a case or alert was created and time elapsed since the case or alert was created under the **Created** column. 
Queue and Assignee Columns	To support sorting by queue and assignee, cases now have separate queue and assignee columns. 
Sorting Enhancements	To help you quickly find a case or alert, you can now sort cases and alerts by three additional columns: Grouped By, Stage, Queue, and Assignee.
Filters	To view only certain kinds of cases or alerts, you can now filter cases and alerts. For cases, you can filter by priority, grouped by value, stage, queue, and assignee.  For alerts, you can filter by priority and grouped by value. 

Feature	Description
Increased Notes Character Limit	To ensure you can communicate everything you want with case notes, you can now add up to 4,000 characters in a single note. 
Threat Timeline Rule Name Enhancement	To better discern the type of rule associated with a detection, you can now see the full name of the rule type in the Threat Timeline. 

[a.]This tool is designed to condense security event data into easy-to-understand language, focusing on important security details. It can also answer follow-up questions and discuss security tech topics, but its accuracy might vary outside these areas. Always double-check responses for crucial decisions. Your queries and data will only be retained temporarily and won't be used for AI training. Exabeam is actively improving this tool and welcomes feedback.

Threat Detection Management

Feature	Description
Incompatible Analytics Rule Disablement	To ensure the analytics engine runs normally, the analytics engine monitors rule training and evaluation processes and prevents you from enabling analytics rules that are incompatible with your data or are highly likely to generate false positive results. Under the **Compatability**, column, these analytics rules are marked as **Incompatible.**

Resolved Issues

Service Health and Consumption Resolved Issues

ID	Description
NGT-1887	The **Health Alerts & Thresholds** notification section under the **App Config** tab now continues to display Cribl cloud collector instances even after getting decommissioned either from Exabeam Cloud Collectors page or from Cribl console. The Cribl collector instances listed in the **App Config** section now have a prefix exa-cribl-logs- before the name of the collector configured from Cribl console. Fixed the associated issue in which the Cribl cloud collector instances were not listed in the **Health Alerts & Thresholds** notification section.

Site Collectors 2.7 Hot Fixes

Release Number	Hot Fix Description
2.7.3	Fixed an issue for collectors to ensure accurate initialization of collectors in ngscd.
2.7.2	Resolved a monitoring issue triggered by the presence of the invalid nifi components.
2.7.1	Resolved an issue that impacted the successful setup of the eStreamer collector.

Site Collectors 2.7 CVE Remediations

The Site Collectors 2.7 (March 2025) release includes remediated security vulnerabilities. For more information about Exabeam's commitment to remediating vulnerabilities for Site Collector, see the Vulnerability Remediation Policy.

There are no open known CVEs in any container image (Nifi). Toolkit has been deprecated and is no longer in use hence no security vulnerabilities update is available for that.

The following table lists the CVEs remediated for the Nifi container and their severity.

Critical	High	Medium	Low
Total: 0	Total: 0	Total: 12	Total: 4

Critical	High	Medium	Low
–	–	• CVE-2024-12133 • CVE-2024-12243 • CVE-2024-26462 • CVE-2024-56171 • CVE-2024-57360 • CVE-2025-0840 • CVE-2025-0927 • CVE-2025-0938 • CVE-2025-1390 • CVE-2025-24528 • CVE-2025-24928 • CVE-2025-27113	• CVE-2024-9143 • CVE-2024-13176 • CVE-2024-26458 • CVE-2024-26461

February 2025

The New-Scale Security Operations Platform includes the following addressed features and new features for February 2025.

Automation Management


Feature	Description
New Region Support for the UK	Support for Automation Management now extends to the UK region. You can now access and use Automation Management in the UK.



Cloud Collectors




Feature	Description
Cisco Meraki Cloud Collector	The Cisco Meraki Cloud Collector is now available as part of Cloud Collectors to facilitate data collection from security events, alerts, configuration changes, and networks from Cisco Meraki APIs.
Mimecast Cloud Collector	The Mimecast Cloud Collector is now available as part of Cloud Collectors Early Access program to facilitate data collection from the data sources Archive Search Logs, TTP Attachment Protection Logs, TTP Impersonation Protect Logs, TTP URL Logs, SIEM Logs, Archive Message View Logs, and Audit Events.. The early access program offers you an opportunity to gain access to the latest cloud collectors before their official release. To participate, see Sign Up for the Early Access Program.
REST API Cloud Collector	The REST API Cloud Collector is now available as part of Cloud Collectors Early Access program to facilitate data collection from REST API endpoints from a broad range of vendors and products. The early access program offers you an opportunity to gain access to the latest cloud collectors before their official release. To participate, see Sign Up for the Early Access Program.



Feature	Description
Sophos Cloud Collector	The Sophos Cloud Collector is now available as part of Cloud Collectors Early Access program to facilitate data collection from the data sources alerts and events. The early access program offers you an opportunity to gain access to the latest cloud collectors before their official release. To participate, see Sign Up for the Early Access Program.

Correlation Rules

Feature	Description
Stopped and Testing Statuses	You can now better understand the state of a correlation rule with two new statuses: Stopped and Testing. The Stopped status indicates that the rule has triggered more than 50 times in five minutes and has automatically been disabled. The Testing status indicates that the rule is enabled in test mode and its outcomes are suppressed.  You can also filter correlation rules by the new statuses. 
Select Outcomes Enhancements	When you create or edit a correlation rule, the step to **Select Outcomes** now clearly explains what happens when a rule triggers and the possible outcomes: • Designating outcomes for a rule is optional. • An event is created every time a rule triggers, even in test mode. If a rule triggers and isn't in test mode, the activity type of the event is `rule-trigger`. If a rule triggers in test mode, the activity type of the event is `rule-trigger-test`. • If you have a license that supports Threat Center, Threat Center may also create an alert when a rule triggers, depending on whether the rule is in test mode. If the rule triggers and isn't in test mode, Threat Center creates an alert. if the rule triggers and is in test mode, Threat Center doesn't create an alert.

Feature	Description
Correlation Rule Details Severity Enhancement	When you view correlation rule details, you can now more quickly identify the rule severity:  • The severity value is now positioned first in its section. • The severity is now color-coded according to its value: Critical, High, Medium, or Low.
Rule Evaluation Delay Explanation	When you create or edit a correlation rule, the step to configure a rule evaluation delay now clearly explains what rule evaluation delay is and that rules are delayed from evaluating events for seven minutes by default.  

Feature	Description
Rule Description Enhancements	You can now add more information to a correlation rule with descriptions. When you create or edit a correlation rule, you can now add a description about the rule.  This description appears in the list of correlation rules and rule details.   If you use a correlation rule template, the correlation rule template description is automatically reused as the description of your new correlation rule.

Feature	Description
Triggered Value to Search Navigation	To view all events related to a correlation rule, you can now navigate to Search using a link next to the number times a rule has been triggered. The query automatically entered in Search is *rules.rule: "<rule name>"*. The link appears in the list of correlation rules:  The link also appears when you view the correlation rule details: 
Email Notification Address Change	Email notifications sent as an outcome are now sent from *no-reply@notify.exabeam.cloud*. To ensure any rules for filtering emails or creating third-party tickets work properly, ensure they use the new email address.
New Region Support for the UK	Support for Correlation Rules now extends to the UK region. You can now access and use Correlation Rules in the UK.

Dashboards

Feature	Description
Auto-Creating a Threat Center Alert Visualization from a Natural Language Prompt	As part of Exabeam Nova and its set of AI-driven capabilities, the use of the natural language prompt for auto-creating a dashboard visualization has been expanded to an additional data model. You can now use the natural language prompt for the **Threat Center Alerts** data model. This enhancement means that you can leverage the natural language prompt in the Dashboard application to describe, in plain language, the **Threat Center Alerts** data you want to visualize. Based on this plain language prompt, the measures, dimensions, filters, and even the chart type are configured automatically. **NOTE** This auto-create option is currently available to create visualizations only for the Event Store **Event** data model and the Threat Center **Alerts** data model. You must be using Threat Center to access the Threat Center **Alerts** data model. If the automatically generated visualization does not produce the data you want to visualize, you can modify the visualization settings manually to produce exactly the desired results. For more information about auto-creating visualizations, see Auto-Create a Visualization from a Natural Language Prompt in the *Dashboards Guide*.

Search

Feature	Description
Support for Device Context Tables	You can now include device context tables in both Basic and Advanced search queries, allowing you to search for information about devices in your environment. Specifically, you can now search for results in the following types of device context tables: • Active Directory • CrowdStrike • Microsoft Entra ID For more information, see Context Tables in Search in the *Search Guide*.


Service Health and Consumption

Feature	Description
Export License View Details to PDF	The License View dashboard now includes an option to export all its details as a PDF file.
Improvements for License View	The License View dashboard now provides you with a new section **Regions Deployed** that displays region name in which the New-Scale Security Operations Platform is deployed, such as US West, US East, Canada, Europe, Switzerland, Saudi Arabia, Singapore, Japan, and Australia.


Site Collectors 2.6


Feature	Description
Kafka Collector	The Kafka Collector is now available as part of Site Collectors to facilitate the collection of logs in any text format from your Kafka server.
Archive Windows Collector	The Archive Windows Collector is now available as part of Site Collectors to facilitate the collection of log events from the following types of archived log files: *.gz, *.tar, *.tar.gz, *.gzip, *.rar, *.7z.
Archive Linux Collector	The Archive Linux Collector is now available as part of Site Collectors to facilitate the collection of log events from archived log sources *.7z, *.arj, *.bzip2, *.cab, *.gzip, *.iso, *.lzh, *.rar, *.gz, *.tar, *.tar.gz, *.z, and *.zip.
Windows File Collector Recovery	You can now update an agent collector from the overview page to recover the collector if it does not collect logs while running. Previously, resolving Windows File Collector log ingestion issues required manual intervention.
Ubuntu 24.04 Support for OVA	Updated the existing Ubuntu 20.04 version to Ubuntu 24.04 for OVA, for better performance, security, and software support.


Threat Center



Feature	Description
Case ID Enhancement	To ensure all cases have a human-readable identifier to which you can refer, all cases are now automatically assigned a unique number as the case ID. You can view the case ID in the list of cases, in a case, emails sent from the case, and webhook notifications sent from the case. You can also search for a case using its case ID. Case IDs for existing cases remain the same and won't have new case IDs retroactively assigned to them.
Entity Attribute Enhancements	If a case or alert contains detections grouped by entity, you can now learn more about the entity and view the entity attributes directly in Threat Center: • In the case or alert **Overview** tab, under **Grouped By**, click **View Details** to view the entity attributes.  • In the list of cases or alerts, under the **GROUPED BY** column, click the entity to view the entity attributes. 
New Region Support for the UK	Support for Threat Center now extends to the UK region. You can now access and use Threat Center in the UK.



Threat Detection Management

Feature	Description
Correlation Rules Stopped and Testing Statuses	You can now better understand the state of a correlation rule with two new statuses: Stopped and Testing. The Stopped status indicates that the rule has triggered more than 50 times in five minutes and has automatically been disabled. The Testing status indicates that the rule is enabled in test mode and its outcomes are suppressed.  You can also filter correlation rules by the new statuses. 
Apply Analytics Rule Updates Without Training	To immediately apply changes to analytics rules, minimize disruptions to other Exabeam applications, ensure the analytics engine continues to run in real time, and ensure you don't use any of your entitled training days, you can now apply analytics rules changes without training the analytics engine. When you apply changes to enabled rules in bulk, you now have the option to select **Apply Changes Without Training**.

Feature	Description
Correlation Rules Select Outcomes Enhancement	When you create or edit a correlation rule, the step to **Select Outcomes** now clearly explains what happens when a rule triggers and the possible outcomes: • Designating outcomes for a correlation rule is optional. • An event is created every time a correlation rule triggers, even in test mode. If a correlation rule triggers and isn't in test mode, the activity type of the event is `rule-trigger`. If a correlation rule triggers in test mode, the activity type of the event is `rule-trigger-test`. • If you have a license that supports Threat Center, Threat Center may also create an alert when a correlation rule triggers, depending on whether the correlation rule is in test mode. If the correlation rule triggers and isn't in test mode, Threat Center creates an alert. if the correlation rule triggers and is in test mode, Threat Center doesn't create an alert.
Correlation Rule Details Severity Enhancement	When you view correlation rule details, you can now more quickly identify the correlation rule severity:  • The severity value is now positioned first in its section. • The severity is now color-coded according to its value: Critical, High, Medium, or Low. • If the correlation rule is assigned a static risk score, the risk score is displayed alongside the severity.


Feature	Description
Correlation Rule Evaluation Delay Explanation	When you create or edit a correlation rule, the step to configure a rule evaluation delay now clearly explains what correlation rule evaluation delay is and that correlation rules are delayed from evaluating events for seven minutes by default.  

Feature	Description
Correlation Rule Description Enhancements	You can now add more information to a correlation rule with descriptions. When you create or edit a correlation rule, you can now add a description about the correlation rule.  This description appears in the list of correlation rules and correlation rule details.   If you use a correlation rule template, the correlation rule template description is automatically reused as the description of your new correlation rule.

Feature	Description
Correlation Rule Triggered Value to Search Navigation	To view all events related to a correlation rule, you can now navigate to Search using a link next to the number times a rule has been triggered. The query automatically entered in Search is *rules.rule: "<rule name>"*. The link appears in the list of correlation rules:  The link also appears when you view the correlation rule details: 
Correlation Rule Email Notification Address Change	Email notifications sent as a correlation rule outcome are now sent from *no-reply@notify.exabeam.cloud*. To ensure any rules for filtering emails or creating third-party tickets work properly, ensure they use the new email address.
New Region Support for the UK	Support for Threat Detection Management now extends to the UK region. You can now access and use Threat Detection Management in the UK.

Resolved Issues

Search Resolved Issues

ID	Description
NGS-4653	Previously, when using the Search API to retrieve events, the **limit** parameter accepted a value of `-1`. This parameter now requires a positive integer to return events when the API runs. The default value is 3,000 events but higher values can be set. 

Site Collectors 2.6 Hot Fixes

Release Number	Hot Fix Description
2.6.6	Improved concurrency in Windows Event Log Collector to optimize overall performance.
2.6.5	Identified and resolved an issue to ensue the upgrade process correctly integrates the dynamic concurrency mechanism for Site Collectors.

Release Number	Hot Fix Description
2.6.4	Implemented a fix to ensure seamless functionality of multi-template configuration changes in the Windows Archive collector.
2.6.3	Resolved an issue that caused syslog agent collector rename failure.
2.6.2	Implemented enhancements for agent collectors.
2.6.1	Fixed an issue related to Windows management service.

Site Collector 2.6: Security Vulnerabilities Remediations

The Site Collectors 2.6 (February 2025) release includes remediated security vulnerabilities. For more information about Exabeam's commitment to remediating vulnerabilities for Site Collector, see the Vulnerability Remediation Policy.

There are no open known CVEs in any container image (Nifi). Toolkit has been deprecated and is no longer in use hence no security vulnerabilities update is available for that.

The following table lists the CVEs remediated for the Nifi container and their severity.

Critical	High	Medium	Low
Total: 0	Total: 0	Total: 4	Total: 1
–	–	• CVE-2025-0395 • CVE-2022-49043 • CVE-2024-53164 • CVE-2024-12254	CVE-2024-34459

Threat Center Resolved Issues

ID	Description
TC-3054	When you built a search using the **Assigned to my queue** quick search, the query used your role instead of your queue.

January 2025



The New-Scale Security Operations Platform includes the following addressed issues and new features for January 2025.


Attack Surface Insights

Feature	Description
Introducing Attack Surface Insights	Welcome to Attack Surface Insights, the directory for organizational resources in your environment, also known as entities. Attack Surface Insights is supported with a New-Scale Analytics or New-Scale Fusion license. To get started with Attack Surface Insights, view the Attack Surface Insights documentation.

Automation Management

Feature	Description
Automation Management Services	To automate complex workflows across multiple third-party security services or Exabeam features, you can now integrate Automation Management with services. For a service, create or import an instance you created in Postman, Swagger, or Python, then create actions for the service. Custom services are available with an add-on to a New-Scale Security Operations portfolio license.
Automation Management Actions	You can now interact with services you integrated with Automation Management using actions. You can use actions in advanced playbooks to call services and use the data returned to automate complex workflows.
Advanced Playbooks	You can now automate complex workflows using advanced playbooks. With the new experience, you can: • Visualize playbook logic and and easily manage steps of a complex workflow • Run actions, branches, and loops • Test the entire playbook or specific steps of the playbook • Save a playbooks as a draft and deploy it only when it's ready to run • View the playbook run history Pre-built playbooks have also been converted to advanced playbooks. Advanced playbooks are available with an add-on to a New-Scale Security Operations portfolio license.
No Trigger Playbooks	You can now create playbooks without triggers. These playbooks can only be manually run on a specific case or alert.

Feature	Description
Automation Management in Threat Center	Automation Management is now more deeply integrated with Threat Center. You can now: • Manually run a playbook or action on a specific case or alert.  • View a history of Automation Management tools you've run on a specific case or alert in dedicated experiences, separate from the case or alert history. In the **Overview** tab under **Automation**, view the five most recently run playbooks and actions:  Under the **Automation** tab, view the full history of all playbooks and actions run on a case or alert:

Feature	Description
	 The **Automation** tab is available with an add-on to a New-Scale Security Operations portfolio license.
Triggered Rule-Based Playbooks for Manual Case or Alert Updates	When you manually edit an alert or case or create a case, rule-based playbooks with the *Alert is modified*, *Case is modified*, and *Case is created* triggers run automatically.

Cloud Collectors

Feature	Description
Box Cloud Collector	The Box Cloud Collector is now available as part of Cloud Collectors to facilitate ingestion of user events and enterprise events from Box.
Cisco Meraki Cloud Collector	The Cisco Meraki Cloud Collector is now available as part of Cloud Collectors Early Access program to facilitate data collection from security events, alerts, configuration changes, and networks from Cisco Meraki APIs. The early access program offers you an opportunity to gain access to the latest cloud collectors before their official release. To participate, see Sign Up for the Early Access Program.
Recorded Future Cloud Collector	The Recorded Future Cloud Collector is now available as part of Cloud Collectors to facilitate ingestion of API Alerts.
ServiceNow Cloud Collector	The ServiceNow Cloud Collector is now available as part of Cloud Collectors Early Access program to facilitate data ingestion from the data sources Sys Audit Role, Sys Attachment, Change Request, Change Task, Sys Audit, Sys Event, Syslog Transaction, Report View, Event, Request, Task, Incident, Interaction, and Problem. The early access program offers you an opportunity to gain access to the latest cloud collectors before their official release. To participate, see Sign Up for the Early Access Program.

Context Management

Feature	Description
Support Context Tables for Device Data	Context Management now supports onboarding device data into the following types of context tables: • Custom and filtered context tables • Active Directory context tables • CrowdStrike context tables • Microsoft Entra ID context tables To facilitate onboarding device data to the Active Directory, CrowdStrike, and Microsoft Entra ID context tables, new tiles are available from the **Context Library** page in Context Management. Data in these device tables is available for use in the downstream Search application. It is not yet available for building dashboards or correlation rules. These device context tables are available with any New-Scale Security Operations or Exabeam Security Operations license. For more information, see Onboarding a Context Table and navigate to a specific context table section.
Support Pre-Built New-Scale Analytics Context Tables	Context Management now provides new pre-built New-Scale Analytics context tables. These context tables are used to support activities by the New-Scale Analytics engine and in the Attack Surface Insights application. These New-Scale Analytics context tables are currently available only for the New-Scale Analytics license. For more information about the new context tables, see Pre-Built New-Scale Analytics Context Tables in the *Context Management Guide*.

Correlation Rules

Feature	Description
Threat Center Outcomes Exclusions for Test Mode	To ensure you investigate and triage only real threats in Threat Center, correlation rules in test mode no longer create Threat Center cases or alerts. Events created from a triggered correlation rules in test mode have the activity type `rule-trigger-test`.

Dashboards

Feature	Description
Support for Pivoting to Search for Rule Triggered Events	To support pivoting into Search for rule-triggered events that are represented in dashboards and visualizations, the **Show Results in Search** option is now available for those events. Using this option allows you to click on a specific area or data point in a visualization and pivot from Dashboards to the Search application. There you can drill down further to investigate the rule-triggered event. For information, see View and Interact with a Dashboard or View and Interact with a Visualization in the *Dashboards Guide*.

Feature	Description
Updated Audit Log Support for Dashboards	Audit log coverage has been updated for dashboards in the New-Scale Security Operations Platform. For clarity, all activity types for dashboards have been renamed from `report` to `dashboard`. In addition, some new dashboard activities are now available in audit logs. The following types of dashboard events can be accessed via the Query Builder in Basic Search: • dashboard-create • dashboard-delete • dashboard-download • dashboard-export • dashboard-import • dashboard-modify • dashboard-publish • folder-create • folder-delete • folder-modify • scheduled_task-create • scheduled_task-delete • scheduled_task-modify For information, see Dashboards in Audit Logs in the *Dashboards Guide*.

Log Stream

Feature	Description
Parser Dependency Visibility	A new **Dependencies** column has been added to the **Log Stream Parsers Overview** tab to provide feedback about the quality and completeness of parsers that are ingesting detection events. For easy reference, this information is available as part of the parser list so there's no need to enter individual parsers to discover missing fields or detection rules. Currently, this feature is available only if you have the New-Scale Analytics license. For more information, see Parser Dependencies in the *Log Stream Guide*.
Manage Enrichment Rules	A new **Enrichments** tab has been added to Log Stream to provide access to view and manage enrichment rules. These enrichment rules are applied automatically as part of the process to enrich parsed event logs with contextual data. The new tab includes lifecycle information about the available enrichment rules, options to enable and disable specific rules, and the ability to view and edit the configuration details of each rule. You can also export rules and import new rules from other environments. Currently, this feature is available only if you have the New-Scale Analytics license. For more information, see Enrichments in the *Log Stream Guide*.
Filter and Route Events	A new **Event Filtering** tab has been added to Log Stream so that you can filter which events should be routed to the New-Scale Analytics detection engine or to the Attack Surface Insights application. This filtering allow you to fine tune which events or types of data are leveraged for detection and for Attack Surface Insights. The new tab provides information at a glance about the volume and types of event data the filters are routing, either to the New-Scale Analytics detection engine or to Attack Surface Insights. The tab also provides access to define and edit the filters. Currently, this feature is available only if you have the New-Scale Analytics license. For more information, see Event Filtering in the *Log Stream Guide*.



New-Scale Platform

Feature	Description
Introducing the New-Scale Security Operations Platform	**Introducing the New-Scale Security Operations Platform** Exabeam is renaming its security operations platform with the introduction of a New -Scale Analytics detection engine that provides a sophisticated approach to threat prioritization, AI-driven automations, and seamless integrations. The New-Scale analytics engine is built as a core component of the New-Scale Platform to ensure that you can swiftly address the highest-risk threats while minimizing manual tuning and false positives. In combination with Exabeam Nova, which provides natural language interactions, you can efficiently navigate the threat landscape and boost SOC productivity. If you are using Advanced Analytics, none of your current access or functionality will be reduced. You can choose to migrate to New-Scale Analytics at your own discretion. The following new product features are available for New-Scale Analytics: • **Attack Surface Insights** Attack Surface Insights is a directory for organizational resources in your environment, also known as entities; examples include users, endpoints, processes, files, servers, and applications. Attack Surface Insights identifies entities in incoming parsed logs, connects related attributes and contextual data to build comprehensive profiles on those entities, and links related entities. • **Threat Detection Management** Threat Detection Management is designed to streamline the way security teams handle detection rules, giving Security Engineers a unified interface for creating, testing, and tuning detections across all engines. By centralizing the management of detection content, this feature helps ensure that security analysts receive accurate, high-fidelity alerts with minimal noise.
New-Scale Security Operations Portfolio Licenses	To support the New-Scale Security Operations Platform, the following new license offerings are available: • **New-Scale SIEM** – A cloud-native, AI-powered solution that centralizes and normalizes log data, offering scalable, real-time threat detection, investigation, and response. • **New-Scale Analytics** – Enhances threat detection with machine learning, dynamic risk scoring, and behavioral analysis, improving the identification and response to credential-based attacks. • **New-Scale Fusion** – Integrates AI-driven analytics, automation, and cloud-native log management to provide advanced threat detection, investigation, and response for security operations. For more information about the licenses and for a table of features available by license type, see New-Scale Security Operations Portfolio Licenses in the *Platform Administration Guide*.

Outcomes Navigator

Feature	Description
UI Improvement	To reduce confusion and simplify the user interface, the **Recommendations** tab in Outcomes Navigator will only be displayed in environments that include Advanced Analytics. The data on the **Recommendations** tab is specific to the Advanced Analytics engine. This data is not relevant for customers with New-Scale licenses, which depend on the New-Scale Analytics Detection engine.

Search

Feature	Description
Support for Device Context Tables	You can now include device context tables in both Basic and Advanced search queries, allowing you to search for information about devices in your environment. Specifically, you can now search for results in the following types of device context tables: • Active Directory • CrowdStrike • Microsoft Entra ID For more information, see Context Tables in Search in the *Search Guide*.
Relative Time Range Option	A new **Relative** time range option is now available when building your Search queries. It provides a more precise and flexible approach to searching within a relative time range. The **Quick** time range options are still available but with the **Relative** option, you are not limited to fixed choices. You can specific a relative start and end date, such as 1 to 3 months ago. The relative options are translated into specific dates, which are displayed in the time range selector box, as shown below. 
Guardrails for Pipe Operator Use	New guardrails have been introduced for the use of the pipe operator in the Advanced search mode. They provide warnings to help prevent overuse or misuse of pipe operators in ways that can be slow and inefficient. When you write a query with a pipe operator that could more effectively be written with an AND operator or a WHERE clause, a warning is displayed below the search bar.  For more information, see the **Pipe Operator** section of Query Using Advanced Query Language Operators in the *Search Guide*.

Feature	Description
Timeline View of Search Results	Exabeam introduces a new Timeline view of search results that brings the investigational timeline experience into the Search application. Analysts and threat hunters can use the Timeline view as a starting point for investigating risky or anomalous events while still leveraging the granular filtering capabilities of the Search application. The Timeline view is designed specifically with this task in mind. It's visually organized so that detection events are easy to spot and investigate. You can drill into the detections or the associated events to find detailed information and data insights. For more information, see Timeline View of Search Results in the *Search Guide*. This feature is currently available only if you have one of the New-Scale licenses. For more information see New-Scale Security Operations Portfolio Licenses.
Rule Details Panel	A new **Rule Details** panel is available for viewing detailed rule information when search results return detection events. This new panel facilitates interactions with events that may represent a security threat or anomalous behavior. The panel includes a raw log message, a full list of parsed fields, and an expandable list of any rules associated with the detection event. For more information see Rule Details in the *Search Guide*. This feature is currently available only if you have one of the New-Scale licenses. For more information see New-Scale Security Operations Portfolio Licenses.
Data Insights	A new **Insights** tab is available in the **Event Details** panel for any search results that include parsed user or device information. The Insights tab provides a quick, easy way to drill into information related to events in your results. It lets you visualize what else is going on around a selected event, within specific time ranges. For example, if an event shows that a user triggered an alert, you can investigate which other assets the user has accessed in the past few days, which countries the user logged in from, or what files the user accessed. For more information, see Data Insights in the *Search Guide*. This feature is currently available only if you have one of the New-Scale licenses. For more information see New-Scale Security Operations Portfolio Licenses.
Entity Searching	A new **Entities** tab has been added to the pre-built search lists in the **Basic Search** window. From the new tab you can search user and entity accounts using more of the enriched data than is available by searching with common event fields. For more information, see Pre-Built Basic Search Lists in the *Search Guide*. This feature is currently available only if you have one of the New-Scale licenses. For more information see New-Scale Security Operations Portfolio Licenses.


Service Health and Consumption



Feature	Description
Enhanced User Experience for License View	The License View now offers an improved user experience to help you seamlessly use the charts and filters.



Site Collectors 2.5


Feature	Description
Multi-template support for Windows File Collector and Linux File Collector	Site Collector now offers multi-template support for the Windows File Collector and the Linux File Collector. You can now apply multiple templates and specify different log conditions for each of the templates.
Splunk fetch interval	The Splunk collector now provides more options for the time interval within which the collector fetches logs.
Support Package Generation Command for Collectors	The Windows Event Log Collector, Windows File Collector and Windows Archive Collector now provide a command on the user interface to share the support package with the Exabeam support team while configuring a collector instance. By running the support package command using PowerShell, users can share the support package with the support team for troubleshooting and remediation of issues if any.
Ubuntu 24.04 support by Site Collector	Site Collector now supports the Ubuntu 24.04 operating system for Site Collection installation.
Early Access Feature	
SSL Connection for the Kafka Collector	In addition to the existing SASL protocol, the Kafka collector now offers an option to connect securely via SSL protocol and add custom security certificates. This feature is now available as part of Site Collectors Early Access program.

Threat Center

Feature	Description
Analytics Rules Detections	If you have a New-Scale Security Operations Portfolio license, you can now investigate triggered analytics rules in Threat Center as detections. 
Risk Score Calculation with Behavioral Analytics	With Threat Detection Management on the New-Scale Security Operations platform, risk score calculations for alerts and cases are now based on behavioral analytics insights and more accurately reflect real risk. The analytics engine assigns detections a rarity score depending on how often Threat Detection Management rules trigger in your environment. Case and alert risk scores are calculated using a combination of detection rarity scores and certain confidence factors.

Feature	Description
Automation Management in Threat Center	Threat Center is now more deeply integrated with Automation Management. You can now: • Manually run a playbook or action on a specific case or alert.  • View a history of Automation Management tools you've run on a specific case or alert in dedicated experiences, separate from the case or alert history. In the **Overview** tab under **Automation**, view the five most recently run playbooks and actions:  Under the **Automation** tab, view the full history of all playbooks and actions run on a case or alert:

Feature	Description
	 The **Automation** tab is available with an add-on to a New-Scale Security Operations portfolio license.
Manual Case Creation	You can now manually create a case from scratch, without associating it with an alert. 
Copilot Case Names	You can now better understand what a case represents and quickly decide which case to work on with AI-generated case names. Only cases converted from an alert have AI-generated case names.
Enhanced Entity Display	Entities are now displayed more intuitively. User entities are shown as their full name or email address. If neither information is available, user entities are shown as their username. Device entities are shown as their host name.
Device Entity Details	To better understand a device entity in the context of a case or alert, you can now view entity device details from Attack Surface Insights directly in Threat Center.

Feature	Description
User Entity Search	To focus your investigation on a specific user entity, you can now search for cases and alerts whose detections are grouped by a specific user entity. When you build a search, you can now navigate to the **Entities** tab to search for a user entity by their full name or known account, like username or email. 
Scope Column	When you view the list of cases and alerts, you can now quickly identify the number of objects associated with a case or alert with a new **SCOPE** column.  Under the **SCOPE** column, you can view the number of: • Rules • Users • Endpoints • MITRE ATT&CK® tactics and techniques • Use cases To view the definition of an object, hover over the object count. 
Open Investigation Timeline Enhancements	To investigate the most pertinent events related to a case or alert in Search, you can now click **Open Investigation Timeline** in a case or alert to automatically navigate to events in Search that have an assigned risk score.

Threat Detection Management

Feature	Description
Introducing Threat Detection Management	Welcome to Threat Detection Management, the the hub on New-Scale Security Operations Platform for the rules you use to detect threats. It centralizes all rules, including both correlation and analytics, and both pre-built and custom, so you can ensure you're surfacing what's important to your organization in one place. Threat Detection Management is supported with a New-Scale SIEM, New-Scale Analytics, or New-Scale Fusion license. To get started with Threat Detection Management, view the Threat Detection Management documentation.
Threat Center Outcomes Exclusions for Test Mode	To ensure you investigate and triage only real threats in Threat Center, correlation rules in test mode no longer create Threat Center cases or alerts. Events created from a triggered correlation rules in test mode have the activity type `rule-trigger-test`.

Resolved Issues

Site Collectors 2.5 Hot Fixes

Release	Hot Fix Description
2.5.8	Resolved an issue in which messages from the syslog collector instances at high EPS lacked a delimiter, resulting in parsing issues. This issue was related to the static metadata header which is only enabled for the New-Scale Security Operations Platform customers. To prevent parsing issues and take advantage of the static metadata header for cost reduction and improved collector efficiency, upgrade to the latest Site Collectors version.
2.5.3	Resolved an issue related to the minifi attribute for the Windows File Collector.
2.5.2	Resolved an issue related to the minifi attribute for the Windows File Collector.
2.5.1	0.9.1 – Fixed an issue with restoration of the Site Collector during an upgrade failure. 0.9.2 – Implemented a fix to ensure appropriate deletion of older controller services. 0.9.3 – Implemented updates for static metadata header. 0.9.4 – Implemented updates for static metadata header.

Site Collectors 2.5 CVE Remediations

The Site Collectors 2.5 (January 2025) release includes remediated security vulnerabilities. For more information about Exabeam's commitment to remediating vulnerabilities for Site Collector, see the Vulnerability Remediation Policy.

There are no open known CVEs in any container image (Nifi). Toolkit has been deprecated and is no longer in use hence no security vulnerabilities update is available for that.

The following table lists the CVEs remediated for the Nifi container and their severity.

Critical	High	Medium	Low
Total: 0	Total: 0	Total: 3	Total: 5

Critical	High	Medium	Low
		• CVE-2024-6763 • CVE-2024-9287 • CVE-2024-12798	• CVE-2024-9681 • CVE-2024-11053 • CVE-2024-12801 • CVE-2024-37891 • CVE-2024-56512

Known Issues

The New-Scale Security Operations Platform includes the following known issues.

Attack Surface Insights

There are no known issues in Attack Surface Insights

Automation Management

ID	Description
ENG-71726	When you select an action in an advanced playbook, the action details become unresponsive and fail to load. To resolve this issue: 1. Edit the action and make a minor change in the code editor; for example, add a space. 2. Deploy the action. 3. Reopen the advanced playbook and ensure the action loads correctly.

Cloud Collectors

There are no known issues in Cloud Collectors.


Context Management

There are no known issues in Context Mangement.

Correlation Rules

ID	Description
CRB-2368	If you enter a description containing multiple lines, Case Manager incidents created using Correlation Rules may contain \n escape sequences in the incident description because \n represents "end of line".
CRB-2767	If a sequence detects the absence of a specific field value and you use the Group by Field functionality on that field, the correlation rule incorrectly triggers on the absence of grouped fields for which the sequence doesn't query. For example, if you use the Group by Field functionality on the *host* field, and the sequence queries for host:"2.2.2.2", the rule triggers on the absence of host:"2.2.2.2" but also on the absence of host:"1.1.1.1" and host:"3.3.3.3".

Dashboards

ID	Description
NGR-595	Filters applying the **is in the last** operator to the **Approx Log Time** field yield inaccurate results when the time unit is equal to our greater than **hours**. As a workaround to this issue, express time lengths in **seconds** or **minutes**. 

Log Sources

There are no known issues for Log Sources.

Log Stream

There are no known issues in Log Stream.

New-Scale Platform

There are no known issues in New-Scale Platform.

Outcomes Navigator


ID	Description
NGCM-309	Outcomes Navigator doesn't properly calculate coverage for Advanced Analytics rules whose rule expressions include session-end or sequence-end events. Affected Advanced Analytics rules include: • A-AL-DhU-count • A-DNS-ABSum-A • A-DNS-AQCount-A • A-DNS-AQNXCount-A • A-DNS-OBSum-A • A-DNS-OQNXCount-A • A-DNS-ZBSum-A • A-EPA-UP-CENUM • A-EPA-UP-HENUM • A-FLDh-Count-A • A-FLDz-Count-A • A-FLSh-Count-A • A-HBytes-Failed-Outbound • A-HBytes-Failed-Outbound-IOT • A-HBytes-Outbound • A-HBytes-Outbound-IOT • AL-GHcount • AL-OHcount • AL-UHcount • AL-UHcount-L • AL-UHcount-M • AL-UHcount-S • A-NETFLOW-dZBytes-Inbound • A-NETFLOW-sH22Bytes-Outbound • A-NETFLOW-sH23Bytes-Outbound • A-NETFLOW-sH25Bytes-Outbound • A-NETFLOW-sH443Bytes-Outbound • A-NETFLOW-sH53Bytes-Outbound • A-NETFLOW-sH80Bytes-Outbound • A-NETFLOW-sHFTPBytes-Outbound • A-NEW-ASSET • A-NEW-ASSET-src • APP-UAgC-F • APP-UFL-COUNT • APP-UOb-Number

ID	Description
	• A-SEQ-UH-16-L • A-SEQ-UH-16-M • A-SEQ-UH-16-S • AS-PV-GSize-A • AS-PV-OSize-A • AS-PV-PCWoL • AS-PV-USCOUNT-A • AS-PV-USize-A • AUTH-F-COUNT • A-WEB-Count-A • A-WEB-DLP-A • A-WEB-GETBytes-In • AWS-DistinctRoleAssumptionsCount-User-A • AWS-PermEnumCount-User-A • A-ZBytes-Outbound • A-ZBytes-Outbound-IOT • B-CS-Bucket-Bytes-A • DB-FL-COUNT • DB-OPCOUNT • DB-OPCOUNT-NEW • DB-OPCOUNT-TOTAL • DB-URSum • DB-URSum-New • DC08d-new • DC14g-new • DC17d • DC17e • DC17f • DC17j • DC17j-new • DC17k • DC17l • DLP-BSum • DLP-GPCOUNT • DLP-UPCOUNT • DS-Count • DS-GCount • DS-UCount • EM-BSum • EM-BSum-in


ID	Description
	• EM-BSum-personal • EM-DNum • EM-FNum • EM-FNum-in • EM-FNum-personal • EM-InB-Perm-A • EPA-GSequenceSize-PS • EPA-HI-COUNT • EPA-OSequenceSize-PS • EPA-UP-CENUM • EPA-UP-HENUM • EPA-USequenceSize-PS • EPA-USequenceSize-WC • FA-GDBytes-A • FA-ODBytes-A • FA-UDBytes-A • FA-UFCOUNT • FA-UFCOUNT-DELETE • FA-UH-DELETE • FA-UR-A • FA-URCOUNT-A • FA-UWCOUNT-A • FDS-Count • FDS-GCount • FDS-UCount • GCP-DistinctOperationCount-User-A • GCP-StorageGetCount-User-A • GCP-StorageListCount-User-A • GCP-UnauthorizedOperationCount-User-A • KL-GSnCOUNT-A • KL-USnCOUNT-A • MFA-Failure-Count-A • PA-COUNT • PA-NoIT • Powershell-Advanced-F • Powershell-Invoke-Count • Powershell-Web-A • PR-BSum • PR-NPSum • RA-GHcount

ID	Description
	• RA-OHcount • RA-UHcount • RA-UHcount-L • RA-UHcount-M • RA-UHcount-S • SA-US-AA • SA-US-AU • SEQ-UH-16 • SEQ-UH-16-L • SEQ-UH-16-M • SEQ-UH-16-S • SEQ-UH-17 • SEQ-UH-18 • SERVICE-ACCOUNT • UW-BSum • UW-FNum • VPN-BSum • WEB-GBytes-A-FS • WEB-GBytes-A-JS • WEB-GBytesSum-EWD • WEB-GSequenceSize-JS • WEB-OBytes-A-FS • WEB-OBytesSum-EWD • WEB-OSequenceSize-JS • WEB-RCCount • WEB-UBlock • WEB-UBytes-A-JS • WEB-UBytesSum-EWD • WEB-UBytesSum-In-FS • WEB-UBytesSum-In-FS-PU • WEB-UBytesSum-Out-FS • WEB-UDLP-A • WEB-UDLP-A-FS • WEB-UDLP-A-JS • WEB-UGETDLP-A • WEB-URank-DLP • WEB-USequenceSize • WEB-USequenceSize-Denied • WEB-USequenceSize-JS • WPA-UACount

Search

ID	Description
ENG-81372	Currently, the option to select a sort order when exporting search results is not available. Exported search results are unordered.
ENG-75846	When using Exabeam Query Language (EQL) in advance search mode, usage of a `NOT` operator without an accompanying `OR` or `AND` operator does not result in an error, despite this syntax being invalid and not officially supported. For example, although the following EQL syntax is invalid, it is unintentionally successful: `subject:"app" NOT vendor:"Exabeam"`  When this issue is resolved, searches that use this invalid syntax will stop working. Therefore, it is highly recommended to always use the explicit operators: `AND NOT` or `OR NOT`
NGS-4325	Occasionally, when using advanced query language operators in Search to generate results in the Table view, the generated table is displayed with a misalignment. The header row is displayed to the left of the column data. This issue appears to be intermittent and has not been reliably reproduced for analysis and resolution. If you encounter this table misalignment issue, and can provide *consistent* steps to reproduce it, please contact your Exabeam account manager.
NGS-3376	Some users are experiencing the interface freezing and becoming unresponsive if they have their "*Rows per view*" setting set to 100.
NGS-1104	When using Safari, the field summary initial event count is inconsistent.

Service Health and Consumption

ID	Description
CC-1350	Legacy cloud collector names are incorrectly displaying as *unknown* and *unspecified* on consumption details charts. Example: 
N/A	Service Health and Consumption dashboards are only available at this time for customers with Exabeam Security Operations Portfolio Licenses

Site Collectors

Issue ID	Description
NGSCL-1517	Site Collector installation fails on RHEL 9 because of lack of network support for TLS v1.3 more secured ciphers, without a clear warning.
NGSCL-1558	A Site Collector instance occasionally produces an `uninstallation failed` error and shows the status as *Uninstalling*.
NGSCL-2447	The search filters on the Site Collectors **Overview** page are case sensitive. Currently, search results are not displayed if you do not match the case with the collector instance name for the key words that you use for searching for collector instances.
NGSCL-2569	While editing a Site Collector instance, in **Advanced Settings**, the **Timezone** field after initial configuration displays the first city name of the time zone such as UTC/PST on the user interface instead of the exact city name which you selected.
NGSCL-3674	While upgrading a Site Collector instance to its latest version, the Windows Event Log agent collector pulls duplicate logs when historic log fetch is enabled.
NGSCL-3961	After upgrading a Site Collector instance from version 1.x to 2.x, the server side collectors Splunk, Oracle, MySQL, MSSQL, QRadar, and EStreamer start to fetch historical data based on an old start fetch timestamp. **Workaround** – If you are using Site Collector version 1.x with the server side collectors installed, and want to upgrade to 2.x version, ensure that you update the *Start Fetch Date* for the Splunk collector and *Iterator column initial value* for Oracle, MSSQL, and MySQL collectors to the current time or to the value based on the iterator you defined. Alternatively, you can choose to wait to upgrade the Site Collector instance from 1.x to 2.x version until this issue is fixed.

Threat Center

There are no known issues in Threat Center.

Threat Detection Management

ID	Description
ENG-78578	Threat Detection Management incorrectly marks all analytics rules as having pending updates even though they've not been updated. For the actual list of analytics rule updates, refer to the Threat Detection Management September release notes.