

Ch 4. Introduction to Recursion

Recursive functions

- A recursive function
 - A function that calls itself, either directly, or indirectly (through another function).

- Example: factorial

$$\text{Let } f(n) = n! = n * (n - 1) * (n - 2) * \dots * 1$$

- A recursive definition of the factorial function

$$f(0) = 0! = 1$$

$$f(1) = 1! = 1$$

$$f(n) = n! = n * (n - 1)! = n * f(n - 1)$$

Iterative Function Factorial

```
int main()
{
    int n;
    cout << "Enter a positive Integer: ";
    cin >> n;
    cout << n << "! = " << f( n ) << endl;
}

int f( int n )
{
    int result = 1;
    for( int i = 2; i <= n; i++ )
        result *= i;
    return result;
}
```

$$f(n) = n! = n * (n - 1) * (n - 2) * \dots * 1$$

Iterative Function Factorial

```
int main()
{
    int n;
    cout << "Enter a positive Integer: ";
    cin >> n;
    cout << n << "! = " << f( n ) << endl;
}

int f( int n )
{
    int result = 1;
    for( int i = n; i >= 2; i-- )
        result *= i;
    return result;
}
```

$$f(n) = n! = n * (n - 1) * (n - 2) * \dots * 1$$

Recursive Function Factorial

```
int main()
{
    int n;
    cout << "Enter a positive Integer: ";
    cin >> n;
    cout << n << "! = " << f( n ) << endl;
}

int f( int n )
{
    if( n <= 1 )
        return 1;
    else
        return          ;
}
```

$$f(n) = 1 \quad \text{for } n \leq 1 \quad (n! = 1)$$

$$f(n) = n * f(n - 1) \quad \text{for } n > 1 \quad (n! = n * (n - 1)!)$$

Recursive Function Factorial

```
int main()
{
    int n;
    cout << "Enter a positive Integer: ";
    cin >> n;
    cout << n << "! = " << f( n ) << endl;
}

int f( int n )
{
    if( n <= 1 )
        return 1;
    else
        return n * f( n - 1 );
}
```

$$f(n) = 1 \quad \text{for } n \leq 1 \quad (n! = 1)$$

$$f(n) = n * f(n - 1) \quad \text{for } n > 1 \quad (n! = n * (n - 1)!)$$

```
int main()
{
    int n;
    cout << "Enter a positive Integer: ";
    cin >> n;
    cout << n << "! = " << f( n ) << endl;
}
```

1

```
int f( int n )
{
    if( n <= 1 ) return 1;
    else
        return n * f( n - 1 );
}
```

```

int main()
{
    int n;
    cout << "Enter a positive Integer: ";
    cin >> n;
    cout << n << "! = " << f( n ) << endl;
}

```

2

```

int f( int n )
{
    if( n <= 1 ) return 1;
    else
        return n * f( n - 1 );
}

```

1

```

int main()
{
    int n;
    cout << "Enter a positive Integer: ";
    cin >> n;
    cout << n << "! = " << f( n ) << endl;
}

```

3

```

int f( int n )
{
    if( n <= 1 ) return 1;
    else
        return n * f( n - 1 );
}

```

2

```

int main()
{
    int n;
    cout << "Enter a positive Integer: ";
    cin >> n;
    cout << n << "! = " << f( n ) << endl;
}

```

4

```

int f( int n )
{
    if( n <= 1 ) return 1;
    else
        return n * f( n - 1 );
}

```

3

```

int main()
{
    int n;
    cout << "Enter a positive Integer: ";
    cin >> n;
    cout << n << "! = " << f( n ) << endl;
}

```

5

```

int f( int n )
{
    if( n <= 1 ) return 1;
    else
        return n * f( n - 1 );
}

```

4

```
#include <iostream>
using namespace std;

int f( int n );

int main()
{
    int n = 4;
    cout << f( n ) << endl;
}

int f( int n )
{
    if( n <= 1 )
        return 1;
    else
        return n * f( n - 1 );
}
```

```
int f( int 4n ) {  
    if( n <= 1 ) return 1;  
    else  
        return n * f( n - 1 ); }
```

```
int f( int n ) {  
    if( n <= 1 ) return 1;  
    else  
        return n * f( n - 1 ); }
```

```
int f( int n ) {  
    if( n <= 1 ) return 1;  
    else  
        return n * f( n - 1 ); }
```

```
int f( int n ) {  
    if( n <= 1 ) return 1;  
    else  
        return n * f( n - 1 ); }
```

```
int f( int 4n ) {  
    if( n <= 1 ) return 1;  
    else  
        return n * f( n - 1 ); }  
3
```

```
int f( int n ) {  
    if( n <= 1 ) return 1;  
    else  
        return n * f( n - 1 ); }
```

```
int f( int n ) {  
    if( n <= 1 ) return 1;  
    else  
        return n * f( n - 1 ); }
```

```
int f( int n ) {  
    if( n <= 1 ) return 1;  
    else  
        return n * f( n - 1 ); }
```

```
int f( int4 n ) {  
    if( n <= 1 ) return 1;  
    else  
        return n * f( n - 1 ); }  
3
```

```
int f( int3 n ) {  
    if( n <= 1 ) return 1;  
    else  
        return n * f( n - 1 ); }  
2
```

```
int f( int2 n ) {  
    if( n <= 1 ) return 1;  
    else  
        return n * f( n - 1 ); }
```

```
int f( int n ) {  
    if( n <= 1 ) return 1;  
    else  
        return n * f( n - 1 ); }
```

```
int f( int4 n ) {  
    if( n <= 1 ) return 1;  
    else  
        return n * f( n - 1 ); }  
3
```

```
int f( int3 n ) {  
    if( n <= 1 ) return 1;  
    else  
        return n * f( n - 1 ); }  
2
```

```
int f( int2 n ) {  
    if( n <= 1 ) return 1;  
    else  
        return n * f( n - 1 ); }  
1
```

```
int f( int1 n ) {  
    if( n <= 1 ) return 1;  
    else  
        return n * f( n - 1 ); }
```

```
int f( int4 n ) {  
    if( n <= 1 ) return 1;  
    else  
        return n * f( n - 1 ); }  
3
```

```
int f( int3 n ) {  
    if( n <= 1 ) return 1;  
    else  
        return n * f( n - 1 ); }  
2
```

```
int f( int2 n ) {  
    if( n <= 1 ) return 1;  
    else  
        return n * f( n - 1 ); }  
1
```

```
int f( int1 n ) {  
    if( n <= 1 ) return 1;  
    else  
        return n * f( n - 1 ); }  
1
```

```

int f( int4 n ) {
    if( n <= 1 ) return 1;
    else
        return n * f( n - 1 ); }
3

```

```

int f( int3 n ) {
    if( n <= 1 ) return 1;
    else
        return n * f( n - 1 ); }
2

```

```

int f( int2 n ) {
    if( n <= 1 ) return 1;
    else
        return n *2 f( n - 1 ); }
1 1

```

```

int f( int1 n ) {
    if( n <= 1 ) return 1;
    else
        return n * f( n - 1 ); }
1

```

```

int f( int 4n ) {
    if( n <= 1 ) return 1;
    else
        return n * f( n - 1 ); }
3

```

```

int f( int 3n ) {
    if( n <= 1 ) return 1;
    else
        return n * 6f( n - 1 ); }
2 2

```

```

int f( int 2n ) {
    if( n <= 1 ) return 1;
    else
        return n * 2f( n - 1 ); }
1 1

```

```

int f( int 1n ) {
    if( n <= 1 ) return 1;
    else
        return n * f( n - 1 ); }
1

```

```

int f( int4 n ) {
    if( n <= 1 ) return 1;
    else
        return n24 * f( n - 1 ); }
           6      3

```

```

int f( int3 n ) {
    if( n <= 1 ) return 1;
    else
        return n6 * f( n - 1 ); }
           2      2

```

```

int f( int2 n ) {
    if( n <= 1 ) return 1;
    else
        return n2 * f( n - 1 ); }
           1      1

```

```

int f( int1 n ) {
    if( n <= 1 ) return 1;
    else
        return n * f( n - 1 ); }

```



```
int main()
{
    int n = 4;
    cout << f( n ) << endl;
}
```

register

n 4 0012FF7C

```
int f( int n )
{
    if( n <= 1 ) return 1;
    else return n * f( n - 1 );
}
```

```
int f( int n )
{
    if( n <= 1 ) return 1;
    else return n * f( n - 1 );
}
```

```
int f( int n )
{
    if( n <= 1 ) return 1;
    else return n * f( n - 1 );
}
```

```
int f( int n )
{
    if( n <= 1 ) return 1;
    else return n * f( n - 1 );
}
```

```
int main()
{
    int n = 4;
    cout << f( n ) << endl;
}
```

register

n 4 0012FF7C

```
int f( int n )
{
    if( n <= 1 ) return 1;
    else return n * f( n - 1 );
}
```

n 4 0012FF20

```
int f( int n )
{
    if( n <= 1 ) return 1;
    else return n * f( n - 1 );
}
```

```
int f( int n )
{
    if( n <= 1 ) return 1;
    else return n * f( n - 1 );
}
```

```
int f( int n )
{
    if( n <= 1 ) return 1;
    else return n * f( n - 1 );
}
```

```
int main()
{
    int n = 4;
    cout << f( n ) << endl;
}
```

register

n 4 0012FF7C

```
int f( int n )
{
    if( n <= 1 ) return 1;
    else return n * f( n - 1 );
}
```

n 4 0012FF20

```
int f( int n )
{
    if( n <= 1 ) return 1;
    else return n * f( n - 1 );
}
```

n 3 0012FEC8

```
int f( int n )
{
    if( n <= 1 ) return 1;
    else return n * f( n - 1 );
}
```

```
int f( int n )
{
    if( n <= 1 ) return 1;
    else return n * f( n - 1 );
}
```

```
int main()
{
    int n = 4;
    cout << f( n ) << endl;
}
```

register

n 4 0012FF7C

```
int f( int n )
{
    if( n <= 1 ) return 1;
    else return n * f( n - 1 );
}
```

n 4 0012FF20

```
int f( int n )
{
    if( n <= 1 ) return 1;
    else return n * f( n - 1 );
}
```

n 3 0012FEC8

```
int f( int n )
{
    if( n <= 1 ) return 1;
    else return n * f( n - 1 );
}
```

n 2 0012FE70

```
int f( int n )
{
    if( n <= 1 ) return 1;
    else return n * f( n - 1 );
}
```

```
int main()
{
    int n = 4;
    cout << f( n ) << endl;
}
```

register

n 4 0012FF7C

```
int f( int n )
{
    if( n <= 1 ) return 1;
    else return n * f( n - 1 );
}
```

n 4 0012FF20

```
int f( int n )
{
    if( n <= 1 ) return 1;
    else return n * f( n - 1 );
}
```

n 3 0012FEC8

```
int f( int n )
{
    if( n <= 1 ) return 1;
    else return n * f( n - 1 );
}
```

n 2 0012FE70

```
int f( int n )
{
    if( n <= 1 ) return 1;
    else return n * f( n - 1 );
}
```

n 1 0012FE18

```
int main()
{
    int n = 4;
    cout << f( n ) << endl;
}
```

register

1

n

4

 0012FF7C

```
int f( int n )
{
    if( n <= 1 ) return 1;
    else return n * f( n - 1 );
}
```

n

4

 0012FF20

```
int f( int n )
{
    if( n <= 1 ) return 1;
    else return n * f( n - 1 );
}
```

n

3

 0012FEC8

```
int f( int n )
{
    if( n <= 1 ) return 1;
    else return n * f( n - 1 );
}
```

n

2

 0012FE70

```
int f( int n )
{
    if( n <= 1 ) return 1;
    else return n * f( n - 1 );
}
```

```
int main()
{
    int n = 4;
    cout << f( n ) << endl;
}
```

register 2

n 4 0012FF7C

```
int f( int n )
{
    if( n <= 1 ) return 1;
    else return n * f( n - 1 );
}
```

n 4 0012FF20

```
int f( int n )
{
    if( n <= 1 ) return 1;
    else return n * f( n - 1 );
}
```

n 3 0012FEC8

```
int f( int n )
{
    if( n <= 1 ) return 1;
    else return n * f( n - 1 );
}
```

```
int f( int n )
{
    if( n <= 1 ) return 1;
    else return n * f( n - 1 );
}
```

```
int main()
{
    int n = 4;
    cout << f( n ) << endl;
}
```

register

6

n

4

 0012FF7C

```
int f( int n )
{
    if( n <= 1 ) return 1;
    else return n * f( n - 1 );
}
```

n

4

 0012FF20

```
int f( int n )
{
    if( n <= 1 ) return 1;
    else return n * f( n - 1 );
}
```

```
int f( int n )
{
    if( n <= 1 ) return 1;
    else return n * f( n - 1 );
}
```

```
int f( int n )
{
    if( n <= 1 ) return 1;
    else return n * f( n - 1 );
}
```

```
int main()
{
    int n = 4;
    cout << f( n ) << endl;
}
```

register

24

n

4

 0012FF7C

```
int f( int n )
{
    if( n <= 1 ) return 1;
    else return n * f( n - 1 );
}
```

```
int f( int n )
{
    if( n <= 1 ) return 1;
    else return n * f( n - 1 );
}
```

```
int f( int n )
{
    if( n <= 1 ) return 1;
    else return n * f( n - 1 );
}
```

```
int f( int n )
{
    if( n <= 1 ) return 1;
    else return n * f( n - 1 );
}
```



```
#include <iostream>
#include <iomanip>
using namespace std;
```

```
int f( int );
```

```
int main()
{
    int n = 5;
    cout << f( n ) << endl;
}
```

```
int f( int n )
{
    if( n <= 1 )
        return 1;
    else
        return n * f( n - 1 );
}
```

register

n 0012FDC8

```
#include <iostream>
#include <iomanip>
using namespace std;
```

```
int f( int );
```

```
int main()
{
    int n = 5;
    cout << f( n ) << endl;
}
```

```
int f( int n )
{
    if( n <= 1 )
        return 1;
    else
        return n * f( n - 1 );
}
```

register



n	5	0012FD78
	⋮	
n	5	0012FDC8

```
#include <iostream>
#include <iomanip>
using namespace std;
```

```
int f( int );
```

```
int main()
{
    int n = 5;
    cout << f( n ) << endl;
}
```

```
int f( int n )
{
    if( n <= 1 )
        return 1;
    else
        return n * f( n - 1 );
}
```

register



n	4	0012FD20
	⋮	
n	5	0012FD78
	⋮	
n	5	0012FDC8

```
#include <iostream>
#include <iomanip>
using namespace std;
```

```
int f( int );
```

```
int main()
{
    int n = 5;
    cout << f( n ) << endl;
}
```

```
int f( int n )
{
    if( n <= 1 )
        return 1;
    else
        return n * f( n - 1 );
}
```

register

n	3	0012FCC8
	⋮	
n	4	0012FD20
	⋮	
n	5	0012FD78
	⋮	
n	5	0012FDC8

```
#include <iostream>
#include <iomanip>
using namespace std;
```

```
int f( int );
```

```
int main()
{
    int n = 5;
    cout << f( n ) << endl;
}
```

```
int f( int n )
{
    if( n <= 1 )
        return 1;
    else
        return n * f( n - 1 );
}
```

register

n	2	0012FC70
	⋮	
n	3	0012FCC8
	⋮	
n	4	0012FD20
	⋮	
n	5	0012FD78
	⋮	
n	5	0012FDC8

```
#include <iostream>
#include <iomanip>
using namespace std;
```

```
int f( int );
```

```
int main()
{
    int n = 5;
    cout << f( n ) << endl;
}
```

```
int f( int n )
{
    if( n <= 1 )
        return 1;
    else
        return n * f( n - 1 );
}
```

register



n	1	0012FC18
	⋮	
n	2	0012FC70
	⋮	
n	3	0012FCC8
	⋮	
n	4	0012FD20
	⋮	
n	5	0012FD78
	⋮	
n	5	0012FDC8

```
#include <iostream>
#include <iomanip>
using namespace std;
```

```
int f( int );
```

```
int main()
{
    int n = 5;
    cout << f( n ) << endl;
}
```

```
int f( int n )
{
    if( n <= 1 )
        return 1;
    else
        return n * f( n - 1 );
}
```

register

1

n	2	0012FC70
	⋮	
n	3	0012FCC8
	⋮	
n	4	0012FD20
	⋮	
n	5	0012FD78
	⋮	
n	5	0012FDC8

```
#include <iostream>
#include <iomanip>
using namespace std;
```

```
int f( int );
```

```
int main()
{
    int n = 5;
    cout << f( n ) << endl;
}
```

```
int f( int n )
{
    if( n <= 1 )
        return 1;
    else
        return n * f( n - 1 );
}
```

register

2

n	3	0012FCC8
	⋮	
n	4	0012FD20
	⋮	
n	5	0012FD78
	⋮	
n	5	0012FDC8

```
#include <iostream>
#include <iomanip>
using namespace std;
```

```
int f( int );
```

```
int main()
{
    int n = 5;
    cout << f( n ) << endl;
}
```

```
int f( int n )
{
    if( n <= 1 )
        return 1;
    else
        return n * f( n - 1 );
}
```

register

6

n	4	0012FD20
	⋮	
n	5	0012FD78
	⋮	
n	5	0012FDC8

```
#include <iostream>
#include <iomanip>
using namespace std;
```

```
int f( int );
```

```
int main()
{
    int n = 5;
    cout << f( n ) << endl;
}
```

```
int f( int n )
{
    if( n <= 1 )
        return 1;
    else
        return n * f( n - 1 );
}
```

register

24

n	5	0012FD78
	⋮	
n	5	0012FDC8

```
#include <iostream>
#include <iomanip>
using namespace std;
```

```
int f( int );
```

```
int main()
{
    int n = 5;
    cout << f( n ) << endl;
}
```

```
int f( int n )
{
    if( n <= 1 )
        return 1;
    else
        return n * f( n - 1 );
}
```

register

120

n

5

 0012FDC8

Recursive Fibonacci Function

Let $f(n)$ be the n -th fibonacci number

$$f(n) = n \quad \text{for } n \leq 1 \quad (f(0) = 0, f(1) = 1)$$

$$f(n) = f(n-1) + f(n-2) \quad \text{for } n > 1$$

```
int main()
{
    int n;
    cout << "Enter a positive Integer: ";
    cin >> n;
    cout << "f( " << n << " ) = " << f( n ) << endl;
}

int f( int n )
{
    if( n <= 1 )
        return ;
    else
        return ;
}
```

Recursive Fibonacci Function

Let $f(n)$ be the n -th fibonacci number

$$f(n) = n \quad \text{for } n \leq 1 \quad (f(0) = 0, f(1) = 1)$$

$$f(n) = f(n-1) + f(n-2) \quad \text{for } n > 1$$

```
int main()
{
    int n;
    cout << "Enter a positive Integer: ";
    cin >> n;
    cout << "f( " << n << " ) = " << f( n ) << endl;
}

int f( int n )
{
    if( n <= 1 )
        return n;
    else
        return f( n - 1 ) + f( n - 2 );
}
```

```
int main()
{
    int n;
    cout << "Enter a nonnegative Integer: ";
    cin >> n;
    cout << f( n ) << endl;
}
```

0

```
int f( int n )
{
    if( n <= 1 )
        return n;
    else
        return f( n - 1 ) + f( n - 2 );
}
```

```
int main()
{
    int n;
    cout << "Enter a nonnegative Integer: ";
    cin >> n;
    cout << f( n ) << endl;
}
```

1

```
int f( int n )
{
    if( n <= 1 )
        return n;
    else
        return f( n - 1 ) + f( n - 2 );
}
```

```

int main()
{
    int n;
    cout << "Enter a nonnegative Integer: ";
    cin >> n;
    cout << f( n ) << endl;
}

```

2

```

int f( int n )
{
    if( n <= 1 )
        return n;
    else
        return f( n - 1 ) + f( n - 2 );
}

```

1

0

1

0

```

int main()
{
    int n;
    cout << "Enter a nonnegative Integer: ";
    cin >> n;
    cout << f( n ) << endl;
}

```

3

```

int f( int n )
{
    if( n <= 1 )
        return n;
    else
        return f( n - 1 ) + f( n - 2 );
}

```

```

int main()
{
    int n;
    cout << "Enter a nonnegative Integer: ";
    cin >> n;
    cout << f( n ) << endl;
}

```

4



```

int f( int n )
{
    if( n <= 1 )
        return n;
    else
        return f( n - 1 ) + f( n - 2 );
}

```

2

1

3

2

```

int main()
{
    int n;
    cout << "Enter a nonnegative Integer: ";
    cin >> n;
    cout << f( n ) << endl;
}

```

5

```

int f( int n )
{
    if( n <= 1 )
        return n;
    else
        return f( n - 1 ) + f( n - 2 );
}

```

3

2

4

3


```
int f( int n3 )
{
    if( n <= 1 )
        return n;
    else
        return f(n - 1) + f(n - 2);
}
```

```
int f( int n )
{
    if( n <= 1 )
        return n;
    else
        return f(n - 1) + f(n - 2);
}
```

```
int f( int n )
{
    if( n <= 1 )
        return n;
    else
        return f(n - 1) + f(n - 2);
}
```

```
int f( int n )
{
    if( n <= 1 )
        return n;
    else
        return f(n - 1) + f(n - 2);
}
```

```
int f( int n )
{
    if( n <= 1 )
        return n;
    else
        return f(n - 1) + f(n - 2);
}
```

```

int f( int n3 )
{
    if( n <= 1 )
        return n;
    else
        return f(n - 1) + f(n - 2);
}

```

```

int f( int n )
{
    if( n <= 1 )
        return n;
    else
        return f(n - 1) + f(n - 2);
}

```

```

int f( int n )
{
    if( n <= 1 )
        return n;
    else
        return f(n - 1) + f(n - 2);
}

```

```

int f( int n )
{
    if( n <= 1 )
        return n;
    else
        return f(n - 1) + f(n - 2);
}

```

```

int f( int n )
{
    if( n <= 1 )
        return n;
    else
        return f(n - 1) + f(n - 2);
}

```

```

int f( int n3 )
{
    if( n <= 1 )
        return n;
    else
        return f(n - 1)2 + f(n - 2)1;
}

```

```

int f( int n2 )
{
    if( n <= 1 )
        return n;
    else
        return f(n - 1)1 + f(n - 2)0;
}

```

```

int f( int n )
{
    if( n <= 1 )
        return n;
    else
        return f(n - 1) + f(n - 2);
}

```

```

int f( int n )
{
    if( n <= 1 )
        return n;
    else
        return f(n - 1) + f(n - 2);
}

```

```

int f( int n )
{
    if( n <= 1 )
        return n;
    else
        return f(n - 1) + f(n - 2);
}

```

```

int f( int 3n )
{
    if( n <= 1 )
        return n;
    else
        return f(n - 1) + f(n - 2);
}

```

```

int f( int 2n )
{
    if( n <= 1 )
        return n;
    else
        return f(n - 1) + f(n - 2);
}

```

```

int f( int n )
{
    if( n <= 1 )
        return n;
    else
        return f(n - 1) + f(n - 2);
}

```

```

int f( int 1n )
{
    if( n <= 1 )
        return n;
    else
        return f(n - 1) + f(n - 2);
}

```

```

int f( int n )
{
    if( n <= 1 )
        return n;
    else
        return f(n - 1) + f(n - 2);
}

```

```

int f( int 3n )
{
    if( n <= 1 )
        return n;
    else
        return f(n - 1) + f(n - 2);
}

```

```

int f( int 2n )
{
    if( n <= 1 )
        return n;
    else
        return f(n - 1) + f(n - 2);
}

```

```

int f( int n )
{
    if( n <= 1 )
        return n;
    else
        return f(n - 1) + f(n - 2);
}

```

```

int f( int 1n )
{
    if( n <= 1 )
        return n;
    else
        return f(n - 1) + f(n - 2);
}

```

```

int f( int n )
{
    if( n <= 1 )
        return n;
    else
        return f(n - 1) + f(n - 2);
}

```

```

int f( int 3n )
{
    if( n <= 1 )
        return n;
    else
        return f(n - 1) + f(n - 2);
}

```

```

int f( int 2n )
{
    if( n <= 1 )
        return n;
    else
        return f(n - 1) + f(n - 2);
}

```

```

int f( int n )
{
    if( n <= 1 )
        return n;
    else
        return f(n - 1) + f(n - 2);
}

```

```

int f( int 1n )
{
    if( n <= 1 )
        return n;
    else
        return f(n - 1) + f(n - 2);
}

```

```

int f( int 0n )
{
    if( n <= 1 )
        return n;
    else
        return f(n - 1) + f(n - 2);
}

```

```

int f( int 3n )
{
    if( n <= 1 )
        return n;
    else
        return f(n - 1) + f(n - 2);
}

```

```

int f( int 2n )
{
    if( n <= 1 )
        return n;
    else
        return f(n - 1) + f(n - 2);
}

```

```

int f( int n )
{
    if( n <= 1 )
        return n;
    else
        return f(n - 1) + f(n - 2);
}

```

```

int f( int 1n )
{
    if( n <= 1 )
        return n;
    else
        return f(n - 1) + f(n - 2);
}

```

```

int f( int 0n )
{
    if( n <= 1 )
        return n;
    else
        return f(n - 1) + f(n - 2);
}

```

```

int f( int 3n )
{
    if( n <= 1 )
        return n;
    else
        return f(n - 1) + f(n - 2);
                1   2           1

```

```

int f( int 2n )
{
    if( n <= 1 )
        return n;
    else
        return f(n - 1) + f(n - 2);
                1   1       0 0

```

```

int f( int n )
{
    if( n <= 1 )
        return n;
    else
        return f(n - 1) + f(n - 2);

```

```

int f( int 1n )
{
    if( n <= 1 )
        return n;
    else
        return f(n - 1) + f(n - 2);
}

```

```

int f( int 0n )
{
    if( n <= 1 )
        return n;
    else
        return f(n - 1) + f(n - 2);
}

```

```

int f( int 3n )
{
    if( n <= 1 )
        return n;
    else
        return f(n - 1) + f(n - 2);
                1   2           1

```

```

int f( int 2n )
{
    if( n <= 1 )
        return n;
    else
        return f(n - 1) + f(n - 2);
                1   1       0 0

```

```

int f( int 1n )
{
    if( n <= 1 )
        return n;
    else
        return f(n - 1) + f(n - 2);
                1

```

```

int f( int 1n )
{
    if( n <= 1 )
        return n;
    else
        return f(n - 1) + f(n - 2);
}

```

```

int f( int 0n )
{
    if( n <= 1 )
        return n;
    else
        return f(n - 1) + f(n - 2);
}

```

```

int f( int 3n )
{
    if( n <= 1 )
        return n;
    else
        return f(n - 21) + f(n - 2);
}
           1  2      1  1

```

```

int f( int 2n )
{
    if( n <= 1 )
        return n;
    else
        return f(n - 1) + f(n - 2);
}
           1  1      0  0

```

```

int f( int 1n )
{
    if( n <= 1 )
        return n;
    else
        return f(n - 1) + f(n - 2);
}

```

```

int f( int 1n )
{
    if( n <= 1 )
        return n;
    else
        return f(n - 1) + f(n - 2);
}

```

```

int f( int 0n )
{
    if( n <= 1 )
        return n;
    else
        return f(n - 1) + f(n - 2);
}

```



```
int main()
{
    int n = 3;
    cout << f( n ) << endl;
}
```

EAX

EDX

n 0012FF7C

```
int f( int n )
{
    if( n <= 1 ) return n;
    else return f( n - 1 ) + f( n - 2 );
}
```

```
int f( int n )
{
    if( n <= 1 ) return n;
    else return f( n - 1 ) + f( n - 2 );
}
```

```
int f( int n )
{
    if( n <= 1 ) return n;
    else return f( n - 1 ) + f( n - 2 );
}
```

```
int main()
{
    int n = 3;
    cout << f( n ) << endl;
}
```

EAX

EDX

n 0012FF7C

```
int f( int n )
{
    if( n <= 1 ) return n;
    else return f( n - 1 ) + f( n - 2 );
}
```

n 0012FF28

```
int f( int n )
{
    if( n <= 1 ) return n;
    else return f( n - 1 ) + f( n - 2 );
}
```

```
int f( int n )
{
    if( n <= 1 ) return n;
    else return f( n - 1 ) + f( n - 2 );
}
```

```
int main()
{
    int n = 3;
    cout << f( n ) << endl;
}
```

EAX

EDX

n 0012FF7C

```
int f( int n )
{
    if( n <= 1 ) return n;
    else return f( n - 1 ) + f( n - 2 );
}
```

n 0012FF28

```
int f( int n )
{
    if( n <= 1 ) return n;
    else return f( n - 1 ) + f( n - 2 );
}
```

n 0012FED0

```
int f( int n )
{
    if( n <= 1 ) return n;
    else return f( n - 1 ) + f( n - 2 );
}
```

```
int main()
{
    int n = 3;
    cout << f( n ) << endl;
}
```

EAX

EDX

n 0012FF7C

```
int f( int n )
{
    if( n <= 1 ) return n;
    else return f( n - 1 ) + f( n - 2 );
}
```

n 0012FF28

```
int f( int n )
{
    if( n <= 1 ) return n;
    else return f( n - 1 ) + f( n - 2 );
}
```

n 0012FED0

```
int f( int n )
{
    if( n <= 1 ) return n;
    else return f( n - 1 ) + f( n - 2 );
}
```

n 0012FE78

```
int main()
{
    int n = 3;
    cout << f( n ) << endl;
}
```

EAX 1

EDX

n 3 0012FF7C

```
int f( int n )
{
    if( n <= 1 ) return n;
    else return f( n - 1 ) + f( n - 2 );
}
```

n 3 0012FF28

```
int f( int n )
{
    if( n <= 1 ) return n;
    else return f( n - 1 ) + f( n - 2 );
}
```

n 2 0012FED0

```
int f( int n )
{
    if( n <= 1 ) return n;
    else return f( n - 1 ) + f( n - 2 );
}
```

```
int main()
{
    int n = 3;
    cout << f( n ) << endl;
}
```

EAX 1
 EDX 1

n 3 0012FF7C

```
int f( int n )
{
    if( n <= 1 ) return n;
    else return f( n - 1 ) + f( n - 2 );
}
```

n 3 0012FF28

```
int f( int n )
{
    if( n <= 1 ) return n;
    else return f( n - 1 ) + f( n - 2 );
}
```

n 2 0012FED0

```
int f( int n )
{
    if( n <= 1 ) return n;
    else return f( n - 1 ) + f( n - 2 );
}
```

```
int main()
{
    int n = 3;
    cout << f( n ) << endl;
}
```

EAX 1

EDX 1

n 3 0012FF7C

```
int f( int n )
{
    if( n <= 1 ) return n;
    else return f( n - 1 ) + f( n - 2 );
}
```

n 3 0012FF28

```
int f( int n )
{
    if( n <= 1 ) return n;
    else return f( n - 1 ) + f( n - 2 );
}
```

n 2 0012FED0

```
int f( int n )
{
    if( n <= 1 ) return n;
    else return f( n - 1 ) + f( n - 2 );
}
```

n 0 0012FE78

```
int main()
{
    int n = 3;
    cout << f( n ) << endl;
}
```

EAX 0

EDX 1

n 3 0012FF7C

```
int f( int n )
{
    if( n <= 1 ) return n;
    else return f( n - 1 ) + f( n - 2 );
}
```

n 3 0012FF28

```
int f( int n )
{
    if( n <= 1 ) return n;
    else return f( n - 1 ) + f( n - 2 );
}
```

n 2 0012FED0

```
int f( int n )
{
    if( n <= 1 ) return n;
    else return f( n - 1 ) + f( n - 2 );
}
```

```
int main()
{
    int n = 3;
    cout << f( n ) << endl;
}
```

EAX 1

EDX 1

n 3 0012FF7C

```
int f( int n )
{
    if( n <= 1 ) return n;
    else return f( n - 1 ) + f( n - 2 );
}
```

n 3 0012FF28

```
int f( int n )
{
    if( n <= 1 ) return n;
    else return f( n - 1 ) + f( n - 2 );
}
```

n 2 0012FED0

```
int f( int n )
{
    if( n <= 1 ) return n;
    else return f( n - 1 ) + f( n - 2 );
}
```

```
int main()
{
    int n = 3;
    cout << f( n ) << endl;
}
```

EAX

1

EDX

1

n

3

 0012FF7C

```
int f( int n )
{
    if( n <= 1 ) return n;
    else return f( n - 1 ) + f( n - 2 );
}
```

n

3

 0012FF28

```
int f( int n )
{
    if( n <= 1 ) return n;
    else return f( n - 1 ) + f( n - 2 );
}
```

```
int f( int n )
{
    if( n <= 1 ) return n;
    else return f( n - 1 ) + f( n - 2 );
}
```

```
int main()
{
    int n = 3;
    cout << f( n ) << endl;
}
```

EAX

1

EDX

1

n

3

 0012FF7C

```
int f( int n )
{
    if( n <= 1 ) return n;
    else return f( n - 1 ) + f( n - 2 );
}
```

n

3

 0012FF28

```
int f( int n )
{
    if( n <= 1 ) return n;
    else return f( n - 1 ) + f( n - 2 );
}
```

n

1

 0012FED0

```
int f( int n )
{
    if( n <= 1 ) return n;
    else return f( n - 1 ) + f( n - 2 );
}
```

```
int main()
{
    int n = 3;
    cout << f( n ) << endl;
}
```

EAX

1

EDX

1

n

3

 0012FF7C

```
int f( int n )
{
    if( n <= 1 ) return n;
    else return f( n - 1 ) + f( n - 2 );
}
```

n

3

 0012FF28

```
int f( int n )
{
    if( n <= 1 ) return n;
    else return f( n - 1 ) + f( n - 2 );
}
```

```
int f( int n )
{
    if( n <= 1 ) return n;
    else return f( n - 1 ) + f( n - 2 );
}
```

```
int main()
{
    int n = 3;
    cout << f( n ) << endl;
}
```

EAX

2

EDX

1

n

3

 0012FF7C

```
int f( int n )
{
    if( n <= 1 ) return n;
    else return f( n - 1 ) + f( n - 2 );
}
```

n

3

 0012FF28

```
int f( int n )
{
    if( n <= 1 ) return n;
    else return f( n - 1 ) + f( n - 2 );
}
```

```
int f( int n )
{
    if( n <= 1 ) return n;
    else return f( n - 1 ) + f( n - 2 );
}
```

```
int main()
{
    int n = 3;
    cout << f( n ) << endl;
}
```

EAX

2

EDX

1

n

3

 0012FF7C

```
int f( int n )
{
    if( n <= 1 ) return n;
    else return f( n - 1 ) + f( n - 2 );
}
```

```
int f( int n )
{
    if( n <= 1 ) return n;
    else return f( n - 1 ) + f( n - 2 );
}
```

```
int f( int n )
{
    if( n <= 1 ) return n;
    else return f( n - 1 ) + f( n - 2 );
}
```


EAX

EDX

```
int main()
{
    int n = 3;
    cout << f( n ) << endl;
}
```

```
int f( int n )
{
    if( n <= 1 )
        return n;
    else
        return f( n - 1 ) + f( n - 2 );
}
```

n 0012FD20

EAX

EDX

```
int main()
{
    int n = 3;
    cout << f( n ) << endl;
}
```

```
int f( int n )
{
    if( n <= 1 )
        return n;
    else
        return f( n - 1 ) + f( n - 2 );
}
```

n	3	0012FCC8
	⋮	
n	3	0012FD20

EAX

EDX

```
int main()
{
    int n = 3;
    cout << f( n ) << endl;
}

int f( int n )
{
    if( n <= 1 )
        return n;
    else
        return f( n - 1 ) + f( n - 2 );
}
```

n	2	0012FC70
	⋮	
n	3	0012FCC8
	⋮	
n	3	0012FD20

EAX

EDX

```
int main()
{
    int n = 3;
    cout << f( n ) << endl;
}

int f( int n )
{
    if( n <= 1 )
        return n;
    else
        return f( n - 1 ) + f( n - 2 );
}
```

n	1	0012FC18
	⋮	
n	2	0012FC70
	⋮	
n	3	0012FCC8
	⋮	
n	3	0012FD20

EAX

1

EDX

--

```
int main()
{
    int n = 3;
    cout << f( n ) << endl;
}

int f( int n )
{
    if( n <= 1 )
        return n;
    else
        return f( n - 1 ) + f( n - 2 );
}
```

n	2	0012FC70
	⋮	
n	3	0012FCC8
	⋮	
n	3	0012FD20

EAX

1

EDX

1

```
int main()
{
    int n = 3;
    cout << f( n ) << endl;
}

int f( int n )
{
    if( n <= 1 )
        return n;
    else
        return f( n - 1 ) + f( n - 2 );
}
```

n	2	0012FC70
	⋮	
n	3	0012FCC8
	⋮	
n	3	0012FD20

EAX

1

EDX

1

```
int main()
{
    int n = 3;
    cout << f( n ) << endl;
}

int f( int n )
{
    if( n <= 1 )
        return n;
    else
        return f( n - 1 ) + f( n - 2 );
}
```

n	0	0012FC18
	⋮	
n	2	0012FC70
	⋮	
n	3	0012FCC8
	⋮	
n	3	0012FD20

EAX

0

EDX

1

```
int main()
{
    int n = 3;
    cout << f( n ) << endl;
}

int f( int n )
{
    if( n <= 1 )
        return n;
    else
        return f( n - 1 ) + f( n - 2 );
}
```

n	2	0012FC70
	⋮	
n	3	0012FCC8
	⋮	
n	3	0012FD20

EAX

1

EDX

1

```
int main()
{
    int n = 3;
    cout << f( n ) << endl;
}

int f( int n )
{
    if( n <= 1 )
        return n;
    else
        return f( n - 1 ) + f( n - 2 );
}
```

n	<table border="1"><tr><td>2</td></tr></table>	2	0012FC70
2			
	<table border="1"><tr><td>⋮</td></tr></table>	⋮	
⋮			
n	<table border="1"><tr><td>3</td></tr></table>	3	0012FCC8
3			
	<table border="1"><tr><td>⋮</td></tr></table>	⋮	
⋮			
n	<table border="1"><tr><td>3</td></tr></table>	3	0012FD20
3			

EAX

1

EDX

1

```
int main()
{
    int n = 3;
    cout << f( n ) << endl;
}
```

```
int f( int n )
{
    if( n <= 1 )
        return n;
    else
        return f( n - 1 ) + f( n - 2 );
}
```

n	<table border="1" style="display: inline-table; vertical-align: middle;"><tr><td>3</td></tr></table>	3	0012FCC8
3			
	<table border="1" style="display: inline-table; vertical-align: middle;"><tr><td>⋮</td></tr></table>	⋮	
⋮			
n	<table border="1" style="display: inline-table; vertical-align: middle;"><tr><td>3</td></tr></table>	3	0012FD20
3			

EAX

1

EDX

1

```
int main()
{
    int n = 3;
    cout << f( n ) << endl;
}

int f( int n )
{
    if( n <= 1 )
        return n;
    else
        return f( n - 1 ) + f( n - 2 );
}
```

n	1	0012FC70
	⋮	
n	3	0012FCC8
	⋮	
n	3	0012FD20

EAX

1

EDX

1

```
int main()
{
    int n = 3;
    cout << f( n ) << endl;
}
```

```
int f( int n )
{
    if( n <= 1 )
        return n;
    else
        return f( n - 1 ) + f( n - 2 );
}
```

n	3	0012FCC8
	⋮	
n	3	0012FD20

EAX

2

EDX

1

```
int main()
{
    int n = 3;
    cout << f( n ) << endl;
}
```

```
int f( int n )
{
    if( n <= 1 )
        return n;
    else
        return f( n - 1 ) + f( n - 2 );
}
```

n	3	0012FCC8
	⋮	
n	3	0012FD20

EAX

2

EDX

1

```
int main()
{
    int n = 3;
    cout << f( n ) << endl;
}
```

```
int f( int n )
{
    if( n <= 1 )
        return n;
    else
        return f( n - 1 ) + f( n - 2 );
}
```

n

3

 0012FD20