

Lecture 07: Objects in JS

Part 1: The Core Concept - What is an Object?

First Thought: An object is a collection of labeled data.

Think of a real-world object, like a person. A person has properties with labels and values:

- Name: "Alice"
- Age: 30
- Is Student: true

A JavaScript object is the exact same thing: a container for named values, which we call **key-value pairs**.

- The **key** is the label (a `string` or `Symbol`).
- The **value** is the data (it can be *any* data type: a number, a string, a boolean, an array, or even another object).

```
// This is an object representing a person let person = { name: "Alice", // Key is "name", Value is "Alice" age: 30, // Key is "age", Value is 30 isStudent: true // Key is "isStudent", Value is true };
```

Part 2: The Basics - Create, Read, Update, Delete (CRUD)

A. Creating an Object

The most common and best way to create an object is using the **object literal** syntax: curly braces `{ }`.

```
// An empty object const car = {}; // An object with properties const user = { username: "js_dev", loginCount: 57, "is-premium-member": true // Keys with special characters must be in quotes };
```

B. Accessing (Reading) Properties

There are two ways to get a value from an object.

1. **Dot Notation (`.`)**: The simplest and most common way. It's clean and easy to read.

```
console.log(user.username); // "js_dev"
```

Limitation: Dot notation only works for keys that are valid JavaScript identifiers (no spaces, hyphens, or starting with a number).

2. **Bracket Notation (`[]`)**: The more powerful and flexible way. The key inside the brackets is a **string**.

```
console.log(user["loginCount"]); // 57 // You MUST use bracket notation for keys with special characters. console.log(user["is-premium-member"]); // true
```

CRITICAL USE CASE: Bracket notation allows you to use a **variable** to determine which property to access.

```
let propertyToAccess = "username"; console.log(user[propertyToAccess]); // "js_dev" (This is impossible with dot notation)
```

C. Updating and Adding (Creating) Properties

You use the same syntax for both. If the property exists, it's updated. If it doesn't, it's created.

```
const book = { title: "The Hobbit" }; // Update an existing property book.title = "The Lord of the Rings"; // Add a new property book.author = "J.R.R. Tolkien"; book.pages = 1178; console.log(book); // { title: "The Lord of the Rings", author: "J.R.R. Tolkien", pages: 1178 }
```

D. Deleting Properties

Use the `delete` keyword.

```
delete book.pages; console.log(book); // { title: "The Lord of the Rings", author: "J.R.R. Tolkien" }
```

Part 3: Objects with Methods (Behavior)

When a function is a value inside an object, it's called a **method**. Methods give objects behavior.

The `this` Keyword First Thought: `this` is a shortcut that means "this object right here."

Inside a method, the `this` keyword refers to the object that the method was called on.

```
const user = { name: "Alice", greeting: function() { // Here, `this` refers to the 'user' object. console.log(`Hello, my name is ${this.name}.`); } }; user.greeting(); // Outputs: "Hello, my name is Alice."
```

When we call `user.greeting()`, `this` becomes `user`. This allows methods to be dynamic and access the data of their own object.

Part 4: Looping Over an Object's Properties (Iteration)

How do you get all the keys and values from an object?

A. The `for...in` Loop (The Old Way)

This loop iterates over the **keys** (property names) of an object.

```
const car = { make: "Honda", model: "Civic", year: 2021 }; for (const key in car) { console.log(`Key: ${key}, Value: ${car[key]}`); }
```

(**Advanced Gotcha:** `for...in` also iterates over properties from the object's prototype chain, which can be unexpected. For this reason, the modern methods below are usually preferred.)

B. The Modern `Object` Methods (The Better Way)

These methods return arrays, which you can then loop over with a `for...of` loop.

- `Object.keys(obj)` : Returns an array of the object's own property keys.
- `Object.values(obj)` : Returns an array of the object's own property values.
- `Object.entries(obj)` : Returns an array of `[key, value]` pairs.

```
const car = { make: "Honda", model: "Civic", year: 2021 }; console.log(Object.keys(car)); // ["make", "model", "year"] console.log(Object.values(car)); // ["Honda", "Civic", 2021] // The .entries() method is perfect with a for...of loop for (const [key, value] of Object.entries(car)) { console.log(`${key}: ${value}`); }
```

Part 5: Advanced Concepts

A. Objects are a Reference Type

This is the same critical concept we saw with arrays. When you assign an object to another variable, you only copy the **reference** (the memory address). Both variables point to the **same object**.

```
let obj1 = { value: 10 }; let obj2 = obj1; // Copies the reference, NOT the object. obj2.value = 20; // Mutates the single object. console.log(obj1.value); // 20 (The original was changed!)
```

B. How to Copy an Object (Shallow Copy)

To create a true copy of an object's top-level properties, use the **spread syntax** (`...`) or `Object.assign()`.

```
const original = { name: "Alice", age: 30 }; // Using spread syntax (most common and modern) const copy = { ...original }; copy.age = 31; console.log(original.age); // 30 (The original is safe!) console.log(copy.age); // 31
```

(**Note:** This is a "shallow" copy. If the object contains other objects, those nested objects will still be references, not copies.)

C. Modern ES6+ Syntax (Syntactic Sugar)

- **Property Value Shorthand:** If you have a variable with the same name as a property key, you can just use the variable name once.

```
const name = "Alice"; const age = 30; // Old way: const userOld = { name: name, age: age }; // New way: const userNew = { name, age }; // Much cleaner
```

- **Method Shorthand:** You can omit the `function` keyword when defining methods.

```
// Old way: const userOld = { sayHi: function() { console.log("Hi"); } }; // New way: const userNew = { sayHi() { console.log("Hi"); } };
```

- **Computed Property Names:** Use a variable as a property key *during creation* by putting it in brackets.

```
let propertyName = "email"; const user = { name: "Alice", [propertyName]: "alice@example.com" }; console.log(user); // { name: "Alice", email: "alice@example.com" }
```

The Modern Way (Recommended): `Object.keys`, `values`, `entries`

First Thought: "I can't loop over an object directly, so I'll ask for a list of its keys (or values) and loop over that list instead."

This is the core idea. These `Object` methods convert the parts of your object into an **array**, and we already know how to loop over arrays (using `for...of`).

Let's use this sample object for all examples:

```
const user = { name: "Alice", forklift: "Linde", age: 30, isStudent: true };
```

1. `Object.keys(obj)` - Looping Over Just the Keys

This method gives you an **array of the object's keys** (the property names).

```
const keys = Object.keys(user); // keys is now: ["name", "age", "isStudent"] // Now we can use a simple for...of loop on this new array for (const key of keys) { // To get the value, we use bracket notation on the original object const value = user[key]; console.log(`The key is "${key}" and the value is "${value}"`); }
```

Output:

```
The key is "name" and the value is "Alice". The key is "age" and the value is "30". The key is "isStudent" and the value is "true".
```

2. `Object.values(obj)` - Looping Over Just the Values

This method gives you an **array of the object's values**. This is useful if you don't care about the property names.

```
const values = Object.values(user); // values is now: ["Alice", 30, true] for (const value of values) { console.log(`The value is: ${value}`); }
```

Output:

```
The value is: Alice The value is: 30 The value is: true
```

3. `Object.entries(obj)` - The Best of Both Worlds

This is often the most useful method. It gives you an **array of `[key, value]` pairs**. Each item in the array is a smaller array containing the key at index 0 and the value at index 1.

```
const entries = Object.entries(user); // entries is now: // [ // ["name", "Alice"], // ["age", 30], // ["isStudent", true] // ]
```

This works perfectly with a `for...of` loop and a technique called **destructuring**, which lets you unpack the key and value into their own variables right in the loop definition.

```
// This is the cleanest and most common modern pattern for (const [key, value] of Object.entries(user)) { console.log(`Key: ${key}, Value: ${value}`); }
```

Output:

```
Key: name, Value: Alice Key: age, Value: 30 Key: isStudent, Value: true
```

This is a powerful and readable pattern that you will see very often in modern JavaScript.

The Traditional Way: `for...in` Loop

First Thought: "For each property key *in* this object, do this."

The `for...in` loop iterates directly over the property names (keys) of an object.

Syntax:

```
for (const key in object) { // code to run }
```

Example:

```
const user = { name: "Alice", age: 30, isStudent: true }; for (const key in user) { // 'key' will be "name", then "age", then "isStudent" const value = user[key]; console.log(`Key: ${key}, Value: ${value}`); }
```

Why `for...in` is Usually Avoided

The `for...in` loop has a major "gotcha" that makes it less safe than the `Object` methods. **It will also loop over properties that the object inherits from its prototype chain.**

This is an advanced concept, but a simple example can show the problem.

```
// Let's modify the master Object prototype (NEVER DO THIS IN REAL CODE!) Object.prototype.isInherited = true; const person = { name: "Bob" }; console.log("--- Using for...in ---"); for (const key in person) { console.log(key); // Outputs: "name", AND "isInherited" } console.log("\n--- Using Object.keys ---"); console.log(Object.keys(person)); // Outputs: ["name"] (It only sees its OWN properties)
```

Because `for...in` sees the inherited `isInherited` property, it can cause unexpected behavior. The `Object.keys()` method correctly ignores it. To make `for...in` safe, you have to add an extra check, which makes it clumsy.

```
for (const key in person) { if (person.hasOwnProperty(key)) { // Now it's safe, but it's more work } }
```

Summary: Which Loop to Use?

Method	Best For...	Why?
<code>for (const [key, value] of Object.entries(obj))</code>	The default choice. Getting both the key and the value.	Clean, readable, uses modern syntax, and is safe (only iterates own properties).
<code>for (const key of Object.keys(obj))</code>	Getting only the keys, and then looking up the values.	Safe and clear. A good alternative to <code>entries</code> .
<code>for (const value of Object.values(obj))</code>	Getting only the values.	Simple and direct if you don't need the keys.
<code>for...in</code>	Generally avoid. Use only if you specifically <i>need</i> to inspect inherited properties.	Can cause bugs by iterating over the prototype chain. The other methods are safer.

1. How to Copy an Object (Shallow vs. Deep)

This is a critical concept because objects are **reference types**. A simple assignment (`let b = a`) **does not create a copy**; it just makes a second variable point to the same object.

First Thought: "I don't want to change my original object. I need a brand new, separate copy to work with."

There are two kinds of copies: shallow and deep.

A. Shallow Copy (The 99% Use Case)

A shallow copy creates a **new top-level object**, but if any of the properties of the original object are themselves objects, it only copies the **references** to those nested objects.

The Modern Way: Spread Syntax (`...`) (ES2018)

This is the most common, readable, and preferred way to make a shallow copy.

```
const originalUser = { name: "Alice", age: 30, address: { // A nested object city: "New York" } }; // Use the spread syntax to create a new object const shallowCopy = { ...originalUser }; // --- Let's test the copy --- // 1. Change a top-level primitive property in the copy shallowCopy.age = 31; console.log(originalUser.age); // 30 (The original is safe!) console.log(shallowCopy.age); // 31 (The copy was changed) // 2. Now, change a property in the NESTED object shallowCopy.address.city = "London"; // The "gotcha" of a shallow copy: console.log(originalUser.address.city); // "London" (The original was also changed!)
```

Why did the original change? Because both `originalUser` and `shallowCopy` contain a reference to the **exact same** `address` object.

The Old Way: `Object.assign()`

This does the same thing as the spread syntax.

```
const shallowCopyAssign = Object.assign({}, originalUser);
```

B. Deep Copy (For Complex, Nested Objects)

A deep copy creates a **new object** and recursively creates new copies of **all nested objects** as well. This ensures that the new object is completely independent of the original.

First Thought: "I need a perfect, independent clone of my object, including all its nested parts."

There is now a **modern, built-in global function** specifically for creating a deep copy:

```
structuredClone()
```

Let's correct the record and explain it in detail.

The Modern, Built-in Solution: `structuredClone()`

First Thought: "Finally, a proper 'Clone' button for my objects."

The `structuredClone()` global function was introduced to solve this exact problem. It is designed to create a **deep copy** of a given value using the "structured clone algorithm," which is the same powerful algorithm that browsers use internally to copy data for features like `postMessage` (sending data between windows).

How it works:

It recursively traverses the entire object, creating brand new copies of every object and array it finds, resulting in a completely independent clone.

Code Example:

```
const originalUser = { name: "Alice", age: 30, joined: new Date("2023-01-15"), //  
  A Date object address: { // A nested object city: "New York" }, roles: ["editor",  
  "viewer"] // An array }; // Use the built-in function to create a deep copy const  
deepClone = structuredClone(originalUser); // --- Let's prove it's a deep copy ---  
// 1. Change a top-level primitive in the clone deepClone.age = 31; // 2. Change  
a property in the NESTED object deepClone.address.city = "London"; // 3. Mutate  
the nested ARRAY deepClone.roles.push("admin"); // 4. Mutate the nested DATE object  
deepClone.joined.setFullYear(2024); // --- Check the original object --- // Everything  
is completely untouched! console.log(originalUser.age); // 30 console.log(  
originalUser.address.city); // "New York" console.log(originalUser.roles); //  
["editor", "viewer"] console.log(originalUser.joined.getFullYear()); // 2023
```

Conclusion: `structuredClone()` is the modern, correct, and recommended way to create a deep copy in JavaScript.

Browser and Node.js Support for `structuredClone()`

This is a relatively new feature, but it now has **excellent support** in all modern environments:

- **Chrome:** Version 98+
- **Firefox:** Version 94+
- **Safari:** Version 15.4+
- **Node.js:** Version 17.0.0+

You can safely use it today in any up-to-date browser or Node.js environment.

Limitations of `structuredClone()`

While it is extremely powerful, the structured clone algorithm is not a magical "clone everything" button. It is designed to clone data, not code or system resources.

It **CANNOT** clone:

- **Functions:** It will throw a `DataCloneError`. Functions have a "scope" and are not considered simple data.
- **DOM Nodes:** It will throw an error. You can't clone a piece of a webpage this way.

- **Class Instances (Prototypes):** It will discard the object's prototype chain. The clone will be a plain object with all the same data properties, but it will no longer be an "instance of" your custom class.
- **Error objects.**

Example of a Failure:

```
const original = { name: "Alice", sayHi: function() { console.log("Hi"); } }; try { const clone = structuredClone(original); } catch (error) { console.error(error.name); // "DataCloneError" console.error(error.message); // "()" => { console.log("Hi"); } could not be cloned." }
```

The "Old" Robust Way: Using a Library

Before `structuredClone()` had widespread support (and for cases where you need to handle things it can't, like class instances), the standard professional practice was to use a battle-tested function from a utility library.

The most famous of these is **Lodash's** `_.cloneDeep()`.

Why use a library function?

- **It's Robust:** `_.cloneDeep()` is incredibly smart. It can handle complex scenarios, including circular references (where an object refers back to itself), and it correctly clones prototypes.
- **It's Battle-Tested:** It has been used in production by millions of developers for over a decade.

Example with Lodash:

```
// You would first need to install lodash: npm install lodash import _ from 'lodash'; const original = { name: "Alice", sayHi: function() { console.log("Hi"); } }; const lodashClone = _.cloneDeep(original); // It even clones the function! lodashClone.sayHi(); // "Hi" console.log(original.sayHi === lodashClone.sayHi); // false (it's a new function reference)
```

Summary

Method	Best For...	Pros	Cons
<code>structuredClone()</code>	The default choice for deep cloning data in modern JS.	Built-in , fast, and handles most data types (including <code>Date</code> , <code>Map</code> , <code>Set</code>).	Cannot clone functions or class prototypes.
<code>JSON.parse(JSON.stringify())</code>	Quick and simple deep cloning of JSON-safe data only .	No dependencies needed.	Silent data loss (functions, <code>undefined</code> are lost). Slower than <code>structuredClone</code> .
Library (e.g., <code>_.cloneDeep</code>)	Maximum robustness. When you need to clone complex objects with functions, class instances, or in older environments.	Handles almost everything correctly.	Requires an external library dependency.

2. Destructuring Assignment (ES6)

First Thought: "Instead of getting the whole box, just give me the specific items I want out of it."

Destructuring is a powerful syntax for "unpacking" values from arrays or properties from objects into distinct variables. It makes your code much cleaner and more readable.

A. Object Destructuring

This lets you pull properties out of an object by name.

```
const user = { id: 123, name: "Alice", email: "alice@example.com", profile: { isAdmin: true } }; // --- Basic Destructuring --- // Old way: // const name = user.name; // const age = user.age; // New way with destructuring: const { name, age } = user; // Create variables 'name' and 'age' from user object. console.log(name); // "Alice" console.log(age); // undefined (because 'age' doesn't exist on the object) // --- Renaming Variables --- // What if you already have a variable named 'name'? You can rename it. const { name: userName, email } = user; console.log(userName); // "Alice" // --- Setting Default Values --- // What if a property might not exist? You can provide a default. const { name: personName, role = "User" } = user; console.log(personName); // "Alice" console.log(role); // "User" (because 'role' didn't exist on the object) // --- Nested Destructuring --- // You can even pull from nested objects. const { profile: { isAdmin } } = user; console.log(isAdmin); // true
```

B. Array Destructuring

This lets you unpack values from an array by their position.

```
const scores = [98, 85, 100, 92]; // Get the first two scores const [firstScore, secondScore] = scores; console.log(firstScore); // 98 console.log(secondScore); // 85 // Skip items with a comma const [winner, , thirdPlace] = scores; console.log(winner); // 98 console.log(thirdPlace); // 100
```

3. How to Use **Symbol**

First Thought: "I need a secret key for my object that will never, ever clash with anyone else's key."

A **Symbol** is a unique and immutable primitive data type. Its purpose is to be used as a **unique property key for an object**. This is useful for preventing name collisions when you add properties to an object that you don't control, or for defining "meta" properties.

A. Creating a Symbol

You create a symbol by calling the **Symbol()** factory function. Every symbol is unique.

```
const sym1 = Symbol("description"); const sym2 = Symbol("description"); console.log(sym1 === sym2); // false (They are completely unique)
```

The string **"description"** is just for debugging; it has no effect on the symbol's identity.

B. Using a Symbol as an Object Key

To use a symbol as a key, you **must use bracket notation** **[]**.

```
const user = { name: "Alice" }; // Let's create a "secret" ID for this user. const secretId = Symbol("userId"); // Add the property using the symbol as the key user[secretId] = "xyz-987-abc"; console.log(user); // { name: "Alice", [Symbol(userId)]: "xyz-987-abc" } // To access it, you must use the original symbol variable console.log(user[secretId]); // "xyz-987-abc" // You CANNOT access it with a string console.log(user["secretId"]); // undefined
```

This ensures that your **secretId** property will never accidentally conflict with a potential future property named **"secretId"**.

C. Symbols are "Hidden" from Normal Iteration

Symbol properties are not included in `for...in` loops or `Object.keys()`, which makes them ideal for metadata that shouldn't interfere with normal object operations.

```
for (const key in user) { console.log(key); // Only outputs: "name" } console.log(
Object.keys(user)); // ["name"] // To get the symbol properties, you must use a
special method: const symbolKeys = Object.getOwnPropertySymbols(user); console.lo
g(symbolKeys); // [Symbol(userId)] console.log(user[symbolKeys[0]]); // "xyz-987-
abc"
```



Exported by Print Notion