queries.sql

```sql
CREATE TABLE Student (
    Course VARCHAR(50)
);

INSERT INTO Student
VALUES (101, 'Rahul', 20, 'BCA');

INSERT INTO Student
VALUES (102, 'Ananya', 19, 'BCA');

INSERT INTO Student
VALUES (103, 'Kiran', 21, 'BCA');

SELECT * FROM Student;

UPDATE Student
SET Age = 21
WHERE Student_ID = 101;

SELECT * FROM Student;

DELETE FROM Student
WHERE Student_ID = 103;

SELECT * FROM Student;
```

I/O | AI Agent

STDIN

Input for the program (Optional)

Output:

```
|        102 | Ananya |   19 | BCA    |
|        103 | Kiran  |   21 | BCA    |
+------------+--------+------+--------+
+------------+--------+------+--------+
| Student_ID | Name   | Age  | Course |
+------------+--------+------+--------+
|        101 | Rahul  |   21 | BCA    |
|        102 | Ananya |   19 | BCA    |
|        103 | Kiran  |   21 | BCA    |
+------------+--------+------+--------+
+------------+--------+------+--------+
| Student_ID | Name   | Age  | Course |
+------------+--------+------+--------+
|        101 | Rahul  |   21 | BCA    |
|        102 | Ananya |   19 | BCA    |
+------------+--------+------+--------+
```

queries.sql

```sql
CREATE TABLE Student (
    Student_ID INT,
    Name VARCHAR(50),
    Age INT,
    Course VARCHAR(50)
);

INSERT INTO Student
VALUES (101, 'Rahul', 20, 'BCA');

INSERT INTO Student
VALUES (102, 'Ananya', 19, 'BCA');

INSERT INTO Student
VALUES (103, 'Kiran', 21, 'BCA');

SELECT * FROM Student;

UPDATE Student
SET Age = 21
WHERE Student_ID = 101;

SELECT * FROM Student;

DELETE FROM Student
```

I/O | AI Agent

STDIN

Input for the program (Optional)

Output:

```
+------------+--------+------+--------+
| Student_ID | Name   | Age  | Course |
+------------+--------+------+--------+
|        101 | Rahul  |   20 | BCA    |
|        102 | Ananya |   19 | BCA    |
|        103 | Kiran  |   21 | BCA    |
+------------+--------+------+--------+
+------------+--------+------+--------+
| Student_ID | Name   | Age  | Course |
+------------+--------+------+--------+
|        101 | Rahul  |   21 | BCA    |
|        102 | Ananya |   19 | BCA    |
|        103 | Kiran  |   21 | BCA    |
+------------+--------+------+--------+
+------------+--------+------+--------+
| Student_ID | Name   | Age  | Course |
+------------+--------+------+--------+
```

ady Light Wiki My

queries.sql

```sql
-- DML Example 1

CREATE TABLE Employee (
    Employee_ID INT,
    Employee_Name VARCHAR(50),
    Department VARCHAR(50),
    Salary INT
);

-- INSERT
INSERT INTO Employee VALUES
(101, 'Rahul', 'IT', 30000),
(102, 'Ananya', 'HR', 28000),
(103, 'Kiran', 'Finance', 35000);

SELECT * FROM Employee;

-- UPDATE
UPDATE Employee
SET Salary = 32000
WHERE Employee_ID = 101;

SELECT * FROM Employee;

-- DELETE
```

I/O | AI Agent

STDIN

Input for the program (Optional)

Output:

```
+-------------+---------------+------------+--------+
| Employee_ID | Employee_Name | Department | Salary |
+-------------+---------------+------------+--------+
|         101 | Rahul         | IT         |  30000 |
|         102 | Ananya        | HR         |  28000 |
|         103 | Kiran         | Finance    |  35000 |
+-------------+---------------+------------+--------+
+-------------+---------------+------------+--------+
| Employee_ID | Employee_Name | Department | Salary |
+-------------+---------------+------------+--------+
|         101 | Rahul         | IT         |  32000 |
|         102 | Ananya        | HR         |  28000 |
|         103 | Kiran         | Finance    |  35000 |
+-------------+---------------+------------+--------+
+-------------+---------------+------------+--------+
| Employee_ID | Employee_Name | Department | Salary |
+-------------+---------------+------------+--------+
```

queries.sql

```sql
CREATE TABLE Employee (
    Department VARCHAR(50),
    Salary INT
);

-- INSERT
INSERT INTO Employee VALUES
(101, 'Rahul', 'IT', 30000),
(102, 'Ananya', 'HR', 28000),
(103, 'Kiran', 'Finance', 35000);

SELECT * FROM Employee;

-- UPDATE
UPDATE Employee
SET Salary = 32000
WHERE Employee_ID = 101;

SELECT * FROM Employee;

-- DELETE
DELETE FROM Employee
WHERE Employee_ID = 103;

SELECT * FROM Employee;
```

I/O | AI Agent

STDIN

Input for the program (Optional)

Output:

```
|         102 | Ananya        | HR         |  28000 |
|         103 | Kiran         | Finance    |  35000 |
+-------------+---------------+------------+--------+
+-------------+---------------+------------+--------+
| Employee_ID | Employee_Name | Department | Salary |
+-------------+---------------+------------+--------+
|         101 | Rahul         | IT         |  32000 |
|         102 | Ananya        | HR         |  28000 |
|         103 | Kiran         | Finance    |  35000 |
+-------------+---------------+------------+--------+
+-------------+---------------+------------+--------+
| Employee_ID | Employee_Name | Department | Salary |
+-------------+---------------+------------+--------+
|         101 | Rahul         | IT         |  32000 |
|         102 | Ananya        | HR         |  28000 |
+-------------+---------------+------------+--------+
```

queries.sql

```sql
-- DML Example 2

CREATE TABLE Product (
    Product_ID INT,
    Product_Name VARCHAR(50),
    Category VARCHAR(50),
    Price INT
);

-- INSERT
INSERT INTO Product VALUES
(1, 'Laptop', 'Electronics', 50000),
(2, 'Keyboard', 'Accessories', 1500),
(3, 'Mouse', 'Accessories', 800);

SELECT * FROM Product;

-- UPDATE
UPDATE Product
SET Price = 1800
WHERE Product_ID = 2;

SELECT * FROM Product;

-- DELETE
```

I/O | AI Agent

STDIN

Input for the program (Optional)

Output:

```
+------------+--------------+-------------+-------+
| Product_ID | Product_Name | Category    | Price |
+------------+--------------+-------------+-------+
|          1 | Laptop       | Electronics | 50000 |
|          2 | Keyboard     | Accessories |  1500 |
|          3 | Mouse        | Accessories |   800 |
+------------+--------------+-------------+-------+
+------------+--------------+-------------+-------+
| Product_ID | Product_Name | Category    | Price |
+------------+--------------+-------------+-------+
|          1 | Laptop       | Electronics | 50000 |
|          2 | Keyboard     | Accessories |  1800 |
|          3 | Mouse        | Accessories |   800 |
+------------+--------------+-------------+-------+
+------------+--------------+-------------+-------+
| Product_ID | Product_Name | Category    | Price |
+------------+--------------+-------------+-------+
```

queries.sql

```sql
CREATE TABLE Product (
    Category VARCHAR(50),
    Price INT
);

-- INSERT
INSERT INTO Product VALUES
(1, 'Laptop', 'Electronics', 50000),
(2, 'Keyboard', 'Accessories', 1500),
(3, 'Mouse', 'Accessories', 800);

SELECT * FROM Product;

-- UPDATE
UPDATE Product
SET Price = 1800
WHERE Product_ID = 2;

SELECT * FROM Product;

-- DELETE
DELETE FROM Product
WHERE Product_ID = 3;

SELECT * FROM Product;
```

I/O | AI Agent

STDIN

Input for the program (Optional)

Output:

```
|          2 | Keyboard     | Accessories |  1500 |
|          3 | Mouse        | Accessories |   800 |
+------------+--------------+-------------+-------+
+------------+--------------+-------------+-------+
| Product_ID | Product_Name | Category    | Price |
+------------+--------------+-------------+-------+
|          1 | Laptop       | Electronics | 50000 |
|          2 | Keyboard     | Accessories |  1800 |
|          3 | Mouse        | Accessories |   800 |
+------------+--------------+-------------+-------+
+------------+--------------+-------------+-------+
| Product_ID | Product_Name | Category    | Price |
+------------+--------------+-------------+-------+
|          1 | Laptop       | Electronics | 50000 |
|          2 | Keyboard     | Accessories |  1800 |
+------------+--------------+-------------+-------+
```