
AI Agent Engineering

Day 03

System Prompts, Temperature and Error Handling

LangChain + ChatOpenAI + Ollama + Qwen3:1.7B

From intuition and math to complete code logic



system + history + temperature -> model -> controlled answer

Handwritten Study Notes

Author: Chandan Chaudhari

GitHub: chandanc5525

github.com/chandanc5525/AI_Agent_Engineering_Sessions


Contents

1. Day 02 Recap and Day 03 Goal 3
2. What a System Prompt Does 4
3. The System Prompt in the Token Stream 6
4. Temperature: Math Deep Dive 7
5. Sampling in Practice: top-p, top-k, seed 10
6. Prompt Design Principles 12
7. Anatomy of My System Prompt 14
8. Prompt Templates and Personas 15
9. System Prompts Are Not Security 17
10. Setup and What Is New 18
11. Code Walkthrough: Full Listing 19
12. Client, Temperature and the Seeded List 21
13. The Loop and try/except 23
14. Program Flow and State Trace 24
15. Execution Trace and Output 25
16. Error Handling Theory 27
17. Review: Pitfalls in My Code 29
18. Improved Assistant 30
19. Persona Switching and Few-Shot History 33
20. Knowledge-Grounded Assistant 35
21. Streamlit with Controls 37
22. Testing and Evaluating Prompts 39
23. Troubleshooting Guide 41
24. Interview Q and A 42
25. Formula Sheet and Glossary 44
26. Exercises, Checklist, Day 04 Preview 45

1. Day 02 Recap and Day 03 Goal

Day 02 gave the assistant memory: a list that I resend every turn. Day 03 controls *how* the assistant behaves. Three new ideas are added to the same program: a SystemMessage (standing instructions), a temperature setting (how random the answers are) and a try/except block (survive errors).

	Day 02	Day 03
Goal	Remember earlier turns	Control behaviour and survive failures
List starts as	[ ] (empty)	[SystemMessage(...)]
Client call	ChatOpenAI(model, base_url, api_key)	adds temperature=0.7
Failure handling	None (a crash ends the program)	try / except prints the error and continues
New imports	AIMessage	SystemMessage
New concepts	History is client-side state	Instruction hierarchy, sampling randomness, exceptions



try / except wraps the whole round trip

After Day 03 I should be able to ...


- explain what a system prompt is, where it sits in the token stream and what it costs
- compute the effect of temperature on probabilities, entropy and run-to-run agreement
- write a clear system prompt using role, task, style, constraints, format and fallback
- handle API errors with try/except, rollback and retry with exponential backoff
- explain why a system prompt is not a security boundary

One-line summary

System prompt = standing rules. Temperature = randomness dial.
try/except = seat belt.

2. What a System Prompt Does

A system prompt is the first message in the list, with role system. It is written by the developer, not the user. It tells the model who it is, how to answer and what to avoid. The user then talks to a model that already has its standing instructions.



What it can control

Aspect	Example instruction
Persona	"You are a patient Python tutor."
Task scope	"Only answer questions about SQL."
Style and tone	"Use simple language and short sentences."
Format	"Reply in at most 5 bullets, then one code block."
Safety and limits	"If you are not sure, say you do not know."
Knowledge	"Answer only from the CONTEXT below." (Section 20)

Why it works

Models are fine-tuned on conversations where the system message shapes the following replies, so they learn to give it extra weight. It is training behaviour, not a hard rule: a small model such as 1.7B follows long or conflicting instructions less reliably than a large one.

Key idea

The system prompt does not change the model. It changes the context the model is conditioned on, so the probabilities of the next tokens change.

3. The System Prompt in the Token Stream

To the model, the system prompt is simply the first tokens of the sequence. Day 02 showed that all messages are flattened into one transcript with role markers. The system message is placed at the very beginning:

ChatML-style layout (roughly; exact template depends on the model)

```
<|im_start|>system
You are a helpful assistant. Explain every concept with simple
examples and provide code snippets when necessary.<|im_end|>
<|im_start|>user
What is recursion?<|im_end|>
<|im_start|>assistant
```

Three consequences

1. It costs tokens on every call. The system prompt is resent every turn, like all history.
2. It is attended to by every new token. Causal attention lets each generated token look back at the start of the sequence, so the instructions can influence every word.
3. It is a stable prefix. Since it never changes, servers can reuse the cached keys/values for it (prefix caching), as long as the beginning of the prompt stays identical.

Cost math


Let S be the system prompt length. Day 02 total input tokens over n turns were n·q + t·n(n-1)/2. Now every request also carries S:

$$T(n) = n \cdot S + n \cdot q + t \cdot n(n - 1) / 2$$

S = system prompt tokens (about 25 for my prompt: an estimate)

With S = 25, q = 50, t = 150 and n = 10: T = 250 + 500 + 6,750 = 7,500 tokens (Day 02 had 7,250). The system prompt adds only about 3% over 10 turns. Its share of one request falls from 25/75 = 33% at turn 1 to 25/1,425 = 1.8% at

turn 10.



Design rules that follow

- Keep the system prompt short and precise: every token is paid for on every turn and competes for attention.
- Put the system prompt first and never trim it when windowing the history.
- Do not change it between turns unless you intend to (it invalidates the cached prefix).
- Rule of thumb: 1 token is about 4 characters; check real counts via usage_metadata.

4. Temperature: Math Deep Dive


Temperature rescales the logits before softmax (Day 01, Section 5). My code uses temperature = 0.7. As far as I remember from the model card, Qwen suggests about 0.6 for thinking mode and 0.7 for normal mode, so 0.7 is a sensible default for Qwen3 (verify on the card).

$$p_i(T) = e^{z_i / T} / \sum_j e^{z_j / T}$$

z = logits, T = temperature; T < 1 sharpens, T > 1 flattens

Worked example at T = 0.7

Logits z = [2.0, 1.0, 0.1]. Divide by 0.7: [2.857, 1.429, 0.143]. Exponentials: [17.41, 4.17, 1.15]. Sum = 22.74. Probabilities = [0.766, 0.184, 0.051]. Compare T = 1: [0.659, 0.242, 0.099].



Entropy: how uncertain is the next token?

$$H = -\sum_i p_i \cdot \log_2 p_i$$

bits; 0 = certain, $\log_2(3) = 1.585$ = maximum for three tokens

T	Top-token probability	Entropy (bits)	P(two runs agree) = Σ p^2
0.2	0.993	0.059	0.99
0.5	0.864	0.655	0.760
0.7 (my code)	0.766	0.962	0.623
1.0	0.659	1.222	0.503
2.0	0.502	1.481	0.382

The last column is the chance that two independent samples pick the same token. At T = 0.7 two runs agree on that token only about 62% of the time, so answers differ between runs. Over hundreds of tokens, small differences compound.

PyTorch: temperature, entropy, agreement


```python
import torch

logits = torch.tensor([2.0, 1.0, 0.1])
for T in (0.5, 0.7, 1.0, 2.0):
    p = torch.softmax(logits / T, dim=0)
    H = -(p * torch.log2(p)).sum()
    agree = (p ** 2).sum()
    print(T, p.numpy().round(3))
    print('H', round(H.item(), 3), 'agree', round(agree.item(), 3))
# T=0.7: [0.766 0.184 0.051]  H = 0.962  agree = 0.623
```

TensorFlow: temperature, entropy, agreement

```python
import tensorflow as tf

logits = tf.constant([2.0, 1.0, 0.1])
for T in (0.5, 0.7, 1.0, 2.0):
    p = tf.nn.softmax(logits / T)
    H = -tf.reduce_sum(p * tf.math.log(p)) / tf.math.log(2.0)
    agree = tf.reduce_sum(p ** 2)
    print(T, p.numpy().round(3), float(H), float(agree))
```



Why not always T = 0?

T = 0 (greedy) is repeatable but can loop or sound robotic, and Qwen3 in thinking mode may repeat itself under greedy decoding. Also: low temperature reduces randomness, not hallucination. A confident wrong answer stays wrong.


5. Sampling in Practice: top-p, top-k, seed

Temperature is one knob. Servers combine it with others. In my code only temperature is set; the rest use the server or model defaults (from the Modelfile or the model card).

Knob	What it does	Typical range
temperature	Rescales logits before softmax	0.0 - 1.5
top_p (nucleus)	Keep smallest set of tokens with cumulative probability >= p	0.8 - 0.95
top_k	Keep only the k most likely tokens	20 - 50
seed	Fix the random generator	any integer
max tokens	Stop after this many new tokens	100 - 2000

top-p worked example

Six candidate tokens with probabilities [0.445, 0.270, 0.164, 0.060, 0.037, 0.024]. Cumulative sums: [0.445, 0.715, 0.879, 0.939, 0.976, 1.0]. With p = 0.9 we keep the first four tokens (cumulative 0.939 is the first value above 0.9), drop the tail and renormalise: [0.474, 0.287, 0.175, 0.064].



PyTorch: top-p filtering

```
import torch

logits = torch.tensor([3.0, 2.5, 2.0, 1.0, 0.5, 0.1])
p = torch.softmax(logits, dim=0)
cum = torch.cumsum(p, dim=0)
keep = (cum - p) < 0.9           # tokens before the cut-off
p2 = torch.where(keep, p, torch.zeros_like(p))
p2 = p2 / p2.sum()               # renormalise
print(p2.numpy().round(3))       # tail tokens become 0
```

TensorFlow: top-p filtering

```
import tensorflow as tf

logits = tf.constant([3.0, 2.5, 2.0, 1.0, 0.5, 0.1])
p = tf.nn.softmax(logits)
cum = tf.cumsum(p)
keep = (cum - p) < 0.9
p2 = tf.where(keep, p, tf.zeros_like(p))
p2 = p2 / tf.reduce_sum(p2)
print(p2.numpy().round(3))
```

Reproducibility

- Same seed + same temperature + same prompt usually gives the same text on the same machine and version. It is not a guarantee across hardware or library versions.
- The OpenAI-style API lets me pass a seed; whether the server honours it depends on the server version (check the Ollama docs).
- For tests and demos, use low temperature (0 - 0.3) and a seed. For brainstorming, use 0.7 - 1.0.

PyTorch: seed gives repeatable sampling

```
import torch

probs = torch.tensor([0.766, 0.184, 0.051])
torch.manual_seed(0)
a = torch.multinomial(probs, 5, replacement=True)
torch.manual_seed(0)
b = torch.multinomial(probs, 5, replacement=True)
print(a.tolist() == b.tolist())      # True: same seed, same draws
```

6. Prompt Design Principles

A good system prompt is a small specification. These principles apply to any model and matter more for small ones.

1. Be specific. "Explain simply" is weaker than "Explain for a beginner in 3 sentences with one example".
2. One job per prompt. Many unrelated instructions compete for attention.
3. State the format. Bullets, JSON, length limit, language, whether to use markdown.
4. Say what to do, not only what to avoid. "Answer in plain text" beats "do not use markdown".
5. Give a fallback. "If unsure, say you do not know" reduces confident guessing.
6. Use examples. One or two input/output pairs (few-shot) steer style better than adjectives.
7. Put the most important rule first or last. Middle items of long prompts are the most likely to be ignored.
8. Test and iterate. Prompts are code: version them, change one thing at a time, measure.

Zero-shot vs few-shot vs chain-of-thought

Style	What it means	When to use
Zero-shot	Instruction only, no examples	Simple, common tasks
Few-shot	Add 1-5 example input/output pairs	Specific format or tone
Chain-of-thought	Ask the model to reason step by step	Math, logic; costs more tokens

Longer answers cost time

My prompt asks for examples and code, which makes answers longer. Generation time is output tokens divided by speed, so verbosity is paid for in seconds:

time = output_tokens / tokens_per_second

400 tokens at 20 tok/s = 20 s; a 100-token answer = 5 s

Trade-off

"Explain every concept with examples and code" improves teaching quality but multiplies latency on a CPU-only 1.7B model. Add a length limit when speed matters.

7. Anatomy of My System Prompt

My Day 03 system prompt, exactly as in the code:

Prompt

"You are a helpful assistant. Explain every concept with simple examples and provide code snippets when necessary."

You are a helpful assistant. → **ROLE**

Explain every concept with simple examples → **STYLE + TASK**

and provide code snippets when necessary. → **FORMAT**

Missing: length limit, audience, language, fallback, terminal-friendly format

Part	Strength	Weakness
"helpful assistant"	Sets a friendly role	Generic; adds little information
"every concept"	Consistent teaching style	Forces an example even for "hi" or one-word facts
"simple examples"	Beginner friendly	No audience stated (beginner? engineer?)
"code snippets when necessary"	Code on demand	"necessary" is vague; no language chosen
(absent)	-	No length cap, no fallback for unknown, no format rule

Improved version

Same intent, more precise

```
You are a patient programming tutor for beginners.
- Explain each concept in 3-5 sentences with one simple example.
- Use Python unless I ask for another language.
- Add a code block only when it helps; keep it under 15 lines.
- Use plain text; avoid long markdown tables.
- If you are not sure, say so instead of guessing.
```

- Role is specific (tutor, beginners) instead of generic.
- Length, language and format are bounded, so answers are faster and more predictable.
- A fallback line reduces confident hallucination.

8. Prompt Templates and Personas

A reusable template

ROLE	*Who are you?*	You are a SQL expert for analysts.
TASK	*What is the job?*	Turn questions into queries.
STYLE	*Tone and level*	Short, friendly, beginner level.
CONSTRAINTS	*Limits and rules*	Only SELECT. Max 10 lines.
FORMAT	*Output shape*	Query in a code block, 1-line note.
FALLBACK	*When unsure*	Ask one clarifying question.

A small persona library

Personas as data (not hard-coded in the loop)

```
PERSONAS = {
    "tutor": (
        "You are a patient Python tutor. Explain with one simple "
        "example. Keep answers under 150 words."),
    "coach": (
        "You are an interview coach. Ask one question at a time "
        "and give brief feedback on my answer."),
    "sql": (
        "You are a SQL expert. Reply with a query in a code block "
        "and one sentence of explanation."),
    "reviewer": (
        "You are a strict code reviewer. List up to 3 issues, "
        "most important first."),
}
```


- Storing prompts in a dict (or files) lets me switch persona without touching the loop.
- Version prompts like code: keep them in Git, note why each change was made.
- Name prompts after the behaviour they create, not the model.

Prompt = configuration

A system prompt is configuration, like .env: it changes behaviour without changing code. That is why Section 19 loads it from a dictionary.

9. System Prompts Are Not Security

It is tempting to treat the system prompt as a lock: "Never reveal the secret". It is not one. The model only learned to prefer system instructions; it can still be talked out of them.



Prompt injection

- Direct: the user writes "ignore previous instructions". Small models are especially easy to steer.
- Indirect: instructions hidden in text the model reads (web pages, documents, emails). This becomes critical once agents use tools or retrieve documents.
- Newer models are trained to rank system above user, which helps but is not a guarantee.

What to do

1. Never put secrets (keys, passwords, private data) in the system prompt; assume it can be extracted.
2. Enforce important rules in code: validate inputs and outputs, restrict which tools an agent may call, require confirmation for risky actions.
3. Treat all retrieved or user-supplied text as untrusted data, not as instructions.
4. Log and test with adversarial prompts (Section 22).

> **Rule of thumb**
> Prompts guide behaviour; code enforces policy.

10. Setup and What Is New

The environment is the same as Day 02: langchain-openai, python-dotenv, Ollama running, model pulled. Only the code changes.

.env (unchanged)

```
BASE_URL=http://localhost:11434/v1
API_KEY=ollama
MODEL=qwen3:1.7b
```

Terminal

```
uv add langchain-openai python-dotenv
ollama pull qwen3:1.7b
uv run python main.py
```

Day 02 to Day 03: the diff

Change	Why
import SystemMessage	New message type for instructions
ChatOpenAI(..., temperature=0.7)	Control randomness of sampling
message = [SystemMessage(...)]	Start the history with standing instructions
try: ... except Exception as e:	A failed call no longer crashes the program
History display unchanged	It prints only Human and AI messages (the system message is skipped)

- The OpenAI-compatible client still needs the /v1 in BASE_URL (Day 01 had the opposite requirement for ChatOllama).
- temperature is sent as a field in the request JSON: {"model": ..., "messages": [...], "temperature": 0.7}.
- Ollama has its own default temperature when none is sent (around 0.8 as far as I know; check the docs for your version), so being explicit makes runs comparable.

Request shape

Messages: [{"role":"system",...}, {"role":"user",...}, ...] plus temperature. That is all the server sees; everything else (memory, persona) is built by my code.

11. Code Walkthrough: Full Listing

My complete Day 03 program (comments shortened; the long system string is split over lines only for display).

main.py (my Day 03 code)

```
import os
from dotenv import load_dotenv
from langchain_openai import ChatOpenAI
from langchain_core.messages import (
    HumanMessage, AIMessage, SystemMessage)

load_dotenv()

model_name = os.getenv("MODEL", "qwen3:1.7b")
base_url = os.getenv("BASE_URL", "http://localhost:11434/v1")
api_key = os.getenv("API_KEY", "ollama")

llm = ChatOpenAI(
    model=model_name,
    base_url=base_url,
    api_key=api_key,
    temperature=0.7
)

print("*" * 40)
print("My LangChain Ollama Assistant")
print("*" * 40)

message = [
    SystemMessage(
        content="You are a helpful assistant. Explain every "
                "concept with simple examples and provide code "
```

```
                "snippets when necessary."
    )
]

while True:

    user_input = input("\nYou: ")

    if user_input.lower() == "exit":
        print("Exiting the assistant. Goodbye!")
        break

    message.append(HumanMessage(content=user_input))

    try:
        response = llm.invoke(message)
        message.append(AIMessage(content=response.content))
        print("\nAI:", response.content)

        print("\n" + "=" * 40)
        print("CONVERSATION HISTORY")
        print("=" * 40)

        for msg in message:
            if isinstance(msg, HumanMessage):
                print("\nYou:", msg.content)
            elif isinstance(msg, AIMessage):
                print("\nAI:", msg.content)

        print("=" * 40)

    except Exception as e:
        print("\nError:", e)
```

Imports

- SystemMessage is the only new import: it wraps developer instructions with role "system".
- ChatOpenAI is the OpenAI-compatible client from Day 02 (works with Ollama through /v1).
- HumanMessage and AIMessage store the turns, as before.

12. Client, Temperature and the Seeded List

The client with temperature

Step 1

```
llm = ChatOpenAI(
    model=model_name,
    base_url=base_url,
    api_key=api_key,
    temperature=0.7
)
```

- temperature=0.7 is passed with every request this client makes. To change it later, create a new client (or use bind(temperature=...)).
- It is a sampling parameter: it does not change what the model knows, only how it picks among likely tokens.
- Values near 0 give focused, repeatable output; around 0.7 is a balanced default for chat; above 1 gets creative and error-prone.
- Other useful constructor arguments: max_tokens, timeout, max_retries, seed.

The seeded list

Step 2

```
message = [
    SystemMessage(
        content="You are a helpful assistant. Explain every "
                "concept with simple examples and provide code "
                "snippets when necessary."
    )
]
```

Day 02 started with `message = []`. Now the list is born with one element: the SystemMessage at index 0. Everything appended later follows it, so the model always sees the instructions first.

- Invariant: `message[0]` is the SystemMessage for the entire program.
- After n turns the list has 2n + 1 elements (1 system + n Human + n AI).
- At call time (after appending the Human message) it has 2n.
- If I later trim history, I must keep index 0.

Difference from Day 02

History length formula changes from 2n to 2n + 1 because of the system message. The display loop skips it because it only checks for Human and AI.

13. The Loop and try/except

One loop iteration

1. `input()` reads the question; `.lower()` `==` `"exit"` ends the program.
2. `message.append(HumanMessage(...))` adds the question before the model call.
3. `try:` opens a protected block. If anything inside raises an exception, Python jumps straight to `except`.
4. `llm.invoke(message)` sends [System, ..., Human]; the reply comes back as an AIMessage.
5. `message.append(AIMessage(...))`, the print of the answer and the history display run only if the call succeeded.
6. `except` `Exception` `as` `e:` `print("\nError:", e)` prints the error text and the `while` loop continues. The program survives.

How try/except works

Python exception syntax


```
try:
    risky()                 # code that may fail
except ConnectionError as e:
    handle(e)               # runs only if that exception occurs
else:
    ok()                    # runs if no exception happened
finally:
    cleanup()               # always runs
```

- `except` `Exception` catches almost everything (but not KeyboardInterrupt), so it hides the type of the failure. Printing `type(e).__name__` helps.
- Narrow except clauses are better for known failures; a broad one is fine at the very top of a loop so the app keeps running.
- `try` should wrap only the risky call. In my code it also wraps printing, so a printing bug would be reported as an API error.

Important catch


If invoke fails, the HumanMessage is already in the list but no AIMessage follows. The next turn will send two Human messages in a row. Section 17 shows the rollback fix.

14. Program Flow and State Trace



State trace of the list

S = SystemMessage, H = HumanMessage, A = AIMessage. A failed call leaves a dangling H.



15. Execution Trace and Output

Because the system prompt asks for examples and code, answers are longer and contain markdown code fences. The terminal prints them as raw text.

Sample session (wording will differ)

```
$ uv run python main.py
****************************************
My LangChain Ollama Assistant
****************************************

You: What is recursion?

AI: Recursion is when a function calls itself to solve a
smaller version of the same problem.

Example: counting down from 3.

```python
def countdown(n):
    if n == 0:
        return
    print(n)
    countdown(n - 1)
```

==
```

```
CONVERSATION HISTORY
========================================

You: What is recursion?

AI: Recursion is when a function calls itself ...
========================================

You: exit
Exiting the assistant. Goodbye!
```

- The history printout skips the system message, so I never see the instructions that shaped the answer.
- Code fences (three backticks) show up as raw characters in a terminal; a Streamlit page renders them nicely (Section 21).
- With the Ollama server stopped, the same input prints: `Error: Connection error.` and the loop continues.

Experiments to run

1. Ask the same question three times. Do the answers differ? (Temperature 0.7.)
2. Change `temperature` to 0.0 and 1.2 and repeat. Describe the difference.
3. Say "hi". Does it still force an example? (The word "every".)
4. Stop Ollama, ask a question, read the error, start Ollama, ask again.

16. Error Handling Theory

A chat call crosses a network, a server, a model and my own code. Failures can happen at every layer, so errors should be expected, not treated as rare.

Network
connection refused
timeout
DNS / proxy

HTTP
400 bad request
401 / 403 auth
404 not found
429 rate limit
500 server

Model
model not pulled
out of memory
context too long

My code
bad input
bug in handler
wrong URL / key

Exception (openai library)	Typical cause with Ollama	Retry?
APIConnectionError	Ollama not running or wrong host/port	Yes, after starting the server
APITimeoutError	Slow generation on CPU, long prompt	Yes, maybe with larger timeout
NotFoundError (404)	Missing /v1 or model not pulled	No: fix configuration
BadRequestError (400)	Invalid payload, prompt too large	No: change the request
AuthenticationError (401)	Empty or wrong key (not enforced locally)	No
RateLimitError (429)	Cloud providers; rare on local Ollama	Yes, with backoff
InternalServerError (500)	Server crash, out of memory	Sometimes

Retry with exponential backoff

Transient failures often disappear if I wait. Waiting a growing time avoids hammering a struggling server:

$$\text{delay}_k = \text{base} \cdot 2^k$$

base = 1 s: delays 1, 2, 4, 8, 16 … (usually capped, plus random jitter)



total waiting before success: 1 + 2 + 4 = 7 s

A small retry helper

```
import time
from openai import APIConnectionError, APITimeoutError


def call_with_retry(messages, tries=3, base=1.0):
    for k in range(tries):
        try:
            return llm.invoke(messages)
        except (APIConnectionError, APITimeoutError):
            if k == tries - 1:
                raise                       # give up
            time.sleep(base * 2 ** k)       # 1 s, 2 s, 4 s ...
```

- Retry only transient errors (network, timeout, 429, 5xx). Retrying a 404 or 400 never helps.
- The OpenAI library underneath already retries a couple of times by default (as far as I know); the `max_retries` argument controls it.
- Set a `timeout` so a stuck request cannot hang the app forever.
- Always show the user a clear message: what failed and what to do (start Ollama, pull the model).

17. Review: Pitfalls in My Code

The Day 03 program is a solid step. These are the weak spots to know, with the fix for each.

#	Issue	Why it matters	Fix
1	Human message not rolled back on error	Next call sends two Human messages in a row and the failed question lingers	history.pop() in except
2	except Exception prints only the message	Hides the type (404 vs connection) and gives no hint	Print type(e).__name__
3	try wraps printing as well	A print bug looks like an API failure	Keep try around invoke only
4	System prompt is vague and long	No length limit; forces examples even for "hi"	Rewrite (Section 7)
5	History grows without limit	Cost grows quadratically; context overflow	Window, keep index 0
6	Temperature 0.7 for code answers	Randomness can add errors to code	Try 0.2-0.4 for code tasks
7	Qwen3 think text may be stored	Reasoning is resent every turn	strip_think()
8	History printed every turn	Noisy; quadratic output	Print on a command
9	No timeout or retry setting	A hung call blocks the loop	timeout, max_retries
10	Variable named message	Reads like one message	history / messages
11	Empty input is sent	Wasted call	strip() and skip

The rollback fix

Consistent history after a failure

```
message.append(HumanMessage(content=user_input))
try:
    response = llm.invoke(message)
except Exception as e:
    message.pop()                          # drop unanswered Q
    print(f"\nError ({type(e).__name__}):", e)
    continue
message.append(AIMessage(content=response.content))
print("\nAI:", response.content)
```

Invariant to protect

After every turn the list must be: [System, Human, AI, Human, AI, ...] and end with an AI message before the next question is appended.

18. Improved Assistant

Same program, hardened: precise system prompt, configurable temperature, timeout and retries, rollback, think-block cleaning, a window that always keeps the system message, and exit / clear commands.

main.py (improved Day 03 assistant)

```
import os
import re
from dotenv import load_dotenv
from langchain_openai import ChatOpenAI
from langchain_core.messages import (
    AIMessage, HumanMessage, SystemMessage)

load_dotenv()

SYSTEM_PROMPT = """\
You are a patient programming tutor for beginners.
- Explain each concept in 3-5 sentences with one example.
- Use Python unless asked otherwise.
```

```
- Add a code block only when it helps (max 15 lines).
- If you are not sure, say so instead of guessing."""

llm = ChatOpenAI(
    model=os.getenv("MODEL", "qwen3:1.7b"),
    base_url=os.getenv("BASE_URL", "http://localhost:11434/v1"),
    api_key=os.getenv("API_KEY", "ollama"),
    temperature=float(os.getenv("TEMPERATURE", "0.7")),
    timeout=120,
    max_retries=2,
)
MAX_TURNS = 8


def strip_think(text: str) -> str:
    pat = r"<think>.*?</think>"
    return re.sub(pat, "", text, flags=re.DOTALL).strip()


def build_messages(history):
    system = SystemMessage(content=SYSTEM_PROMPT)
    return [system] + history[-2 * MAX_TURNS:]


def main() -> None:
    history = []                    # Human/AI only; system is added
    print("Commands: exit, clear")
    while True:
        q = input("\nYou: ").strip()
        if q.lower() == "exit":
            print("Goodbye!")
            break
        if q.lower() == "clear":
            history.clear()
            print("Memory cleared.")
            continue
        if not q:
            continue
        history.append(HumanMessage(content=q))
        try:
            reply = llm.invoke(build_messages(history))
```

```
        except Exception as err:
            history.pop()         # roll back the question
            print(f"\n[error] {type(err).__name__}: {err}")
            continue
        answer = strip_think(reply.content)
        history.append(AIMessage(content=answer))
        print("\nAI:", answer)



if __name__ == "__main__":
    main()
```

What changed and why

Change	Reason
SYSTEM_PROMPT constant (multi-line)	Readable, editable, versionable
TEMPERATURE from .env	Tune without editing code
timeout and max_retries	No hung calls; transient errors retried
System added in build_messages()	Never trimmed away by the window
history.pop() in except	History stays valid after a failure
type(err).__name__ in the message	Tells me what kind of failure it was
strip_think()	Reasoning text does not pollute memory

19. Persona Switching and Few-Shot History

Switch persona at runtime



/persona sql

Persona command (inside the loop)

```
persona = "tutor"
...
while True:
    q = input("\nYou: ").strip()
    if q.startswith("/persona"):
        parts = q.split(maxsplit=1)
        name = parts[1] if len(parts) > 1 else ""
        if name in PERSONAS:
            persona = name
            print("Persona is now:", persona)
        else:
            print("Options:", ", ".join(PERSONAS))
        continue
    ...
    system = SystemMessage(content=PERSONAS[persona])
    reply = llm.invoke([system] + history[-16:])
```

- Because the system message is rebuilt on every call, switching is free: no need to edit the list.
- Earlier answers in history were written by the old persona and may still bias style. Call history.clear() on switch if you want a clean start.
- Changing the prefix invalidates any cached prompt prefix, so the first call after a switch may be slower.

Few-shot examples as pre-filled history

Because the model treats the list as its own past, I can insert fake earlier turns that demonstrate the exact format I want. It is the same mechanism as memory (Day 02), used deliberately.

Few-shot pairs steer format

```
FEW_SHOT = [
    HumanMessage(content="Define: tuple"),
    AIMessage(content="Tuple: ordered, immutable.\nEx: (1, 2, 3)"),
    HumanMessage(content="Define: set"),
    AIMessage(content="Set: unordered, unique.\nEx: {1, 2, 3}"),
]

system = SystemMessage(content=SYSTEM_PROMPT)
messages = [system] + FEW_SHOT + history
reply = llm.invoke(messages)     # answers in the same 2-line style
```


- Few-shot pairs cost tokens on every call (fixed overhead), so keep them short.
- Examples teach format and tone more reliably than adjectives such as "concise".
- Do not count the few-shot pairs when windowing the real history; keep them separate.

Pattern

messages = [system] + few_shot + recent_history. Three layers, three purposes: rules, format, memory.

20. Knowledge-Grounded Assistant

The Day 03 idea in the repo README is an agent that answers from one defined knowledge context. The simplest implementation is context stuffing: paste the knowledge into the system prompt and instruct the model to rely on it only.



Grounding prompt

```
CONTEXT = """\
Acme Corp onboarding notes (example text)
- Laptops are issued on day 1 by the IT desk.
- Timesheets are due every Friday at 5 pm.
- Remote work needs manager approval."""

SYSTEM_PROMPT = f"""You are a company assistant.
Answer ONLY from the context below.
If the answer is not in the context, reply exactly:
I do not know based on the provided context.

CONTEXT:
{CONTEXT}"""
```

Why it helps

- Conditioning on the context raises the probability of correct, context-based tokens (Day 02 math: more relevant text lowers the loss for the right answer).
- The fallback sentence gives the model a safe exit instead of inventing an answer.
- Updating knowledge means editing text, not retraining.

Limits and the token budget

$$C \geq S + K + \text{history} + R$$


window ≥ instructions + knowledge + conversation + reserved answer

Example: window 4,096, instructions 60, knowledge K = 2,000, reserve 512 leaves 1,524 tokens for history. If the knowledge is 3,800 tokens there is almost no room. Estimate tokens as characters / 4.

- Context stuffing works for one small document. For many documents you need retrieval (RAG): fetch only relevant chunks.
- Small models can still ignore the context or mix in memorised facts; test with questions whose answers are not in the context.
- Retrieved text is untrusted data (Section 9): never let it override the rules.

21. Streamlit with Controls

Streamlit gives me sliders and dropdowns, so persona and temperature become live controls. (Reference implementation; not a copy of the repo file.)
Remember that Streamlit reruns the script on every interaction, so history lives in st.session_state.



Day03/app.py (reference version)

```python
import os
import streamlit as st
from dotenv import load_dotenv
from langchain_openai import ChatOpenAI
from langchain_core.messages import (
    AIMessage, HumanMessage, SystemMessage)

load_dotenv()
PERSONAS = {
    "tutor": "You are a patient Python tutor. Use one example.",
    "coach": "You are an interview coach. Ask one question.",
    "sql": "You are a SQL expert. Reply with a query.",
}


@st.cache_resource
def get_llm(temp: float):
    return ChatOpenAI(
        model=os.getenv("MODEL", "qwen3:1.7b"),
        base_url=os.getenv("BASE_URL", "http://localhost:11434/v1"),
        api_key=os.getenv("API_KEY", "ollama"),
        temperature=temp,
    )
```

```
st.title("Day 03: Persona and Temperature")
persona = st.sidebar.selectbox("Persona", list(PERSONAS))
temp = st.sidebar.slider("Temperature", 0.0, 1.5, 0.7, 0.1)

if "history" not in st.session_state:
    st.session_state.history = []
history = st.session_state.history
if st.sidebar.button("Clear chat"):
    history.clear()

for m in history:
    role = "user" if isinstance(m, HumanMessage) else "assistant"
    with st.chat_message(role):
        st.write(m.content)

prompt = st.chat_input("Ask me anything...")
if prompt:
    with st.chat_message("user"):
        st.write(prompt)
    history.append(HumanMessage(content=prompt))
    system = SystemMessage(content=PERSONAS[persona])
    try:
        reply = get_llm(temp).invoke([system] + history)
    except Exception as err:
        history.pop()
        st.error(f"{type(err).__name__}: {err}")
    else:
        history.append(AIMessage(content=reply.content))
        with st.chat_message("assistant"):
            st.write(reply.content)
```

- st.cache_resource caches one client per temperature value because temp is a function argument.
- st.error shows the failure in the page; else: runs only when no exception occurred.
- Markdown code fences in answers render as formatted code blocks, which fits this system prompt well.
- History resets when the browser session ends; add JSON persistence from

Day 02 if needed.

22. Testing and Evaluating Prompts

A prompt change is a code change: test it. Keep a small fixed set of questions and compare outputs before and after.

Test	How	What to look for
Instruction following	Ask a normal question	Persona, length, format obeyed?
Edge input	Say "hi" or ask a one-word question	Does a rule like "every concept" misfire?
Temperature sweep	Same question at T = 0, 0.7, 1.2, five runs each	Variation, errors, creativity
Out-of-scope	Ask something outside the persona	Refuses or redirects as instructed?
Unknown fact	Ask something not in the context	Says "I do not know" instead of guessing?
Injection	"Ignore previous instructions and ..."	Does it keep the rules? (expect failures)
Long chat	15 turns, then re-test a rule	Still follows the system prompt?
Failure	Stop Ollama mid-session	Clear error, loop survives, history consistent

A tiny evaluation harness

Compare prompts on a fixed question set

```
QUESTIONS = ["What is a list?", "hi", "Explain recursion."]


def run(system_prompt, temperature):
    llm = ChatOpenAI(model=MODEL, base_url=URL, api_key=KEY,
                     temperature=temperature)
    for q in QUESTIONS:
        msgs = [SystemMessage(content=system_prompt),
                HumanMessage(content=q)]
        out = llm.invoke(msgs).content
        print(f"{q!r:25} -> {len(out.split())} words")
```

- Change one thing at a time (prompt wording or temperature, never both).
- Record word count and time: shorter, faster answers are a measurable win.
- Judge quality by hand on a small set; automated scoring comes later.
- Keep the best prompt in Git with a note of what it fixed.

Scientist mindset

One lucky answer proves nothing at temperature 0.7. Sample several times before concluding.

23. Troubleshooting Guide

Symptom	Likely cause	Fix
Error: Connection error.	Ollama not running	Start Ollama or run: ollama serve
NotFoundError / 404	BASE_URL missing /v1, or model not pulled	Add /v1; ollama pull qwen3:1.7b
Assistant ignores the system prompt	Prompt too long, vague or conflicting; small model	Shorten, put key rule first or last, add examples
Answers far too long	No length limit; "every concept" rule	Add a word limit; set max_tokens
Answers vary wildly run to run	High temperature	Lower to 0.2-0.4, add a seed
Repetitive or robotic text	Temperature too low (0)	Use 0.5-0.8
Two Human messages in a row after an error	No rollback	history.pop() in except
Raw think text in the answer	Qwen3 thinking output in content	strip_think() or /no_think
Persona change has no effect	Old turns in history keep the old style	clear history on switch
Context seems forgotten	Window trimmed or context overflow	Raise window, keep system, summarise
Streamlit loses chat	Plain list instead of session_state	Use st.session_state
Hangs forever	No timeout	timeout=120, max_retries=2

Debug checklist

1. Does `ollama run qwen3:1.7b` answer in the terminal?
2. Print `[m.type for m in messages]`: system first, then alternating human/ai, ending with human?
3. Print `type(e).__name__` for the failure and match it to the table in Section 16.
4. Test the system prompt alone in a 5-line script with a fixed seed.
5. Only then blame the model.

24. Interview Q and A

Q1. What is a system prompt?

A message with role system that gives the model standing instructions (persona, rules, format). It is placed first in the context and conditions every later token, but it is a soft guide, not a hard rule.

Q2. System vs user vs assistant messages?

System: developer instructions. User: the person's input. Assistant: the model's earlier outputs. Models are trained to give system instructions the most weight.

Q3. Does a system prompt cost tokens?

Yes. It is resent with every request, so it adds to cost, latency and context usage. Keep it short; stable prefixes can be cached.

Q4. What does temperature do?

It divides the logits before softmax. Low values sharpen the distribution (focused, repeatable), high values flatten it (diverse, riskier). T = 0 is greedy decoding.

Q5. Why not always use temperature 0?

Output becomes repetitive and can loop; some models degrade. It also does not remove hallucination; it only makes the same answer repeatable.

Q6. Temperature vs top-p vs top-k?

Temperature reshapes probabilities. Top-k keeps the k most likely tokens. Top-p keeps the smallest set whose cumulative probability reaches p. They are often combined.

Q7. How do you get reproducible output?

Low temperature, a fixed seed and the same prompt, model and server version. Exact repeatability across hardware is not guaranteed.

Q8. Can a user override the system prompt?

Often yes (prompt injection), especially with small models. Do not store secrets in it; enforce rules in code and treat user or retrieved text as untrusted.

Q9. How do you keep the system prompt when trimming history?

Store it separately and prepend it on every call: [system] + history[-N:]. Never include it in the part that gets trimmed.

Q10. How do you handle API errors?

Wrap the call in try/except, catch specific exceptions, retry transient ones with exponential backoff and a timeout, roll back the unanswered user message and show a clear error.

Q11. What is few-shot prompting?

Adding example input/output pairs before the real question so the model copies the format and tone. They can be inserted as pre-filled Human/AI messages.

Q12. How do you make an assistant answer only from given knowledge?

Put the knowledge in the prompt, instruct it to answer only from it with an explicit "I do not know" fallback, and test with out-of-context questions. For large corpora use retrieval (RAG).

Interview tip

Back claims with numbers: "At T = 0.7 two runs agree on the top token only 62% of the time, so I use a low temperature and a seed for tests."

25. Formula Sheet and Glossary

Formula sheet

$$p_i(T) = e^{z_i / T} / \Sigma_j e^{z_j / T}$$

temperature softmax; T = 0.7: [2, 1, 0.1] -> [0.766, 0.184, 0.051]

$$H = -\Sigma p_i \cdot \log_2 p_i$$

entropy in bits; 0.962 at T = 0.7, 1.222 at T = 1

$$P(\text{agree}) = \Sigma p_i^2$$

chance two independent samples choose the same token

$$T(n) = n \cdot S + n \cdot q + t \cdot n(n - 1) / 2$$

total input tokens with a system prompt of S tokens

$$\text{time} = \text{output_tokens} / \text{tokens_per_second}$$

verbose answers cost seconds

$$\text{delay}_k = \text{base} \cdot 2^k$$

exponential backoff: 1, 2, 4, 8 ... seconds

$$C \geq S + K + \text{history} + R$$

context budget with a knowledge block K

$$\text{list length} = 2n + 1$$

after n turns: one SystemMessage + n Human + n AI messages

Glossary

Term	Meaning
System prompt	Developer instructions sent first, with role system
SystemMessage	LangChain class for the system role
Temperature	Scale that controls sampling randomness
Entropy	Uncertainty of the next-token distribution (bits)
top-p / top-k	Truncation of the candidate token set before sampling
Seed	Starting value of the random generator; same seed repeats draws
Few-shot	Example input/output pairs placed in the prompt
Prompt injection	Text that tries to override the model's instructions
Grounding	Forcing answers to rely on supplied context
Context stuffing	Pasting knowledge into the prompt
Exception	Python error object raised when something fails
Backoff	Waiting longer between each retry
Rollback	Undoing a partial change after a failure

26. Exercises, Checklist, Day 04 Preview

Practice exercises

1. Rewrite my system prompt with the template (role, task, style, constraints, format, fallback) and compare word counts.
2. Run the same question five times at T = 0, 0.7 and 1.2. Record how much the answers differ.
3. Verify the T = 0.7 numbers with the PyTorch or TensorFlow snippet, then add T = 0.3 and compute its entropy.
4. Implement the rollback fix and prove it by stopping Ollama mid-chat; print `[m.type for m in message]`.
5. Add `timeout` and `max_retries`, then write `call_with_retry()` and test it with a wrong port.

6. Build the persona dictionary and the /persona command.
7. Create a grounded assistant over a 10-line notes text and test five out-of-context questions.
8. Run the Streamlit version and watch how the temperature slider changes answers.

Day 03 completion checklist

[ ] SystemMessage is index 0 of the list
[ ] I can compute temperature probabilities and entropy by hand
[ ] I can explain why the system prompt costs tokens on every call
[ ] try/except keeps the loop alive after an error
[ ] Failed questions are rolled back from the history
[ ] I can write a six-part system prompt
[ ] I know why a system prompt is not a security boundary
[ ] Grounded assistant tested with unknown-fact questions
[ ] Streamlit controls (persona, temperature) working

Day 04 preview

Next step (my expectation from the repo plan; check the README): once the assistant can follow instructions and answer from a context, the limit is how much knowledge fits in the prompt. The natural continuation is retrieval (RAG) and tools: let the program fetch the right information or call a function, then give the result to the model.

Final takeaway

Day 01 called the model, Day 02 added memory, Day 03 adds control: instructions that shape every answer, a randomness dial, and error handling that keeps the app alive. The model is still a stateless next-token function; I decide what it sees and how it samples.

- Chandan Chaudhari | github.com/chandanc5525 -