

TADM23 - Practice Test 1

Questions, Correct Answers & Explanations

Source: Practice Test 1 - Results, Attempt 2 | 40 questions

QUESTION 1 of 40

How does SAP HANA encrypt the data persistence layer?

A	By page level	✓ Correct
B	By row level	
C	By table level	
D	By column level	

Correct answer: A

EXPLANATION

SAP HANA encrypts data at rest in the persistence layer using the AES-256 encryption algorithm at the "Page Level".

Refer the below SAP Documentation to learn more regarding this:

SAP HANA Database Encryption

QUESTION 2 of 40

What is the purpose of the SAP HANA secure user store (hdbuserstore)? Note: There are 2 correct answers to this question.

A	To configure an SAP HANA auto-restart for fault recovery	
B	To configure failover support in a 3-tier scenario	✓ Correct
C	To store connection information on the SAP HANA XS advanced engine	
D	To store connection information on the SAP HANA database client	✓ Correct

Correct answers: B, D

EXPLANATION

Let's understand what is SAP HANA secure user store (hdbuserstore)?

The secure user store (hdbuserstore) is a tool installed with the SAP HANA client. Use it to store connection information to SAP HANA systems securely on the client, this information also includes username, password, hostname, port etc. With the help of hdbuserstore client applications can connect to SAP HANA without users having to enter this information. It is typically used by scripts connecting to SAP HANA.

Below is a labeled screenshot of how hdbuserstore keys are stored:

With the above explanation it is clear that option "To store connection information on the SAP HANA database client" is a Valid option as the sole purpose of hdbuserstore (which is part of HANA Client) is to store connection information.

Other than that You can also use the secure store to configure failover support for application servers in a 3-tier scenario by storing a list of all the hosts that the application server can connect to.

Hence we can conclude the correct options to this question is:

To store connection information on the SAP HANA database client
To configure failover support in a 3-tier scenario
Refer the below SAP Documentation to learn more regarding this:
Secure User Store (hdbuserstore)
hdbuserstore Commands

QUESTION 3 of 40

What actions can you perform using the SAP_FIORI_FOUNDATION_S4 task list?

Note: There are 3 correct answers to this question.

A	Generate SAP Fiori foundation roles.	✓ Correct
B	Enable SAP GUI for HTML.	✓ Correct
C	Replicate backend catalogs.	✓ Correct
D	Create users with generated business roles.	
E	Schedule a job for calculation of SAPUI5 application index.	

Correct answers: A, B, C

EXPLANATION

What is SAP_FIORI_FOUNDATION_S4 Task list?

You use task list SAP Fiori - Initial Setup for SAP Fiori Applications in SAP S/4HANA (SAP_FIORI_FOUNDATION_S4) to perform initial configuration and activation of the SAP Fiori launchpad.

In its essence, the task list performs automates & simplifies the following configuration tasks in the system:

From the above list of tasks list we can conclude the correct answer for this question, which are:

Enable SAP GUI for HTML.

Generate SAP Fiori foundation roles.

Replicate backend catalogs.

Refer the below SAP Documentation to learn more regarding this:

Rapid Activation of SAP Fiori | SAP Help Portal

QUESTION 4 of 40

What is the definition of “Transport Group” in Transport Management System (TMS)?

A	A collection of systems that are controlled by the same transport domain controller	
B	A collection of systems that are assigned to the same transport target group	
C	A collection of systems that are connected by transport routes	
D	A collection of systems that share the same transport directory	✓ Correct

Correct answer: D

EXPLANATION

Answer to this question is simple, but let us understand few more SAP TMS Terminology which would be more helpful.

What is TMS (Transport Management System)?

STMS stands for SAP Transport Management System, a tool that helps to organize, perform, and monitor transports between SAP Systems. Transport contains a package which is used to transfer data from one SAP installation to another (ideally from DEV-->QA-->PROD System), data like new development object/table etc.

What is Domain Controller & Member Systems?

A Domain Controller is used to control the landscape. There will be only one domain controller in the landscape. Initially it is set to development and later can be moved to on higher available system such as PRD/QAS/Pre-production but to keep the things simple most of the cases we keep DEV as Domain Controller. The other systems are included in the domain and referred as member systems.

Now What is a "Transport Group" in Transport Management System (TMS)?

A Transport group consists of one or more SAP systems that share a common transport directory. transport directory consist of co-files, data files & various log files related to transport. Having a common transport directory for multiple systems means it would be easier manage and move the transport between these systems.

If you are new to STMS, below is a labeled representation of TMS Route and Domain Overview console:

With the above explanation and demonstration, we can conclude that the only correct answer for this question is "A collection of systems that share the same transport directory".

Refer the below SAP Documentation to learn more regarding this:

SAP Library - Change and Transport System - Overview (BC-CTS)

QUESTION 5 of 40

During startup, an AS Java-based SAP system generates an error. Which file contains information about manager and services?

A	jvm_bootstrap.out	
B	std_server.out	✓ Correct
C	dev_jstart	
D	dev_icm	

Correct answer: B

EXPLANATION

There are several logs & trace files which stores information for AS JAVA System Stop & Start process, these files helps us troubleshoot any issues which are encountered while starting or stopping AS JAVA system, you can locate these files under /usr/sap/<SID>/<Instancename>/work Directory. Let us understand what files are these and what information each of this file consist of:

dev_jstart: dev_jstart is the trace file for the Instance Controller. dev_jstart is the most important trace file for problem messages when starting NetWeaver AS Java. Current messages are written at the end of the file.

dev_<node name>: dev_<node name> such as dev_server0 is the trace file for the server processes, the ICM and so on. The trace file dev_<node name> is written for each process started and thus for each ICM and server process.

jvm_<node name>.out: jvm_<node name>.out file such as jvm_bootstrap.out is the output file for the Java Virtual Machine (JVM). Each node (except ICM) process represents a Java node such as a bootstrap or a server and therefore a JVM. The output of a JVM is forwarded to the file jvm_<node name>.out in the work directory of a Java instance.

std_server<X>.out: std_server<X>.out file such as std_server0.out is the default output files for the started managers and services of the the corresponding nodes.

AS JAVA Startup Log/Traces

Refer the below SAP Documentation to learn more regarding this:

Developer Trace and Log Files

QUESTION 6 of 40

In which subdirectories of sapmnt can you find information about startup problems of an AS Java-based SAP Application? Note: There are 2 correct answers to this question.

A	J<Instance Number>/work	✓ Correct
B	J<Instance Number>/log	
C	D<Instance Number>/work	
D	SCS<Instance Number>/work	✓ Correct

Correct answers: A, D

EXPLANATION

There are two correct Answers for this question, let us go through each of options we have & figure out:

D<Instance Number>/work - Here the option is pointing towards /usr/sap/<SID>/D<Instance Number> Directory but the question is for AS JAVA Instance, this folder (D<Instance Number>/work) is only present in AS ABAP System and not in AS JAVA. Hence we can Eliminate this option.

J<Instance Number>/work - This seems like Valid option, this option is pointing towards the path /usr/sap/<SID>/J<Instance Number>/work Directory which is present in a AS JAVA Instance, This Path Consist of log files which can help us understand any startup related issues our Java Application Instance is having. Hence this is a Correct Answer

J<Instance Number>/log - This option can be a confusing one, this is pointing towards /usr/sap/<SID>/J<Instance Number>/log path which is a valid path but note that this path for log files, but note that System startup related logs are not present under this path. Hence we can Eliminate this option.

SCS<Instance Number>/work - This is another valid option, this option is pointing towards the path /usr/sap/<SID>/SCS<Instance Number>/work directory which contains log files for any startup related issues specifically for SCS (message server) Instance. Hence this is a Correct Answer.

More Information about AS JAVA Log files for startup & shutdown related issues were explained in other question which was "During startup, an AS Java-based SAP system generates an error. Which file contains information about manager and services?"

Refer the below SAP Documentation to learn more regarding this:

Developer Trace and Log Files

QUESTION 7 of 40

Which of the following background jobs has the highest priority?

A	Class A job without a target server	
B	Class C job without a target server	
C	Class C job with a target server	
D	Class A job with a target server	✓ Correct

Correct answer: D

EXPLANATION

In an AS ABAP based system, Jobs are classified in three classes:

Class A (Highest Priority)

Class B (Medium Priority)

Class C (Lowest Priority)

Furthermore, these priorities may vary depending on whether a Target server is designated during Job scheduling. This preference only applies if multiple jobs of various priorities request background processing at the same time.

Please refer to the diagram below for a visual explanation of Job Priorities:

Refer the below SAP Documentation to learn more regarding this:

Scheduling Background Jobs | SAP Help Portal

QUESTION 8 of 40

Which file systems are supported for the data and log volumes of the SAP HANA 2.0 database system? Note: There are 2 correct answers to this question.

A	Btrfs	
B	OCFS2	
C	GPFS	✓ Correct
D	XFS	✓ Correct

Correct answers: C, D

EXPLANATION

Let's understand how HANA works with File systems support:

In general, the Linux distributions support many file systems. But SAP HANA do not support all the file systems, there are exception to what is supported.

Below file systems are certified and supported by SAP HANA according to SAP:

XFS

NFS

GPFS

and below File systems are explicitly not supported by SAP HANA:

OCFS2

EXT3

BTRFS

MPFS

Refer the below SAP Documentation to learn more regarding this:

2622671 - SAP HANA Certified and Supported Hardware | SAP Knowledge Base Article

QUESTION 9 of 40

What is the correct parameter replacement sequence in an AS java based SAP system? Note: the sequences below are sorted by priority from highest to lowest

- | | | |
|----------|--|------------------|
| A | 1. Instance custom
2. Template default
3. Template custom | |
| B | 1. Instance custom
2. Template custom
3. Template default | |
| C | 1. Template default
2. Template custom
3. Instance custom | ✓ Correct |
| D | 1. Template custom
2. Instance custom
3. Template default | |

Correct answer: C

EXPLANATION

Let us first understand what are these configuration template in AS JAVA System?

In Release 7.10, the concept of Zero Administration was introduced in the AS Java. The aim is to simplify the technical configuration of the AS Java and to adjust it dynamically to changes in the system environment. Configuration templates were introduced to implement the concept.

Changes to these Configuration templates are made via AS JAVA config tool, and just like profile parameter these are read by the AS JAVA System in certain order of priority. Just for better understanding in case you have never worked on AS JAVA Config tool, refer the below labeled screenshot of Config Tool:

Different types of Configuration Templates are:

> **DEFAULT** Configuration Template: This has all the Default Values which are set while Installing the AS JAVA SAP Instance.

> **Custom Global** Configuration Template: Any changes done to the **DEFAULT** Configuration Template value can be done on Custom Global Template. (Note that Customer changes at Custom Global level are allowed but only if expressly instructed by SAP)

> **Template Default**: SAP provides concrete default configuration settings for individual products with this templates.

> **Template Custom**: At Template Custom level, customer changes can be made using the Config Tool, These changes override the settings of the previous level (Template Default etc).

> **Instance Custom**: All Instance-specific customer changes are made on this template. It has highest priority amongst each Template.

Now to answer the main question, we need to understand in what order of priority does AS JAVA System prioritize and read these configuration templates, to understand this better refer the below diagram demonstrating the priorities of these Configuration Template:

Refer the below SAP Documentation to learn more regarding this:

Zero Administration

QUESTION 10 of 40

In an embedded deployment, which protocol is used by object pages to access the SAP S/4HANA system?

A	InA	
B	DIAG	
C	OData	✓ Correct
D	RFC	

Correct answer: C

EXPLANATION

Object pages in SAP S/4HANA uses the Open Data Protocol (OData) to access the system in an embedded deployment. OData is a REST-based protocol that allows you to use any programming language or model to connect to SAP and non-SAP applications. Most APIs of SAP S/4HANA are based on OData V2, and CRUD (Create, Read, Update, Delete) of each OData API supports HTTP POST, GET, PUT/PATCH, and DELETE.

Hence the correct answer to which protocol is used by object pages to access the SAP S/4HANA system in an embedded deployment is OData.

Refer the below SAP Documentation to learn more regarding this:

What is OData in SAP?

QUESTION 11 of 40

You are running an SAP HANA database in log mode "normal". Under what circumstances does the database automatically execute a regular log backup?

Note: There are 2 correct answers to this question.

A	When the time threshold is exceeded	✓ Correct
B	When the log buffer is full	
C	When the log segment is full	✓ Correct
D	When a commit occurs	

Correct answers: A, C

EXPLANATION

What is Log Backup in context of HANA Database?

A log backup is a backup of the transaction log, which contains all the changes made to the database since the last backup. This type of backup ensures that all transactions are captured in the backup and can be used for point-in-time recovery.

What is Log Segment in context of HANA Database?

To put in my own simple words, It has the record of the transactions that have been committed in memory and has reached the log volume file system as log segments and is yet to reach the data volumes which only happens after a save point .

Now to answer this question we need to understand when does HANA log backup run Automatically, HANA log backup runs automatically in the following situations:

When the log segment is full.

When the log segment is closed after exceeding the configured time threshold.

When Initially the database is started.

Hence according to the above the valid options to this question is:

When the time threshold is exceeded.

When the log segment is full.

Refer the below SAP Documentation to learn more regarding this:

HANA log segments and its states

Log Backup

QUESTION 12 of 40

Your SAP S/4HANA Server system consists of an ABAP Central Services instance, a Primary Application Server instance, and two Additional Application Server instances. How many system profile files are evaluated for this SAP system during system start?

A	8	
B	4	
C	9	
D	5	✓ Correct

Correct answer: D

EXPLANATION

Let's start with the basics, what is an SAP Profile file?

SAP parameters are stored in text files that reside in the file system of the application server. These text files are known as profile files. These files reside under /usr/sap/<SID>/SYS/profile directory, number of profile files for a system can differ depending on how many instances it has. Every SAP System has a DEFAULT Profile file named as DEFAULT.PFL on the server which has all the defined Parameters that will be applied to all the SAP Instances by Default. Each SAP Instance will also have their own Profile file so Parameters can be configured for each Individual Instance separately if required. These SAP Profile files are evaluated during every system startup.

Now Let us understand the architecture of the system described in this question and number of profile files which will be evaluated during the System startup using the below diagram:

According to the diagram, system will have to evaluate 5 SAP Profile files during the System startup:

DEFAULT.PFL

<SID>_ASCS<InstanceNumber>_<Hostname>.PFL --> FOR ASCS

<SID>_D<InstanceNumber>_<Hostname>.PFL --> For Primary Instance

<SID>_D<InstanceNumber>_<Hostname>.PFL --> For Additional Application Instance 1

<SID>_D<InstanceNumber>_<Hostname>.PFL --> For Additional Application Instance 2

From the above explanation we can conclude that the correct answer for this question is 5.

QUESTION 13 of 40

When importing a transport request, which steps are executed by a batch job?

Note: There are 3 correct answers to this question.

A	Import of dictionary objects	✓ Correct
B	Distribution	
C	Move nametabs	✓ Correct
D	Activation of dictionary objects	
E	Activation of ABAP programs	✓ Correct

Correct answers: A, C, E

EXPLANATION

While Importing a transport, batch jobs are used during these three steps:

Import of dictionary objects (Batch Job - RDDIMPDP)

Move Nametabs (Batch Job - RDDMNTAB)

Activation of ABAP programs (Batch Job - RDDDIC3L)

Below is an illustrated diagram to understand the workflow & steps involved in a Transport Import:

Steps During Transport Import

Refer the below SAP Documentation to learn more regarding this:

Starting an Import: Options

Importing transport requests | SAP Help Portal

QUESTION 14 of 40

You have passed the initial authentication for an SAP Fiori transactional app.

Which authentication technology is used for subsequent OData calls of this app?

A	SAP logon tickets	
B	X.509 client certificates	
C	ABAP Session Security	✓ Correct
D	SAML 2.0	

Correct answer: C

EXPLANATION

If a user has already passed the initial authentication for an SAP Fiori transactional app, the subsequent OData calls for that app will use ABAP Session Security for authentication.

Refer the below SAP Documentation to learn more regarding this:

Configuring ABAP Server Session Security (sap.com)

QUESTION 15 of 40

From top to bottom, what is the hierarchy of the NetWeaver Administrator (NWA)?

A	Work Center → Work Set → Function	✓ Correct
B	Function → Work Center → Work Set	
C	Work Center → Function → Work Set	
D	Work Set → Work Center → Function	

Correct answer: A

EXPLANATION

What is SAP NetWeaver Administrator?

SAP NetWeaver Administrator is a Web-based framework tool for administration, configuration and monitoring. It consists of respective integrated tools that help you to configure, administer and monitor your SAP NetWeaver system, its components, and the applications running on top of it. The NWA can be called using the following URL: `http://<hostname>:<http-port>/nwa`.

Now to Answer this question, let us see the below Labeled NetWeaver Administrator Interface and understand it's hierarchy:

The NWA provides access to various functions. Which functions are available in the NWA depends on the installed product. The functions are sorted into work sets and these are then sorted into work centers. For example, the function Sequence Monitoring is located in the work set Application and Scenario Communication, which is located in the work center Configuration.

From the above explanation we can understand the hierarchy of Java NWA flows from Work Center → Work Set → Function.

Hence correct answer to this question is Work Center → Work Set → Function.

Refer the below SAP Documentation to learn more regarding this:

SAP NetWeaver Administrator

QUESTION 16 of 40

When you install SAP Solution Manager 7.2 AS Java, what information do you need to provide? Note: There are 2 correct answers to this question.

A	The package path to additional language installation media	
B	The package path to an archive for SAP JVM	✓ Correct
C	The decision to use an External ABAP System as UME Data Source	✓ Correct
D	The decision whether to install an SAP Gateway integrated in the SCS instance	

Correct answers: B, C

EXPLANATION

Let us go through all the options we have here:

The decision whether to install an SAP Gateway integrated in the SCS instance: We have no option to decide if we want to install integrated SAP Gateway in SCS Instance while installing AS JAVA Instance for Solution Manager 7.2.

The package path to an archive for SAP JVM: This is a Valid option, for every AS JAVA Installation either for SAP Solution Manager or some other AS JAVA SAP Component, we have to provide SAP JVM SAR Media to SWPM to proceed with the installation. Refer the below screenshot from SWPM for more understanding:

The package path to additional language installation media: There is No way & no option to provide package path for additional language installation media while installing AS JAVA Instance for SAP Solution Manager 7.2. Hence this is an Invalid option for this question.

The decision to use an External ABAP System as UME Data Source: This is a Valid option, while Installing AS JAVA Instance for Solution Manager 7.2, we do get option to choose an External ABAP System as UME Data Source, refer the below screenshot from SWPM to understand this option more:

To Conclude, the two correct options for this question is:

The package path to an archive for SAP JVM

The decision to use an External ABAP System as UME Data Source

Refer the below SAP Documentation to learn more regarding this:

Solution Manager 7.2 - Installation and Configuration - I - Installations

QUESTION 17 of 40

When performing a standard SAP HANA database system installation, which users will be created or validated during that installation? Note: There are 2 correct answers to this question.

A	SAPADM	✓ Correct
B	<SID>CRYPT	
C	SYSTEM	✓ Correct
D	SAP<SID>	

Correct answers: A, C

EXPLANATION

To Answer this question, let us go through each of our options:

SYSTEM - SYSTEM User is the most powerful user of your HANA Database, it is a highly privileged system user that is automatically created on Database during the installation of the SAP HANA database. Hence this is one of the valid answer for this question.

SAP<SID> - There is no user such as SAP<SID>, hence this is just a distractor and not a correct option.

<SID>CRYPT - <SID>CRYPT user is an OS Level User which is only created if you choose to enable trusted local secure store, learn more about LSS (Local Secure Store) here. Since this user is not created during a Default HANA installation hence it is not an valid option for this question.

SAPADM - SAPADM user is created automatically during the Default HANA installation, it is used as an Admin user for SAP Host Agent. Hence this is a valid answer for this question.

To have more understanding go through the below table demonstrating different users with their usage and creation criteria:

Refer the below SAP Documentation to learn more regarding this:

Users Created During Installation

QUESTION 18 of 40

When performing a local client copy, which client copy profiles are available?

Note: There are 3 correct answers to this question.

A	Customizing, User Master Record and User Variants.	✓ Correct
B	User Master Records and Authorization Profiles	✓ Correct
C	All Client-Specific Data w/o Change Documents	✓ Correct
D	Customizing including Cross-Client Customizing	
E	Application Data and User Master Data	

Correct answers: A, B, C

EXPLANATION

What is Copy Profile?

It is possible to restrict the data involved in the client copy or transport to certain data types. For this purpose, SAP provides a set of copy profiles. These profiles are predefined, you cannot change them nor can you create your own. The Below table shows all the Copy Profile given by SAP as of now:

According to the above table the available & correct options for this question would be

SAP_ALL - All Client-Specific Data w/o Change Documents.

SAP_UCSV - Customizing, User Master Record and User Variants.

SAP_USER - User Master Records and Authorization Profiles

Let us also understand why are the below options incorrect:

Customizing including Cross-Client Customizing - Copy Profile (SAP_EXPC) is a bit different than all the Copy Profile we see in the above table, as option to export both client-dependent and cross-client customizing. The Copy Profile options we see in the above table are used to export only client dependent Data.

Application Data and User Master Data - There is no Copy Profile option which can copy both Application Data & User Master Data, hence this is just a distractor and not a valid option.

Refer the below SAP Documentation to learn more regarding this:

Copy Profiles

QUESTION 19 of 40

What can you configure by maintaining table HTTPURLLOC?

A	The hostname of the URL launched by transaction /UI2/FLP	✓ Correct
B	The URL used by classic applications	
C	The URL of a local Web server for user assistance resources	
D	The path of the URL launched by transaction /UI2/FLP	

Correct answer: A

EXPLANATION

What is HTTPURLLOC Table?

The table HTTPURLLOC is used to determine the protocol, host and port when the ABAP system uses to generates URLs. For example: to generate public URLs, instead of technical URLs like <host>:<port>.

HTTPURLLOC Controls which & how the URL will be generated and launched by our system, be it for /UL2/FLP or some other possible URLs.

In the context and the options we have for this question, the correct answer to what we can configure by maintaining table HTTPURLLOC is hostname of the URL launched by transaction /UI2/FLP.

An example of an entry in HTTPURLLOC Table is given below:

All other options are distractor and doesn't imply what HTTPURLLOC table is actually used for.

Hence the only correct answer to this question is "The hostname of the URL launched by transaction /UI2/FLP"

Refer the below SAP Documentation to learn more regarding this:

Configuration Table HTTPURLLOC

QUESTION 20 of 40

Using standard transport protocol settings, after importing a transport request, which log file provides the return codes of the individual import steps? (Note: These answers use the following abbreviations: year , week: , quarter , SAP system ID , and a 5-digit number .)

A	ALOG<YY><WW>.<SID>	✓ Correct
B	SLOG<YY><WW>.<SID>	
C	ULOG<YY>_<Q>	
D	<SID>E9<NNNNN>.<SID>	

Correct answer: A

EXPLANATION

Lets first understand the usage of all the logs given in the options:

So ALOG, ULOG & SLOG all three are created by tp tool while Importing a transport, It is important to monitor these logs in case you are facing an issue with long running Imports.

Below is detailed explanation of each one of these log and what Information they contain:

ULOG: ULOG Records all tp commands that are free of syntax errors, and is named using the name convention ULOG<YY>_<Q> (YY is the year, Q is the quarter of the year). Each line in the ULOG file represents a tp command.

SLOG: SLOG is used to monitor the transport activities of a specific SAP system. It contains a general overview of performed transports indicating the return code and thus the success of each transport. The name of the SLOG file can be set as tp parameter using the global tp parameter SYSLOG. The default setting is SLOG<YY><WW>.<SID> (YY is the year, WW the calendar week).

ALOG: ALOG records the return code for all transport steps handled in the common transport directory. The name of the ALOG file can be set as tp parameter using the global tp parameter ALLLOG. The default value is ALOG<YY><WW>.<SID>.

<SID>E9<NNNNN>.<SID> is a distractor here and have no relevance to this question.

From the above explanation we can conclude that ALOG<YY><WW>.<SID> is the correct option here containing return codes of the individual import steps.

Refer the below SAP Documentation to learn more regarding this:

Log File ALOG (SAP Library - Software Logistics)

slog, alog, ulog contains - SAP Community

QUESTION 21 of 40

You are preparing an installation of an AS ABAP-based SAP system. You already downloaded all software that Maintenance Planner can calculate. What else must you download?

A	SAPCAR	✓ Correct
B	SPAM/SAINT update	
C	SAP kernel	
D	SAP Host Agent	

Correct answer: A

EXPLANATION

While Downloading Installation Media using Maintenance Planner, following files are downloaded:

Stack-XML file

SWPM

SUM

Latest SAP Host Agent Latest Kernel

SPAM/SAINT Update

Database Backup files for products installed with SWPM 2.0

Support Packages for SP Stack

Apart from the above these components have to be downloaded Manually:

Latest SAPCAR

RDBMS software

RDBMS Client software

Database Export Media for products installed with SWPM 1.0

Export Media for additional languages

Installation and Update Guides (SUM Guides)

Hence Correct Answer to this question is SAPCAR.

QUESTION 22 of 40

Which app types need SAP HANA as system database? Note: There are 3 correct answers to this question.

A	Analytical apps	✓ Correct
B	Classic applications	
C	Transactional apps	✓ Correct
D	Fact sheet apps	✓ Correct

Correct answers: A, C, D

EXPLANATION

SAP HANA has a unique design, it does not require sums, indexes, materialized views, or aggregates. This reduces the database footprint. Everything is calculated on demand and in the main memory. This process makes it possible for companies to run online transaction processing (OLTP) and analytical applications (OLAP) on the same instance at the same time making it a perfect database for:

Analytical apps

Transactional apps

Fact Sheet apps

Refer the below SAP Documentation to learn more regarding this:

Application Types (sap.com)

QUESTION 23 of 40

When installing an SAP S/4HANA Server 1909 system, which actions can the Software Provisioning Manager (SWPM) perform only when the installation is started with the option SAPINST_STACK_XML? Note: There are 3 correct answers to this question.

A	Import additional languages	✓ Correct
B	Apply a SPAM/SAINT update	✓ Correct
C	Set up Transport Management System (TMS)	✓ Correct
D	Install an SAP Host Agent	
E	Set the password of user DDIC in client 000	

Correct answers: A, B, C

EXPLANATION

To Answer this question, we need to understand what is Up-To-Date Installation?

SAP Up-To-Date Installation is a way of combining two tools, SWPM (used for Installation) & SUM (used for upgrade) to Install & Upgrade SAP System all together in one go. As the question Implies we are launching SWPM SAPINST_STACK_XML options, which means Up-To-Date Installation method is being used here.

Using Up-To-Date Installation method comes with other advantages of SUM Tool which are:

Apply a SPAM/SAINT update

Set up Transport Management System (TMS)

Import additional languages

Refer the below SAP Documentation to learn more regarding this:

Up-To-Date Installation

QUESTION 24 of 40

What can you do to determine the SAPUI5 patch level in an AS ABAP-based SAP system?

A	Execute the ICF service /sap/public/bc/ui5_ui5	
B	Use the program /UI5/UI5_UPLOAD_PATCH_TO_MIME	
C	Check the version of software component SAP_UI	✓ Correct
D	Use the program WDG_MAINTAIN_UR_MIMES	

Correct answer: C

EXPLANATION

SAPUI5 Patch Level can be easily identified by checking the SAP_UI Software Component Version under SYSTEM > STATUS as shown in the below image:

QUESTION 25 of 40

What are prerequisites for enabling communication between a standalone SAP Web Dispatcher and an AS ABAP-based SAP system? Note: There are 2 correct answers to this question.

A	Activation of ICF service /sap/public/ping	
B	Activation of ICF service /sap/public/icf_info/icr_groups	✓ Correct
C	Identification of the HTTP port of the ABAP message server	✓ Correct
D	Identification of the HTTP port of the PAS instances ICM process	

Correct answers: B, C

EXPLANATION

Valid Prerequisites for enabling communication between a standalone SAP Web Dispatcher and an AS ABAP-based SAP system are as follows:

Identification of the HTTP port of the ABAP message server: Web Dispatcher connects to Message server where it gets information about the SAP system, which is needed for load distribution, hence while setting up configuration between SAP WD & AS ABAP System we first need to Identify HTTP/HTTPS Port of our ABAP Message Server.

Activation of ICF service /sap/public/icf_info/icr_groups: Activating /sap/public/icf_info/icr_groups service provides information related to the configuration and status of ICM routing groups. ICM is a core component in SAP NetWeaver systems responsible for handling HTTP, HTTPS, and SMTP requests. The routing groups help in defining how requests should be distributed across different server nodes.

Other two options below are invalid here as /sap/public/ping is just a simple service used to perform connectivity test to ensure that the SAP system is reachable via HTTP & PAS instances HTTP Port is not required as Pre-requisites for setting up communication between a standalone SAP Web Dispatcher and an AS ABAP-based SAP system.

Refer the below SAP Documentation to learn more regarding this:

Architecture and Functions of the SAP Web Dispatcher

QUESTION 26 of 40

In an SAP S/4HANA Server system, a target system alias, FIORI, is maintained for source system alias S4FIN. Which connection is relevant for the extraction of back-end catalogs with alias S4FIN?

A	S4FIN_RFC	
B	S4FIN_HTTPS	✓ Correct
C	FIORI_HTTPS	
D	FIORI_RFC	

Correct answer: B

EXPLANATION

The S4FIN_HTTPS RFC destination in SAP is a configuration used primarily for Fiori applications to communicate with the backend S/4HANA system. This destination ensures that the communication is secure using HTTPS, as indicated by the suffix "_HTTPS", It is typically used in extraction of back-end catalogs with alias S4FIN.

QUESTION 27 of 40

You are importing an SAP Support Package Stack with transaction SPAM. Which steps require SAP system downtime? Note: There are 2 correct answers to this question.

A	Modification adjustment of dictionary objects (SPDD)	
B	Import of inactive dictionary objects (DD IMPORT)	
C	Activation of dictionary objects (DD ACTIVATION)	✓ Correct
D	Modification adjustment of other objects (SPAU)	✓ Correct

Correct answers: C, D

EXPLANATION

What is SPAM (Support Package Manage)?

Support Package Manager (transaction SPAM) provides you with an easy and effective way of importing SAP support packages into your system letting you do SP Upgrade for different components in your system!

As this question is regards to SPAM Import process, to answer effectively we need to understand all stages of SPAM Import process.

SPAM Import process can be Divided into 4 phases:

Preparation

Import 1

Import 2

Post Processing

Each Phases has Multiple Activity which are processed to Finish to Import process, only Import 2 Phase comes under System Downtime, to Understand this better let us go through the below Diagramatical Explanation:

Now if we keep our options side by side with the above diagram, we can conclude that only Activation of dictionary objects (DD ACTIVATION) & Modification adjustment of other objects (SPAU) are the steps which will require downtime and comes under Import 2 Phase.

Hence the Correct options to this question are Activation of dictionary objects (DD ACTIVATION) & Modification adjustment of other objects (SPAU).

Refer the below SAP Documentation to learn more regarding this:

Technical Upgrade - SPDD & SPAU Phase - SAP Community

QUESTION 28 of 40

You are using a Change and Transport System (CTS) for the transport of native SAP HANA applications. Which tool can you use to create a transport request for these applications in the CTS system?

A	Transport Organizer (Extended View) (in transaction SE01)	
B	Transport Organizer Web UI (in transaction STMS)	✓ Correct
C	Transport Organizer (in transaction SE09)	
D	Database Assistant (in transaction DB50N)	

Correct answer: B

EXPLANATION

Remember for creating Transport request for any NON-ABAP Application such as HANA Database Transport Organizer Web UI (in transaction STMS) is used. Hence the correct answer to this question is Transport Organizer Web UI (in transaction STMS).

Refer the below SAP Documentation to learn more regarding this:

Creating Transport Requests for Non-ABAP Objects - SAP Documentation

QUESTION 29 of 40

You want to configure the transport domain for the transport of AS Java-based SAP systems (for example SAP Enterprise Portal).

Which entry type do you create for these systems in the System Overview area of the Transport Management System (transaction STMS)?

A	External System	
B	Virtual System	
C	Java Stack Configuration	
D	Non-ABAP System	✓ Correct

Correct answer: D

EXPLANATION

In STMS, if we want to configure any system which is not AS ABAP, we will have to create an entry for these systems in STMS as "NON-ABAP System". This applied for AS JAVA or even for Standalone HANA Database system.

Refer the below SAP Documentation to learn more regarding this:

Defining and Configuring Non-ABAP Systems in STMS

Hence we can conclude the correct answer for this question is "Non-ABAP System".

QUESTION 30 of 40

You configure the Transport Management System (TMS) as part of the installation of an AS ABAP-based SAP system. What information can you supply for the first SAP system that uses a specific transport directory? Note: There are 3 correct answers to this question.

A	The name of the Transport Domain	✓ Correct
B	The user ID of a new user that will be created	
C	The password of a new user that will be created	✓ Correct
D	The description of the AS ABAP-based SAP system	✓ Correct
E	The name of the Transport Group	

Correct answers: A, C, D

EXPLANATION

While configuring TMS System for a newly installed AS-ABAP System, We need to provide below three details to the system as part of the process:

The description of the AS ABAP-based SAP system - Involves providing a descriptive name or details about the system for identification purposes.

The name of the Transport Domain - Defines the transport domain to which the system will belong.

The password of a new user that will be created - Password to TMSADM user which is created as part of TMS Configuration.

Refer the below SAP Documentation to learn more regarding this:

Transport Management System - Concept

QUESTION 31 of 40

You are logged onto an AS ABAP-based SAP system. What happens when you release a task of a transport request that contains changes to a program?

- | | | |
|----------|---|------------------|
| A | The object list is handed over to the transport request. | ✓ Correct |
| B | The repository locks are released. | |
| C | A data file and a cofile are created. | |
| D | A version is created in version management. | |

Correct answer: A

EXPLANATION

Lets go through all the options one by one to understand the most valid answer to this question:

A data file and a cofile are created: Data files and cofiles are created when the entire transport request is released, not when an individual task within the request is released. Hence this is an invalid option.

The repository locks are released: Releasing a task does not release repository locks. The locks on the objects are typically maintained until the transport request is fully released and transported. Releasing the task is about finalizing changes within that task, not affecting the locks. Hence this is an invalid option.

A version is created in version management: A version in version management is created when you save changes to the program, not necessarily when you release a task. Version management is more about tracking changes over time, independent of the transport process. Hence this is an invalid option.

The object list is handed over to the transport request: When you release a task, the system takes the list of objects and changes that were part of that task and hands them over to the parent transport request. This means the transport request now contains all the changes from the released task, making them ready for further actions (such as releasing the transport request itself). Hence is is the most valid & correct option we have.

Refer the below SAP Documentation to learn more regarding this:

All About Transport Request

QUESTION 32 of 40

Under which Java System Properties category do you find an AS Java-based Manager & Services in the SAP NetWeaver Administrator (NWA)?

- | | | |
|----------|-----------------|------------------|
| A | Applications | |
| B | Kernel | ✓ Correct |
| C | VM Environment | |
| D | Services | ✓ Correct |

Correct answers: B, D

EXPLANATION

What is Java System Properties?

The Java System Properties is simply a page/tool under JAVA NWA which enables you to view and edit online the current system configuration of the AS Java. This includes default and custom property data. There are different categories here segregated depending on the types of configuration items present in them. Refer the below screenshot to understand this clearly:

Now in this given question, it is asking us, under which of the category does it contain AS Java-based Manager & Services Configuration, and the clear answer to this is under kernel & services categories.

This is described in the SAP Document: Java System Properties

Hence the valid option to this question is:

Kernel

Services

QUESTION 33 of 40

How are savepoints triggered in HANA Database? Note: There are 2 correct answers to this question.

A	By issuing a transactional commit	
B	By performing a delta merge	
C	By a database soft shutdown	✓ Correct
D	By performing a database backup	✓ Correct

Correct answers: C, D

EXPLANATION

What is HANA Savepoints?

SAP HANA persists in-memory data by using savepoints. Each SAP HANA service has its own separate savepoints. A savepoint is a periodic point in time, when all the changed data is written to storage, in the form of pages. During a savepoint operation, the SAP HANA database flushes all changed data from memory to the data volumes.

How & When are Savepoints triggered?

The frequency for Savepoints creation can be configured. Savepoints are also triggered automatically by a number of other operations such as:

Data Backup

Reclaim datavolume

Auto merge function (mergedog)

Database startup

Database shutdown and restart

Savepoints can be manually triggered by executing the statement ALTER SYSTEM SAVEPOINT.

From the above we can conclude correct answer to this question are:

By performing a database backup

By a database soft shutdown

Refer the below SAP Documentation to learn more regarding this:

HANA - Savepoint details

QUESTION 34 of 40

Which services can you stop in the SAP HANA cockpit from the SYSTEMDB Manage Services app? Note: There are 2 correct answers to this question.

A	Preprocessor	✓ Correct
B	Index server	
C	Compile server	✓ Correct
D	Daemon	

Correct answers: A, C

EXPLANATION

Starting and Stopping Individual SAP HANA Database Services:

You can stop and start some of the SAP HANA database Individual services. From the SYSTEMDB it is possible to stop the following services:

Name server

Preprocessor

Web dispatcher

Compile server

Just like SYSTEMDB, We can also Stop Individual services from TENANTDB which are:

Index server

XS EngineFigure

Refer the below labeled screenshot from HANA Studio & HANA Cockpit for Stopping Individual HANA Services:

From the above explanation we can conclude Preprocessor & Compile server are the correct answer here!

Daemon is an essential service in SYSTEMDB & hence cannot be stopped, & Index server is an service which is only present in TENANTDB hence is an invalid option here as question is specifically asking about services in SYSTEMDB

Refer the below SAP Documentation to learn more regarding this:

Checking the SAP HANA Services

QUESTION 35 of 40

In an AS ABAP-based SAP system, you need to create a user that is not enabled for dialog interaction and is subject to the validity period of passwords. Which user type do you choose?

A	Communication	✓ Correct
B	Reference	
C	Service	
D	System	

Correct answer: A

EXPLANATION

To Answer this question, let us understand what types of users can be create an in AS ABAP SAP System:

Dialog User: This user type is tailored for online access, suitable for RFC and background jobs. It's typically chosen when creating a user ID for an actual person.

System User: System users are designed for background jobs and RFC, excluding dialog logons (SAP GUI). They lack the capability to change their own passwords, requiring intervention from a user administrator. This user type is primarily intended for internal processes such as Transport Management System (TMS), Central User Administration (CUA), or Application Link Enabling (ALE).

Communication User: Similar to system users (No Dialog Login), communication users serve background jobs and RFC. One important & unique point about communication users is, they can change their passwords themselves needing no manual intervention.

Service User: Service users are dialog users aimed at accommodating a broader, anonymous user base, particularly useful when accessing the system anonymously via a web application.

Reference User: Reference users function as templates for creating operational users with identical authorizations. Primarily encountered in the realm of internet users generated through Transaction SU01, a reference user lacks the ability to log on in any manner and cannot be utilized in background jobs.

From the above context we can conclude that only communication user is a type of user which cannot be used for Dialog login and plus has expiration date for password, which is what in this question.

Hence Correct Answer to this is Communication.

Refer the below SAP Documentation to learn more regarding this:

User Administration in ABAP Systems (sap.com)

QUESTION 36 of 40

What is the correct sequence of the following four steps when you restart the SAP HANA database system?

- A** Aborted transactions are rolled back. Row tables are loaded into memory. Open transactions are recovered. Column tables are loaded.
- B** **Row tables are loaded into memory. Open transactions are recovered. Aborted transactions are rolled back. Column tables are loaded.** ✓ **Correct**
- C** Aborted transactions are rolled back. Open transactions are recovered. Row tables are loaded into memory. Column tables are loaded.
- D** Row tables are loaded into memory. Column tables are loaded. Open transactions are recovered. Aborted transactions are rolled back.

Correct answer: B

EXPLANATION

Correct HANA Restart Sequence is:

Row tables are loaded into memory. Open transactions are recovered. Aborted transactions are rolled back. Column tables are loaded.

Please follow the below Illustration to Understand the whole sequence of HANA Database restart :

SAP HANA Restart Sequence

It is highly recommended to go through this free SAP Learning module to understand more about HANA Start & Stop Process: [Starting and Stopping SAP HANA](#)

QUESTION 37 of 40

Which of the following is a command line tool is used to start or stop SAP systems and SAP instances?

- | | | |
|----------|-------------------|------------------|
| A | ICMon | |
| B | SAP MC | |
| C | JSmon | |
| D | SAPControl | ✓ Correct |

Correct answer: D

EXPLANATION

Let us understand all the tools we have in options:

ICMon: -

An interface channel in Interface and Connection Monitoring (ICMon) can be set up and monitored in two different monitoring use-cases. One is the application operations related view of Integration Monitoring. The second one is the more business process focused view from Business Process Monitoring. It has no functionality to start & stop SAP Instances. Hence under context of this question this is an Incorrect Option.

JSmon: -

JSmon is a AS-JAVA Based command line monitoring tool, used to monitor state of AS-JAVA Processes. Hence under context of this question this is an Incorrect Option.

SAPControl: -

SAPControl is a command line program which comes with SAP Kernel, it can be used to Start/Stop/Monitoring an SAP System.

For example, SAPControl command to start & Monitor a System is given below:

```
sapcontrol -nr <Instance No.> -function StartSystem
```

```
sapcontrol -nr <Instance No.> -function GetProcessList
```

Hence under context of this question this is the correct Option.

SAP MC: -

SAP MC stands for SAP Management Console, it can also be used to Start/Stop/Monitor an SAP Instance, but this comes with a Graphical Interface and is not a command line tool. Hence under context of this question this is an Incorrect Option.

Demonstration of SAP MC/MMC.

Refer the below SAP Documentation to learn more regarding this:

Using the Command Line Program jsmon (sap.com)

Starting and Stopping SAP Systems Using SAPControl

SAP Management Console

Interface and Connection Monitoring Setup (sap.com)

QUESTION 38 of 40

What are some start conditions of a background job in an AS ABAP- based SAP system? Note: There are 3 correct answers to this question.

A	Switching the operation mode	✓ Correct
B	Triggering a background event	✓ Correct
C	Reaching a specific date and time	✓ Correct
D	Defining an external command	
E	Creating a job server group	

Correct answers: A, B, C

EXPLANATION

A SAP Job can be scheduled to start mainly using the below two ways:

After an Event - Such as after a Predecessor job ends or Change in Operation Mode of a SAP System.

After Reaching a specific date & time - Background jobs can be simply scheduled to start at a specific date and time even with set iteration like daily weekly or monthly.

Hence from the above options we have, below are the three valid options:

Switching the operation mode (Event Based Scheduling)

Triggering a background event (Event Based Scheduling)

Reaching a specific date and time (Time Based Scheduling)

Refer the below SAP Documentation to learn more regarding this:

Specifying Job Start Conditions

QUESTION 39 of 40

Which processes can run optionally as part of ABAP SAP Central Services (ASCS)? Note: There are 2 correct answers to this question.

A	Message Server	
B	RFC Gateway	✓ Correct
C	Enqueue Server	
D	Web Dispatcher	✓ Correct

Correct answers: B, D

EXPLANATION

SAP Central Services compulsorily have two services, those are:

Message Server

Enqueue Server

Apart from these above two services, You can optionally Install SAP Web Dispatcher & RFC Gateway Server on SAP Central Services.

Hence Correct Answer for this question is SAP Web Dispatcher & RFC Gateway.

Now that we have concluded the correct answer let us use this question to understand the architecture of ASCS (SAP Central Services) & summarize all the services present in it!

> ABAP Message Server (MS) handles communication between the distributed dispatchers within the AS ABAP. It enables scalability of several parallel application servers. The message server is configured only once per SAP system.

> Enqueue Server (ES) manages the lock table that contains the logical database locks of the SAP system. It exists once for each SAP system and is part of the ASCS instance. RFC Gateway reader (RFC GW) enables communication between SAP systems, or between SAP systems and external application systems. One GW exists per dispatcher.

> Internet Communication Manager (ICM) enables the communication with the SAP system using web protocols such as HTTP, HTTPS and SMTP. The ICM receives requests from the client and either performs them directly or forwards them to the dispatcher of its instance for processing. It can also direct web requests from its instance to a web server and send the response back to the instance. In a SAP S/4HANA server system you have always one ICM process per dispatcher configured. If you run a SAP Business Suite system on ASABAP, you can configure no or a maximum of one ICM process per dispatcher.

> Web Dispatcher is used to distribute HTTP requests across all instances of an SAP system. It is the central point of entry to the SAP system from the internet. For each incoming request, it must decide on the instance to which it forwards the request. When it accepts a connection, it distributes the requests to ensure an even distribution across the servers (load balancing).

Refer the below SAP Documentation to learn more regarding this:

Architecture of SAP NetWeaver Application Server ABAP

QUESTION 40 of 40

Which of the following actions can be executed in transaction RZ11 (Edit Profile Parameters)? Note: There are 2 correct answers to this question.

A	Download values of all profile parameters in one step.	
B	Set new values for profile parameters in profile files.	
C	Display the value of individual profile parameters.	✓ Correct
D	Change values of dynamic profile parameters.	✓ Correct

Correct answers: C, D

EXPLANATION

Lets go through all the options we have:

Download values of all profile parameters in one step -

There is No option in Transaction RZ11 to download all the SAP Profile parameters in one go, hence this is an Incorrect Option.

Display the value of individual profile parameters -

RZ11 has functionality and is used to display Individual profile parameters with their Default/Current value. Hence this is a Correct Option. This is demonstrated in the screenshot below:

RZ11 - Main Screen to Search Individual Parameter

Set new values for profile parameters in profile files -

There is No option in RZ11 to set new profile parameters in profile files, this can be instead done in transaction code RZ10. Hence this is an Incorrect Option.

Change values of dynamic profile parameters -

Dynamic parameters are those which can be changed without SAP System restart. RZ11 has functionality to change a dynamically changeable system parameter. Hence this is a Correct Option. This is demonstrated in the screenshot below:

RZ11 - Option to change Dynamic Parameter

Refer the below SAP Documentation to learn more regarding this:

Changing Profile Parameters Dynamically (Transaction RZ11)