

TADM23 - Practice Test 2

Questions, Correct Answers & Explanations

Source: Practice Test 2 - Results, Attempt 1 | 40 questions

QUESTION 1 of 40

How can the system database administrator disable tenant database functionalities? Note: There are 2 correct answers to this question.

- | | | |
|----------|---|-----------|
| A | Using the hdbuserstore tool | |
| B | Using the Manage Restricted Features app | ✓ Correct |
| C | Using the Manage Database Configuration app | ✓ Correct |
| D | Using the resident hdblcmm tool | |

Correct answers: B, C

EXPLANATION

To maximize control over the security of your system, you can disable features in tenant databases, for example import and export operations or the ability to back up the database.

This can be done via two ways, either by using Manage Restricted Features app or Manage Database Configuration app.

Refer the below screenshot to understand steps to disable features on tenant database using Manage Restricted Features app:

Refer the below SAP Document to understand more about this:

Disable Features on a Tenant Database

QUESTION 2 of 40

When using the java Startup and Control Framework to shut down an AS Java-based SAP system, which of the following stop the server processes?

- | | | |
|----------|---------------------|-----------|
| A | Instance Controller | ✓ Correct |
| B | Database | |
| C | ICM | |
| D | Sapstartsrv | |

Correct answer: A

EXPLANATION

Let us first get straight to the answer and then understand why others are Incorrect.

The Instance Controller starts, stops, and monitors the processes of a Java instance - primarily the server and ICM process. SAP Signal Handling is implemented with the Instance Controller to forward the start and stop commands to the processes of the Java stack. Hence the correct answer to this question Instance Controller.

Now Let us understand what does other options represents here & why are they incorrect:

ICM: The Internet Communication Manager (ICM) is responsible for accepting incoming HTTP/HTTPS requests and forwarding these to the SAP dialog instance, ICM is monitored and administrated using SMICM T-Code. This has no relevance of ICM with controlling AS-JAVA server processes.

Sapstartsrv: The SAP start service runs on every computer where an instance of the Application Server ABAP (AS ABAP) is started. It is implemented as a service on Windows, and as a daemon on UNIX. Main functionality of Sapstartsrv is to start/stop & monitor runtime state/logs of SAP Systems. As this question is specific to stopping the server processes of AS-JAVA instance which is done by instance controller and not by Sapstartsrv, Hence this is an incorrect option.

Database: Database is just a distractor option here, Database as a term doesn't represent any service or program.

Refer the below SAP Documentation to learn more regarding this:

Architecture of the Java Startup Framework (sap.com)

QUESTION 3 of 40

Which file system locations do you need to specify when installing the SAP HANA multi-host database system using the default settings? Note: There are 2 correct answers to this question.

A	/usr/sap/hostctrl	
B	/hana/shared	✓ Correct
C	/hana/log/<SID>	✓ Correct
D	/usr/sap/<SID>	

Correct answers: B, C

EXPLANATION

While installing the SAP HANA multi-host database system using the default settings, HDBLCM will mandatory ask us for the following path file system location:

/hana/data/<SID>: The default path to the data directory depends on the system ID of the SAP HANA host.

/hana/shared/<SID>: The mount directory is used for shared files between all hosts in an SAP HANA system. This directory needs to be accessible to each of the servers in the SAP HANA cluster. In case of Multi-Host Installation, this mount has to be shared between each host.

/hana/log/<SID>: The default path to the log directory depends on the system ID of the SAP HANA host.

Hence the correct answer for this question here is:

/hana/shared

/hana/log/<SID>

Below is the Illustration Demonstrating SAP HANA File system for Multi-Host Installation:

Refer the below SAP Documentation to learn more regarding this:

Recommended File System Layout

QUESTION 4 of 40

You want to configure the TMS QA Approval procedure for an AS ABAP-based system landscape. Which approval steps can you choose? Note: There are 3 correct answers to this question.

A	To be approved by request owner	✓ Correct
B	To be approved by developer	
C	To be approved by system administration	✓ Correct
D	To be approved by project manager	
E	To be approved by department	✓ Correct

Correct answers: A, C, E

EXPLANATION

What is TMS QA Approval procedure?

To Increase Quality Assurance of transports which are being imported from Quality to Production system, SAP Offer an option for QA Approval Procedure. This is not activated by default but when activated each transport request which are being forwarded from QA will be requiring a set of Approval to be processed.

Now the question is regards to approval steps which can be choosen while setting up QA Approval Procedure:

When Activating QA Approval Procedure we have option to setup three step approval, which are:

Approval by request owner

Approval by department

Approval by system administrator

Hence above three approval steps are the valid options for this question.

Refer the below SAP Documentation to learn more regarding this:

Using the TMS Quality Assurance Approval Procedure

QUESTION 5 of 40

For an SAP HANA tailored datacenter integration (TDI) approach, what is the additional disk space factor required during delta merge operations?

A	2	
B	3	
C	1.2	✓ Correct
D	1.6	

Correct answer: C

EXPLANATION

According to SAP HANA tailored datacenter integration (TDI) approach, SAP Recommends to have 20% of additional space (Which is 1.2 times) which is required for delta merge operations, because the affected tables are temporarily duplicated on disk for a short period of time.

Hence the correct answer to this question is 1.2.

Refer the below SAP Documentation to learn more regarding this:

Performing SAP HANA Sizing

QUESTION 6 of 40

You are configuring outbound e-mails for an AS ABAP-based SAP system. What can you use to set the default domain?

- | | | |
|----------|--|------------------|
| A | Report RSADRCK7 | |
| B | Profile parameter is /SMTP/virt_host_<X> | |
| C | Transaction SCOT | ✓ Correct |
| D | File DOMAIN.CFG | |

Correct answer: C

EXPLANATION

We can configure Default Domain for outbound e-mails using SCOT T-code:

This can be done after navigate into SCOT > Business Communication Administration > Settings > SMTP Connection > Out-bound Messages > Settings > tab Outbound Settings > field Default Domain.

Hence correct answer to this question is "Transaction SCOT".

Refer the below SAP Documentation to learn more regarding this:

outgoing email configuration in ABAP systems for n... - SAP Community

QUESTION 7 of 40

In which situations can you resume the failed recovery of your productive SAP HANA tenant database? Note: There are 2 correct answers to this question.

- | | | |
|----------|---|------------------|
| A | An aborted recovery of the configuration files | |
| B | An aborted recovery of a complete data backup | |
| C | An aborted recovery of a delta data backup | ✓ Correct |
| D | An aborted recovery of a log backup | ✓ Correct |

Correct answers: C, D

EXPLANATION

To Answer this question let us go through all the options one-by-one:

An aborted recovery of the configuration files - There is no option to recover only configuration files of an HANA Database, As of HANA 2.0 SPS06 onwards, content of the configuration files can be backed up with each delta or full data HANA backup.

An aborted recovery of a complete data backup - If a complete data backup recovery gets failed/aborted, there is no way to resume it back from where it failed, only way is to trigger the recovery from the beginning.

An aborted recovery of a delta data backup - If the recovery of a delta data backup is interrupted, you can resume it. The delta backup contains changes since the last complete data backup, and SAP HANA is capable of resuming the application of these changes from the point of interruption.

An aborted recovery of a log backup - Similar to delta data recovery, log backup recovery can be also resumed from the point of interruption.

Hence to answer this question, recovery can be resumed if interrupted are:

An aborted recovery of a delta data backup

An aborted recovery of a log backup

Refer the below SAP Documentation to learn more regarding this:

SAP HANA Backup Types | SAP Help Portal

QUESTION 8 of 40

Which characteristics describe an SAP HANA multitenant database container (MDC) system? Note: There are 3 correct answers to this question.

A	The name server provides index server functionality for the system database.	✓ Correct
B	Database isolation increases the isolation between tenant databases on operating system level.	✓ Correct
C	Each tenant database runs its own compile server and the preprocessor server.	
D	The name server owns information about the location of tables and table partitions in databases.	
E	A multitenant database container system is identified by a single system ID (SID).	✓ Correct

Correct answers: A, B, E

EXPLANATION

Let us understand each options we have and decide if it is valid or invalid:

The name server provides index server functionality for the system database: Yes, this is a valid option. As name server provides functionality to SYSTEM DB for storing and processing the data just like Index Server.

Database isolation increases the isolation between tenant databases on operating system level: Yes, this is a valid option. One of the most important characteristic of MDC HANA Database is, all tenant databases are isolated from each other on operating system level, providing high level data security to each tenant.

Each tenant database runs its own compile server and the preprocessor server: No, this is a Invalid/False option as compile server & preprocessor server both runs on SYSTEM DB and are shared across tenant databases.

The name server owns information about the location of tables and table partitions in databases: No, this is a Invalid/False option as name server does not own information about the location of tables and table partitions in databases, it owns the information about the topology of the SAP HANA system, including knowledge of the tenant databases that exist in the system.

Information about the location of tables and table partitions is stored in the relevant tenant database catalog.

A multitenant database container system is identified by a single system ID (SID): Yes, this is a valid option, MDC HANA Database is identified by a single System ID (SID) for example a MDC HANA Installation can be identified by SID HD1, and then we can have multiple tenant databases inside this single SID HD1.

Hence from above we can conclude the correct options for this question is:

The name server provides index server functionality for the system database.

Database isolation increases the isolation between tenant databases on operating system level.

A multitenant database container system is identified by a single system ID (SID).

Refer the below SAP Documentation to learn more regarding this:

SAP HANA Multitenant Database Containers

QUESTION 9 of 40

Which tasks can you perform when using the Resident SAP HANA database lifecycle manager (HDBLCM)? Note: There are 2 correct answers to this question.

A	Rename the SAP HANA database system.	✓ Correct
B	Extract the SAP HANA database system components.	
C	Uninstall the SAP HANA database system and its components.	✓ Correct
D	Update the SAP HANA database system and its components.	✓ Correct

Correct answers: A, C, D

EXPLANATION

HDBLCM can be categorized into two:

Resident HDBLCM - Resident HDBLCM is integrated HDBLCM Present on the host where HANA Database is installed.

Installation Media HDBLCM - Installation Media HDBLCM is HDBLCM which you download from SAP Market place specifically for Installation or Upgrade of HANA Database.

Now both HDBLCM have their own use cases, Resident HDBLCM are used for certain tasks and Installation Media HDBLCM are used for some other set of tasks, this is clearly defined in the below Illustration:

Hence according to the above illustration the valid options for this question is:

Rename the SAP HANA database system.

Uninstall the SAP HANA database system and its components.

Update the SAP HANA database system and its components.

Refer the below SAP Documentation to learn more regarding this:

Choosing the Correct SAP HANA HDBLCM for Your Task

Illustrating the Resident HDBLCM (sap.com)

QUESTION 10 of 40

Which parameters are mandatory when using the HDBLCM tool to install the SAP HANA database system in batch mode? Note: There are 2 correct answers to this question.

A	Installation path	
B	SAP HANA System ID (SID)	✓ Correct
C	Data and log path	
D	Password of user sapadm	✓ Correct

Correct answers: B, D

EXPLANATION

Let us first understand what is Batch Mode Installation?

Batch mode installation is an Advance method of installation SAP HANA Database without any user intervention, this basically means we just need to run one single command to complete an entire HANA Installation, the single command itself consist required Parameters (command line option for batch mode) or path to a text config file containing all the parameters which are required (config file option for batch mode) to install SAP HANA.

Below is example of hdbclm batch mode command line option & config file option:

Now while using batch mode installation, there are certain mandatory parameters which needs to be there in command line or config file for batch mode installation to run successfully, these parameters are SAP HANA System ID (SID) & User passwords.

Hence for this question the valid options are:

SAP HANA System ID (SID)

Password of user sapadm

Refer the below SAP Documentation to learn more regarding this:

Use Batch Mode to Perform Platform LCM Tasks | SAP Help Portal

HANA Tutorials: Installing SAP HANA in batch mode

QUESTION 11 of 40

Updating an AS Java-based SAP system. Which actions can Software Update Manager execute? Note: There are 2 correct answers to this question.

A	Lock the development environment	
B	Update without using a stack configuration file (stack xml file)	✓ Correct
C	Update SAP Host Agent	
D	Check the archives authenticity	✓ Correct

Correct answers: B, D

EXPLANATION

While updating an AS-JAVA based SAP System using SUM, SUM have following options:

Check the Archives Authenticity: During the "Define Target" Phase, we have an option to Check Authenticity of all the available upgrade media files, this option verifies the media using signature checks. This option can be used by enabling checkbox "Check archives authenticity". Refer the below diagram where this is demonstrated.

Update without using a stack configuration file (stack xml file): In AS-JAVA Upgrade, we have an option to upgrade JAVA Components without providing stack XML file, using "Manually Prepared Directory" option. This option is exclusive for AS-JAVA System and is not available for AS-ABAP Systems. We need to keep all the media file in an directory and provide the path to SUM tool to proceed without Stack XML File. Refer the below diagram where this is demonstrated.

To understand this in a better way, please refer the below screenshot from SUM where the above two options are highlighted:

Let us understand why the other two options are incorrect:

Update SAP Host Agent: SUM has no option to update SAP Host Agent during upgrade. Hence this is just a distractor and an invalid option.

Lock the development environment: Option to Lock Development Environment is a valid option, but this only is available while upgrading AS-ABAP System, the question here is specific to AS-JAVA System where this option is not available. Hence with context of this question is not a valid option.

Refer the below SAP Documentation to learn more regarding this:

Software Update Manager (sap.com)

QUESTION 12 of 40

Which of the following tools are used when importing a transport request? Note: There are 3 correct answers to this question.

A	RDDIMPDP	✓ Correct
B	R3load	
C	Transport Control Program (tp)	✓ Correct
D	RDDNEWPP	
E	R3trans	✓ Correct

Correct answers: A, C, E

EXPLANATION

While running an Transport Import the below three tools are being used:

RDDIMPDP - RDDIMPDP is an SAP Job which runs at the application level, this is one of the most crucial jobs used for TR Import, RDDIMPDP is responsible for Importing, Handling, Monitoring of Transport request. When RDDIMPDP is started, it checks the table TRBAT to find out if there is an action to be performed for the transport requests such as mass activation, distribution, or table conversion. It sets the header entry to R (for run), and starts the appropriate RDD* program as a background task, reschedules itself, and exits.

Transport Control Program (tp) - The transport control program tp is used for controlling transports between SAP systems, applying SAP Support Packages, and for performing release upgrades. The tp program tracks transports by controlling exports and imports of objects between SAP systems. The program also ensures that the steps in exporting and importing objects are performed in the correct sequence and that imports into a target system are done in the same sequence as the exports from the source system. tp is an operating system level program, which uses special programs, such as C programs, operating system commands, and ABAP programs in the SAP system.

R3trans - R3trans is a transport tool at operating system level used to transport data between SAP systems. R3trans is usually called by other programs such as tp, the transport control program. For transports between SAP systems, to access the database, tp indirectly calls R3trans by causing UNIX to issue a fork(), Windows to issue a CreateProcess(), and AS/400 to issue a spawn(). During export, R3trans stores the object data extracted from the database in data files in the transport subdirectory data. The format of these data files, R3trans format, is independent of the platform. During import, R3trans reuses these data files.

We can understand the more about this by the help of below illustration representing SAP Transport Import Process:

Refer the below SAP Documentation to learn more regarding this:

Importing Transport Requests (sap.com)

QUESTION 13 of 40

You want to set up a printer locally on a Microsoft Windows?based AS ABAP. Which host spool access method must you use?

- | | | |
|----------|---|-----------|
| A | L | |
| B | U | |
| C | G | |
| D | C | ✓ Correct |

Correct answer: D

EXPLANATION

Let us understand what is host spool access method?

When you configure the output device in a device definition under SAP, you need to specify the access method with which the output device will be connected to the SAP System, this depends on whether you are using local or remote printing. The access method is identified by a letter and informs the system which architecture is in use and which operating system you are using.

Below table consist of all the available spool access method supported by SAP & their use cases:

Now looking at our question, we need to setup a printer (spool) Locally on a Microsoft Windows environment, checking the above table with all the supported access method and our specific requirement, we can conclude Spool Access method of C Type is most appropriate option for us, It is for Local Printing and is supported on Microsoft Windows Environment.

Refer the below SAP Documentation to learn more regarding this:

Access Methods (sap.com)

QUESTION 14 of 40

You have configured an SAP Web Dispatcher and set: wdisp/ssl_encrypt=2 icm/server_port_<XX>=...PROT=HTTP. Which communication channels does this establish?

- | | | |
|----------|--|-----------|
| A | HTTP between the client and SAP Web Dispatcher. HTTPS between SAP Web Dispatcher and the SAP system | ✓ Correct |
| B | HTTPS between the client and SAP Web Dispatcher. HTTP between SAP Web Dispatcher and the SAP system | |
| C | HTTP between the client and SAP Web Dispatcher. HTTP between SAP Web Dispatcher and the SAP system | |
| D | HTTPS between the client and SAP Web Dispatcher. HTTPS between SAP Web Dispatcher and the SAP system | |

Correct answer: A

EXPLANATION

To Answer this question we need to understand both the parameter described here:

wdisp/ssl_encrypt: This parameter determines how the SAP Web Dispatcher handles inbound HTTP requests. The following values are acceptable to this parameter:

0 = Forward the request unencrypted.

1 = Encrypt the request again with SSL, in case the request arrived via HTTPS protocol.

2 = Always forward the request encrypted with SSL.

According to the context of this question `wdisp/ssl_encrypt = 2`, which means all the requests coming to WD will be forwarded to backend SAP system using encryption (SSL).

`icm/server_port_<XX>`: You can use this parameter to specify the service or port that is to be used for a protocol, we are using this parameter enabled ICM Port and Protocol, According to the context of this question `icm/server_port_<XX>=...PROT=HTTP`, which means we are using this to enable ICM HTTP Port and Protocol for external traffic (client) to connect to Web Dispatcher using .

Let understand with the above parameter configured on web dispatcher, what will be the connectivity looking like using the below illustration:

From the above explanation and illustration, we can conclude that the correct option for this question is "HTTP between the client and SAP Web Dispatcher. HTTPS between SAP Web Dispatcher and the SAP system".

Refer the below SAP Documentation to learn more regarding this:

SSL Parameters for the Web Dispatcher

`icm/server_port_<xx>`

QUESTION 15 of 40

Working in an AS ABAP-based SAP system that runs on Linux. Where is the spool data stored when you use the value IGI for the profile parameter `rspo/store_location`?

- | | | |
|----------|--|-----------|
| A | <code>/usr/sap/<SID>/D<NN>/work</code> | |
| B | <code>/usr/sap/<SID>/sys/global</code> | ✓ Correct |
| C | <code>/usr/sap/<SID>/D<NN>/data</code> | |
| D | <code>/usr/sap/<SID>/sys/profile</code> | |

Correct answer: B

EXPLANATION

The print data of a spool request is stored at the operating system level in the global directory which is `/usr/sap/<SID>/sys/global`.

QUESTION 16 of 40

During the installation of SAP Solution Manager AS ABAP 7.2, which of the following user IDs does SAPinst suggest for SAP Solution Manager AS Java 7.2? Note: There are 2 correct answers to this question.

- | | | |
|----------|-------------------|-----------|
| A | J2EE_ADMIN | ✓ Correct |
| B | SAP* | |
| C | SAPJSF | ✓ Correct |
| D | Administrator | |

Correct answers: A, C

EXPLANATION

While Installing SAP Solution Manager AS ABAP 7.2, SAPinst (SWPM) ask to set-up following users which is required for UME (User Management Engine):

J2EE_ADMIN - The J2EE_ADMIN user in SAP is a default administrative user for managing and administering the Java stack of an SAP system.

J2EE_GUEST - The J2EE_GUEST user is an guest user account with minimal authorization used for anonymous access to AS-JAVA SAP Instance.

SAPJSF - The SAPJSF is an communication user used for RFC Connection between the Java Application Server & ABAP Application Server.

Below is the snippet from SWPM Screen where it is asking to set-up the above users:

Hence from the above we can conclude the valid options given for this question are:

J2EE_ADMIN

SAPJSF

Refer the below SAP Documentation to learn more regarding this:

Solution Manager 7.2 - Installation and Configurat... - SAP Community

QUESTION 17 of 40

For AS ABAP-based SAP systems, you can use Software Update Manager to update which of the following? Note: There are 2 correct answers to this question.

A	Database system	
B	Software component SAP_BASIS	✓ Correct
C	SAP Notes	
D	SAP kernel	✓ Correct

Correct answers: B, D

EXPLANATION

From the available options, SUM is capable of upgrading "Software component SAP_BASIS" & "SAP Kernel".

Let us also understand why the other two options are invalid:

Database system: Database system can be only upgraded according to Database vendor methodology & cannot be upgraded via SUM tool. hence this is also an invalid option.

SAP Notes: SUM has no option to Implement/Apply SAP Notes to the system, this has to be done via SNOTE T-Code. hence this is also an invalid option.

Therefore, the only correct options for this question are:

Software component SAP_BASIS

SAP kernel

Refer the below SAP Documentation to learn more regarding this:

Software Update Manager (sap.com)

QUESTION 18 of 40

During the import of a transport request, which tools write log files to the /usr/sap/trans and it's subdirectories? Note: There are 3 correct answers to this question.

A	RDDMNTAB	✓ Correct
B	R3load	
C	R3trans	✓ Correct
D	RDDMASGL	✓ Correct
E	SAPup	

Correct answers: A, C, D

EXPLANATION

To answer this question, let us first take out the incorrect options:

R3load - R3load is not used during an Transport Import, neither does it write logs under trans directory. Hence this is an distractor option and is not valid.

SAPup - SAPup is a process that runs on the SAP NetWeaver server and is part of the Software Update Manager (SUM) tool, It has no revelance with Transport Import process. Hence this is also an invalid option.

Now this leave us which three below options, let us understand what each option/tool do:

RDDMNTAB - RDDMNTAB Job put new ABAP runtime objects into the active runtime environment, database structures are adjusted, if necessary. It writes logs under trans directory with nomenclature P<date>.<target SID>.

R3trans - This takes care for the main import, all other objects and data are imported. It writes logs under trans directory with nomenclature <source SID>I9<number>.<target SID>.

RDDMASGL - With RDDMASGL Runtime descriptions (nametabs) are generated. This is the begin of the downtime. It writes logs under trans directory with nomenclature <source SID>A9<number>.<target SID>.

Hence we can conclude above are three valid tools from options which writes log under trans & it's sub-directories during the Import process.

Also refer the below Illustrated flowchat for an overview of TR Import process & it's sequence:

Refer the below SAP Documentation to learn more regarding this:

Importing Transport Requests (sap.com)

QUESTION 19 of 40

You are running an AS ABAP-based SAP system. Which parts does the Internet Server Cache (ISC) of the ICM process consist of? Note: There are 3 correct answers to this question.

A	Browser cache	
B	CPU cache	
C	Disk cache	✓ Correct
D	UFO cache	✓ Correct
E	Memory cache	✓ Correct

Correct answers: C, D, E

EXPLANATION

What is Internet Server Cache (ISC)?

Internet Server Cache (ISC) is an component under ICM responsible to improve performance of ICM by handling caching for the incoming requests.

To answer this question, let us go through the below diagramitical representation of Internet Server Cache (ISC):

From the above diagram we can understand ISC contains three types of Cache:

UFO Cache - this store cache for Invalid requests ("UnFound Objects") that lead to error situations in the application server or the database are directly rejected, so that the system is protected against invalid or malignant requests.

Memory Cache - this stores cache for data available in memory, helping with boosting performance and decreasing response time.

Disk Cache - this stores cache for data available in Disk, similar to memory cache this helping with boosting performance and decreasing response time with Increase capacity advantage of Disk.

The above three cache types are also the valid options for this question. Other two option we have, which are Browser cache & CPU cache are invalid and are just distractor options as these cache doesn't exist in Internet Server Cache (ISC).

Refer the below SAP Documentation to learn more regarding this:

ICM Server Cache

QUESTION 20 of 40

You use transaction OSS1 in your freshly installed AS ABAP-based SAP system. Which name will be used automatically for the generated RFC connection?

A	BACK	
B	NONE	
C	SAPOSS	✓ Correct
D	SERVICE	

Correct answer: C

EXPLANATION

When using transaction OSS1 in your freshly installed AS ABAP-based SAP system, A New RFC connection will be created and will be named as SAPOSS.

BACK and NONE are internal RFC connections and SERVICE isn't the name of an RFC connection but a type of user record that can be created in the SAP system.

Hence the correct answer to this question is:

SAPOSS

QUESTION 21 of 40

You are installing a Primary Application Server and a Central Services instance for an AS Java-based SAP system. What is the minimum number of Java server nodes you must configure?

A	4	
B	2	
C	0	
D	1	✓ Correct

Correct answer: D

EXPLANATION

SAP AS-JAVA Application only requires minimum 1 Java server nodes to get the Started. We can increase the number of java server nodes later according to the Instance usage/Load using Java config tool. therefore the correct answer to this question is "1".

QUESTION 22 of 40

Which work process types can create spool requests? Note: There are 2 correct answers to this question.

A	Dialog	✓ Correct
B	Update	
C	Spool	
D	Background	✓ Correct

Correct answers: A, D

EXPLANATION

Spool request can be created by Dialog work processes or by Background work processes. Spool work processes do not create spool requests, it is only responsible for creating output request. whereas Update work processes are responsible for performing Asynchronous database changes and have no relevance to Spool request creation.

Hence the valid answer for this question is

Dialog

Background

Refer the below SAP Documentation to learn more regarding this:

SPOOL PROCESS

Work Process

QUESTION 23 of 40

Which instances have processes that establish a connection to the database of an SAP system? Note: There are 2 correct answers to this question.

A	Enqueue Replication Server	
B	Primary Application Server	✓ Correct
C	Additional Application Server	✓ Correct
D	Central Services	

Correct answers: B, C

EXPLANATION

This is a really simple question, but let us utilize this to understand use cases of all these instances:

Central Services: Central services form the basis of communication and synchronization for the SAP System. They are responsible for lock administration, message exchange, and load balancing within the SAP System between Primary & Additional Application Server. Two main components of central services are Message server & Enqueue server.

Enqueue Replication Server: The enqueue replication server (ERS) is an optional component that can be installed in high-availability configurations to duplicate the ES. The ERS runs on another host than the ES (Present in Central Services) and contains a replica of the lock table. Every entry saved in the primary lock table is also written to the secondary lock table. If the central services instance is restarted, a copy of the replicated lock table is read to restore the lock entries.

Primary Application Server: The primary application server (PAS) is the first application instance installed on the SAP system. Primary Application Instance has the root component of SAP System, ICM for handling HTTP/HTTPS/SMTP Requests, ABAP Dispatcher to send different requests to correct work processes such as Dialog, Update, Background & Spool. nothing can be processed in an SAP system without an Application Instance.

Additional Application Server: All other application Instances installed or added after Primary Application Server are called Additional Application Server. Architecture wise Additional Application Server is completely identical to PAS. A SAP System can have multiple Additional Application Server depending on the System Load. Having multiple Additional Application Servers provides a form of high availability to the system. If any Application Instance experiences technical issues and goes down, the other servers can maintain the system's functionality.

Refer the below Diagram for SAP AS-ABAP Platform Architecture combining all four SAP Application Server:

Now coming back to the question, Which instances have processes that establish a connection to the database?

Only Primary Application Server & Additional Application Server has established connection to the Database, which means if Database Connectivity is lost for some reason these Instances won't be able to start or process SAP Transaction and will be stuck, whereas Central Services & Enqueue Replication Server doesn't need to connect to the database, which enables them to run even if Database is unavailable for some reason.

Therefore, the correct answer for this question is:

Primary Application Server

Additional Application Server

QUESTION 24 of 40

When updating an SAP S/4HANA Server system using Software Update Manager (SUM), you will be asked for the passwords for which users?

A	SAP* in client 000	
B	DDIC in client 000	✓ Correct
C	SYSTEM in SAP HANA Tenant database	✓ Correct
D	TMSADM in client 000	

Correct answers: B, C

EXPLANATION

When updating an SAP S/4HANA Server system using SUM, you will be asked for the passwords of DDIC in client 000 and SYSTEM in the SAP HANA Tenant database.

The passwords for the users SAP* in client 000 or TMSADM in the client 000 are never required for SAP S/4HANA Upgrade.

QUESTION 25 of 40

In an AS ABAP-based SAP system, what can you use to change the value of a dynamically switchable parameter at runtime?

A	Report RSPFPAR	
B	Transaction Edit profile parameters (RZ11)	✓ Correct
C	Transaction Edit profiles (RZ10)	
D	Command line tool sappfpar	

Correct answer: B

EXPLANATION

To change the value of a dynamically switchable parameter at runtime, We will have to use Transaction Edit profile parameters (RZ11), a Demonstration of this T-Code is given below, We will have to use "Change Value" Option Highlighted below to change value of Dynamic Parameter, in this case for parameter rdisp/scheduler/prio_high/max_runtime:

Now let us also understand why other options are not correct:

Report RSPFPAR - Report RSPFPAR is a simple SAP Report to display profile parameter values for the SAP System. There is no option to change value of a dynamic parameter using this report.

Transaction Edit profiles (RZ10) - RZ10 can be used to update profile files & values on them from SAP Layer, but RZ10 cannot be used to change value of a dynamic parameter.

Command line tool sappfpar - Program sappfpar lets you check the minimum and maximum (worst case) swap space requirements for an SAP application server. It also checks the shared memory requirements and if the parameters em/initial_size_MB and abap/heap_area_total are correctly set. This command line tool has no relevance with changing Dynamic parameter.

Hence, only correct option here is "Transaction Edit profile parameters (RZ11)"

QUESTION 26 of 40

you have restarted the primary application server instance. after the restart, change will take effect for which profiles?Note:- These are 2 correct answers to this question.

A	Central services instance profile	
B	Default profile	✓ Correct
C	Additional Application server instance profile	
D	Primary Application Server instance profile	✓ Correct

Correct answers: B, D

EXPLANATION

If only Primary Application Server Instance is restarted, then while restarting the PAS Instance will read and evaluate two profile files:

DEFAULT Profile: DEFAULT Profile is read and evaluated by all types of Instances, be it ASCS, PAS, AAS. Any parameter set in DEFAULT Profile is applied to all the Instances of that SAP System.

Primary Application Server instance profile: PAS Profile is read & evaluated by only Primary Application Instance while starting or restarting. All the parameter set in this profile are applied only to Primary Application Instance. Also if same parameter is configured in DEFAULT & PAS Profile with different values then value of PAS Profile will be prioritized and would be applied on PAS Instance.

Refer the below illustration to understand the evaluation sequence of SAP Parameter Profile:

Refer the below SAP Documentation to learn more regarding this:

SAP Profile Parameters

QUESTION 27 of 40

Using the Java Startup and Control Framework, what is the correct sequence of steps to start an application server of an AS Java-based SAP system?

- 1. Start Offline Deployment**
- 2. Start bootstrap process**
- 3. Start ICM/Server process(es)**
- 4. Connect to SCS instance**

A	4, 1, 2, 3	✓ Correct
B	1, 3, 4, 2	
C	2, 4, 1, 3	
D	4, 1, 3, 2	

Correct answer: A

EXPLANATION

The startup procedure in the Startup and Control Framework involves multiple run-levels:

The Instance Controller starts and connects to the Central Services instance.

It reads the instance.properties file from the cluster directory.

Run-level 1: The Instance Controller reads configuration files and starts a jstart process for offline deployment, using files from the Cluster/bootstrap directory. The process completes after deployment.

Run-level 2: The Instance Controller reads configuration files again, starting a jstart process for the bootstrap process, which synchronizes data and binaries from the database to the file system. The

process completes after synchronization.

The Instance Controller rereads the instance.properties file.

Run-level 3: The Instance Controller reads configuration files again, starting the ICM and jstart processes for each server, which connect to the database using binaries from the Cluster/bin directories.

According to the above detailed described sequence the correct sequence to answer this question is:

Connect to SCS instance

Start Offline Deployment

Start bootstrap process

Start ICM/Server process(es)

Hence correct option is "4, 1, 2, 3 "

QUESTION 28 of 40

The purpose of a security policy in an AS ABAP-based SAP system is to establish a comprehensive framework of rules and guidelines to ensure the protection of the system's data and resources.

- | | | |
|----------|--|------------------|
| A | To define security relevant system profile parameters | ✓ Correct |
| B | To Assign selected security attributes and their values to roles | |
| C | To assign selected security attributes and their values to users | |
| D | To define possible authentication mechanisms | |

Correct answer: A

EXPLANATION

The purpose of a security policy in an AS ABAP-based SAP system is to establish a comprehensive framework of rules and guidelines to ensure the protection of the system's resources.

One way to do this is by defining security relevant system profile parameters, like login/fails_to_user_lock which defines the number of failed login attempts before a user account is locked or login/min_password_lng which Specifies the minimum length of passwords.

QUESTION 29 of 40

What action(s) can you perform in the SAP HANA cockpit to back up the complete database system?

- | | | |
|----------|---|------------------|
| A | Back up the system database and all tenant databases individually. | ✓ Correct |
| B | Back up the system database and all tenant databases in one step. | |
| C | Back up the system using a fallback snapshot for every database. | |
| D | Back up the system using a database snapshot and a data snapshot. | |

Correct answer: A

EXPLANATION

From the above options HANA Cockpit only have functionality to Back up the system database and all tenant databases individually.

Other options given in this question are not supported by HANA Cockpit, at least as of now.

Back up the system database and all tenant databases in one step: there is no option in HANA Cockpit to backup SYSTEM DB & all available Tenant in one go/one step, backup has to be taken individually for

SYSTEMDB & each Tenant.

Back up the system using a fallback snapshot for every database & back up the system using a database snapshot and a data snapshot: As of now HANA Cockpit does not support backing up using fallback snapshot or database snapshot. Hence these are invalid options.

Refer the below SAP Documentation to learn more regarding this:

Create Data Backups and Delta Backups (SAP HANA Cockpit) | SAP Help Portal

QUESTION 30 of 40

In an AS ABAP-based SAP system, a user performs the second dialog step in a dialog transaction. The dialog work process used in the first dialog step is occupied by a different user. What happens with this second user request?

- | | | |
|----------|--|------------------|
| A | The dialog work process that handled the first dialog step performs a rollout to handle the request. | |
| B | The request is processed asynchronously by an update work process. | |
| C | The request remains in the request queue until the dialog work process that handled the first dialog step is free again. | |
| D | The request is processed by a different free dialog work process. | ✓ Correct |

Correct answer: D

EXPLANATION

In an AS ABAP-based SAP system, when a user performs the second dialog step in a dialog transaction and the dialog work process used in the first dialog step is occupied by a different user, the system handles the request using another available dialog work process. Here's how the process works:

Work Process Allocation: SAP systems use a pool of dialog work processes to handle user requests. These work processes are stateless and not tied to a specific user session for the duration of a transaction.

Context Switching: When a user initiates a transaction, the dialog work process processes the request and then becomes free to handle other user requests. The context of the transaction is stored in shared memory.

Second Dialog Step: When the user performs the second dialog step, the system does not require the same work process that handled the first step. Instead, it assigns any available dialog work process to handle the request.

Context Retrieval: The newly assigned dialog work process retrieves the user's transaction context from the shared memory, allowing it to continue processing the transaction seamlessly from where it left off.

Request Handling: The newly assigned work process handles the user's second dialog step and processes the request accordingly.

In summary, the SAP system ensures efficient processing of dialog steps by dynamically assigning any available dialog work process to handle user requests, without needing to reserve a specific work process for the entire duration of a transaction. This approach optimizes resource utilization and enhances system performance.

QUESTION 31 of 40

When restarting an Additional Application Server instance, which profiles are evaluated? Note: There are 2 correct answers to this question

A	Instance profiles of the Primary Application Server	
B	Instance profiles of the Additional Application Server	✓ Correct
C	Instance profile of the Central Services instance	
D	Default profile	✓ Correct

Correct answers: B, D

EXPLANATION

If only Additional Application Server Instance is restarted, then while restarting the AAS Instance will read and evaluate two profile files:

DEFAULT Profile: DEFAULT Profile is read and evaluated by all types of Instances, be it ASCS, PAS, AAS. Any parameter set in DEFAULT Profile is applied to all the Instances of that SAP System.

Application Server Instance profile: AAS Profile is read & evaluated only by Application Server Instance while starting or restarting. All the parameter set in this profile are applied only to Application Server Instance. Also if same parameter is configured in DEFAULT & AAS Profile with different values then value present AAS Profile will be prioritized and would be applied on AAS Instance.

Refer the below illustration to understand the evaluation sequence of SAP Parameter Profile:

Refer the below SAP Documentation to learn more regarding this:

SAP Profile Parameters

QUESTION 32 of 40

Which operating system process initiates the start procedure of an AS Java-based SAP system instance?

A	Sapcpe	
B	Sapstartsrv	✓ Correct
C	Saphostexec	
D	Jstart	

Correct answer: B

EXPLANATION

The correct answer to the question "Which operating system process initiates the start procedure of an AS Java-based SAP system instance?" is:

Sapstartsrv

Here's an explanation of each option:

Sapcpe - Sapcpe (SAP Central Process Executor) is a program responsible for copying executable binaries and other related files from a central directory to the local instance directory. It ensures that all instances in a distributed environment have the necessary binaries to run.

Sapstartsrv - Sapstartsrv (SAP Start Service) is the process that initiates the start procedure of an SAP system instance. It is responsible for starting, stopping, and monitoring the SAP system instances, including AS Java. When an SAP system is started, sapstartsrv is the first process that gets triggered, and it then starts other necessary processes, including the Java server processes.

Saphostexec - Saphostexec (SAP Host Executable) is a service used for system-level monitoring and management tasks. It provides functionalities like executing commands at the operating system level, system monitoring, and performing administrative tasks. It is not directly responsible for starting an SAP system instance.

Jstart - Jstart is the process responsible for starting the Java instance of the SAP system. It gets triggered by sapstartsrv during the startup sequence of an AS Java-based SAP system instance. Jstart handles the initialization and startup of the Java environment and related components.

In summary, sapstartsrv is the process that initiates the start procedure, and it then triggers other processes like jstart for the Java-specific components of the SAP system.

Refer the below SAP Documentation to learn more regarding this:

SAP Start Service

QUESTION 33 of 40

What is the purpose of a pre-production system in an AS ABAP-based four-system landscape? Note: There are 2 correct answers to this question.

A	To isolate the next urgent correction or project cycle.	✓ Correct
B	To act as a failover system for the production system.	
C	To detect cross reference errors.	✓ Correct
D	To implement urgent corrections.	

Correct answers: A, C

EXPLANATION

The purpose of a pre-production system in an AS ABAP-based four-system landscape includes the following correct answers:

To isolate the next urgent correction or project cycle.

To detect cross reference errors.

Here is an explanation of each option:

To isolate the next urgent correction or project cycle:

In a four-system landscape, the pre-production system (also known as the quality assurance system) is used to test urgent corrections or project changes before they are moved to production. This ensures that any changes are thoroughly tested in an environment that closely mimics the production system, helping to isolate and identify potential issues before they affect the live system.

To act as a failover system for the production system:

A pre-production system is not typically used as a failover system for the production system. Failover systems are designed for high availability and disaster recovery purposes, whereas the pre-production system is used for testing and validation purposes. Hence this is not a valid option.

To detect cross reference errors:

The pre-production system is used to catch errors that might occur due to cross-references between different parts of the application. By thoroughly testing in this environment, it helps ensure that all dependencies and interactions between components are functioning correctly before going live.

To implement urgent corrections:

While urgent corrections are tested in the pre-production system, the actual implementation (or application) of these corrections happens in the production system after successful testing. The pre-production system is used to verify these corrections under controlled conditions. This doesn't make it the most suitable options for this question.

Summary:

In a four-system landscape (Development, Quality Assurance, Pre-Production, and Production), the pre-production system plays a crucial role in ensuring changes are properly tested and validated. This helps in isolating urgent corrections and detecting errors, thus ensuring a stable and reliable production environment.

QUESTION 34 of 40

Which software components (among others) can be found in every AS ABAP-based SAP system? Note: There are 2 correct answers to this question.

A	SAP_BASIS	✓ Correct
B	SAP_APPL	
C	S4CORE	
D	SAP_ABA	✓ Correct

Correct answers: A, D

EXPLANATION

The software components SAP_BASIS and SAP_ABA can be found in every AS ABAP-based SAP system.

The software component SAP_APPL can be found in SAP ECC systems. The software component S4CORE can be found in SAP S/4HANA systems.

Refer the below SAP Documentation to learn more regarding this:

Software Components in SAP ERP

QUESTION 35 of 40

Which tools can you use to start an SAP system? Note: There are 2 correct answers to this question.

A	SAP Management Console (SAP MC).	✓ Correct
B	SAPControl.	✓ Correct
C	The Microsoft Service Manager.	
D	The Internet Communication Manager (ICM).	

Correct answers: A, B

EXPLANATION

The tools you can use to start an SAP system are:

SAP Management Console (SAP MC).

SAPControl.

Let us understand each option we have for better understanding:

SAP Management Console (SAP MC):

The SAP Management Console (SAP MC) is a graphical user interface tool provided by SAP to manage and monitor SAP systems. It allows administrators to start, stop, and monitor SAP instances. It provides a centralized platform for system management tasks and is a common tool used by system administrators.

SAPControl:

SAPControl is a command-line tool used for managing SAP instances. It provides functions to start, stop, and monitor SAP systems. SAPControl can be used on both Windows and Unix-based systems and is often used for scripting and automation purposes. It interacts with the SAP Start Service (sapstartsrv) to perform these operations.

The Microsoft Service Manager:

The Microsoft Service Manager is a tool in the Windows operating system used to manage Windows services. While it can be used to start and stop services, it is not specifically designed for managing SAP systems. SAP systems are better managed using SAP-specific tools like SAP MC or SAPControl.

The Internet Communication Manager (ICM):

The Internet Communication Manager (ICM) is a component of the SAP NetWeaver Application Server that handles HTTP, HTTPS, and SMTP requests. It is not a tool for starting or stopping the entire SAP system; rather, it is a part of the SAP system that handles communication tasks once the system is running.

Summary:

The tools specifically designed and commonly used to start an SAP system are SAP Management Console (SAP MC) and SAPControl. These tools provide the necessary functionality to manage the lifecycle of SAP instances, including starting and stopping them.

Refer the labeled screenshot below for SAPMC/SAPMMC & SAPControl:

SAPMC

SAPControl

QUESTION 36 of 40

Which service is located in each tenant database of an SAP HANA system?

A	Pre-processor server	
B	Name server	
C	Compile server	
D	Index Server	✓ Correct

Correct answer: D

EXPLANATION

From the above options, Name Server, Compile Server & Pre-Processor Server are only present in SYSTEM DB. Compile Server & Pre-Processor Server runs on SYSTEMDB and is shared across all tenants, each tenant doesn't have its own compile & Pre-Processor server.

Whereas Index Server is exclusively available on each Tenant Database, it is the core component of the SAP HANA database. It handles all SQL/MDX statement processing and is responsible for managing actual data and processing transactions.

Refer the below SAP Documentation to learn more regarding this:

Checking the SAP HANA Services

QUESTION 37 of 40

What does SAP recommend you size before you install SAP HANA in a tailored data center integration (TDI).

Note: There are three correct answers to this question.

A	Main Memory	✓ Correct
B	Persistent Storage	✓ Correct
C	IOPS	✓ Correct
D	Network Throughput	
E	SAP Application Performance Standard (SAPS)	

Correct answers: A, B, C

EXPLANATION

Before installing SAP HANA in a tailored data center integration (TDI) environment, SAP recommends sizing the following:

Main Memory

Persistent Storage

IOPS

Here's an explanation of each option:

Main Memory: Main Memory is crucial for SAP HANA because it is an in-memory database. Sizing the main memory correctly ensures that the system can handle the data volume and workload it will process. Insufficient memory can lead to performance issues and system instability.

Persistent Storage: Persistent Storage is essential for data durability and recovery. SAP HANA uses persistent storage to save data during database operations and for recovery purposes in case of a failure. Properly sizing persistent storage ensures that there is adequate space for data and logs, which is critical for performance and reliability.

IOPS: IOPS (Input/Output Operations Per Second) measures the performance of storage systems. Sizing IOPS correctly is important to ensure that the storage can handle the read/write operations required by SAP HANA. High IOPS is necessary for efficient data loading, transaction processing, and overall system performance.

Network Throughput: Network Throughput is important for data transfer within the system and between systems in a distributed environment. But for a Single HANA Installation on tailored data center integration (TDI), Network Throughput is not the most significant performance indicator. Hence this is not a suitable option for this question.

SAP Application Performance Standard (SAPS): SAP Application Performance Standard (SAPS) is a measure of system performance that indicates how well the system can handle SAP application workloads. While sizing SAPS is important for the overall system performance and capacity planning, it is not specific to the TDI installation requirements of SAP HANA. SAPS is more related to the overall performance characteristics of the SAP applications rather than the specific infrastructure requirements for SAP HANA in a TDI setup.

Summary:

When preparing for an SAP HANA installation in a TDI environment, it is crucial to size Main Memory, Persistent Storage and IOPS correctly. These components are fundamental to ensuring the system can handle the data volume, workload, and performance requirements of SAP HANA.

Refer the below SAP Documentation to learn more regarding this:

Performing SAP HANA Sizing

QUESTION 38 of 40

What processes does an ABAP Central services instance provide at a minimum?

Note: There are 2 correct answers to this question.

A	ABAP Enqueue Server	✓ Correct
B	SAP Gateway	
C	Integrated Web Dispatcher	
D	ABAP Message Server	✓ Correct

Correct answers: A, D

EXPLANATION

At Minimum, ABAP Central services provides ABAP Message Server & ABAP Enqueue Server service on it. whereas SAP Gateway & Integrated Web Dispatcher are optional and can be installed on top of plain ABAP Central services.

Hence the correct option for this question is:

ABAP Enqueue Server

ABAP Message Server

Refer the below SAP Documentation to learn more regarding this:

Architecture of SAP NetWeaver Application Server ABAP

QUESTION 39 of 40

In an SAP Fiori app, what is used as source for the data in a dynamic tile?

A	RFC	
B	InA	
C	BSP	
D	OData	✓ Correct

Correct answer: D

EXPLANATION

In an SAP Fiori app, an OData service is typically used as the source for the data in a dynamic tile. Dynamic tiles are interactive UI elements that display real-time data, such as key performance indicators (KPIs), counters, or status updates, which are dynamically retrieved and updated.

The primary source of data for dynamic tiles is an OData service. OData (Open Data Protocol) is a standardized protocol for building and consuming RESTful APIs. It allows the tile to fetch data from SAP backend systems in a structured and consistent manner.

Refer the below SAP Documentation to learn more regarding this:

Introducing OData (sap.com)

QUESTION 40 of 40

Identify activities that you should complete before executing an update of your SAP system using Software Update Manager (SUM). Which activities will make updating your SAP system easier, if executed in advance & is Recommended by SAP?

A	Read and follow the corresponding SAP Notes for the version of SUM you will be using.	✓ Correct
B	Check for modifications that might require attention during the update.	✓ Correct
C	Execute SAP Load Generator before starting the update.	
D	Check available disk space and free space in the database.	✓ Correct

Correct answers: A, B, D

EXPLANATION

To Answer this question, let us go through each option one by one and understand their significance:

Read and follow the corresponding SAP Notes for the version of SUM you will be using.

Reading and following the corresponding SAP Notes for the version of SUM you will be using is crucial before executing an update. These notes contain important information, best practices, and potential issues that you may encounter during the update process. Following these notes will help you prepare adequately and avoid common pitfalls.

Check for modifications that might require attention during the update.

Checking for modifications is a correct option because during the update is essential to ensure a smooth update process. Any customizations or modifications made to the SAP system may need to be adjusted or re-implemented after the update. Identifying these modifications in advance will help you plan for any necessary changes and minimize disruptions.

Execute SAP Load Generator before starting the update.

Executing SAP Load Generator before starting the update is not a recommended activity or required by SAP for preparing for an update using Software Update Manager (SUM). The SAP Load Generator is typically used for load testing and performance tuning, and it is not directly related to the update process. though it is recommended to execute SGEN Post Upgrade is completed.

Check available disk space and free space in the database.

Checking available disk space and free space in the database is a critical step before executing an update using Software Update Manager (SUM). Adequate disk space is necessary for storing temporary files, logs, and backups generated during the update process. Insufficient disk space can lead to update failures or data corruption. Checking and ensuring sufficient disk space will help prevent potential issues during the update.

From the above explanation we can conclude the correct options for this question are:

Read and follow the corresponding SAP Notes for the version of SUM you will be using.

Check for modifications that might require attention during the update.

Check available disk space and free space in the database.