

SUBMERSIBLE ELECTRICAL SEWAGE PUMPS

SUBMERSIBLE PORTABLE INSTALLATION (S TYPE) AND SUBMERSIBLE PERMANENT INSTALLATION (P TYPE)

SPS208S/P 20 HP (15 Kw)

6" (150mm) Hose
8" (200mm) Optional
(Flange - Optional)

TECHNICAL DETAILS

MECHANICAL SEALS

Tandem TC/TC mechanical seals enclosed in pressure compensated oil chamber.

BEARINGS

Upper bearing : Single row, deep groove ball bearing.
Lower bearing : Double row, angular contact bearing.

POWER CABLE

Cable Size : 7 core 4.0 sq.mm + 2 core 1.0 sq.mm
Cable Length : 15 meters
EPR insulated, water and oil proof copper conductor flexible cable.

IMPELLER

Type : Single Channel
Material : C.I. IS210 FG 260

STANDARD MOC

Pump Casing : C.I. IS 210 FG 260
Rotor Shaft : SS 431
Hardware : SS 304
"O" Rings : Nitrile Rubber
Mech. Seals : TC/TC

MOTOR (STAR-DELTA START)

continuous rated, 4-pole induction motor with squirrel cage rotor.

Frequency (Hz)	50
AC Supply (Phase)	3
Voltage (V)	415
Speed (RPM)	1450
Power Rating (Kw)	15
Current Rating (FL) (Amp)	30.6
Max. Temperature of Pumped Fluid (°C)	40
Max. Starts/Stop Per Hour	15

PUMP DIMENSIONS

Pump height (mm) : 1030
Pump Width (mm) : 890

PUMP WEIGHT

(S - Type) Approx. without cable (Kg) : 310
(P - Type) Approx. without cable (Kg) : 385

PUMP SUBMERGENCE

Pump submergence below Fluid level maximum 10 meters.

SOLID HANDLING CAPACITY : 100 mm

SURFACE TREATMENT

Primer with Epoxy and black choloric paint for long life.



PERFORMANCE CURVES

