

Program 1: Single Quote Handling

Problem

Write a C program that accepts a command containing single quotes and preserves everything inside the quotes literally.

Example:

Input:

```
echo 'Hello $USER'
```

Output:

```
Hello $USER
```

Program 2: Double Quote Handling

Problem

Write a C program that identifies double-quoted strings and preserves spaces inside them.

saikrishna__90156@DESKTOP- X

+ v

```
saikrishna__90156@DESKTOP-2JF9H5T:~$ nano skill5.c
saikrishna__90156@DESKTOP-2JF9H5T:~$ gcc skill5.c -o skill5
saikrishna__90156@DESKTOP-2JF9H5T:~$ ./skill5
Enter text: i love you
Parsed Output: i love you
saikrishna__90156@DESKTOP-2JF9H5T:~$ nano skill5a.c
saikrishna__90156@DESKTOP-2JF9H5T:~$ gcc skill5a.c -o skill5a
saikrishna__90156@DESKTOP-2JF9H5T:~$ ./skill5a
Enter text: i love you too
Parsed Output: i love you too
saikrishna__90156@DESKTOP-2JF9H5T:~$ cat skill5.c
#include <stdio.h>
#include <string.h>

int main() {
    char input[200];
    int insideQuote = 0;
    int i;

    printf("Enter text: ");
    fgets(input, sizeof(input), stdin);

    printf("Parsed Output: ");

    for (i = 0; input[i] != '\0'; i++) {
        if (input[i] == '\\') {
            insideQuote = !insideQuote;
        }
        else {
            printf("%c", input[i]);
        }
    }
}
```

```
        return 0;
    }
saikrishna__90156@DESKTOP-2JF9H5T:~$ cat skill5a.c
#include <stdio.h>
#include <string.h>

int main() {
    char input[200];
    int insideQuote = 0;
    int i;

    printf("Enter text: ");
    fgets(input, sizeof(input), stdin);

    printf("Parsed Output: ");

    for (i = 0; input[i] != '\0'; i++) {
        if (input[i] == '\\') {
            insideQuote = !insideQuote;
        }
        else {
            printf("%c", input[i]);
        }
    }

    return 0;
}
saikrishna__90156@DESKTOP-2JF9H5T:~$ |
```

saikrishna__90156@DESKTOP- X

+ v

```
saikrishna__90156@DESKTOP-2JF9H5T:~$ nano skill5.c
saikrishna__90156@DESKTOP-2JF9H5T:~$ gcc skill5.c -o skill5
saikrishna__90156@DESKTOP-2JF9H5T:~$ ./skill5
Enter text: i love you
Parsed Output: i love you
saikrishna__90156@DESKTOP-2JF9H5T:~$ nano skill5a.c
saikrishna__90156@DESKTOP-2JF9H5T:~$ gcc skill5a.c -o skill5a
saikrishna__90156@DESKTOP-2JF9H5T:~$ ./skill5a
Enter text: i love you too
Parsed Output: i love you too
saikrishna__90156@DESKTOP-2JF9H5T:~$ cat skill5.c
#include <stdio.h>
#include <string.h>

int main() {
    char input[200];
    int insideQuote = 0;
    int i;

    printf("Enter text: ");
    fgets(input, sizeof(input), stdin);

    printf("Parsed Output: ");

    for (i = 0; input[i] != '\0'; i++) {
        if (input[i] == '\\') {
            insideQuote = !insideQuote;
        }
        else {
            printf("%c", input[i]);
        }
    }
}
```