

NAME: J.CHANDRA HASINI
ROLL_NO:2520030086
SUBJECT: OSSP (PRATICAL)

1. Pipes.c

```
GNU nano 8.7.1 pipe.c
#include <stdio.h>
#include <unistd.h>
#include <sys/wait.h>
#include <string.h>

int main()
{
    int fd[2];
    pid_t pid;
    char message[] = "Hello from Parent";
    char buffer[100];

    pipe(fd);

    pid = fork();

    if (pid == 0)
    {
        // Child
        close(fd[1]);

        read(fd[0], buffer, sizeof(buffer));

        printf("Child received: %s\n", buffer);

        close(fd[0]);
    }
    else
    {
        // Parent
        close(fd[0]);

        write(fd[1], message, strlen(message) + 1);

        close(fd[1]);

        wait(NULL);
    }
}
```

hasini@DESKTOP-UTC BQ51:~\$ nano pipe.c
hasini@DESKTOP-UTC BQ51:~\$ gcc pipe.c -o pipe
hasini@DESKTOP-UTC BQ51:~\$./pipe
Child received: Hello from Parent
hasini@DESKTOP-UTC BQ51:~\$

2. Signal.c

```
GNU nano 8.7.1 signal.c *
#include <stdio.h>
#include <stdlib.h>
#include <signal.h>

void myhandler(int signo)
{
    printf("\nSignal Received\n");
    printf("Signal Number = %d\n", signo);
    exit(1);
}

int main()
{
    signal(SIGSEGV, myhandler);

    int x = 0;

    printf("Enter the number : ");
    scanf("%d", &x);

    printf("The entered number is %d\n", x);
}
```

```
hasini@DESKTOP-UTCBQ51:~$ nano signal.c
hasini@DESKTOP-UTCBQ51:~$ gcc signal.c -o signal
hasini@DESKTOP-UTCBQ51:~$ ./signal
Enter the number : 13
The entered number is 13
hasini@DESKTOP-UTCBQ51:~$ |
```