

Indian Institute of Information Technology Allahabad

Assignment - Process & Threads (Oct 2021)

M.Tech

Course Name	Course Code	Deadline
Programming Practices	—	-

Important Instructions: This is an individual assignment i.e., not to be done in a team/group. You have to submit a zip file of the programs. Submit the assignment files on Google classroom page. Late submissions will not be entertained. These are very basic problems and it is easy to find the solution to this assignment on the Internet as well. However, during evaluation we may ask you to explain the code and also solve any related problem on the spot. Hence, practising these solutions yourself is the best option. So please use your ethics and do the assignment to improve your learning.

1. Use the `ps`, `ps lx`, `ps tree` and `ps -aux` command to display the process attributes.
2. Learn the `top` command to display the resource utilization statistics of processes:
 - Open a terminal and type the `top` command
 - Start a browser and see the effect on the `top` display
 - Compile a C program and observe the same effect (Use a long loop - say `while(1)` to observe the effect)
 - From the `top` display, answer the following:
 - How much memory is free in the system?
 - Which process is taking more CPU?
 - Which process has got maximum memory share?
 - Write a CPU bound C program and a I/O bound C program (e.g. using more `printf` statements within `while(1)` loop), compile and execute both of them.
3. Write a program in C that creates a child process, waits for the termination of the child and lists its PID, together with the state in which the process was terminated (in decimal and hexadecimal)
4. Write a C program such that it forks a new process. Then the parent process and the child process should create one more process such that the program in all has four running processes. Each process should print its process ID and its parent process ID. Draw process hierarchy starting from parent process.
5. In a C program, print the address of the variable and enter into a long loop (say using `while(1)`).
 - Start three to four processes of the same program and observe the printed address values.
 - Show how two processes which are members of the relationship parent-child are concurrent from execution point of view, initially the child is copy of the parent, but every process has its own data.

6. Test the source code below:

```
for(i = 1; i <= 10; i++){
    fork();
    printf("The process with the PID=%d",getpid());
}
```

In the next phase, modify the code, such as after all created processes have finished execution, in a file `process management.txt` the total number of created processes should be stored.

7. Write two programs: one called `client.c`, the other called `server.c`. The client program lists a prompt and reads from the keyboard two integers and one of the characters '+' or '-'. The read information is transmitted with the help of the system call `exec` to a child process, which executes the server code. After the child (server) process finishes the operation, it transmits the result to parent process (client) with the help of the system call `exit`. The client process prints the result on the screen and also reprints the prompt, ready for a new reading.
8. Write a C program that takes a file name as a command line parameter and sorts a set of integers stored in the file (use any sorting method). You can assume that the file will always be there in the current directory and that it will always contain a set of integers (maximum no. of integers is 1000). The sorted output is written to the display and the input file is left unchanged. Compile the C file into an executable named "sort1". Name the C file `sort1.c`. Now write a C program (`xsort.c`) that implements a command called "xsort" that you will invoke from the shell prompt. The syntax of the command is "xsort <filename>". When you type the command, the command opens a new xterm window (terminal), and then sorts the integers stored in the file <filename> using the program "sort1". Look up the man pages for xterm, fork and the different variations of `exec*` system calls (such as `execv`, `execve`, `execlp` etc.) to do this assignment. Submit the C files `sort1.c` and `xsort.c`.
9. Perform a parallel matrix multiplication using POSIX threads in C/C++. Compare the execution time of the program against serial matrix multiplication code by modifying the number of threads used to do the matrix multiplication.