Status	Finished
Started	Tuesday, 20 October 2026, 4:10 PM
Completed	Tuesday, 20 October 2026, 4:16 PM
Duration	6 mins 7 secs
Grade	**15.00** out of 15.00 (**100**%)

Question **1**

Correct

Mark 1.00 out of 1.00

What is printed when the following code is run?

```
tup = ('30', '3', '2', '8')
print(sorted(tup,reverse = True))
```

a. ['30', '8', '3', '2']

b. ['2', '3', '30', '8']

c. ['2', '3', '8', '30']

d. ['8', '30', '3', '2'] ✓

Question **2**

Correct

Mark 1.00 out of 1.00

Which of the following Python code will create a set?

(i) set1=set((0,9,0))
(ii) set1=set([0,2,9])
(iii) set1={}

a. All of the above

b. ii

c. i,ii ✓

d. iii

Question **3**

Correct

Mark 1.00 out of 1.00

Find the output of the given Python program?

```
t1 = (1,2,3,(4,5))
t2 = (3,2,1,(4,5))
print(t1>t2)
```

a. True

b. Error

c. False ✓

d. Error

Question **4**

Correct

Mark 1.00 out of 1.00

Choose the correct option.

a. In Python, a tuple can contain only strings as its elements.

b. In Python, a tuple can contain either string or integer but not both at a time.

c. In Python, a tuple can contain both integers and strings as its elements. ✓

d. In Python, a tuple can contain only integers as its elements.

Question **5**

Correct

Mark 1.00 out of 1.00

```
What is the output of the following code?
```

```
aTuple = (10, 20, 30, 40, 50, 60, 70, 80)
print(aTuple[2:5], aTuple[:4], aTuple[3:])
```

a. (30, 40, 50) (10, 20, 30, 40) (40, 50, 60, 70, 80) ✓

b. (30, 40, 50)(40, 50, 60, 70, 80)

c. (30, 40, 50) (10, 20, 30, 40)

d. (10, 20, 30, 40) (40, 50, 60, 70, 80)

Question **6**

Correct

Mark 1.00 out of 1.00

If a=(15,16,17,18,19,25), then a[1:-1] will be

Note :

a=(15,16,17,18,19,25)

print((a[1:-1]))

a. Error

b. (25,19,18,17)

c. (16,17,18,19) ✓

d. (16,17,18)

Question **7**

Correct

Mark 1.00 out of 1.00

What is the output of the following union operation

```
set1 = {10, 20, 30, 40}
set2 = {50, 20, "10", 60}

set3 = set1.union(set2)
print(set3)
```

a. SynatxError: Different types cannot be used with sets

b. {40, '10', 50, 20, 60, 30}

c. {40, 10, '10', 50, 20, 60, 30} ✓

d. {40, 10, 50, 20, 60, 30}

Question **8**

Correct

Mark 1.00 out of 1.00

What will be the output of following Python code?

```
set1={2,5,3}

set2={3,1}

set3={}

set3=set1&set2

print(set3)
```

a. {2,5,3,1}

b. {2,5,1}

c. {}

d. {3} ✓

Question **9**

Correct

Mark 1.00 out of 1.00

What is the output of the given below program?

```
t1 = (1,2,3)
t2 = (4,5,6)
x = t1+t2
print(x)
```

a. (1,2,3,4,5,6) ✓

b. Error

c. (1,2,3,3,2,1)

d. (1,2,3)(4,5,6)

Question **10**

Correct

Mark 1.00 out of 1.00

What is the output of the following

```
set1 = {10, 20, 30, 40, 50}
set2 = {60, 70, 10, 30, 40, 80, 20, 50}

print(set1.issubset(set2))
print(set2.issuperset(set1))
```

a. True
False

b. False
False

c. False
True

d. True ✓
True

Question **11**

Correct

Mark 1.00 out of 1.00

What is the output of the following set operation

```
sampleSet = {"Yellow", "Orange", "Black"}
sampleSet.update(["Blue", "Green", "Red"])
print(sampleSet)
```

a. {'Yellow', 'Orange', 'Red', 'Black', 'Green', 'Blue'} ✓

b. {'Yellow', 'Orange', 'Black', ["Blue", "Green", "Red"]}

c. TypeError: update() doesn't allow list as a argument.

d. Name Error

Question **12**

Correct

Mark 1.00 out of 1.00

Find the output of the given Python program?

t1 = (55, 44, 33, 22, 11)

x = [t1[i] for i in range(0, len(t1), 2)]

print(x)

- a. ([55,33,11])
- b. [(55,33,11)]
- c. (55,33,11)
- d. [55, 33, 11] ✓

Question **13**

Correct

Mark 1.00 out of 1.00

What will the below Python code do?

```
set1={2,3}

set2={3,2}

set3={2,1}

if(set1==set2):

    print("yes")

else:

    print("no")

if(set1==set3):

    print("yes")

else:

    print("no")
```

- a. Yes, No ✓
- b. No, No
- c. "==" is not supported for set in Python
- d. Yes, Yes

Question **14**

Correct

Mark 1.00 out of 1.00

Select which is true for Python tuple?

- a. A tuple is unordered
- b. A tuple maintains the order of items ✓
- c. None of these
- d. We can change the tuple once created

Question **15**

Correct

Mark 1.00 out of 1.00

What is the output of the following code

```
aSet = {1, 'rec', ('cse', 'ece'), True}
print(aSet)
```

- a. {‘rec’, 1, (‘cse’, ‘ece’),True}
- b. {‘rec’, 1, (‘cse’, ‘ece’)} ✓
- c. {‘rec’, True, (‘cse’, ‘ece’)}
- d. Error