



PACIFIC
GRAPHICS
2026
SINGAPORE

CT2Yarn: Yarn Level Reconstruction of Crochet from Computed Tomography

Chang Luo, Nobuyuki Umetani

The University of Tokyo



October 2026 · Singapore



UTokyo

Background: What's Crochet?

- Distinct from Knitting, fabricated as a uniform 2D grid.
- Crochet is fabricated in 1D Line has more freedom.



- **Machine fabricable**, just put multiple hooks.
- **Hand-craft only**, due to the flexibility.
- Mainly for sweaters, scarfs, hats, etc.
- Mainly for amigurumi, flat patch decoration, etc.

Background: Why Computed Tomography?


- CT Scan can see internal structure.



2D Image of Crochet



CT Scanner



CT Volume with slices

- Propose a method to reconstruct the crochet.



Crochet



CT Volume Data



Centerline


- If we could reconstruct the yarn geometry structure, then...

- ✓ More **realistic fiber-level rendering** of the crocheted fabrics.



Physics Based Rendering

- ✓ **Physics Simulation** with mechanical properties.




Physics Simulation

Motivation: Potential Applications

- Semantics reconstruction will help...


- ✓ Recover the **unknown pattern**, or **validation** of the made crochet.



Bought crochets from somewhere

<https://www.youtube.com/watch?v=9ThrkgGhBVw>

- ✓ Stich by stich replay of the crochet process as a **teaching tutorial**.



Video Tutorials are hard to follow

<https://youtu.be/oAlGR-6nInI?si=vMMrchuMs75cvBd5>

Related Work: Knitting Reconstruction [Alexandre+19]

- Recover Knit Instruction from 2D Images.




Limitation: Knitting is very organized



- **2D Image** is too hard for Crochet
- **No Uniform Grid** in Crochet



Capture



2D Image



Machine Knit Instruction


Related Work: Crochet Synthesis [Michal+22]

- Generate text crochet instruction for Closed Mesh.





Limitation: Different Modelling Direction



- This is **Forward Synthesis**
- Designed **only for Amigurumi**





Input



Crochet Graph




Crochet Instruction





Hand-crafted Crochet


Related Work: CT Hair Reconstruction [Shen+23]

- 3D CT Volume Scan $\rightarrow$ Hair strands.



- Crochet is more sensitive to local topology error.






- (b) Volume $\mathcal{V}$: size in $H \times W \times D$, intensity value in each voxel.
- (c,d) Oriented Points $\mathcal{P}$ and Center Points $\hat{\mathcal{P}} : (X,Y,Z)$.
- (e) Fragments $\mathcal{F}$: local typology built from center points.
- (f) Centerline $\mathcal{C}$: global typology of the entire crochet yarn.


Method: Direction detection

- Given a 3D CT Volume, want to compute **direction per voxel**.




Method: Direction detection with Gabor kernels

- Gabor kernels could be used to detect directions.




Method: Gabor in 3D

- $K = 32$ directions sampling on a hemi-sphere.
- For each direction calculate the response in Volume $\mathcal{V}$.





Method: Direction detection

- Directions are extracted per voxel.





Method: Centerline Extraction

- Where is the **skeleton (centerline)** of the yarn?
- Mean Shift is an algorithm for clustering.




Method: Centerline Extraction by Mean-Shift

- Mean-Shift push points to their local centers iteratively.





$$x' = \frac{1}{|S_r(x)|} \sum_{x_i \in S_r(x)} x_i$$




Method: Centerline Extraction by Mean-Shift

- Project the shift to perpendicular direction.





$$x' = \text{Proj}_{\Pi(x)} \left(\frac{1}{|S_r(x)|} \sum_{x_i \in S_r(x)} x_i \right)$$




Method: Centerline Extraction by Mean-Shift

- Weighting with cosine similarity.





$$w(x_i, x) = \cos^\alpha(x_i, x)$$

$$x' = \text{Proj}_{\Pi(x)} \left(\frac{1}{\left| \sum_{x_i \in S_r(x)} w_i \right|} \sum_{x_i \in S_r(x)} w_i x_i \right)$$



Method: Centerline Extraction by Mean-Shift


- Anisotropic kernel shape!



$$\sigma_{perp} = r \quad \sigma_{tan} = \rho r$$


$$w(x_i, x) = \exp \left[-\frac{1}{2} \left(\frac{\delta_{tan}^2}{\sigma_{tan}^2} + \frac{\delta_{perp}^2}{\sigma_{perp}^2} \right) \right] \cos^\alpha(x_i, x)$$

$$x' = \text{Proj}_{\Pi(x)} \left(\frac{1}{\left| \sum_{x_i \in S_r(x)} w_i \right|} \sum_{x_i \in S_r(x)} w_i x_i \right)$$




Method: Centerline Extraction by Mean-Shift


Naive




+ Projection




+ Projection + Direction




+ Projection + Direction + Anisotropic




- **Minimum Spanning Tree** (MST) builds fragments with connection radius given by user.



- **Automatic** and manual tools to build global topology.




Ring



Twig


Method: Automatic Repairing

- Automatic and manual tools to build global topology.




Method: Manual Repairing

- Automatic and manual tools to build global topology.



Bezier



Freehand

Results: Qualitative Evaluation

Color coded fragments

Red – Manual | Green – Auto

Reference

Chain C



Chain S



Chain O



Results: Qualitative Evaluation


Color coded fragments

Red – Manual | Green – Auto



Reference





Patch 1



Patch 2



Patch 3



Results: Qualitative Evaluation

Color coded fragments

Red – Manual | Green – Auto

Reference




Letter P



Number 2



Letter G




Number 6




- Crochet sample stills need to be loose and simple.
- When tightly crocheted, manual repair is necessary.



Tight crochet



Normal crochet




Loose crochet

Applications: Rendering




Applications: Rendering

RGB Reference Photo



Applications: Physics Simulation

RGB Reference Photo




Applications: Physics Simulation

RGB Reference Photo




Application: Template Fitting

- Auto-regressively, can obtain the semantic stitch pattern!



Application: Template Fitting


- We can obtain the **semantic stitch pattern**!



- **Human-In-the-Loop** yarn centerline reconstruction.

- **Input:** CT Scan of Crochet

- **Output:** Centerline Curve



- **Future plan:**

- Annotate more samples as a large dataset for scaling up to support the machine learning.
- Finding an optimization method to include the discrete decisions to repair the topology.



PACIFIC
GRAPHICS
2026
SINGAPORE

Thank you for your attention!

Chang Luo, Nobuyuki Umetani

The University of Tokyo

October 2026 · Singapore



UTokyo