

Choice probabilities in dynamic models follow the same structure as static cases

Key difference: use conditional value functions v 's instead of utilities u 's

Choice probabilities in dynamic models follow the same structure as static cases

Key difference: use conditional value functions v 's instead of utilities u 's

For multinomial logit with choice set J alternatives:

$$p_{jt}(X_{it}) = \frac{\exp(v_{jt}(X_{it}))}{\sum_{k=1}^J \exp(v_{kt}(X_{it}))}$$

Choice probabilities in dynamic models follow the same structure as static cases

Key difference: use conditional value functions v 's instead of utilities u 's

For multinomial logit with choice set J alternatives:

$$p_{jt}(X_{it}) = \frac{\exp(v_{jt}(X_{it}))}{\sum_{k=1}^J \exp(v_{kt}(X_{it}))}$$

This is why we defined the conditional value functions the way that we did:

So that we could express the current-period choice probabilities conveniently

Before we get to the likelihood, let's remind ourselves what we're trying to estimate:

$$v_{jt}(X_{it}; \alpha, \beta, \gamma) = u_{jt}(X_{it}; \alpha) + \beta \int \mathbb{E}_{\epsilon} \left\{ \max_k v_{kt+1}(X_{it+1}; \alpha, \beta, \gamma) + \epsilon_{ikt+1} \right\} dF_{jt}(X_{it+1} | X_{it}; \gamma)$$

Three sets of parameters to estimate:

Before we get to the likelihood, let's remind ourselves what we're trying to estimate:

$$v_{jt}(X_{it}; \alpha, \beta, \gamma) = u_{jt}(X_{it}; \alpha) + \beta \int \mathbb{E}_{\epsilon} \left\{ \max_k v_{kt+1}(X_{it+1}; \alpha, \beta, \gamma) + \epsilon_{ikt+1} \right\} dF_{jt}(X_{it+1}|X_{it}; \gamma)$$

α : Flow utility parameters

Before we get to the likelihood, let's remind ourselves what we're trying to estimate:

$$v_{jt}(X_{it}; \alpha, \beta, \gamma) = u_{jt}(X_{it}; \alpha) + \beta \int \mathbb{E}_{\epsilon} \left\{ \max_k v_{kt+1}(X_{it+1}; \alpha, \beta, \gamma) + \epsilon_{ikt+1} \right\} dF_{jt}(X_{it+1} | X_{it}; \gamma)$$

β : Discount factor

Before we get to the likelihood, let's remind ourselves what we're trying to estimate:

$$v_{jt}(X_{it}; \alpha, \beta, \gamma) = u_{jt}(X_{it}; \alpha) + \beta \int \mathbb{E}_{\epsilon} \left\{ \max_k v_{kt+1}(X_{it+1}; \alpha, \beta, \gamma) + \epsilon_{ikt+1} \right\} dF_{jt}(X_{it+1} | X_{it}; \gamma)$$

γ : Parameters governing state transitions

Putting it all together, assume the following:

- $\epsilon_{ijt} \stackrel{iid}{\sim} \text{T1EV}$
- $u_{jt}(X_{it}; \alpha) = X_{it}\alpha_j$

Putting it all together, assume the following:

- $\epsilon_{ijt} \stackrel{iid}{\sim} \text{T1EV}$
- $u_{jt}(X_{it}; \alpha) = X_{it}\alpha_j$

Then

$$p_{jt}(X_{it}; \alpha, \beta, \gamma) = \frac{\exp [X_{it}\alpha_j + \beta \int \log (\sum_k \exp (v_{kt+1}(X_{it+1}; \alpha, \beta, \gamma))) dF_{jt}(X_{it+1}|X_{it}; \gamma) + \beta c]}{\sum_m \exp [X_{it}\alpha_m + \beta \int \log (\sum_{k'} \exp (v_{k't+1}(X_{it+1}; \alpha, \beta, \gamma))) dF_{mt}(X_{it+1}|X_{it}; \gamma) + \beta c]}$$

When taking this model to data, there are two model objects we need to match:

1. Getting the p 's to match the d 's (choices)
2. Getting the mapping between X_t and X_{t+1}

The likelihood function thus incorporates both choice and state transition probabilities:

$$\mathcal{L}(\alpha, \beta, \gamma; X) = \prod_i \prod_t \prod_j [p_{jt}(X_{it}; \alpha, \beta, \gamma) f_{jt}(X_{it+1} | X_{it}; \gamma)]^{d_{it}=j}$$

The likelihood function thus incorporates both choice and state transition probabilities:

$$\mathcal{L}(\alpha, \beta, \gamma; X) = \prod_i \prod_t \prod_j [p_{jt}(X_{it}; \alpha, \beta, \gamma) f_{jt}(X_{it+1} | X_{it}; \gamma)]^{d_{it}=j}$$

where γ governs the transitions of the state variables X 's

The likelihood function thus incorporates both choice and state transition probabilities:

$$\mathcal{L}(\alpha, \beta, \gamma; X) = \prod_i \prod_t \prod_j [p_{jt}(X_{it}; \alpha, \beta, \gamma) f_{jt}(X_{it+1}|X_{it}; \gamma)]^{d_{it}=j}$$

where γ governs the transitions of the state variables X 's

Taking logs gives the log-likelihood:

$$\ell(\alpha, \beta, \gamma) = \sum_i \sum_t \sum_j (d_{it} = j) \{ \log[p_{jt}(X_{it}; \alpha, \beta, \gamma)] + \log[f_{jt}(X_{it+1}|X_{it}; \gamma)] \}$$

The log likelihood is additively separable in parameters

The log likelihood is additively separable in parameters

This allows for **two-stage estimation**:

The log likelihood is additively separable in parameters

This allows for **two-stage estimation**:

1. Estimate γ from state transitions

The log likelihood is additively separable in parameters

This allows for two-stage estimation:

1. Estimate γ from state transitions
2. Taking $\hat{\gamma}$ as given, estimate α, β from choice probabilities

The log likelihood is additively separable in parameters

This allows for **two-stage estimation**:

1. Estimate γ from state transitions
2. Taking $\hat{\gamma}$ as given, estimate α, β from choice probabilities

Separability simplifies computational burden at cost of statistical efficiency

Bringing in the backwards recursion ideas from last video, algorithm is as follows:

Bringing in the backwards recursion ideas from last video, algorithm is as follows:

1. Start with initial guess of (α, β, γ)

Bringing in the backwards recursion ideas from last video, algorithm is as follows:

1. Start with initial guess of (α, β, γ)
2. Solve value functions v_{jt} backwards from terminal period using Bellman equation

Bringing in the backwards recursion ideas from last video, algorithm is as follows:

1. Start with initial guess of (α, β, γ)
2. Solve value functions v_{jt} backwards from terminal period using Bellman equation
3. Compute policy functions (choice probabilities, $p_{jt}(X_{it}; \alpha, \beta, \gamma)$) using current v_{jt} 's

Bringing in the backwards recursion ideas from last video, algorithm is as follows:

1. Start with initial guess of (α, β, γ)
2. Solve value functions v_{jt} backwards from terminal period using Bellman equation
3. Compute policy functions (choice probabilities, $p_{jt}(X_{it}; \alpha, \beta, \gamma)$) using current v_{jt} 's
4. Evaluate log likelihood $\ell(\alpha, \beta, \gamma)$ and update parameter guesses

Bringing in the backwards recursion ideas from last video, algorithm is as follows:

1. Start with initial guess of (α, β, γ)
2. Solve value functions v_{jt} backwards from terminal period using Bellman equation
3. Compute policy functions (choice probabilities, $p_{jt}(X_{it}; \alpha, \beta, \gamma)$) using current v_{jt} 's
4. Evaluate log likelihood $\ell(\alpha, \beta, \gamma)$ and update parameter guesses
5. Repeat steps 2–5 until convergence

Key insight: Value function iteration nested within likelihood maximization

Key insight: Value function iteration nested within likelihood maximization

- The backwards recursion gives optimal behavior for any given parameter values

Key insight: Value function iteration nested within likelihood maximization

- The backwards recursion gives optimal behavior for any given parameter values
- MLE finds which parameter values make that optimal behavior consistent with observed data

Key insight: Value function iteration nested within likelihood maximization

- The backwards recursion gives optimal behavior for any given parameter values
- MLE finds which parameter values make that optimal behavior consistent with observed data
- Must solve at *all* states—not just observed ones—because state transitions depend on choice probabilities at unvisited states