

Example data structure in a discrete choice experiment:

ID	Scenario	Alternative	Chosen	Z
1	1	A	1	2.3
1	1	B	0	1.8
1	1	C	0	3.1
1	2	A	0	2.5
1	2	B	1	2.9
1	2	C	0	1.7
2	1	A	0	3.2
2	1	B	1	4.1
2	1	C	0	2.8

Example data structure in a discrete choice experiment:

ID	Scenario	Alternative	Chosen	Z
1	1	A	1	2.3
1	1	B	0	1.8
1	1	C	0	3.1
1	2	A	0	2.5
1	2	B	1	2.9
1	2	C	0	1.7
2	1	A	0	3.2
2	1	B	1	4.1
2	1	C	0	2.8

Each individual faces multiple scenarios, each with multiple alternatives

- Estimation proceeds as if one has panel data on choices (Rust, 1987)

- Estimation proceeds as if one has panel data on choices (Rust, 1987)
- Each choice scenario is another observation in the individual's panel

- Estimation proceeds as if one has panel data on choices (Rust, 1987)
- Each choice scenario is another observation in the individual's panel
- Can estimate assuming multinomial logit, nested logit, mixed logit, etc.

Example data structure for rank-ordered logit:

ID	Scenario	Alternative	Rank	Z
1	1	A	1	2.3
1	1	B	3	1.8
1	1	C	2	3.1
1	2	A	2	2.5
1	2	B	1	2.9
1	2	C	3	1.7
2	1	A	3	3.2
2	1	B	1	4.1
2	1	C	2	2.8

Example data structure for rank-ordered logit:

ID	Scenario	Alternative	Rank	Z
1	1	A	1	2.3
1	1	B	3	1.8
1	1	C	2	3.1
1	2	A	2	2.5
1	2	B	1	2.9
1	2	C	3	1.7
2	1	A	3	3.2
2	1	B	1	4.1
2	1	C	2	2.8

Rank = 1 indicates most preferred alternative in each scenario

Here, we use the **exploded logit** model (Beggs et al., 1981) for estimation

Here, we use the **exploded logit** model (Beggs et al., 1981) for estimation

The “choice probability” is the joint event of a particular ranking of options

Here, we use the [exploded logit](#) model (Beggs et al., 1981) for estimation

The “choice probability” is the joint event of a particular ranking of options

It's a product of logit P 's, where the choice set decreases as options are ranked:

$$\Pr(\text{Ranking} = 1, \dots, J) = \frac{\exp(Z_{i1}\gamma)}{\sum_{k=1}^J \exp(Z_{ik}\gamma)} \frac{\exp(Z_{i2}\gamma)}{\sum_{k=2}^J \exp(Z_{ik}\gamma)} \dots \frac{\exp(Z_{iJ-1}\gamma)}{\sum_{k=J-1}^J \exp(Z_{ik}\gamma)}$$

- We can also add mixing to these probabilities to get a **mixed exploded logit**

- We can also add mixing to these probabilities to get a **mixed exploded logit**
- Note that rank ordering provides more information than 0/1 choice data

- We can also add mixing to these probabilities to get a **mixed exploded logit**
- Note that rank ordering provides more information than 0/1 choice data
- We now know the relative preference of the $J - 1$ non-chosen options