

# Class10 Structural Bioinformatics Pt1

## (11/01/24)

Janie Chang-Weinberg (A69037446)

What is in the PDB database anyway? Summary data grabbed from: <https://www.rcsb.org/stats/summary>

```
pdbstats <- read.csv("PDB_stats_summaryfile.csv", row.names = 1)
pdbstats
```

	X.ray	EM	NMR	Multiple.methods	Neutron	Other
Protein (only)	167,317	15,698	12,534	208	77	32
Protein/Oligosaccharide	9,645	2,639	34	8	2	0
Protein/NA	8,735	4,718	286	7	0	0
Nucleic acid (only)	2,869	138	1,507	14	3	1
Other	170	10	33	0	0	0
Oligosaccharide (only)	11	0	6	1	0	4
Total						
Protein (only)	195,866					
Protein/Oligosaccharide	12,328					
Protein/NA	13,746					
Nucleic acid (only)	4,532					
Other	213					
Oligosaccharide (only)	22					

```
x <- pdbstats$Total
x
```

```
[1] "195,866" "12,328" "13,746" "4,532" "213" "22"
```

```
#as.numeric(x): Warning: NAs introduced by coercion[1] NA NA NA NA 213 22
```

```
gsub(',', '', x)
```

```
[1] "195866" "12328" "13746" "4532" "213" "22"
```

doesn't like the commas, ask google. can also use "claude" use gsub to replace commas with nothings

```
convertednocomma <- function(x){  
  #remove comma  
  x <- gsub(',', '', x)  
  #convert to numeric  
  x <- as.numeric(x)  
  return(x)  
}
```

```
convertednocomma(pdbstats$Total)
```

```
[1] 195866 12328 13746 4532 213 22
```

```
n.tot <- sum(convertednocomma(pdbstats$Total))  
n.tot
```

```
[1] 226707
```

The `apply()` function is very useful as it can take any function and "Apply" it over either the ROWS or COLs of a data.frame.

```
colSums(apply(pdbstats, 2, convertednocomma))/n.tot
```

X.ray	EM	NMR	Multiple.methods
0.8325592064	0.1023479646	0.0635181093	0.0010498132
Neutron	Other	Total	
0.0003617003	0.0001632063	1.0000000000	

```
#wait fuck help idk why its not working
```

```
#another way of importing data to avoid issues with commas in the numbas
#library(readr)
#read_csv("PDB_stats_summaryfile.csv")
```

Q1: What percentage of structures in the PDB are solved by X-Ray and Electron Microscopy.

```
n.xray <- sum(convertednocomma(pdbstats$X.ray))
n.em <- sum(convertednocomma(pdbstats$EM))

xraypercent <- ((n.xray/n.tot)*100)
empercent <- ((n.em/n.tot)*100)

xraypercent
```

```
[1] 83.25592
```

```
empercent
```

```
[1] 10.2348
```

83.26% (xray%), 10.23% (EM%)

## Using Mol\*



Figure 1: My first image from Mol-star :D

Q4: Water molecules normally have 3 atoms. Why do we see just one atom per water molecule in this structure?

Cannot see Hydrogen at this resolution, the only atom being displayed here is oxygen.

Q5: There is a critical “conserved” water molecule in the binding site. Can you identify this water molecule? What residue number does this water molecule have

This water molecule’s residue number is HOH 308

Q6: Generate and save a figure clearly showing the two distinct chains of HIV-protease along with the ligand. You might also consider showing the catalytic residues ASP 25 in each chain

and the critical water (we recommend “Ball & Stick” for these side-chains). Add this figure to your Quarto document.



Figure 2: with Aspartate residues and H2O mol

### Use the Bio3D package for structural Bioinformatics

```
library(bio3d)
pdb <- read.pdb("1hsg")
```

Note: Accessing on-line PDB file

```
pdb
```

```
Call: read.pdb(file = "1hsg")
```

```
Total Models#: 1
```

```
Total Atoms#: 1686, XYZs#: 5058 Chains#: 2 (values: A B)
```

```
Protein Atoms#: 1514 (residues/Calpha atoms#: 198)
```

```
Nucleic acid Atoms#: 0 (residues/phosphate atoms#: 0)
```

```
Non-protein/nucleic Atoms#: 172 (residues: 128)
```

```
Non-protein/nucleic resid values: [ HOH (127), MK1 (1) ]
```

```
Protein sequence:
```

```
PQITLWQRPLVTIKIGGQLKEALLDTGADDTVLEEMSLPGRWKPKMIGGIGGFIKVRQYD
QILIEICGHKAIGTVLVGPTPVNIIGRNLLTQIGCTLNFPQITLWQRPLVTIKIGGQLKE
ALLDTGADDTVLEEMSLPGRWKPKMIGGIGGFIKVRQYDQILIEICGHKAIGTVLVGPTP
VNIIGRNLLTQIGCTLNF
```

```
+ attr: atom, xyz, seqres, helix, sheet,
      calpha, remark, call
```

```
attributes(pdb)
```

```
$names
```

```
[1] "atom" "xyz" "seqres" "helix" "sheet" "calpha" "remark" "call"
```

```
$class
```

```
[1] "pdb" "sse"
```

```
head(pdb$atom)
```

	type	eleno	elety	alt	resid	chain	resno	insert	x	y	z	o	b
1	ATOM	1	N	<NA>	PRO	A	1	<NA>	29.361	39.686	5.862	1	38.10
2	ATOM	2	CA	<NA>	PRO	A	1	<NA>	30.307	38.663	5.319	1	40.62
3	ATOM	3	C	<NA>	PRO	A	1	<NA>	29.760	38.071	4.022	1	42.64
4	ATOM	4	O	<NA>	PRO	A	1	<NA>	28.600	38.302	3.676	1	43.40
5	ATOM	5	CB	<NA>	PRO	A	1	<NA>	30.508	37.541	6.342	1	37.87
6	ATOM	6	CG	<NA>	PRO	A	1	<NA>	29.296	37.591	7.162	1	38.40
	segid	elesy	charge										
1	<NA>	N	<NA>										
2	<NA>	C	<NA>										

```
3 <NA>      C   <NA>
4 <NA>      O   <NA>
5 <NA>      C   <NA>
6 <NA>      C   <NA>
```

```
pdbseq(pdb)[25]
```

```
25
"D"
```

Q7. How many amino acids are there in this structure?

```
length(pdbseq(pdb))
```

```
[1] 198
```

There are 198 amino acids in this structure

Q8. Name one of the two non-protein residues?

HOH (water)

Q9. How many protein chains are in this structure?

```
2
```

```
adk <- read.pdb("6s36")
```

Note: Accessing on-line PDB file

PDB has ALT records, taking A only, rm.alt=TRUE

```
adk
```

```
Call: read.pdb(file = "6s36")
```

```
Total Models#: 1
```

```
Total Atoms#: 1898, XYZs#: 5694 Chains#: 1 (values: A)
```

```
Protein Atoms#: 1654 (residues/Calpha atoms#: 214)
```

```
Nucleic acid Atoms#: 0 (residues/phosphate atoms#: 0)
```

Non-protein/nucleic Atoms#: 244 (residues: 244)

Non-protein/nucleic resid values: [ CL (3), HOH (238), MG (2), NA (1) ]

Protein sequence:

MRIILLGAPGAGKGTQAQFIMEKYGIPQISTGDMLRAAVKSGSELGKQAKDIMDAGKLV  
DELVIALVKERIAQEDCRNGFLDGFRTIPQADAMKEAGINVDYVLEFDVPDELIVDKI  
VGRRVHAPSGRVYHVKFNPVKVEGKDDVTGEELTTRKDDQEETVRKRLVEYHQMTAPLIG  
YYSKEAEAGNTKYAKVDGTPVAEVRADLEKILG

+ attr: atom, xyz, seqres, helix, sheet,  
calpha, remark, call

```
library(r3dmol)
source("https://tinyurl.com/viewpdb")
```


```
library(shiny)
view.pdb(pdb)
```



```
modes <- nma(adk)
```

```
Building Hessian...      Done in 0.031 seconds.  
Diagonalizing Hessian... Done in 0.34 seconds.
```

```
plot(modes)
```



```
mktrj(modes, pdb=adk, file='adk.pdb') #give it the pdb= thing to have proper seq
```

```
mktrj(modes, file="adk_m7.pdb")
```

Q10. Which of the packages above is found only on BioConductor and not CRAN?

biocmanager

Q.11 Which of the above packages is not found on BioConductor or CRAN?

bio3d

Q.12 True or False? Functions from the devtools package can be used to install packages from GitHub and BitBucket?

True

```
library(bio3d)
aa <- get.seq("lake_A")
```

Warning in get.seq("lake\_A"): Removing existing file: seqs.fasta

Fetching... Please wait. Done.

aa

```
      1      .      .      .      .      .      .      60
pdb|1AKE|A  MRIILLGAPGAGKGTQAQFIMEKYGIPQISTGDMRLAAVKSGSELGKQAKDIMDAGKLV
      1      .      .      .      .      .      .      60

      61      .      .      .      .      .      .      120
pdb|1AKE|A  DELVIALVKERIAQEDCRNGFLLDGFPR TIPQADAMKEAGINVDYVLEFDVPDELIVDRI
      61      .      .      .      .      .      .      120

      121      .      .      .      .      .      .      180
pdb|1AKE|A  VGRRVHAPSGRVYHVKNPPKVEGKDDVTGEELTRKDDQEETVRKRLVEYHQM TAPLIG
      121      .      .      .      .      .      .      180

      181      .      .      .      214
pdb|1AKE|A  YYSKEAEAGNTKYAKVDGTPVAEVRADLEKILG
      181      .      .      .      214
```

Call:

```
read.fasta(file = outfile)
```

Class:

```
fasta
```

Alignment dimensions:

```
1 sequence rows; 214 position columns (214 non-gap, 0 gap)
```

+ attr: id, ali, call

Q13. How many amino acids are in this sequence, i.e. how long is this sequence?

There are 214 AAs

```
##Blast or hmmer search
```

```
b <- blast.pdb(aa)
```

```
Searching ... please wait (updates every 5 seconds) RID = JNZ3R4MK016
```

```
.....
```


```
Reporting 85 hits
```

```
##Plot a summary of search results:
```

```
hits <- plot(b)
```

```
* Possible cutoff values:    197 11
    Yielding Nhits:         19 85
```

```
* Chosen cutoff value of:    197
    Yielding Nhits:         19
```



```
##List some "Top Hits" and download their .pdb files:
```

```
head(hits$pdb.id)
```

```
[1] "1AKE_A" "8BQF_A" "4X8M_A" "6S36_A" "8Q2B_A" "8RJ9_A"
```

```
files <- get.pdb(hits$pdb.id, path="pdbs", split=TRUE, gzip=TRUE)
```

```
Warning in get.pdb(hits$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):  
pdbs/1AKE.pdb.gz exists. Skipping download
```

```
Warning in get.pdb(hits$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):  
pdbs/8BQF.pdb.gz exists. Skipping download
```

```
Warning in get.pdb(hits$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):  
pdbs/4X8M.pdb.gz exists. Skipping download
```

```
Warning in get.pdb(hits$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):  
pdbs/6S36.pdb.gz exists. Skipping download
```

```
Warning in get.pdb(hits$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):  
pdbs/8Q2B.pdb.gz exists. Skipping download
```

```
Warning in get.pdb(hits$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):  
pdbs/8RJ9.pdb.gz exists. Skipping download
```

```
Warning in get.pdb(hits$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):  
pdbs/6RZE.pdb.gz exists. Skipping download
```

```
Warning in get.pdb(hits$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):  
pdbs/4X8H.pdb.gz exists. Skipping download
```

```
Warning in get.pdb(hits$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):  
pdbs/3HPR.pdb.gz exists. Skipping download
```

```
Warning in get.pdb(hits$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):  
pdbs/1E4V.pdb.gz exists. Skipping download
```

```
Warning in get.pdb(hits$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):  
pdbs/5EJE.pdb.gz exists. Skipping download
```

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):  
pdbs/1E4Y.pdb.gz exists. Skipping download

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):  
pdbs/3X2S.pdb.gz exists. Skipping download

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):  
pdbs/6HAP.pdb.gz exists. Skipping download

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):  
pdbs/6HAM.pdb.gz exists. Skipping download

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):  
pdbs/4K46.pdb.gz exists. Skipping download

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):  
pdbs/4NP6.pdb.gz exists. Skipping download

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):  
pdbs/3GMT.pdb.gz exists. Skipping download

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):  
pdbs/4PZL.pdb.gz exists. Skipping download

	0%
====	5%
=====	11%
=====	16%
=====	21%
=====	26%
=====	32%



##Align and Superimpose structures:

```
pdbbs <- pdbaln(files, fit = TRUE, exefile="msa")
```

Reading PDB files:

```
pdbbs/split_chain/1AKE_A.pdb
pdbbs/split_chain/8BQF_A.pdb
pdbbs/split_chain/4X8M_A.pdb
pdbbs/split_chain/6S36_A.pdb
pdbbs/split_chain/8Q2B_A.pdb
pdbbs/split_chain/8RJ9_A.pdb
pdbbs/split_chain/6RZE_A.pdb
pdbbs/split_chain/4X8H_A.pdb
pdbbs/split_chain/3HPR_A.pdb
pdbbs/split_chain/1E4V_A.pdb
pdbbs/split_chain/5EJE_A.pdb
```

```

pdbs/split_chain/1E4Y_A.pdb
pdbs/split_chain/3X2S_A.pdb
pdbs/split_chain/6HAP_A.pdb
pdbs/split_chain/6HAM_A.pdb
pdbs/split_chain/4K46_A.pdb
pdbs/split_chain/4NP6_A.pdb
pdbs/split_chain/3GMT_A.pdb
pdbs/split_chain/4PZL_A.pdb
    PDB has ALT records, taking A only, rm.alt=TRUE
.   PDB has ALT records, taking A only, rm.alt=TRUE
..  PDB has ALT records, taking A only, rm.alt=TRUE
.   PDB has ALT records, taking A only, rm.alt=TRUE
.   PDB has ALT records, taking A only, rm.alt=TRUE
.   PDB has ALT records, taking A only, rm.alt=TRUE
..  PDB has ALT records, taking A only, rm.alt=TRUE
..  PDB has ALT records, taking A only, rm.alt=TRUE
.... PDB has ALT records, taking A only, rm.alt=TRUE
.   PDB has ALT records, taking A only, rm.alt=TRUE
....

```

#### Extracting sequences

```

pdb/seq: 1   name: pdbs/split_chain/1AKE_A.pdb
    PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 2   name: pdbs/split_chain/8BQF_A.pdb
    PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 3   name: pdbs/split_chain/4X8M_A.pdb
pdb/seq: 4   name: pdbs/split_chain/6S36_A.pdb
    PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 5   name: pdbs/split_chain/8Q2B_A.pdb
    PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 6   name: pdbs/split_chain/8RJ9_A.pdb
    PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 7   name: pdbs/split_chain/6RZE_A.pdb
    PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 8   name: pdbs/split_chain/4X8H_A.pdb
pdb/seq: 9   name: pdbs/split_chain/3HPR_A.pdb
    PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 10  name: pdbs/split_chain/1E4V_A.pdb
pdb/seq: 11  name: pdbs/split_chain/5EJE_A.pdb
    PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 12  name: pdbs/split_chain/1E4Y_A.pdb
pdb/seq: 13  name: pdbs/split_chain/3X2S_A.pdb

```

```

pdb/seq: 14  name: pdbs/split_chain/6HAP_A.pdb
pdb/seq: 15  name: pdbs/split_chain/6HAM_A.pdb
PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 16  name: pdbs/split_chain/4K46_A.pdb
PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 17  name: pdbs/split_chain/4NP6_A.pdb
pdb/seq: 18  name: pdbs/split_chain/3GMT_A.pdb
pdb/seq: 19  name: pdbs/split_chain/4PZL_A.pdb

```

```

ids <- basename.pdb(pdb$id)
#plot(pdb, labels=ids)

#commenting out, as R will not render this figure. It is appended to the final PDF.

```

##Annotate PDB Structures

```

anno <- pdb.annotate(ids)
unique(anno$source)

```

```

[1] "Escherichia coli"
[2] "Escherichia coli K-12"
[3] "Escherichia coli O139:H28 str. E24377A"
[4] "Escherichia coli str. K-12 substr. MDS42"
[5] "Photobacterium profundum"
[6] "Vibrio cholerae 01 biovar El Tor str. N16961"
[7] "Burkholderia pseudomallei 1710b"
[8] "Francisella tularensis subsp. tularensis SCHU S4"

```

```
anno
```

	structureId	chainId	macromoleculeType	chainLength	experimentalTechnique
1AKE_A	1AKE	A	Protein	214	X-ray
8BQF_A	8BQF	A	Protein	234	X-ray
4X8M_A	4X8M	A	Protein	214	X-ray
6S36_A	6S36	A	Protein	214	X-ray
8Q2B_A	8Q2B	A	Protein	214	X-ray
8RJ9_A	8RJ9	A	Protein	214	X-ray
6RZE_A	6RZE	A	Protein	214	X-ray
4X8H_A	4X8H	A	Protein	214	X-ray
3HPR_A	3HPR	A	Protein	214	X-ray
1E4V_A	1E4V	A	Protein	214	X-ray



5EJE_A	5EJE	A	Protein	214	X-ray
1E4Y_A	1E4Y	A	Protein	214	X-ray
3X2S_A	3X2S	A	Protein	214	X-ray
6HAP_A	6HAP	A	Protein	214	X-ray
6HAM_A	6HAM	A	Protein	214	X-ray
4K46_A	4K46	A	Protein	214	X-ray
4NP6_A	4NP6	A	Protein	217	X-ray
3GMT_A	3GMT	A	Protein	230	X-ray
4PZL_A	4PZL	A	Protein	242	X-ray
	resolution	scopDomain			pfam
1AKE_A	2.000	Adenylate kinase	Adenylate kinase, active site lid (ADK_lid)		
8BQF_A	2.050	<NA>	Adenylate kinase, active site lid (ADK_lid)		
4X8M_A	2.600	<NA>	Adenylate kinase (ADK)		
6S36_A	1.600	<NA>	Adenylate kinase (ADK)		
8Q2B_A	1.760	<NA>	Adenylate kinase, active site lid (ADK_lid)		
8RJ9_A	1.590	<NA>	Adenylate kinase (ADK)		
6RZE_A	1.690	<NA>	Adenylate kinase (ADK)		
4X8H_A	2.500	<NA>	Adenylate kinase, active site lid (ADK_lid)		
3HPR_A	2.000	<NA>	Adenylate kinase (ADK)		
1E4V_A	1.850	Adenylate kinase	Adenylate kinase (ADK)		
5EJE_A	1.900	<NA>	Adenylate kinase (ADK)		
1E4Y_A	1.850	Adenylate kinase	Adenylate kinase, active site lid (ADK_lid)		
3X2S_A	2.800	<NA>	Adenylate kinase (ADK)		
6HAP_A	2.700	<NA>	Adenylate kinase, active site lid (ADK_lid)		
6HAM_A	2.550	<NA>	Adenylate kinase (ADK)		
4K46_A	2.010	<NA>	Adenylate kinase, active site lid (ADK_lid)		
4NP6_A	2.004	<NA>	Adenylate kinase (ADK)		
3GMT_A	2.100	<NA>	Adenylate kinase (ADK)		
4PZL_A	2.100	<NA>	Adenylate kinase (ADK)		
	ligandId				
1AKE_A	AP5				
8BQF_A	AP5				
4X8M_A	<NA>				
6S36_A	CL (3),NA,MG (2)				
8Q2B_A	AP5,S04,MP0				
8RJ9_A	ADP (2)				
6RZE_A	NA (3),CL (2)				
4X8H_A	<NA>				
3HPR_A	AP5				
1E4V_A	AP5				
5EJE_A	AP5,C0				
1E4Y_A	AP5				
3X2S_A	JPY (2),AP5,MG				

6HAP_A	AP5	
6HAM_A	AP5	
4K46_A	ADP, AMP, PO4	
4NP6_A	<NA>	
3GMT_A	SO4 (2)	
4PZL_A	CA, FMT, GOL	
		ligandName
1AKE_A		BIS(ADENOSINE)-5'-PENTAPHOSPHATE
8BQF_A		BIS(ADENOSINE)-5'-PENTAPHOSPHATE
4X8M_A		<NA>
6S36_A		CHLORIDE ION (3), SODIUM ION, MAGNESIUM ION (2)
8Q2B_A	BIS(ADENOSINE)-5'-PENTAPHOSPHATE, SULFATE ION, 3[N-MORPHOLINO]PROPANE SULFONIC ACID	
8RJ9_A		ADENOSINE-5'-DIPHOSPHATE (2)
6RZE_A		SODIUM ION (3), CHLORIDE ION (2)
4X8H_A		<NA>
3HPR_A		BIS(ADENOSINE)-5'-PENTAPHOSPHATE
1E4V_A		BIS(ADENOSINE)-5'-PENTAPHOSPHATE
5EJE_A		BIS(ADENOSINE)-5'-PENTAPHOSPHATE, COBALT (II) ION
1E4Y_A		BIS(ADENOSINE)-5'-PENTAPHOSPHATE
3X2S_A	N-(pyren-1-ylmethyl)acetamide (2), BIS(ADENOSINE)-5'-PENTAPHOSPHATE, MAGNESIUM ION	
6HAP_A		BIS(ADENOSINE)-5'-PENTAPHOSPHATE
6HAM_A		BIS(ADENOSINE)-5'-PENTAPHOSPHATE
4K46_A	ADENOSINE-5'-DIPHOSPHATE, ADENOSINE MONOPHOSPHATE, PHOSPHATE ION	
4NP6_A		<NA>
3GMT_A		SULFATE ION (2)
4PZL_A		CALCIUM ION, FORMIC ACID, GLYCEROL
		source
1AKE_A		Escherichia coli
8BQF_A		Escherichia coli
4X8M_A		Escherichia coli
6S36_A		Escherichia coli
8Q2B_A		Escherichia coli
8RJ9_A		Escherichia coli
6RZE_A		Escherichia coli
4X8H_A		Escherichia coli
3HPR_A		Escherichia coli K-12
1E4V_A		Escherichia coli
5EJE_A	Escherichia coli 0139:H28 str. E24377A	
1E4Y_A		Escherichia coli
3X2S_A	Escherichia coli str. K-12 substr. MDS42	
6HAP_A	Escherichia coli 0139:H28 str. E24377A	
6HAM_A		Escherichia coli K-12
4K46_A		Photobacterium profundum

4NP6\_A        *Vibrio cholerae* 01 biovar El Tor str. N16961  
 3GMT\_A                      *Burkholderia pseudomallei* 1710b  
 4PZL\_A *Francisella tularensis* subsp. *tularensis* SCHU S4


1AKE\_A STRUCTURE OF THE COMPLEX BETWEEN ADENYLATE KINASE FROM ESCHERICHIA COLI AND THE INHIBITORS  
 8BQF\_A  
 4X8M\_A  
 6S36\_A  
 8Q2B\_A                                      *E. coli* Adenylate Kinase variant D158A (PDB ID: 8Q2B)  
 8RJ9\_A                                      *E. coli* adenylate kinase Asp84A (PDB ID: 8RJ9)  
 6RZE\_A  
 4X8H\_A  
 3HPR\_A  
 1E4V\_A  
 5EJE\_A                                      Crystallization of *E. coli* Adenylate Kinase variant D158A (PDB ID: 5EJE)  
 1E4Y\_A  
 3X2S\_A  
 6HAP\_A  
 6HAM\_A  
 4K46\_A  
 4NP6\_A  
 3GMT\_A  
 4PZL\_A                                      The crystal structure of *Francisella tularensis* Adenylate Kinase (PDB ID: 4PZL)

		citation	rObserved	rFree
1AKE_A		Muller, C.W., et al. J Mol Biol (1992)	0.19600	NA
8BQF_A	Scheerer, D., et al. Proc Natl Acad Sci U S A (2023)		0.22073	0.25789
4X8M_A	Kovermann, M., et al. Nat Commun (2015)		0.24910	0.30890
6S36_A	Rogne, P., et al. Biochemistry (2019)		0.16320	0.23560
8Q2B_A	Nam, K., et al. J Chem Inf Model (2024)		0.18320	0.22440
8RJ9_A	Nam, K., et al. Sci Adv (2024)		0.15190	0.20290
6RZE_A	Rogne, P., et al. Biochemistry (2019)		0.18650	0.23500
4X8H_A	Kovermann, M., et al. Nat Commun (2015)		0.19610	0.28950
3HPR_A	Schrank, T.P., et al. Proc Natl Acad Sci U S A (2009)		0.21000	0.24320
1E4V_A	Muller, C.W., et al. Proteins (1993)		0.19600	NA
5EJE_A	Kovermann, M., et al. Proc Natl Acad Sci U S A (2017)		0.18890	0.23580
1E4Y_A	Muller, C.W., et al. Proteins (1993)		0.17800	NA
3X2S_A	Fujii, A., et al. Bioconjug Chem (2015)		0.20700	0.25600
6HAP_A	Kantaev, R., et al. J Phys Chem B (2018)		0.22630	0.27760
6HAM_A	Kantaev, R., et al. J Phys Chem B (2018)		0.20511	0.24325
4K46_A	Cho, Y.-J., et al. To be published		0.17000	0.22290
4NP6_A	Kim, Y., et al. To be published		0.18800	0.22200
3GMT_A	Buchko, G.W., et al. Biochem Biophys Res Commun (2010)		0.23800	0.29500
4PZL_A	Tan, K., et al. To be published		0.19360	0.23680

	rWork	spaceGroup
1AKE_A	0.19600	P 21 2 21
8BQF_A	0.21882	P 2 21 21
4X8M_A	0.24630	C 1 2 1
6S36_A	0.15940	C 1 2 1
8Q2B_A	0.18100	P 1 21 1
8RJ9_A	0.15010	P 21 21 2
6RZE_A	0.18190	C 1 2 1
4X8H_A	0.19140	C 1 2 1
3HPR_A	0.20620	P 21 21 2
1E4V_A	0.19600	P 21 2 21
5EJE_A	0.18630	P 21 2 21
1E4Y_A	0.17800	P 1 21 1
3X2S_A	0.20700	P 21 21 21
6HAP_A	0.22370	I 2 2 2
6HAM_A	0.20311	P 43
4K46_A	0.16730	P 21 21 21
4NP6_A	0.18600	P 43
3GMT_A	0.23500	P 1 21 1
4PZL_A	0.19130	P 32

##Perform PCA

```
pc.xray <- pca(pdbbs)
plot(pc.xray)
```




##Calculate RMSD and show structure-based clustering

```
rd <- rmsd(pdb)
```

Warning in rmsd(pdb): No indices provided, using the 199 non NA positions

```
hc.rd <- hclust(dist(rd))
grps.rd <- cutree(hc.rd, k=3)
plot(pc.xray, 1:2, col="grey50", bg=grps.rd, pch=21, cex=1)
```



```
plot(pdbbs, labels=ids)
```

