

# RNA Seq Mini Proj Class14

Janie Chang-Weinberg (A69037446)

## Import Data

We need two things: Counts MetaData (what DESeq calls colData- as it describes the columns in Counts)

```
counts <- read.csv("GSE37704_featurecounts.csv", row.names=1)
metadata <- read.csv("GSE37704_metadata.csv")
```

Start with a sneak peak:

```
head(counts)
```

	length	SRR493366	SRR493367	SRR493368	SRR493369	SRR493370
ENSG00000186092	918	0	0	0	0	0
ENSG00000279928	718	0	0	0	0	0
ENSG00000279457	1982	23	28	29	29	28
ENSG00000278566	939	0	0	0	0	0
ENSG00000273547	939	0	0	0	0	0
ENSG00000187634	3214	124	123	205	207	212
	SRR493371					
ENSG00000186092	0					
ENSG00000279928	0					
ENSG00000279457	46					
ENSG00000278566	0					
ENSG00000273547	0					
ENSG00000187634	258					

```
head(metadata)
```

	id	condition
1	SRR493366	control_sirna
2	SRR493367	control_sirna
3	SRR493368	control_sirna
4	SRR493369	hoxa1_kd
5	SRR493370	hoxa1_kd
6	SRR493371	hoxa1_kd

We want the columns in `counts` to match the rows in the `metadata`

```
colnames(counts)
```

```
[1] "length"      "SRR493366" "SRR493367" "SRR493368" "SRR493369" "SRR493370"
[7] "SRR493371"
```

```
metadata$id
```

```
[1] "SRR493366" "SRR493367" "SRR493368" "SRR493369" "SRR493370" "SRR493371"
```

Since `counts` and `metadata` columns do not match, we must remove the `length` column from the `counts` dataset

```
countData <- counts[,-1]
head(countData)
```

	SRR493366	SRR493367	SRR493368	SRR493369	SRR493370	SRR493371
ENSG00000186092	0	0	0	0	0	0
ENSG00000279928	0	0	0	0	0	0
ENSG00000279457	23	28	29	29	28	46
ENSG00000278566	0	0	0	0	0	0
ENSG00000273547	0	0	0	0	0	0
ENSG00000187634	124	123	205	207	212	258

```
all(colnames(countData) == metadata$id)
```

```
[1] TRUE
```

yay now they match.

## Data CleanUp

### Must filter out zero counts

It is standard practice to remove any genes/transcripts that we have no data for, ie. zero counts in all columns

```
to.keep.inds <- rowSums(countData) > 0
cleanCounts <- countData[to.keep.inds,]
head(cleanCounts)
```

	SRR493366	SRR493367	SRR493368	SRR493369	SRR493370	SRR493371
ENSG00000279457	23	28	29	29	28	46
ENSG00000187634	124	123	205	207	212	258
ENSG00000188976	1637	1831	2383	1226	1326	1504
ENSG00000187961	120	153	180	236	255	357
ENSG00000187583	24	48	65	44	48	64
ENSG00000187642	4	9	16	14	16	16

### Setup for DESeq

```
library(DESeq2)
```

```
dds <- DESeqDataSetFromMatrix(countData = cleanCounts,
                              colData = metadata,
                              design= ~condition)
```

Warning in DESeqDataSet(se, design = design, ignoreRank): some variables in design formula are characters, converting to factors

### DESeq

```
dds <- DESeq(dds)
```

estimating size factors

estimating dispersions

gene-wise dispersion estimates

mean-dispersion relationship

final dispersion estimates

fitting model and testing

```
res <- results(dds)
```

## Inspect Results

```
head(res)
```

log2 fold change (MLE): condition hoxa1 kd vs control sirna


Wald test p-value: condition hoxa1 kd vs control sirna

DataFrame with 6 rows and 6 columns

	baseMean	log2FoldChange	lfcSE	stat	pvalue
	<numeric>	<numeric>	<numeric>	<numeric>	<numeric>
ENSG00000279457	29.9136	0.1792571	0.3248216	0.551863	5.81042e-01
ENSG00000187634	183.2296	0.4264571	0.1402658	3.040350	2.36304e-03
ENSG00000188976	1651.1881	-0.6927205	0.0548465	-12.630158	1.43989e-36
ENSG00000187961	209.6379	0.7297556	0.1318599	5.534326	3.12428e-08
ENSG00000187583	47.2551	0.0405765	0.2718928	0.149237	8.81366e-01
ENSG00000187642	11.9798	0.5428105	0.5215599	1.040744	2.97994e-01
	padj				
	<numeric>				
ENSG00000279457	6.86555e-01				
ENSG00000187634	5.15718e-03				
ENSG00000188976	1.76549e-35				
ENSG00000187961	1.13413e-07				
ENSG00000187583	9.19031e-01				
ENSG00000187642	4.03379e-01				

## Data Viz

```
plot(res$log2FoldChange, -log(res$padj))
```



## Pathway Analysis

### Annotation of genes

First I need to translate my Ensembl IDs in my `res` object to Entrez and gene symbol formats.

For this I will use the `AnnotationDbi` package and its `mapIds()` function

Need to know what format stuff is currently in, and what we would like to “translate” them into.

We currently have Ensembl IDs, but to use KEGG, we need to use Entrez IDs.

```
library(AnnotationDbi)
library(org.Hs.eg.db)
```

```
columns(org.Hs.eg.db)
```

```
[1] "ACCNUM"      "ALIAS"        "ENSEMBL"      "ENSEMBLPROT"  "ENSEMBLTRANS"
[6] "ENTREZID"    "ENZYME"       "EVIDENCE"     "EVIDENCEALL"  "GENENAME"
[11] "GENETYPE"    "GO"           "GOALL"        "IPI"           "MAP"
[16] "OMIM"        "ONTOLOGY"     "ONTOLOGYALL"  "PATH"          "PFAM"
[21] "PMID"        "PROSITE"      "REFSEQ"       "SYMBOL"        "UCSCKG"
[26] "UNIPROT"
```

Let's map to "SYMBOL," "ENTREZID," and "GENENAME," from our "ENSEMBL" ids.

```
res$genename <- mapIds(org.Hs.eg.db,
  keys=rownames(res),
  keytype = "ENSEMBL",
  column = "GENENAME",
  multiVals = "first")
```

'select()' returned 1:many mapping between keys and columns

```
head(res)
```

log2 fold change (MLE): condition hoxa1 kd vs control sirna

Wald test p-value: condition hoxa1 kd vs control sirna

DataFrame with 6 rows and 7 columns

	baseMean	log2FoldChange	lfcSE	stat	pvalue
	<numeric>	<numeric>	<numeric>	<numeric>	<numeric>
ENSG00000279457	29.9136	0.1792571	0.3248216	0.551863	5.81042e-01
ENSG00000187634	183.2296	0.4264571	0.1402658	3.040350	2.36304e-03
ENSG00000188976	1651.1881	-0.6927205	0.0548465	-12.630158	1.43989e-36
ENSG00000187961	209.6379	0.7297556	0.1318599	5.534326	3.12428e-08
ENSG00000187583	47.2551	0.0405765	0.2718928	0.149237	8.81366e-01
ENSG00000187642	11.9798	0.5428105	0.5215599	1.040744	2.97994e-01
	padj	genename			
	<numeric>	<character>			
ENSG00000279457	6.86555e-01	NA			
ENSG00000187634	5.15718e-03	sterile alpha motif ..			
ENSG00000188976	1.76549e-35	NOC2 like nucleolar ..			
ENSG00000187961	1.13413e-07	kelch like family me..			
ENSG00000187583	9.19031e-01	pleckstrin homology ..			
ENSG00000187642	4.03379e-01	PPARGC1 and ESRR ind..			

```
res$symbol <- mapIds(org.Hs.eg.db,
                     keys=rownames(res),
                     keytype = "ENSEMBL",
                     column = "SYMBOL")
```

'select()' returned 1:many mapping between keys and columns

```
res$entrezid <- mapIds(org.Hs.eg.db,
                      keys=rownames(res),
                      keytype = "ENSEMBL",
                      column = "ENTREZID")
```

'select()' returned 1:many mapping between keys and columns

```
head(res)
```

log2 fold change (MLE): condition hoxa1 kd vs control sirna

Wald test p-value: condition hoxa1 kd vs control sirna

DataFrame with 6 rows and 9 columns

	baseMean	log2FoldChange	lfcSE	stat	pvalue
	<numeric>	<numeric>	<numeric>	<numeric>	<numeric>
ENSG00000279457	29.9136	0.1792571	0.3248216	0.551863	5.81042e-01
ENSG00000187634	183.2296	0.4264571	0.1402658	3.040350	2.36304e-03
ENSG00000188976	1651.1881	-0.6927205	0.0548465	-12.630158	1.43989e-36
ENSG00000187961	209.6379	0.7297556	0.1318599	5.534326	3.12428e-08
ENSG00000187583	47.2551	0.0405765	0.2718928	0.149237	8.81366e-01
ENSG00000187642	11.9798	0.5428105	0.5215599	1.040744	2.97994e-01
	padj	genename	symbol	entrezid	
	<numeric>	<character>	<character>	<character>	
ENSG00000279457	6.86555e-01	NA	NA	NA	
ENSG00000187634	5.15718e-03	sterile alpha motif ..	SAMD11	148398	
ENSG00000188976	1.76549e-35	NOC2 like nucleolar ..	NOC2L	26155	
ENSG00000187961	1.13413e-07	kelch like family me..	KLHL17	339451	
ENSG00000187583	9.19031e-01	pleckstrin homology ..	PLEKHN1	84069	
ENSG00000187642	4.03379e-01	PPARGC1 and ESRR ind..	PERM1	84808	

Before going any further lets focus in on a subset of “top” hits.

We can use a starting point log2FC of +/-2 and an adjusted P-value of 0.05

Let's do the foldchange one first

```
top.inds <- (abs(res$log2FoldChange) > 2) & (res$padj <= 0.05)
top.inds[is.na(top.inds)] <- FALSE
```

Let's save our "top genes" to a .csv file!

```
top.genes <- res[top.inds,]
write.csv(top.genes, file="top_geneset.csv")
```

Now we can do some pathway analysis (finally!)

```
library(gage)
```

```
library(gageData)
library(pathview)
```

```
#####
Pathview is an open source software package distributed under GNU General
Public License version 3 (GPLv3). Details of GPLv3 is available at
http://www.gnu.org/licenses/gpl-3.0.html. Particullary, users are required to
formally cite the original Pathview paper (not just mention it) in publications
or products. For details, do citation("pathview") within R.
```

The pathview downloads and uses KEGG data. Non-academic uses may require a KEGG license agreement (details at <http://www.kegg.jp/kegg/legal.html>).

```
#####
```

```
data(kegg.sets.hs)
data(sigmet.idx.hs)
```

```
# focus on signaling and metabolic pathways
kegg.sets.hs = kegg.sets.hs[sigmet.idx.hs]
```

```
foldchanges = res$log2FoldChange
names(foldchanges) = res$entrezid
head(foldchanges)
```



<NA>	148398	26155	339451	84069	84808
0.17925708	0.42645712	-0.69272046	0.72975561	0.04057653	0.54281049

```
keggres <- gage(foldchanges, gsets = kegg.sets.hs)
```

```
attributes(keggres)
```

```
$names
[1] "greater" "less"    "stats"
```

```
head(keggres$less)
```

	p.geomean	stat.mean	p.val
hsa04110 Cell cycle	8.995727e-06	-4.378644	8.995727e-06
hsa03030 DNA replication	9.424076e-05	-3.951803	9.424076e-05
hsa03013 RNA transport	1.246882e-03	-3.059466	1.246882e-03
hsa03440 Homologous recombination	3.066756e-03	-2.852899	3.066756e-03
hsa04114 Oocyte meiosis	3.784520e-03	-2.698128	3.784520e-03
hsa00010 Glycolysis / Gluconeogenesis	8.961413e-03	-2.405398	8.961413e-03

	q.val	set.size	exp1
hsa04110 Cell cycle	0.001448312	121	8.995727e-06
hsa03030 DNA replication	0.007586381	36	9.424076e-05
hsa03013 RNA transport	0.066915974	144	1.246882e-03
hsa03440 Homologous recombination	0.121861535	28	3.066756e-03
hsa04114 Oocyte meiosis	0.121861535	102	3.784520e-03
hsa00010 Glycolysis / Gluconeogenesis	0.212222694	53	8.961413e-03

```
pathview(foldchanges, pathway.id ="hsa04110")
```

'select()' returned 1:1 mapping between keys and columns

Info: Working in directory /Users/janiec-w/Desktop/Classes/BGGN213 Bioinformatics/pProjects/J

Info: Writing image file hsa04110.pathview.png

```
data(go.sets.hs)
data(go.subs.hs)

# Focus on Biological Process subset of GO
gobpsets = go.sets.hs[go.subs.hs$BP]

gores = gage(foldchanges, gsets=gobpsets)
```

```
head(gores$less)
```

	p.geomean	stat.mean	p.val
G0:0048285 organelle fission	1.536227e-15	-8.063910	1.536227e-15
G0:0000280 nuclear division	4.286961e-15	-7.939217	4.286961e-15
G0:0007067 mitosis	4.286961e-15	-7.939217	4.286961e-15
G0:0000087 M phase of mitotic cell cycle	1.169934e-14	-7.797496	1.169934e-14
G0:0007059 chromosome segregation	2.028624e-11	-6.878340	2.028624e-11
G0:0000236 mitotic prometaphase	1.729553e-10	-6.695966	1.729553e-10
	q.val	set.size	exp1
G0:0048285 organelle fission	5.841698e-12	376	1.536227e-15
G0:0000280 nuclear division	5.841698e-12	352	4.286961e-15
G0:0007067 mitosis	5.841698e-12	352	4.286961e-15
G0:0000087 M phase of mitotic cell cycle	1.195672e-11	362	1.169934e-14
G0:0007059 chromosome segregation	1.658603e-08	142	2.028624e-11
G0:0000236 mitotic prometaphase	1.178402e-07	84	1.729553e-10

```
sig_genes <- res[res$padj <= 0.05 & !is.na(res$padj), "symbol"]
print(paste("Total number of significant genes:", length(sig_genes)))
```

```
[1] "Total number of significant genes: 8147"
```

```
head(sig_genes)
```

```
ENSG00000187634 ENSG00000188976 ENSG00000187961 ENSG00000188290 ENSG00000187608
      "SAMD11"      "NOC2L"      "KLHL17"      "HES4"      "ISG15"
ENSG00000188157
      "AGRN"
```

```
write.table(sig_genes,
            file="significant_genes.txt",
            row.names=FALSE,
            col.names=FALSE,
            quote=FALSE)
```




Figure 1: Overview