

信息	结果1	结果2	概况	状态					
Id	User	Host	db	Command	Time	State	Info	Rows_sent	Rows_examined
14483707	rp	10.0.4.10	(Null)	Binlog Dump	15277240	Master has sent all binlog to slave; waiti	(Null)	0	0
95649496	rp	10.155.1	(Null)	Binlog Dump	2846403	Master has sent all binlog to slave; waiti	(Null)	0	0
108865959	root	10.0.150.1	HXT	Sleep	25947		(Null)	1	1
108865960	root	10.0.150.1	HXT	Sleep	25947		(Null)	1	1
108866721	root	10.0.150.1	HXT	Sleep	25839		(Null)	1	1
108866724	root	10.0.150.1	HXT	Sleep	25839		(Null)	1	1
108931102	root	10.0.150.1	HXT	Sleep	15045		(Null)	1	1
108931115	root	10.0.150.1	HXT	Sleep	15045		(Null)	1	1
108986699	root	host251-1	HXT	Query	5494	Waiting for table metadata lock	ALTER TABLE news_company ADD UNIQUE comp_0	0	0
108988375	root	10.0.200.6	HXT	Query	5444	Waiting for table metadata lock	INSERT INTO news_company ( company_id, then_0	0	0
108988428	root	10.0.200.6	HXT	Query	5420	Waiting for table metadata lock	INSERT INTO news_company ( company_id, then_0	0	0
108988444	root	10.0.200.6	HXT	Query	5443	Waiting for table metadata lock	INSERT INTO news_company ( company_id, then_0	0	0
108988491	root	10.0.200.6	HXT	Query	5441	Waiting for table metadata lock	INSERT INTO news_company ( company_id, then_0	0	0
108988505	root	10.0.200.6	HXT	Query	5442	Waiting for table metadata lock	INSERT INTO news_company ( company_id, then_0	0	0
108988509	root	10.0.200.6	HXT	Query	5440	Waiting for table metadata lock	INSERT INTO news_company ( company_id, then_0	0	0
108988510	root	10.0.200.6	HXT	Query	5434	Waiting for table metadata lock	INSERT INTO news_company ( company_id, then_0	0	0
108988516	root	10.0.200.6	HXT	Query	5439	Waiting for table metadata lock	INSERT INTO news_company ( company_id, then_0	0	0
108988522	root	10.0.200.6	HXT	Query	5435	Waiting for table metadata lock	INSERT INTO news_company ( company_id, then_0	0	0
108988531	root	10.0.200.6	HXT	Query	5438	Waiting for table metadata lock	INSERT INTO news_company ( company_id, then_0	0	0
108988539	root	10.0.200.6	HXT	Query	5435	Waiting for table metadata lock	INSERT INTO news_company ( company_id, then_0	0	0
108988559	root	10.0.200.6	HXT	Query	5422	Waiting for table metadata lock	INSERT INTO news_company ( company_id, then_0	0	0
108988562	root	10.0.200.6	HXT	Query	5433	Waiting for table metadata lock	INSERT INTO news_company ( company_id, then_0	0	0
108988567	root	10.0.200.6	HXT	Query	5434	Waiting for table metadata lock	INSERT INTO news_company ( company_id, then_0	0	0
108988574	root	10.0.200.6	HXT	Query	5421	Waiting for table metadata lock	INSERT INTO news_company ( company_id, then_0	0	0
108988583	root	10.0.200.6	HXT	Query	5401	Waiting for table metadata lock	INSERT INTO news_company ( company_id, then_0	0	0
108988596	root	10.0.200.6	HXT	Query	5416	Waiting for table metadata lock	INSERT INTO news_company ( company_id, then_0	0	0
108988597	root	10.0.200.6	HXT	Query	5435	Waiting for table metadata lock	INSERT INTO news_company ( company_id, then_0	0	0

## 解锁方法

```
show full processlist;
```

3 SHOW FULL PROCESSLIST:								
消息	结果1	结果2	概况	状态				
Id	User	Host	db	Command	Time	State	Info	Rows_se
14483707	rp	10.0.4.10	(Null)	Binlog Dump	15534459	Master has sent all binlog to slave; w	(Null)	0
95649496	rp	10.15.5.1	(Null)	Binlog Dump	3103622	Master has sent all binlog to slave; w	(Null)	0
110296634	root	host251-jhxt		Sleep	114		(Null)	0
110297553	root	host251-jhxt		Sleep	1214		(Null)	0
110297554	root	host251-j	(Null)	Sleep	2560		(Null)	0
110301912	root	host251-jhxt		Sleep	366		(Null)	0
110301922	root	host251-jhxt		Query	0	(Null)	SHOW FULL PROCESSLIST	0
110303458	root	host251-jhxt		Query	18	Copying to tmp table	SELECT nm.id,nm.news_title,sg.intelligence_name,nm.news_0	0
110303955	root	10.0.200.6	hxt	Sleep	1		(Null)	0
110303958	root	10.0.200.6	hxt	Sleep	0		(Null)	0

```

6 EXPLAIN SELECT
7   nm.id,
8   nm.news_title,
9   sg.intelligence_name,
10  nm.news_media,
11  nm.news_post_time
12 FROM
13   news_intelligence nm,
14   sys_intelligence sg
15 WHERE
16   nm.intelligence_id = sg.id
17 AND nm.news_status = 0
18 AND date(nm.news_post_time) = date(now())
19 ORDER BY
20   nm.news_post_time DESC
21 LIMIT 0, 20;

```

信息	结果1	概况	状态							
	select_type	table	type	possible_keys	key	key_len	ref	rows	Extra	
	SIMPLE	sg	ALL	PRIMARY	(Null)	(Null)	(Null)	2023	Using temporary; Using filesort	
	SIMPLE	nm	ref	news_status,intelligence_id	intelliger 8		HXT.sg.id,const	2760	Using where	

explain select..... (貌似Using temporary; Using filesort特别特别慢会锁表, 应避免)

找到锁进程, kill id ;(亲测可用)

kill 110303458;(成功解锁)

第二种: show open TABLES WHERE In\_use > 0;

```

6 show open TABLES WHERE In_use > 0;

```

信息	结果1	结果2	概况	状态				
	Database	Table	In_use	Name_locked				
▶	HXT	news_company	1	0				

mysql > UNLOCK TABLES;(同时锁两个表的时候貌似不能解锁)

```
1 show open TABLES;
```

信息	结果1	概况	状态		
Database	Table	In_use	Name_locked		
▶ HXT	news_sens	0	0		
mysql	procs_priv	0	0		
HXT	news_hot	0	0		
performance_schema	events_waits_history_long	0	0		
mysql	time_zone_name	0	0		
HXT	industry_report_blog	0	0		
HXT	weixin_type	0	0		
HXT	chart_publicmedia_gzbd	0	0		
HXT	chart_publicmedia_bd	0	0		
PO	sys_intelligence_module	0	0		
PO	sys_industry	0	0		
HXT	company_weixin_type	0	0		
PO	company_monitor_module	0	0		
PO	company_account_favorite	0	0		
HXT	company_research_report	0	0		
HXT	sys_briefing	0	0		
PO	company_briefing	0	0		
HXT	chart_publicmedia_all	0	0		
HXT	chart_publicmedia_gzqs	0	0		
HXT	stat_overview_zf	0	0		
performance_schema	events_waits_current	0	0		
performance_schema	cond_instances	0	0		
HXT	history_news_company	0	0		
HXT	sys_media	0	0		