

Learning the network

11-785 Introduction to Deep Learning
– lecture 3 –

TAVE Research DL001

Heeji Won

Contents

- 01. How do we construct the network?
- 02. Perceptron Algorithm
- 03. Perceptron with differentiable activation functions
- 04. Learning through Empirical Risk Minimization

Contents


01. How do we construct the network?

02. Perceptron Algorithm

03. Perceptron with differentiable activation functions

04. Learning through Empirical Risk Minimization


01. How do we construct the network?




We learned ...

- The MLP can represent anything
- But how do we construct it?

Option 1. Construct by hand




Not possible for all problems




01. How do we construct the network?

Option 2. Automatic estimation of an MLP



$$\hat{W} = \operatorname{argmin}_W \int_X \operatorname{div}(f(X; W), g(X)) dX$$

- $\operatorname{div}()$ is a divergence function that goes to zero when $f(X; W) = g(X)$



find W minimizing this area


- ✓ In practice, $g(X)$ is unknown
=> use **training samples**

01. How do we construct the network?


Option 2. Automatic estimation of an MLP

Sample $g(X)$

- get input-output pairs (X_i, d_i)



- We must learn the entire function from these few samples
- ✓ Estimate the network parameters to fit the training points exactly



find W minimizing this area

- ✓ In practice, $g(X)$ is unknown
=> use **training samples**

Contents

01. How do we construct the network?


02. Perceptron Algorithm

03. Perceptron with differentiable activation functions

04. Learning through Empirical Risk Minimization


02. Perceptron Algorithm

- Learning the perceptron




- ✓ Learning the perceptron is the same as learning the hyperplane

$$\sum_i w_i x_i = 0 \Leftrightarrow w^T x = 0$$




02. Perceptron Algorithm

- Learning the perceptron



$x \in +1$ 이면, $W = x$



$x \in -1$ 이면, $W = -x$


02. Perceptron Algorithm

- Perceptron Algorithm
 - Cycle through the training instances
 - Only update W on misclassified instances
 - If instance misclassified
 - If instance is **positive class**
(positive misclassified as negative)

$$W = W + X_i$$

- If instance is **negative class**
(negative misclassified as positive)


$$W = W - X_i$$



The new weight vector

02. Perceptron Algorithm

- Perceptron Algorithm for complex problems



- We have to check every possible way of relabeling for each neuron
- The perceptron learning algorithm cannot directly be used to learn a MLP

=> Greedy algorithms

Contents

01. How do we construct the network?


02. Perceptron Algorithm

03. Perceptron with differentiable activation functions

04. Learning through Empirical Risk Minimization


03. Perceptron with differentiable function

Step function




- ✓ same # of errors
- ✓ Step function doesn't tell how far the data is from the boundary

Differentiable function



⇒ Can now quantify **how much** the output differs from the desired target

03. Perceptron with differentiable function




$$\frac{dy}{dz} = \sigma'(z)$$

$$\frac{dy}{dw_i} = \frac{dy}{dz} \frac{dz}{dw_i} = \sigma'(z) x_i$$

$$\frac{dy}{dx_i} = \frac{dy}{dz} \frac{dz}{dx_i} = \sigma'(z) w_i$$

generalization



$$y_j^k = \sigma \left(\sum_i w_{i,j}^{k-1} y_i^{k-1} \right)$$

- ✓ Using the chain rule, y is a differentiable function of every inputs x_i and weights w_i
- ✓ This means that we can compute the change in the output for small changes in either the input or the weights

Contents

- 01. How do we construct the network?
- 02. Perceptron Algorithm
- 03. Perceptron with differentiable activation functions
- 04. Learning through Empirical Risk Minimization**

04. Empirical risk minimization

- Learn through Empirical risk minimization
 - The expected divergence(or risk) is the average divergence over the entire input space

$$E[\text{div}(f(X; W), g(X))] = \int_x \text{div}(f(X; W), g(X)) P(X) dX$$

- Given a training set of input–output pairs, $(X_1, d_1), \dots, (X_N, d_N)$
- The empirical estimate of expected risk is the average divergence over the samples (unbiased estimator)

$$E[\text{div}(f(X; W), g(X))] \approx \frac{1}{N} \sum_{i=1}^N \text{div}(f(X_i; W), d_i)$$

$$\begin{aligned} \text{Loss}(W) &= \frac{1}{N} \sum_i \text{div}(f(X_i; W), d_i) \\ \hat{W} &= \text{argmin}_W \text{Loss}(W) \end{aligned}$$

Thank you