

Normalization, Regularization

11-785 Introduction to Deep Learning

– lecture 8 –

TAVE Research DL001

Heeji Won

Contents

01. Divergence

02. Batch Normalization

03. Solutions for Overfitting

Contents

01. Divergence

02. Batch Normalization


03. Solutions for Overfitting

01. Divergence


"The convergence of the gradient descent depends on the divergence"

$$Loss = \frac{1}{T} \sum_t Div(Y_t, d_t; W_1, W_2, \dots, W_K)$$


The best type of divergence is steep far from the optimum, but shallow at the optimum



- L2 vs KL



- L2 is popular for networks that perform numeric prediction/regression
- KL is popular for networks that perform classification
- L2 is not convex while KL is convex



Contents



01. Divergence

02. Batch Normalization

03. Solutions for Overfitting


02. Batch Normalization

- The solution for covariate shifts
 - The problem is each minibatch may have a different distribution
 - So, normalize batches



- Batch normalization is a covariate adjustment unit that happens after the weighted addition of inputs
- Is done independently for each unit
- The adjustment occurs over individual minibatches

02. Batch Normalization



31

$$u_i = \frac{z_i - \mu_B}{\sqrt{\sigma_B^2 + \epsilon}}$$

Normalize minibatch to zero-mean unit variance

$$\hat{z}_i = \gamma u_i + \beta$$

Neuron-specific terms

Shift to right position

✓ In the case of Inference, use the average over all training minibatches

$$\mu_{BN} = \frac{1}{Nbatches} \sum_{batch} \mu_B(batch)$$



$$\sigma_{BN}^2 = \frac{B}{(B-1)Nbatches} \sum_{bat} \sigma_B^2(batch)$$

Loss(minibatch)

$$= \frac{1}{B} \sum_t Div \left(Y_t \left(X_t, \mu_B(X_t, X_{t' \neq t}), \sigma_B^2(X_t, X_{t' \neq t}, \mu_B(X_t, X_{t' \neq t})) \right), d_t(X_t) \right)$$

02. Batch Normalization

- Backpropagation



$$\frac{du_i}{dz_i} = \frac{\partial u_i}{\partial z_i} + \frac{\partial u_i}{\partial \mu_B} \frac{d\mu_B}{dz_i} + \frac{\partial u_i}{\partial \sigma_B^2} \frac{d\sigma_B^2}{dz_i}$$

$$\frac{du_j}{dz_i} = \begin{cases} \frac{1}{\sqrt{\sigma_B^2 + \epsilon}} + \frac{-1}{B\sqrt{\sigma_B^2 + \epsilon}} + \frac{-(z_i - \mu_B)^2}{B(\sigma_B^2 + \epsilon)^{3/2}} & \text{if } j = i \\ \frac{-1}{B\sqrt{\sigma_B^2 + \epsilon}} + \frac{-(z_i - \mu_B)^2}{B(\sigma_B^2 + \epsilon)^{3/2}} & \text{if } j \neq i \end{cases}$$

Contents


01. Divergence

02. Batch Normalization

03. Solutions for Overfitting


03. Solutions for overfitting

- The unconstrained model



As $|w|$ increases, the response becomes steeper

- Deeper networks



Deeper networks impose more smoothness than shallow ones

- Regularized training

$$L(W_1, W_2, \dots, W_K) = \frac{1}{T} \sum_t \text{Div}(Y_t, d_t; W_1, W_2, \dots, W_K) + \frac{1}{2} \lambda \sum_k \|W_k\|_F^2$$

- Increasing λ assigns greater importance to shrinking the weights

$$L(W_1, W_2, \dots, W_K) = \frac{1}{T} \sum_t \text{Div}(Y_t, d_t) + \frac{1}{2} \lambda \sum_k \|W_k\|_F^2$$

- Batch mode:

$$\Delta W_k = \frac{1}{T} \sum_t \nabla_{W_k} \text{Div}(Y_t, d_t)^T + \lambda W_k$$

- SGD:

$$\Delta W_k = \nabla_{W_k} \text{Div}(Y_t, d_t)^T + \lambda W_k$$

- Minibatch:

$$\Delta W_k = \frac{1}{b} \sum_{\tau=t}^{t+b-1} \nabla_{W_k} \text{Div}(Y_\tau, d_\tau)^T + \lambda W_k$$

- Update rule:

$$W_k \leftarrow W_k - \eta \Delta W_k$$

Thank you