

L^AT_EX 2_ε Cheat Sheet

Document classes

book Default is two-sided.
report No \part divisions.
article No \part or \chapter divisions.
letter Letter (?).
slides Large sans-serif font.

Used at the very beginning of a document:

\documentclass{class}. Use \begin{document} to start contents and \end{document} to end the document.

Common documentclass options

10pt/11pt/12pt Font size.
letterpaper/a4paper Paper size.
twocolumn Use two columns.
twoside Set margins for two-sided.
landscape Landscape orientation. Must use dvips
-t landscape.
draft Double-space lines.
Usage: \documentclass[opt, opt]{class}.

Packages

fullpage Use 1 inch margins.
anysize Set margins: \marginwidth{l}{r}{t}{b}.
multicol Use *n* columns: \begin{multicols}{n}.
latexsym Use L^AT_EX symbol font.
graphicx Show image: \includegraphics[width=x]{file}.
url Insert URL: \url{http://...}.

Use before \begin{document}. Usage: \usepackage{package}
For russian language:

\usepackage[utf8]{inputenc}
\usepackage[russian]{babel}
For footnotes in headings:
\usepackage[stable]{footmisc}

Title

\author{text} Author of document.
\title{text} Title of document.
\date{text} Date.

These commands go before \begin{document}. The declaration \maketitle goes at the top of the document.

Miscellaneous

\pagestyle{empty} Empty header, footer and no page numbers.
\tableofcontents Add a table of contents here.

Document structure

\part{title} \subsubsection{title}
\chapter{title} \paragraph{title}
\section{title} \subparagraph{title}
\subsection{title}

Use \setcounter{secnumdepth}{x} suppresses heading numbers of depth > *x*, where **chapter** has depth 0. Use a *, as in \section*{title}, to not number a particular item—these items will also not appear in the table of contents.

Text environments

\begin{comment} Comment (not printed). Requires verbatim package.
\begin{quote} Indented quotation block.
\begin{quotation} Like quote with indented paragraphs.
\begin{verse} Quotation block for verse.

Lists

\begin{enumerate} Numbered list.
\begin{itemize} Bulleted list.
\begin{description} Description list.
\item text Add an item.
\item[x] text Use *x* instead of normal bullet or number. Required for descriptions.

References

\label{marker} Set a marker for cross-reference, often of the form \label{sec:item}.
\ref{marker} Give section/body number of marker.
\pageref{marker} Give page number of marker.
\footnote{text} Print footnote at bottom of page.

Floating bodies

\begin{table}[place] Add numbered table.
\begin{figure}[place] Add numbered figure.
\begin{equation}[place] Add numbered equation.
\caption{text} Caption for the body.
The *place* is a list valid placements for the body. t=top, h=here, b=bottom, p=separate page, !=place even if ugly.
Captions and label markers should be within the environment.

Text properties

Font face

Command	Declaration	Effect
\textrm{text}	{\rmfamily text}	Roman family
\textsf{text}	{\sffamily text}	Sans serif family
\texttt{text}	{\ttfamily text}	Typewriter family
\textmd{text}	{\mdseries text}	Medium series
\textbf{text}	{\bfseries text}	Bold series
\textup{text}	{\upshape text}	Upright shape
\textit{text}	{\itshape text}	<i>Italic shape</i>
\textsl{text}	{\slshape text}	<i>Slanted shape</i>
\textsc{text}	{\scshape text}	SMALL CAPS SHAPE
\emph{text}	{\em text}	<i>Emphasized</i>
\textnormal{text}	{\normalfont text}	Document font
\underline{text}		<u>Underline</u>

The command (tttt) form handles spacing better than the declaration (ttt) form.

Font size

\tiny	<small>tiny</small>	\Large	<big>Large</big>
\scriptsize	<small>scriptsize</small>	\LARGE	<big>LARGE</big>
\footnotesize	<small>footnotesize</small>		
\small	<small>small</small>	\huge	<big>huge</big>
\normalsize	<small>normalsize</small>		
\large	<small>large</small>	\Huge	<big>Huge</big>

These are declarations and should be used in the form {\small ...}, or without braces to affect the entire document.

Verbatim text

\begin{verbatim} Verbatim environment.
\begin{verbatim*} Spaces are shown as ␣.
\verb!text! Text between the delimiting characters (in this case ‘!’) is verbatim.

Justification

Environment	Declaration
\begin{center}	\centering
\begin{flushleft}	\raggedright
\begin{flushright}	\raggedleft

Miscellaneous

\linespread{x} changes the line spacing by the multiplier *x*.

Text-mode symbols

Symbols

&	\&	-	_	...	\ldots	•	\textbullet
\$	\\$	^	\^{}		\textbar	\	\textbackslash
%	\%	~	\~{}	#	\#	\$	\\$

Delimiters

‘ ‘ ‘ ‘	{ \{	[[((<	\textless
, , , ,	} \}]]))	>	\textgreater

Dashes

Name	Source	Example	Usage
hyphen	-	X-ray	In words.
en-dash	--	1–5	Between numbers.
em-dash	---	Yes—or no?	Punctuation.

Line and page breaks

\begin{newline} Begin new line without new paragraph.
\prohibitpagebreak Prohibit pagebreak after linebreak.
\kill Don’t print current line.
\pagebreak Start new page.
\noindent Do not indent current line.

Miscellaneous

\today December 5, 2013.
\$\sim\$ Prints ~ instead of ~{}, which makes ~.
~ Space, disallow linebreak (W.J.~Clinton).
\@. Indicate that the . ends a sentence when following an uppercase letter.
\hspace{l} Horizontal space of length *l* (Ex: *l* = 20pt).
\vspace{l} Vertical space of length *l*.
\rule{w}{h} Line of width *w* and height *h*.

Tabular environments

tabbing environment

\= Set tab stop. \> Go to tab stop.
Tab stops can be set on “invisible” lines with \kill at the end of the line. Normally \ is used to separate lines.

tabular environment

\begin{array}[pos]{cols}
\begin{tabular}[pos]{cols}
\begin{tabular*}[width][pos]{cols}

tabular column specification

<code>l</code>	Left-justified column.
<code>c</code>	Centered column.
<code>r</code>	Right-justified column.
<code>p{width}</code>	Same as <code>\parbox[t]{width}</code> .
<code>@{decl}</code>	Insert <i>decl</i> instead of inter-column space.
<code> </code>	Inserts a vertical line between columns.

tabular elements

<code>\hline</code>	Horizontal line between rows.
<code>\cline{x-y}</code>	Horizontal line across columns <i>x</i> through <i>y</i> .
<code>\multicolumn{n}{cols}{text}</code>	A cell that spans <i>n</i> columns, with <i>cols</i> column specification.

Math mode

For inline math, use `\(...\)` or `$....$`. For displayed math, use `\[...]` or `\begin{equation}`.

Superscript ^{<i>x</i>}	<code>~{x}</code>	Subscript _{<i>x</i>}	<code>_x</code>
$\frac{x}{y}$	<code>\frac{x}{y}</code>	$\sum_{k=1}^n$	<code>\sum_{k=1}^n</code>
$\sqrt[n]{x}$	<code>\sqrt[n]{x}</code>	$\prod_{k=1}^n$	<code>\prod_{k=1}^n</code>

Math-mode symbols

\leq	<code>\leq</code>	\geq	<code>\geq</code>	\neq	<code>\neq</code>	\approx	<code>\approx</code>
\times	<code>\times</code>	\div	<code>\div</code>	\pm	<code>\pm</code>	\cdot	<code>\cdot</code>
\circ	<code>\circ</code>	\circ	<code>\circ</code>	\prime	<code>\prime</code>	\cdots	<code>\cdots</code>
∞	<code>\infty</code>	\neg	<code>\neg</code>	\wedge	<code>\wedge</code>	\vee	<code>\vee</code>
\supset	<code>\supset</code>	\forall	<code>\forall</code>	\in	<code>\in</code>	\rightarrow	<code>\rightarrow</code>
\subset	<code>\subset</code>	\exists	<code>\exists</code>	\notin	<code>\notin</code>	\Rightarrow	<code>\Rightarrow</code>
\cup	<code>\cup</code>	\cap	<code>\cap</code>	$ $	<code> </code>	\Leftrightarrow	<code>\Leftrightarrow</code>
\dot{a}	<code>\dot{a}</code>	\hat{a}	<code>\hat{a}</code>	\bar{a}	<code>\bar{a}</code>	\tilde{a}	<code>\tilde{a}</code>
α	<code>\alpha</code>	β	<code>\beta</code>	γ	<code>\gamma</code>	δ	<code>\delta</code>
ϵ	<code>\epsilon</code>	ζ	<code>\zeta</code>	η	<code>\eta</code>	ε	<code>\varepsilon</code>
θ	<code>\theta</code>	ι	<code>\iota</code>	κ	<code>\kappa</code>	ϑ	<code>\vartheta</code>
λ	<code>\lambda</code>	μ	<code>\mu</code>	ν	<code>\nu</code>	ξ	<code>\xi</code>
π	<code>\pi</code>	ρ	<code>\rho</code>	σ	<code>\sigma</code>	τ	<code>\tau</code>
υ	<code>\upsilon</code>	ϕ	<code>\phi</code>	χ	<code>\chi</code>	ψ	<code>\psi</code>
ω	<code>\omega</code>	Γ	<code>\Gamma</code>	Δ	<code>\Delta</code>	Θ	<code>\Theta</code>
Λ	<code>\Lambda</code>	Ξ	<code>\Xi</code>	Π	<code>\Pi</code>	Σ	<code>\Sigma</code>
Υ	<code>\Upsilon</code>	Φ	<code>\Phi</code>	Ψ	<code>\Psi</code>	Ω	<code>\Omega</code>

Bibliography and citations

When using BibTeX, you need to run `latex`, `bibtex`, and `latex` twice more to resolve dependencies.

Citation types

<code>\cite{key}</code>	Full author list and year. (Watson and Crick 1953)
-------------------------	--

BibTeX entry types

<code>@article</code>	Journal or magazine article.
<code>@book</code>	Book with publisher.
<code>@booklet</code>	Book without publisher.
<code>@conference</code>	Article in conference proceedings.
<code>@inbook</code>	A part of a book and/or range of pages.
<code>@incollection</code>	A part of book with its own title.
<code>@misc</code>	If nothing else fits.
<code>@phdthesis</code>	PhD. thesis.
<code>@proceedings</code>	Proceedings of a conference.
<code>@techreport</code>	Tech report, usually numbered in series.
<code>@unpublished</code>	Unpublished.

BibTeX fields

<code>address</code>	Address of publisher. Not necessary for major publishers.
<code>author</code>	Names of authors, of format
<code>booktitle</code>	Title of book when part of it is cited.
<code>chapter</code>	Chapter or section number.
<code>edition</code>	Edition of a book.
<code>editor</code>	Names of editors.
<code>institution</code>	Sponsoring institution of tech. report.
<code>journal</code>	Journal name.
<code>key</code>	Used for cross ref. when no author.
<code>month</code>	Month published. Use 3-letter abbreviation.
<code>note</code>	Any additional information.
<code>number</code>	Number of journal or magazine.
<code>organization</code>	Organization that sponsors a conference.
<code>pages</code>	Page range (2,6,9--12).
<code>publisher</code>	Publisher's name.
<code>school</code>	Name of school (for thesis).
<code>series</code>	Name of series of books.
<code>title</code>	Title of work.
<code>type</code>	Type of tech. report, ex. "Research Note".
<code>volume</code>	Volume of a journal or book.
<code>year</code>	Year of publication.

Not all fields need to be filled. See example below.

Common BibTeX style files

<code>abbrv</code>	Standard	<code>abstract</code>	alpha with abstract
<code>alpha</code>	Standard	<code>apa</code>	APA
<code>plain</code>	Standard	<code>unsrt</code>	Unsorted

The LaTeX document should have the following two lines just before `\end{document}`, where `bibfile.bib` is the name of the BibTeX file.

```
\bibliographystyle{plain}
\bibliography{bibfile}
```

BibTeX example

The BibTeX database goes in a file called `file.bib`, which is processed with `bibtex` file.

```
@String{N = {Na\-ture}}
@Article{WC:1953,
  author = {James Watson and Francis Crick},
  title = {A structure for Deoxyribose Nucleic Acid},
  journal = N,
  volume = {171},
  pages = {737},
  year = 1953
}
```

Sample LaTeX document

```
\documentclass[11pt]{article}
\usepackage{fullpage}
\title{Template}
\author{Name}
\begin{document}
\maketitle

\section{section}
\subsection*{subsection without number}
text \textbf{bold text} text. Some math:  $\$2+2=5\$$ 
\subsection{subsection}
text \emph{emphasized text} text. \cite{WC:1953}
discovered the structure of DNA.
```

```
A table:
\begin{table}[!th]
\begin{tabular}{|l|c|r|}
\hline
first & row & data \\
second & row & data \\
\hline
\end{tabular}
\caption{This is the caption}
\label{ex:table}
\end{table}
```

```
The table is numbered \ref{ex:table}.
\end{document}
```

Copyright © 2012 Winston Chang
<http://www.stdout.org/~winston/latex/>
Edited by Ekaterina Titkova, 2013
<https://github.com/katyatitkova/>