

Data manipulation: basics for data frame

Qiang Shen

Dec. 5, 2017

Data arrangement

- ▶ basics of data arrangement
- ▶ apply

Example

- ▶ gender different of leadership

Creating new variables

```
q1+q2
q12<-leadership$q1+leadership$q2
leadership
leadership$q12<-leadership$q1+leadership$q2
leadership
leadership$q12<-with(leadership,q1+q2)
leadership<-within(leadership,{q12=q1+q2})
leadership<-within(leadership,{
  q12=q1+q2
  q_mean=(q1+q2)/2
})
leadership
```

Arithmetic operators

Operator	Description
+	Addition
-	Subtraction
*	Multiplication
/	Division
^ or **	Exponentiation
<code>x%%y</code>	Modulus (x mod y) 5%%2 is 1
<code>x%/%y</code>	Integer division 5%/%2 is 2

Figure 1:

Creating new variables continued

[illegible]

Recoding variables



Operator	Description
<	Less than
<=	Less than or equal to
>	Greater than
>=	Greater than or equal to
==	Exactly equal to
!=	Not equal to
!x	Not x
x y	x or y
x & y	x and y
isTRUE(x)	Test if x is TRUE

Recoding variables

```
leadership$age[leadership$age == 99] <- NA
leadership
leadership$agecat[leadership$age > 75] <- "Elder"
leadership$agecat[leadership$age > 45 &
                  leadership$age <= 75] <- "Middle Aged"
leadership$agecat[leadership$age <= 45] <- "Young"
leadership
```


Recoding variables continued

```
# compact version
```

```
leadership <- within(leadership, {  
  agecat <- NA  
  agecat[age > 75] <- "Elder"  
  agecat[age >= 55 & age <= 75] <- "Middle Aged"  
  agecat[age < 55] <- "Young"  
})  
leadership
```

Rename

```
names(leadership)[2]<- "testDate" #rename one variable  
names(leadership)[5:9] <-c('aq1',"aq2","aq3","aq4","aq5")  
names(leadership)[names(leadership)=='gender']<- 'Gender'  
leadership
```

Rename continued

– reshape

```
if (!(require(reshape))) install.packages("reshape")  
library(reshape)  
leadership  
rename(leadership, c(manager = "managerID", date = "testDate"))
```

Missing data: NA

```
mean(leadership$aq4)
mean(leadership$aq4,na.rm=T)
na.omit(leadership)
leadership
leadership[which(leadership$aq4!=NA),]
leadership[!is.na(leadership$aq4),]
```

Format convert

```
leadership$age <- as.numeric(leadership$age)
is.numeric(leadership$age)
leadership$age <- as.character(leadership$age)
is.character(leadership$age)
leadership$age <- as.numeric(leadership$age)
is.numeric(leadership$age)
```

missing data

```
value<-c(5,5,6,7,5,NA,3,5)
value==5
```

```
## [1] TRUE TRUE FALSE FALSE TRUE NA FALSE TRUE
```

```
value!=5
```

```
## [1] FALSE FALSE TRUE TRUE FALSE NA TRUE FALSE
```

```
a <- c(1,2,2,5,1,NA,0,2)
b <- c(1,NA,4,7,1,NA,-1,2)
d <- c(1,1,NA,6,1,NA,1,2)
k<-data.frame(a,b,d)
logic<-sapply(k,is.na)
k$e<-rowSums(!logic)
```

```
k$value<-rowSums(k[,c('a','b','d')],na.rm=T)
```

Sort data

```
attach(leadership)
newdata <- leadership[order(age), ]
newdata
detach(leadership)
attach(leadership)
newdata <- leadership[order(gender, -age), ]### blank on th
newdata
detach(leadership)
```

Select variables

```
newdata <- leadership[, c(5:9)]  #blank on the left side for  
newdata  
myvars <- c("aq1", "aq2", "aq3", "aq4", "aq5")  
newdata <- leadership[myvars]  
newdata  
myvars <- paste("aq", 1:5, sep = "")  
myvars  
newdata <- leadership[myvars]
```


Drop variables

```
newdata <- leadership[,c(-7, -8)]
newdata
newdata <- leadership[c(-7, -9)]
newdata <- leadership[,c(-7:-9)]

leadership[, -13]
leadership$season<-NULL
leadership

myvars <- names(leadership) %in% c("aq3", "aq4")
myvars
newdata <- leadership[!myvars]
```

Select Observations

```
newdata <- leadership[1:3, ]  
newdata <- leadership[which(leadership$gender == "M" &  
                             leadership$age > 30), ]  
attach(leadership)  
newdata <- leadership[gender == "M" & age > 30, ]  
newdata <- leadership[which(gender == "M" & age > 30), ]  
###blank on the right side for the observation selection  
detach(leadership)
```

Subset with subset() function

```
newdata <- subset(leadership, age >= 35 | age < 24, c(aq1,  
newdata <- subset(leadership, gender == "M" & age > 25, sel  
newdata <- subset(leadership, rownames=1:3, select = Gender
```

Using SQL statements to manipulate data frames

```
if(!require(sqldf)) install.packages('sqldf')
newdf <- sqldf("select * from mtcars where carb=1 order by
               row.names = TRUE)

newdf
newdf <- sqldf("select avg(mpg) as avg_mpg, avg(displ) as av
               gear from mtcars where cyl in (4, 6) group by gear")
newdf
```