

# Final Team Report for HC System: A Novel GWAPs Disaster Monitoring System

---

Team: Hotpot  
Changkun Ou : <11406972>  
Yifei Zhan : <Matrikelnummer>  
Zhe Li : <11194275>

July 3, 2017

## CONTENTS

<b>1</b>	<b>Introduction</b>	<b>3</b>
1.1	Related information on the topic field . . . . .	3
1.2	Purpose of HC system . . . . .	3
1.3	Human contribution to the system . . . . .	3
<b>2</b>	<b>Functionality of a novel HC system</b>	<b>4</b>
2.1	Functionality as seen by a user . . . . .	4
2.2	Functionality as seen by a stakeholder . . . . .	4
2.3	Incentivization concept . . . . .	4
2.3.1	Task Generator . . . . .	4
2.3.2	Player Rating Model . . . . .	4
2.3.3	Disaster Level Evaluation Model . . . . .	5
2.3.4	Data Persistence . . . . .	6
<b>3</b>	<b>System Design and UI Elements</b>	<b>8</b>
3.1	System Architectures . . . . .	8
3.2	Algorithm for Data Aggregation . . . . .	8

3.3	Technologies used for implementation . . . . .	8
3.4	Front End . . . . .	8
3.5	Back End . . . . .	8
3.6	User Interfaces of the system . . . . .	8
3.7	Summary . . . . .	8
<b>4</b>	<b>System Evaluation and Success Criteria</b>	<b>10</b>
4.1	Limitation of the System . . . . .	10
4.2	Evaluation and success criteria . . . . .	10
4.2.1	Model Evaluation . . . . .	10
4.2.2	Issues on Social Aspects . . . . .	10
4.2.3	Issues on Ethical Aspects . . . . .	10
<b>5</b>	<b>Future Works</b>	<b>11</b>
5.1	Possible extensions of the HC system . . . . .	11
5.2	Thoughts on interaction with other HC system . . . . .	11

ABSTRACT Abstract test

# 1 INTRODUCTION

Introduction cite test [4]

The contribution of this report are as follows:

- a novel Human Computation system based on Game with Purpose for Disaster Monitoring;
- xxx

## 1.1 RELATED INFORMATION ON THE TOPIC FIELD

## 1.2 PURPOSE OF HC SYSTEM

## 1.3 HUMAN CONTRIBUTION TO THE SYSTEM

## 2 FUNCTIONALITY OF A NOVEL HC SYSTEM

### 2.1 FUNCTIONALITY AS SEEN BY A USER

A player can finish infinity Round tasks, a Round task contains N tagging tasks, the player tagging task is to:

- Select a Region Of Interests(ROI) upon the presented satellite image;
- Tag the ROI from a provided tag list or input their own tag, the provided tag list contains:  $T_1, T_2, \dots, T_n$ , other(input needed)

Note that:

- A ROI is a sub-rectangle-window of a image;
- Multiple selections;
- Anyone can directly participant without registration, but system records an ID

### 2.2 FUNCTIONALITY AS SEEN BY A STAKEHOLDER

#### 2.3 INCENTIVIZATION CONCEPT

##### 2.3.1 TASK GENERATOR

A task generator combines images from satellite and Result DB:

- Split a certain monitoring area image to pieces of images;
- Mix images from Result DB and pack as a Tagging Task which to be assigned to player.

##### 2.3.2 PLAYER RATING MODEL

Players input vector:

(anonymous\_id, image, event\_time, ROI, tag\_list)

Model output:

(anonymous\_id, trust\_value)

Note that:

- (*anonymous\_id, image, event\_time, ROI*) is the primary key of the input vector;
- A player can generate multiple vectors to rating system even for same image;
- The event\_time is the capture time of the satellite image.




Figure 2.1: Weight Definition Visualization

For a certain image  $img$  at time  $t$ , Rating: player  $i \rightarrow$  player  $j$ :

$$w_{ij} = \sum_{ROI \in ROIs} \frac{ROI(i, j)}{ROI(i)} \times \frac{Cov(tags(i), tags(j))}{var(tags(i))var(tags(j))} \geq 0$$

Normalized Adjacency Matrix:

$$A = \left( \frac{w_{ij}}{\sum_j w_{ij}} \right)$$

Obviously,  $A$  is **irreducible, real, non-negative, column-stochastic, and diagonal element being positive**, then eigenvalue of  $A$  is the player trust value.

When a new player tagging task need to be rated,

- which means we need introduce a new node to the graph
- need calculate the trust value of new graph
- let  $t$  is the trust value of new player
- if  $t \geq \text{mean}(\text{old\_eigenvalues})$ , then it is a reliable player, otherwise drop it.

### 2.3.3 DISASTER LEVEL EVALUATION MODEL

Query input:

$(\text{time}) \text{ or } (\text{area\_id}) / (\text{area\_id}, \text{time})$

Model output:

$(\text{area\_id}, \text{time}, \text{disaster\_level})$

Note that:

- All results are evaluated from reliable tasks
- Evaluation Model generated by all reliable history

Now we have trusted results, each area has its tagging history.  
For an area at time t, define disaster level as follows:

$$v_{area} = \frac{\sum_{tag \in tags} w_{tag} \times \#(tag)}{\sum_{area \in areas} \sum_{tag \in tags} w_{tag} \times \#(tag)}$$

where  $w_{tag}$  is pre-defined weight by system,  $\#(tag)$  is the occur number of a tag.  
Return value:

- disaster region:  $\cup_{ROI \in ROIs} ROI$
- disaster level:  $v_{area}$

#### 2.3.4 DATA PERSISTENCE

Trusted DB Fields:

```

1  [
2      {
3          "anonymous_id": number,
4          "tasks": [
5              {
6                  "image": image_path,
7                  "at_time": time,
8                  "ROI": [
9                      {
10                         "latitude": number,
11                         "longitude": number,
12                         "tags": [tag1, tag2, ...]
13                     }
14                 ]
15             }
16         ]
17         "trust_value": number
18     }
19 ]
20

```

Listing 1: Trusted Database Field

Result DB Fields:

```

1  [
2      {
3          area_id": number,
4          "history": [
5              {
6                  at_time: time,
7                  "image": image_path,
8                  "ROI": [

```

```
9           {
10             "latitude": number,
11             "longitude": number,
12             "tags": [tag1, tag2, ...]
13           }
14     ],
15     "disaster_level": number
16   }
17 ]
18 }
19 ]
20 ]
```

Listing 2: Results Database Field

## 3 SYSTEM DESIGN AND UI ELEMENTS

### 3.1 SYSTEM ARCHITECTURES




Figure 3.1: System Design Overview

### 3.2 ALGORITHM FOR DATA AGGREGATION

### 3.3 TECHNOLOGIES USED FOR IMPLEMENTATION

For a prototype, we decided to use the following framework to implement everything:

- Polymer
- Node.js
- MongoDB

### 3.4 FRONT END

### 3.5 BACK END

### 3.6 USER INTERFACES OF THE SYSTEM

### 3.7 SUMMARY

- Task Generator combines trusted results assign to players;
- Always treat player as new player, but integrated as old player if exists;



- Use ROI matching rate as graph edge weight, eigenvalue as trust value of player;
- Disaster Evaluation use pre-defined weight, then defined the disaster level

## 4 SYSTEM EVALUATION AND SUCCESS CRITERIA

### 4.1 LIMITATION OF THE SYSTEM

### 4.2 EVALUATION AND SUCCESS CRITERIA

#### 4.2.1 MODEL EVALUATION

#### 4.2.2 ISSUES ON SOCIAL ASPECTS

#### 4.2.3 ISSUES ON ETHICAL ASPECTS

## 5 FUTURE WORKS

In this report, we present a disaster monitoring system, which aggregate human tagging input based on Network Analysis.

### 5.1 POSSIBLE EXTENSIONS OF THE HC SYSTEM

### 5.2 THOUGHTS ON INTERACTION WITH OTHER HC SYSTEM

## REFERENCES

- [1] Shivani Agarwal. Ranking Methods in Machine Learning A Tutorial Introduction. *SIAM International Conference on Data Mining*, 2010.
- [2] Phillip Bonacich and Paulette Lloyd. Eigenvector-like measures of centrality for asymmetric relations. *Social Networks*, 23(3):191–201, 2001.
- [3] François Bry. Human Computation and Economics. (March):1–12, 2012.
- [4] François Bry. Human Computation-Enabled Network Analysis for a Systemic Credit Risk Rating. *Handbook of Human Computation*, pages 1–31, 2013.
- [5] Chris Burges, Tal Shaked, Erin Renshaw, Ari Lazier, Matt Deeds, Nicole Hamilton, and Greg Hullender. Learning to rank using gradient descent. *Proceedings of the 22nd international conference on Machine learning - ICML '05*, pages 89–96, 2005.
- [6] Zhe Cao, Tao Qin, Tie-Yan Liu, Ming-Feng Tsai, and Hang Li. Learning to rank. *Proceedings of the 24th international conference on Machine learning - ICML '07*, pages 129–136, 2007.
- [7] European Commission. Syria crisis. *Forced Migration Review*, (March):3, 2016.
- [8] Kevin Fran, Marco Saerens, and Pierre Dupont. Classification in Graphs using Discriminative Random Walks.
- [9] Sepandar D. Kamvar, Mario T. Schlosser, and Hector Garcia-Molina. The Eigentrust algorithm for reputation management in P2P networks. *Proceedings of the twelfth international conference on World Wide Web - WWW '03*, page 640, 2003.
- [10] Edith Law and Luis Von Ahn. Input-Agreement : A New Mechanism for Collecting Data Using Human Computation Games. *Proc. SIGCHI Conference on Human Factors in Computing Systems*, pages 1–10, 2009.
- [11] Brian Mcfee and Gert Lanckriet. Metric Learning to Rank. *Icml*, pages 775–782, 2010.
- [12] Yukikazu NAKAMOTO. A Short Introduction to Learning to Rank. *IEICE Transactions on Information and Systems*, E94-D(1):1–2, 2011.
- [13] Luis von Ahn and Laura Dabbish. Designing games with a purpose. *Communications of the ACM*, 51(8):57, 2008.
- [14] LI Yong-Jun and DAI Ya-Fei. Research on Trust Mechanism for Peer-to-Peer Network. *Chinese Journal of Computers*, 33(3):390–405, 2010.