A Novel GWAP System for

Disaster Monitoring


Team Hotpot:


- Changkun Ou
- Yifei Zhan
- Zhe Li

Functionalities

Functionalities: Player & Stakeholder

Mockup: https://invis.io/WQCKJRPJK#/243555585_home-Page


















Date: 27/07/2017

Technology stack suggestion:


Front-end: Polymer, Back-end: Node.js / Python, Database: MongoDB

Design

Design: Architecture




Design: Data Flow



LMU IFI SS2017 "Human Computation" - TeamHotpot - Exam Presentation

Date: 27/07/2017


Design: User Task




Design: Definition

Definition: The **Region of Interests (ROI)** is an indicator that represents the one of the selected two dimensional regions from player. The *i*-th ROI from player p in image k at image create time t is denoted by $ROI_{p,i,k,t}$.

Considering image k implies time t, for convenience, we usually simplified $ROI_{p,i,k,t}$ to $ROI_{p,i,k}$.





LMU IFI SS2017 "Human Computation" - TeamHotpot - Exam Presentation


Date: 27/07/2017

Design: Model Refine (1)

Player Rating Graph (Image Dependent)

For a certain image k, player p rate player q by the following:

$$w_{p,q,k} = \sum_{i=1}^{n} \sum_{i=1}^{m} \left(\frac{|ROI_{p,i,k} \cap ROI_{q,j,k}|}{|ROI_{p,i,k}|} \left(2 + \frac{Cov(T_{p,i,k}, T_{q,j,k}; v)}{Cov(T_{p,i,k}, T_{p,i,k}; v)Cov(T_{q,j,k}, T_{q,j,k}; v)} \right) \right)$$



Malicious player detection

With player p selected m ROIs, player q selected n ROIs, where:

 $ROI_{p,i,k}$ is the *i*-th selected ROI region from player \boldsymbol{p} ;

 $|ROI_{p,i,k}|$ is the **surface** of $ROI_{p,i,k}$

v is the **weight vector** of all tags

 $T_{p,i,k}$ is the *i*-th selected ROI's tags vector from player $oldsymbol{p}$

Cov(x, y; v) is the **weighted covariance** of x and y via v;

$$A=(a_{p,q,k})=\left(\frac{w_{p,q,k}}{\sum_{q}w_{p,q,k}}\right) \quad \mbox{is irreducible, real, non-negative,} \\ \mbox{column-stochastic, and diagonal} \\ \mbox{element being positive.}$$

Player p

Design: Model Refine (2)

FAQ on Player Rating Graph (Image Dependent)

What is the "2"?

– It is a translation from [–1, 1] to [1, 3]

For a certain image k, player $p \rightarrow$ (rate) player q by the following:

$$w_{p,q,k} = \sum_{j=1}^{n} \sum_{i=1}^{m} \left(\frac{|ROI_{p,i,k} \cap ROI_{q,j,k}|}{|ROI_{p,i,k}|} \left(2 + \frac{Cov(T_{p,i,k}, T_{q,j,k}; v)}{Cov(T_{p,i,k}, T_{p,i,k}; v)Cov(T_{q,j,k}, T_{q,j,k}; v)} \right) \right)$$


Player Rating Step 2 Malicious player detection

Why we need Pearson Correlation?


Because user inputs have two parts:

- ROI —> handle by ROI intersection over rating person ROI
- Tags —> handle by Pearson Correlation

It is a metric measures the tags relation as well as the ROI Intersection division between two players



Yes, it is fully connected for each image *k*:



Player q

Design: Model Refine (3)

FAQ on Player Rating Graph (Image Independent)?

Can we give a global image independent Player Rating Graph?

Might not possible and not make sense. Counter example: Considering:

Player A: ImageA, ImageB, ImageC

Player B: ImageB, ImageC, ImageD

Player C: ImageA,

ImageE, ImageF

A directly sum for all image's ROI intersection does not make sense. From A to C, only one image sum; but from A to b sums two images



Malicious player detection

Assume we fixed this issue by a hard thinking,

Can we use agent from trusted people by tagging all images to ensure the image independent model's graph globally strong connected?

Two major issues for this solution:

- 1. Cost large labor (requires trusted people)
- 2. If the labor finished tags, we have no reason to use this HC system.

The fact is in the early stage of this project, I considered it first but abandoned (found few consideration on the manuscript).

We don't know solution yet, deep thinking on this issue is needed, But beyond the achievements we achieved in this semester.

Date: 27/07/2017

Design: Model Refine (4)



Step 3

Disaster level
Based on reliable
task results

After the Step2, player result is determinated. Finally, we can calculate the disaster level.


Definitions:

- Tags vector $T_{p,i,k}$: player p, i–th ROI on image k;
- Weight vector v: globally frequency for all tags as a vector;

Disaster level (DL):

$$DL = \sum_{k} \left(v \cdot \left(\sum_{i} T_{p,i,k} \right) \right)$$

Design: Initialization



Is enough player required for initial the system? No, it only needs two pre-trusted persons.

Evaluations

Evaluations: Tech Criteria by Simulation


Generate random data and test the Rating Model through accuracy and recall, even ROC curve. (This is the common indicators for classification problem)

 $ROI_{p,i,k}$ has four parameters: start coordinates (x,y), height and width.

FAQ:

Does the start point influence this simulation idea (Generate random datasets)?


No, it doesn't. Direction is not Important in this case.



Evaluations: Social & Ethics Aspects (1)

- Leakage of data
- Besides leak to ordinary users, the employees of UNICEF should have no right to access the entire database.






Evaluations: Social & Ethics Aspects (2)

The number of players

- A. more users: more tags (higher accuracy of our level of disaster)
- B. more users: trustworthy (higher trusted value which can filter malicious groups)

IPR (Intellectual Property Rights)




LMU IFI SS2017 "Human Computation" - TeamHotpot - Exam Presentation

Date: 27/07/2017

Evaluations: Social & Ethics Aspects (3)

Potential problem for leakage solution: Information loss

Solution: "Half Shifting" Cut



Limitations

Limitations (1): Evaluation Outdated

Each evaluation get invalid if region image is outdated



Limitations (2): Game Play and Playability

- Users may meet the situation that there is no available ROI in several continuous rounds.
- E.g. Lake, forest, mountain, desert, some city area, nothing to tag.






Future Works

Future Extensions & Interactions

- 1. General System with Replaceable Rating Model: malicious detection algorithm can be replaced by any other machine learning algorithm with enough data.
- 2. Collaborative Computing for Playability: Collaborative computer vision computing improves playability.
- 3. CAPTCHA Integrated System: the grate wastes of the computing power of humankind.








Date: 27/07/2017

Future Extensions & Interactions

4. CAPTCHA Integrated System:





Conclusions



- GWAP, Image Tagging HC System (Image Dependent)
 - + Only requires two initial persons
 - + Participants play game individually without registration
 - + Web-based, cross all platforms
 - + Theoretical proved, with theoretical criterial
- 2. Social & Ethics
 - + Incentivization: Altruism
 - + Leakage & Privacy: Fragments
 - + Malicious Player: Model algorithm
- 3. Limitations
 - + Evaluation outdated
 - + Playability for senseless area
- 4. Further Extensions & Interactions
 - + The "general" system
 - + Machine vision improvements
 - + CAPTCHA integration

Achievements Summary

- Efforts:

+ Changkun Ou: System Design

+ Yifei Zhan: Mockup

+ Zhe Li: Issues discovery

- Front end Mockup, back end system design (clear architecture with two math models),
 thoughts on possible issues yield by this design
- Beamers: lab1, lab2, lab3, final exam
- Report:
- + Version Control: https://github.com/changkun/hc-ss17-disaster-monitoring

Unrefined version		
Changkun Ou	Yifei Zhan	Zhe Li
* Typesetting * Abstract * Ch3: Design * Ch4 Intro * Ch4.1.1: Model Evaluation * Ch4.2.1: Evaluation Outdated * Ch5.1: Conclusions	* Chapter 2: Functionalities * Ch5 Intro * Chapter 5.2: System Extensions	* Ch1: Introduction * Ch4.1.2: Social&Ethical Issues * Ch4.2.2: Information Loss * Ch4.2.3: Playability * Ch5.3: Other Interactions