

An Introduction to Recent Mobile Affective Inferring Techniques: Methods, Applications and Their Challenges

Ou Changkun

Abstract—Affective Computing has been considered as one of the most important aspects in massive human-computer interaction related projects. This paper provides a broad introduction to the recent advances in affective computing based on mobile technologies. We expand the emotion inferring principles for different mobile commodity sensors, user interfaces and their possible combinations in the recent researches. Then we compare the recent popular machine learning methods and models for these sensor, and highlight the most useful methods and models with their performance. Our comparisons are not limited to traditional machine learning algorithm, they are also includes the representation learning models. In the end, we discussed few novel applications based on mobile affective computing techniques, such as how adaptive user interface and usability testing works in an emotion-aware system, as well as current limitations and open challenges of this research area.

Index Terms—Affective Computing, Emotion Inferring, Machine Learning, User Experience, Human Computer Interaction

1 INTRODUCTION

With the long-term research on emotion theory from psychology and neuroscience[20, 45], emotion has been confirmed to be a significant effect [21] on human communication, decision making, perception and so on.

Affective computing is an emerging interdisciplinary research field ranging from computer vision, machine learning, nature language understanding and human computer interaction, as well as cognitive and social sciences.

On the perspective of human computer interaction, Picard [36] pointed out that affective computing involved projects can be used for *reducing user frustration enabling comfortable communication of user emotion, developing infrastructure and applications to handle affective information*, as well as *building tools that help develop social-emotional skills*.

Figure 1 shows the hierarchically-structured taxonomy of this paper. In the following sections, we first how recent researches involve different mobile commodity sensors to inferring user emotions in Section 2.

2 RELATED MOBILE TECHNIQUES

- [43] gives image for different information and different related sensing. - [39] gives multimodal considerations image. 90% literature consider visual, audio and text information as multimodal affect analysis

2.1 Vision Sensors

We emphasis vision sensors in the first place since face and facial expressions are undoubtedly one of the most important nonverbal channels used by the human being to convey internal emotion. This part mainly discusses vision sensors, which includes RGB camera and depth camera, and illustrates how vision sensor can be used for affective emotion inferring.

Pure RGB cameras has been widely used in commercial smart-phone as image sensor. For the camera with depth informations on mobile (recently introduced TrueDepth Camera in iPhone X¹) combines infrared camera, flood illuminator, proximity sensor, ambient light sensor, front facing camera and dot projector to provide depth images of facial information of a user.

- Ou Changkun is studying Human-Computer Interaction at the University of Munich, Germany, E-mail: hi@changkun.us
- This research paper was written for the Media Informatics Advanced Seminar “Human Computer Interaction”, 2017

¹<https://www.apple.com/iphone-x/#truedepth-camera>

□

2.2 Touch Sensors

Capacitive touch screen provides touch position, touch pressure, touch angle through time within a specific application context [17, 14, 41, 2] This part mainly discusses touch sensors, which includes capacitive touch screen and 3D touch screen. And also explain why touch sensor can be used for affective computing (they are applicable because of specific application context), mainly cite these papers: ...

2.3 Motion Sensors

Motion sensors typically combines gyroscope and accelerometer, with this combination they can also provide device attitude This part illustrate [40, 32, 1]

Motion sensors become important because it could tells us what is user's body language.

2.4 Audio Sensors

Audio sensor usually refers to built-in microphones, it collects voice information from current environments, which can infers user emotions based on their speech contents

Audio sensors mainly infers to input and output microphones. This leans two part of affective computing:

First is inferring emotions from user speech. This task can also split as two part of inferring task, and one is directly infer from voice; another is recognize speech text from user, then understanding or inferring from text.

Second is output a emotional speech from machines.

2.5 GPS Sensors

GPS sensors provides geographical information of a user. With Location Based Services, user emotion can be inferred by their location

2.6 Application Context

2.7 Techniques Fusion

This section should present a table for the combination of previous sensors.

3 METHODS & MODELS

In this section, we present technical method and models in different data type aspects.

3.1 Vision Aspect

The normal RGB camera brings us focusing on how conduct emotion recognition with RGB images. Through depth camera was recently introduced on commercial mobile phone, its principle basically as same as Microsoft Kinect. Considering these two different sensor aspects, we dive into two different research area on vision sensors.




Figure 1. Hierarchically-structured taxonomy of this paper.

[31]

3.2 Voice Aspect

Voice Aspect as we discussed in the previous section, emotion inferring from user speech is basically processing user speech.

There is another method, which is inferring users' emotions for human-mobile voice dialogue applications.

3.3 Touch Aspect

- linear model: [41] hand crafted features, for three classes (happy, unhappy, neutral); [2] 7 proposed features, for four classes (Excited, Relaxed, Frustrated, Bored)
- feature engineer: [14] application specific, application context
-

3.4 Other Aspect

- Vision method: pre-trained ModelNet;
- Touch method: artificial feature engineering with support vector machine;
- Motion method: artificial feature engineering with support vector machine;
- Audio method: Speech to Text with Nature Language Processing, sequence to sequence model;

4 APPLICATIONS

[36]

4.1 Dialogue & Chatbot system

4.1.1 Affective Interaction

[6, 19]

4.2 Emotion-aware system

4.2.1 Adaptive User Interfaces

[8, 13, 22]

4.2.2 Usability Testing

5 CHALLENGES AND LIMITATIONS

The primary limitation of traditional AC research refers to as impermeable emotions.

[35]

5.1 State Understanding

Continuous emotion state understanding is much more challenge since its not related to external emotion but also related to internal emotions, various emotions can be expressed as follows map (see figure 2).




Figure 2. A map of human emotions [42].

5.2 Technology-driven

5.3 UX-driven

6 CONCLUSIONS

In this paper, we investigated the recent papers among mobile affective computing related to human computer interaction projects.

Section 2 discussed different principles in various mobile commodity sensors for emotion inferring in previous studies. These includes:

vision, touch, motion, audio and GPS sensors. We also considered the combinations of these sensor. According to our investigation, the following combinations has been applied in mobile affective computing: XXX and XXX; However, XXX and XXX are unmined and open topics.

Next, in the Section 3, we carried out the review of emotion inferring methods based on different type of data from different sensors, and compared the tested methods and inferring models from previous researches. In these comparison, we first reviewed various models for user emotion inferring, researchers usually transfers emotion inferring problem into a classification problem or a regression problem. As a classification problem, most researchers consider user emotions can be inferred to three different state (Happy, Unhappy, Neutral, XXXX); Whereas as a regression problem, they define and calculate a continuous variable then try to learn a regression function for emotion inferring based on machine learning method. In each subsection, we highlighted the most useful methods for different type of emotion inferring that concluded by the most recent research papers, they are: XXX and XXX.

In Section 4, this paper surveys few novel applications in human-computer interaction related projects driven by emotion inferring. XXX considers user emotion as XXX and introduced XXX for XXX. XXXXXXXX

Though we researched the technic scientific approaches of emotion inferring or affective computing in human computer interaction related topics, Section 5 pointed out the current challenges and limitations of this research area. The main challenges of this area are XXXX and XXX. Moreover, the generalisability of affective computing applications are subject to certain limitations. For instance, XXX and XXX.

Today, new technologies and technic methods provide us new opportunities of affect computing in an unobtrusive mobile devices. Since the complexity of the interpretation of human behavior at a very deep level is tremendous and requires a highly interdisciplinary collaboration, we believe the true break-throughs application in this field can be established by precisely modeling and new sensing technologies in the future.

REFERENCES

- [1] Jeremy N Bailenson, Nick Yee, Scott Brave, Dan Merget, and David Koslow. "Virtual interpersonal touch: expressing and recognizing emotions through haptic devices". In: *Human-Computer Interact.* 22.November (2007), pp. 325–353. ISSN: 0737-0024. DOI: 10.1080/07370020701493509.
- [2] S Bhattacharya. "A predictive linear regression model for affective state detection of mobile touch screen users". In: *International Journal of Mobile Human Computer Interaction* 9.1 (2017), pp. 30–44. ISSN: 1942-390X. DOI: 10.4018/IJMHCI.2017010103. URL: <https://www.scopus.com/inward/record.uri?eid=2-s2.0-84994051845&doi=10.4018/IJMHCI.2017010103&partnerID=40&md5=a3c3eeecad6e2a24b3c416bd99e1d934>.
- [3] Samit Bhattacharya. "Model for Affective State Detection of Mobile Touch Screen Users". In: 9.1 (2017), pp. 10–13. DOI: 10.4018/IJMHCI.2017010103.
- [4] Jeffrey P Bigham and Michael S Bernstein. "Human-Computer Interaction and Collective Intelligence". In: *The handbook of collective intelligence* (2014).
- [5] Jessica R. Cauchard, Kevin Y. Zhai, Marco Spadafora, and James A. Landay. "Emotion encoding in human-drone interaction". In: *ACM/IEEE International Conference on Human-Robot Interaction* 2016-April (2016), pp. 263–270. ISSN: 21672148. DOI: 10.1109/HRI.2016.7451761.
- [6] Cristina Conati, Stacy Marsella, and Ana Paiva. "Affective interactions". In: *Proc. 10th Int. Conf. Intell. user interfaces - IUI '05* (2005), p. 7. DOI: 10.1145/1040830.1040838. URL: <http://portal.acm.org/citation.cfm?doid=1040830.1040838>.
- [7] Elizabeth a Crane, N Sadat Shami, and Christian Peter. "Let's get emotional: emotion research in human computer interaction". In: *Proceedings of ACM CHI 2007 Conference on Human Factors in Computing Systems 2* (2007), pp. 2101–2104. DOI: 10.1145/1240866.1240958. URL: <http://doi.acm.org/10.1145/1240866.1240958>.
- [8] Kasra Dalvand. "An Adaptive User-Interface Based on User's Emotion". In: ().
- [9] Charles Darwin and Phillip Prodger. *The expression of the emotions in man and animals*. Oxford University Press, USA, 1998.
- [10] Fiona Dermody. "Multimodal positive computing system for public speaking with real-time feedback". In: *Proceedings of the 18th ACM International Conference on Multimodal Interaction - ICMI 2016* (2016), pp. 541–545. DOI: 10.1145/2993148.2997616. URL: <http://dl.acm.org/citation.cfm?doid=2993148.2997616>.
- [11] Mohamad A Eid, Senior Member, and Hussein A L Osman. "Affective Haptics : Current Research and Future Directions". In: 4 (2016).
- [12] N. Fragopanagos and J. G. Taylor. "Emotion recognition in human-computer interaction". In: *Neural Networks* 18.4 (2005), pp. 389–405. ISSN: 08936080. DOI: 10.1016/j.neunet.2005.03.006.
- [13] Julián Andrés Galindo, Sophie Dupuy-chessa, and Éric Céret. "TOWARD A UI ADAPTATION APPROACH DRIVEN BY USER EMOTIONS". In: 1 ().
- [14] Yuan Gao, Nadia Bianchi-Berthouze, and Hongying Meng. "What Does Touch Tell Us about Emotions in Touchscreen-Based Gameplay?". In: *ACM Trans. Comput. Interact.* 19.4 (2012), pp. 1–30. ISSN: 10730516. DOI: 10.1145/2395131.2395138. URL: <http://dl.acm.org/citation.cfm?doid=2395131.2395138>.
- [15] Jose Maria Garcia-Garcia, Victor M R Penichet, and Maria D Lozano. "Emotion Detection: A Technology review 1". In: *Interacción 2017* (2017). DOI: 10.1145/3123818.3123852.
- [16] Mariam Hassib, Daniel Buschek, Pawel W Wozniak, and Florian Alt. "HeartChat: Heart Rate Augmented Mobile Chat to Support Empathy and Awareness". In: *Proceedings of the 2017 CHI Conference on Human Factors in Computing Systems* (2017), pp. 2239–2251. DOI: 10.1145/3025453.3025758. URL: <http://doi.acm.org/10.1145/3025453.3025758>.
- [17] Matthew J Hertenstein, Matthew J Hertenstein, Rachel Holmes, Rachel Holmes, Margaret McCullough, Margaret McCullough, Dacher Keltner, and Dacher Keltner. "The Communication of Emotion via Touch". In: *Emotion* 9.4 (2009), pp. 566–573. ISSN: 1528-3542. DOI: 10.1037/a0016108.
- [18] Heinke Hihn, Sascha Meudt, and Friedhelm Schwenker. "Inferring mental overload based on postural behavior and gestures". In: *Proceedings of the 2nd workshop on Emotion Representations and Modelling for Companion Systems - ERM4CT '16* (2016), pp. 1–4. DOI: 10.1145/3009960.3009961. URL: <http://dl.acm.org/citation.cfm?doid=3009960.3009961>.
- [19] David Hutchison and John C Mitchell. *Affective Computing and Intelligent Interaction*. Vol. 6974. 2011. ISBN: 978-3-642-24599-2. DOI: 10.1007/978-3-642-24600-5. arXiv: 9780201398298. URL: <http://link.springer.com/10.1007/978-3-642-24600-5>.
- [20] William James. "What is an emotion?" In: *Mind* 9.34 (1884), pp. 188–205.
- [21] William James. *What is an Emotion?* Simon and Schuster, 2013.

- [22] Robin Kaiser and Karina Oertel. "Emotions in HCI: An Affective E-Learning System". In: *Computer (Long Beach, Calif)*. (2006), pp. 105–106.
- [23] Hyun-Jun Kim and Young Sang Choi. "Exploring emotional preference for smartphone applications". In: *2012 IEEE Consumer Communications and Networking Conference (CCNC)*. 2012, pp. 245–249. DOI: 10.1109/CCNC.2012.6181095.
- [24] Joohee Kim, Na Hyeon Lee, Byung-Chull Bae, and Jun Dong Cho. "A Feedback System for the Prevention of Forward Head Posture in Sedentary Work Environments". In: *Proceedings of the 2016 ACM Conference Companion Publication on Designing Interactive Systems - DIS '16 Companion* (2016), pp. 161–164. DOI: 10.1145/2908805.2909414. URL: <http://dl.acm.org/citation.cfm?doid=2908805.2909414>.
- [25] Rodrigo C Lentini, Beatrice Ionascu, Friederike A Eyssel, Scandar Copti, and Mohamad Eid. "Authoring Tactile Gestures: Case Study for Emotion Stimulation". In: (2017).
- [26] Rodrigo C Lentini, Beatrice Ionascu, Friederike A Eyssel, Scandar Copti, and Mohamad Eid. "Authoring Tactile Gestures: Case Study for Emotion Stimulation". In: (2017).
- [27] Daniel Lopez-Martinez and Rosalind Picard. "Multi-task Neural Networks for Personalized Pain Recognition from Physiological Signals". In: (2017), pp. 3–6. arXiv: 1708.08755. URL: <http://arxiv.org/abs/1708.08755>.
- [28] Antonella Mazzoni and Nick Bryan-kinns. "Mood Glove: A haptic wearable prototype system to enhance mood music in film". In: *Entertainment Computing* 17 (2016), pp. 9–17. ISSN: 1875-9521. DOI: 10.1016/j.entcom.2016.06.002. URL: <http://dx.doi.org/10.1016/j.entcom.2016.06.002>.
- [29] Daniel McDuff, Abdelrahman Mahmoud, Mohammad Mavadati, May Amr, Jay Turcot, and Rana el Kaliouby. "AFFDEX SDK: A Cross-Platform Real-Time Multi-Face Expression Recognition Toolkit". In: *Proceedings of the 2016 CHI Conference Extended Abstracts on Human Factors in Computing Systems - CHI EA '16* (2016), pp. 3723–3726. DOI: 10.1145/2851581.2890247. URL: <https://www.affective.com/wp-content/uploads/2017/03/McDuff%2016%20Affdex.pdf>. URL: <http://dl.acm.org/citation.cfm?doid=2851581.2890247>.
- [30] Edward Melcer and Katherine Isbister. "Motion, Emotion, and Form: Exploring Affective Dimensions of Shape". In: *Late-Breaking Work: Designing Interactive Systems* (2016), pp. 1430–1437. DOI: 10.1145/2851581.2892361. URL: <http://dx.doi.org/10.1145/2851581.2892361>.
- [31] Ali Mollahosseini, Behzad Hasani, and Mohammad H. Mahoor. *AffectNet: A Database for Facial Expression, Valence, and Arousal Computing in the Wild*. 2017. DOI: 10.1109/TAFFC.2017.2740923. arXiv: 1708.03985.
- [32] Aske Mottelson and Kasper Hornbæk. "An affect detection technique using mobile commodity sensors in the wild". In: *ACM Int. Jt. Conf. Pervasive Ubiquitous Comput.* (2016), pp. 781–792. DOI: 10.1145/2971648.2971654.
- [33] Ganapreeta R. Naidu. "A Computational Model of Culture-Specific Emotion Detection for Artificial Agents in the Learning Domain". In: *Proceedings of the 2015 ACM on International Conference on Multimodal Interaction - ICMI '15* (2015), pp. 635–639. DOI: 10.1145/2818346.2823307. URL: <http://dl.acm.org/citation.cfm?doid=2818346.2823307>.
- [34] Phuong Pham and Jingtao Wang. "Understanding Emotional Responses to Mobile Video Advertisements via Physiological Signal Sensing and Facial Expression Analysis". In: *Proceedings of the 22nd International Conference on Intelligent User Interfaces - IUI '17* (2017), pp. 67–78. DOI: 10.1145/3025171.3025186. URL: <http://dl.acm.org/citation.cfm?doid=3025171.3025186>.
- [35] Rosalind W. Picard. "Affective computing: Challenges". In: *International Journal of Human Computer Studies* 59.1-2 (2003), pp. 55–64. ISSN: 10715819. DOI: 10.1016/S1071-5819(03)00052-1. arXiv: arXiv:1011.1669v3.
- [36] Rosalind W. Picard. "Affective Computing for HCI". In: *Proceedings of the 8th HCI International on Human-Computer Interaction: Ergonomics and User Interfaces* (1999), pp. 829–833. ISSN: 0001-5989. arXiv: 742338. URL: <http://dl.acm.org/citation.cfm?id=647943.742338>.
- [37] Matthew Pike, Richard Ramchurn, and Max L. Wilson. "Two-way Affect Loops in Multimedia Experiences". In: *Proceedings of the 2015 British HCI Conference* (2015), pp. 117–118. DOI: 10.1145/2783446.2783595. URL: <http://doi.acm.org/10.1145/2783446.2783595>.
- [38] Eugenia Politou, Efthimios Alepis, and Constantinos Patsakis. "A survey on mobile affective computing". In: *Comput. Sci. Rev.* (2017). ISSN: 15740137. DOI: 10.1016/j.cosrev.2017.07.002. URL: <http://dx.doi.org/10.1016/j.cosrev.2017.07.002>.
- [39] Soujanya Poria, Erik Cambria, Rajiv Bajpai, and Amir Hussain. "A review of affective computing: From unimodal analysis to multimodal fusion". In: *Information Fusion* 37 (2017), pp. 98–125. ISSN: 1566-2535. DOI: 10.1016/j.inffus.2017.02.003. URL: <http://dx.doi.org/10.1016/j.inffus.2017.02.003>.
- [40] Rajib Rana and Margee Hume. "Opportunistic and Context-aware Affect Sensing on Smartphones: The Concept, Challenges and Opportunities." In: (), pp. 1–13.
- [41] Sachin Shah, J. Narasimha Teja, and Samit Bhattacharya. "Towards affective touch interaction: predicting mobile user emotion from finger strokes". In: *J. Interact. Sci.* 3.1 (2015), p. 6. ISSN: 2194-0827. DOI: 10.1186/s40166-015-0013-z. URL: <http://www.journalofinteractionscience.com/content/3/1/6>.
- [42] stanchew. *A map of human emotions*. <https://stanchew.wordpress.com/2012/04/23/a-map-of-human-emotions/>. [Online; accessed 20-November-2017]. 2012.
- [43] Jianhua Tao and Tieniu Tan. "Affective computing: A review". In: *Lecture Notes in Computer Science (including subseries Lecture Notes in Artificial Intelligence and Lecture Notes in Bioinformatics)* 3784 LNCS (2005), pp. 981–995. ISSN: 03029743. DOI: 10.1007/11573548_125.
- [44] Jordan Tewell, Jon Bird, and George R. Buchanan. "The Heat is On: A Temperature Display for Conveying Affective Feedback". In: *Proceedings of the 2017 CHI Conference on Human Factors in Computing Systems - CHI '17* (2017), pp. 1756–1767. DOI: 10.1145/3025453.3025844. URL: <http://dl.acm.org/citation.cfm?doid=3025453.3025844>.
- [45] Sherry Turkle. *The second self: Computers and the human spirit*. MIT Press, 2005.
- [46] Novita Belinda Wunarto and Yustinus Eko Soelistio. "Towards Indonesian Speech-Emotion Automatic Recognition (I-SPEAR)". In: 2017 (2017), pp. 8–11.

- [47] Zhihong Zeng, Jilin Tu, Ming Liu, Tong Zhang, Nicholas Rizzolo, Zhenqiu Zhang, Thomas S. Huang, Dan Roth, and Stephen Levinson. "Bimodal HCI-related affect recognition". In: *Proceedings of the 6th international conference on Multimodal interfaces - ICMI '04* (2004), p. 137. DOI: 10.1145/1027933.1027958. URL: <http://portal.acm.org/citation.cfm?doid=1027933.1027958>.
- [48] Shengkai Zhang and Pan Hui. "A Survey on Mobile Affective Computing". In: 1 (2014). arXiv: 1410.1648. URL: <http://arxiv.org/abs/1410.1648>.

DRAFT