

Generative Models



2014



2015



2016



2017



2018




2019



2020



2021



StableDiffusion





What I cannot create,
I do not understand

Autoencoder

Not a generative model

Variational Autoencoder (VAE)

Generative Adversarial Networks (GANs)

Flow Model

Diffusion Model

Autoencoder

Not a generative model

Variational Autoencoder (VAE)

Elegant

Generative Adversarial Networks (GANs)

*Easy to
control,
hard to
train*


Flow Model

*Elegant but hard to
control*

Diffusion Model

*Create highest quality but
computationally costly*

Autoencoder




$$\text{Reconstruction Loss} = L_1(X, X') = |X - X'|$$

Autoencoder


```
def train(encoder, decoder, data_loader, epochs=5):  
  
    for epoch in range(epochs):  
        for x, _ in data_loader:  
            # Encode and decode  
            latent = encoder(x)  
            output = decoder(latent)  
  
            # Manual MSE loss  
            loss = torch.mean((output - x) ** 2)
```

Autoencoder

Ways to get to good representation:
(Un-) Self-supervised



Autoencoder




Real



Reconstructed



Autoencoder (not a generative model)




Q1: is it a person?


Q2: can you draw one?


A:




Why continuous distribution (manifold)?








Some latent space




Discriminative


Generative



Discriminative




Generative



Discriminative classifier

$$p(y=c|x)$$




Generative classifier

$$p(y=c|x) = p(y=c) \ p(x|y=c)$$

Conditional Density

Goal of a Generative Model

$$p(X) \sim p'(X)$$




*Often use normal distribution
as the starting point*

$$p(Z) = N(0,1)$$

*Creating a distribution of
data that mimic the
real distribution*

Goal of a Generative Model

$$p(X) \sim p'(X)$$




Model was optimized to get this

$$p(X) = \sum_z p(X|Z) p(Z)$$

*We can only approximate
this by observation*



We can assign this

Goal of a Generative Model




$$p(X) = \sum_z p(X|Z) p(Z)$$

Autoencoder is not a generative model




Autoencoder




$$\text{Loss} = L_2(X, X') = |X - X'|^2$$

Variational Autoencoder (VAE)




We want $p(Z|X)$ to be a normal distribution
where we can sample from


Variational Autoencoder (VAE)



Optimize by KL divergence



Similar to a normal distribution
(small KL divergence)



$$q_\phi(z|x) = \mathcal{N}(\mu, \sigma^2)$$

$$p(z) = \mathcal{N}(0, 1)$$

$$D_{KL}(q_\phi(z|x)||p(z)) = \int q_\phi(z|x) \log \frac{q_\phi(z|x)}{p(z)} dz$$


$$D_{KL} = \mathbb{E}_{z \sim q_\phi(z|x)} \left[-\frac{1}{2} \log(\sigma^2) - \frac{(z - \mu)^2}{2\sigma^2} + \frac{z^2}{2} \right]$$

$$= -\frac{1}{2} (\log(\sigma^2) + 1 - \sigma^2 - \mu^2)$$


kl_loss = -0.5 * torch.mean
(1 + logvar - mu.pow(2) - logvar.exp())

$$-\frac{1}{2} \log(\sigma^2) \quad \mu^2 \quad \sigma^2$$

Sample from the latent space



Variational autoencoder



$$p(X') = \sum_z p(X|Z) p(Z)$$

$$\sim \sum_z p(X|Z) p(Z|X)$$

VAE reparametrize

Input → Encoder → z (AE)

Input → Encoder → (μ, logvar) → Reparameterize → z (VAE)
 ↑ ↑
 params random ϵ

```
def reparameterize(mu, logvar):  
    std = torch.exp(0.5 * logvar)  
    eps = torch.randn_like(std)  
    return mu + eps * std
```

$$\sigma = e^{0.5 \log(\sigma^2)}$$
$$z = \mu + \epsilon \cdot \sigma$$

```
mu, logvar = encoder(x)
z = reparameterize(mu, logvar)
output = decoder(z)
```


(Input → Encoder → $(\mu, \log \sigma)$ → Reparameterize → z)

```
recon_loss = torch.mean((output - x) ** 2)
```



```
# KL divergence loss
kl_loss = -0.5 * torch.mean
(1 + logvar - mu.pow(2) - logvar.exp())
```

```
total_loss = recon_loss + kl_loss
```


Generative Adversarial Networks (GANs)




Generative Adversarial Networks (GANs)



Generative Adversarial Networks (GANs)



Generative Adversarial Networks (GANs)



Adversarial Loss:

classify (BCE) real/fake
lsgan
wgan

Vallina GAN Loss

$$\text{Loss}_D = \underset{\text{Real}}{E[\log(D(x))]} + \underset{\text{Fake}}{E[\log(1-D(G(z)))]}$$

$$\text{Loss}_G = E[\log(D(G(z)))]$$


REAL

LSGAN Loss

$$\text{Loss}_D = \underset{\text{Real}}{E[(D(x) - 1)^2]} + \underset{\text{Fake}}{E[D(G(z))^2]}$$

$$\text{Loss}_G = E[D(G(z) - 1)^2]$$

REAL



GANs



VAE



GANs



VAE



Conditional GANs




Image as condition GAN






Image + condition GAN



Conditional GAN

000008000
080008000
000000000
000088000
000000000
000000000
000000000
000000000
000000000
000000000

0323856789
0323956789
0323456789
0323456789
0323456789
0323456789
0323456789
0323456789
0323456789
0323456789

0123456789
0123456789
0123456789
0123456789
0123456789
0123456789
0123456789
0123456789
0123456789
0123456789


0123456789
0123456789
0123456789
0123456789
0123456789
0123456789
0123456789
0123456789
0123456789
0123456789

(a) AC-GAN 10 epochs

(b) AC-GAN 20 epochs

(c) AC-GAN 50 epochs

GAN (no condition)



GAN (image as condition)




Image + Conditional GAN (Facial editing)

[
Beard [
Old No Beard
Blond Old
Mouth open Brown
.....] Mouth close
.....]



Paired (supervised)

Training:




Generating:



Unpaired (Unsupervised?)



Training:



Generating:





Supervised Learning: you have the answers



Unsupervised (unpaired) translation


Generating:

Training:



Biomedical applications : supervised




Cross-modality



Follow-ups



low tier to high tier












Supervised

Low
Quality
(Source)



Learned

High
Quality
(Target)

Generated




Supervised: inverse problem





Synthetic Supervised

Training:




Testing:




Synthetic Paired

Training:




Testing:




Problem with synthetic pairs:

*T may not be modeled accurately
 $T(L > H)$ is hard to assume*


Summary of supervised (Paired) translation



Unpaired learning by “Cyclic Consistency”




x should be close to x''




y should be close to y''


Inverse problem with unpaired data (CycleGAN, DiscoGAN, DualGAN etc.)





Cyclic Consistency Loss






Unsupervised Learning: learn from the data





Data too costly to label



Difficult to acquire imaging with ground-truth






(a) A translation removing tumors

(b) A translation adding tumors


Zebras ↘ Horses





zebra → horse



horse → zebra













No intrinsic physical dimension
Mostly can be judged by PSNR,
SSIM...etc..

Has intrinsic physical dimensions
Need to be judged by some physical / clinical outcome

Are those real? “Educated Guess”




Quality Measurements: FID



Summary

GAN



Conditional GAN




Image as condition GAN






Image + condition GAN



Summary

Paired



Unpaired (these problem is not solved and has many approaches)

