

Data Wrangling

with pandas

Cheat Sheet

<http://pandas.pydata.org>

Tidy Data – A foundation for wrangling in pandas



Each **variable** is saved in its own **column**



Each **observation** is saved in its own **row**

Tidy data complements pandas's **vectorized operations**. pandas will automatically preserve observations as you manipulate variables. No other format works as intuitively with pandas.



M * A

Syntax – Creating DataFrames

	a	b	c
1	4	7	10
2	5	8	11
3	6	9	12

```
df = pd.DataFrame(  
    {"a": [4, 5, 6],  
     "b": [7, 8, 9],  
     "c": [10, 11, 12]},  
    index = [1, 2, 3])  
Specify values for each column.
```

```
df = pd.DataFrame(  
    [[4, 7, 10],  
     [5, 8, 11],  
     [6, 9, 12]],  
    index=[1, 2, 3],  
    columns=['a', 'b', 'c'])  
Specify values for each row.
```

n	v	a	b	c
d	1	4	7	10
e	2	5	8	11
	3	6	9	12

```
df = pd.DataFrame(  
    {"a": [4, 5, 6],  
     "b": [7, 8, 9],  
     "c": [10, 11, 12]},  
    index = pd.MultiIndex.from_tuples(  
        [('d', 1), ('d', 2), ('e', 2)],  
        names=['n', 'v']))  
Create DataFrame with a MultiIndex
```

Method Chaining


Most pandas methods return a DataFrame so that another pandas method can be applied to the result. This improves readability of code.

```
df = (pd.melt(df)  
     .rename(columns={  
         'variable': 'var',  
         'value': 'val'})  
     .query('val >= 200'))
```

Reshaping Data – Change the layout of a data set



pd.melt(df)
Gather columns into rows.



df.pivot(columns='var', values='val')
Spread rows into columns.



pd.concat([df1, df2])
Append rows of DataFrames



pd.concat([df1, df2], axis=1)
Append columns of DataFrames

df.sort_values('mpg')
Order rows by values of a column (low to high).

df.sort_values('mpg', ascending=False)
Order rows by values of a column (high to low).


df.rename(columns = {'y': 'year'})
Rename the columns of a DataFrame

df.sort_index()
Sort the index of a DataFrame

df.reset_index()
Reset index of DataFrame to row numbers, moving index to columns.

df.drop(['Length', 'Height'], axis=1)
Drop columns from DataFrame

Subset Observations (Rows)



df[df.Length > 7]
Extract rows that meet logical criteria.

df.drop_duplicates()
Remove duplicate rows (only considers columns).

df.head(n)
Select first n rows.

df.tail(n)
Select last n rows.

df.sample(frac=0.5)
Randomly select fraction of rows.


df.sample(n=10)
Randomly select n rows.

df.iloc[10:20]
Select rows by position.

df.nlargest(n, 'value')
Select and order top n entries.

df.nsmallest(n, 'value')
Select and order bottom n entries.

Subset Variables (Columns)



df[['width', 'length', 'species']]
Select multiple columns with specific names.

df['width'] or **df.width**

Select single column with specific name.

df.filter(regex='regex')
Select columns whose name matches regular expression *regex*.

regex (Regular Expressions) Examples	
<code>'\.'</code>	Matches strings containing a period '.'
<code>'Length\$'</code>	Matches strings ending with word 'Length'
<code>'^Sepal'</code>	Matches strings beginning with the word 'Sepal'
<code>'^x[1-5]\$',</code>	Matches strings beginning with 'x' and ending with 1,2,3,4,5
<code>''^(?!Species\$).''</code>	Matches strings except the string 'Species'

df.loc[:, 'x2': 'x4']
Select all columns between x2 and x4 (inclusive).

df.iloc[:, [1, 2, 5]]
Select columns in positions 1, 2 and 5 (first column is 0).

df.loc[df['a'] > 10, ['a', 'c']]
Select rows meeting logical condition, and only the specific columns.

Logic in Python (and pandas)		
<code><</code>	Less than	<code>!=</code> Not equal to
<code>></code>	Greater than	<code>df.column.isin(values)</code> Group membership
<code>==</code>	Equals	<code>pd.isnull(obj)</code> Is NaN
<code><=</code>	Less than or equals	<code>pd.notnull(obj)</code> Is not NaN
<code>>=</code>	Greater than or equals	<code>&, , ~, ^, df.any(), df.all()</code> Logical and, or, not, xor, any, all

<http://pandas.pydata.org/> This cheat sheet inspired by RStudio Data Wrangling Cheatsheet (<https://www.rstudio.com/resources/cheatsheets/2015/02/data-wrangling-cheatsheet.pdf>) Written by Irv Luttig, Braxton Consultants