

```

plugins {
    id 'java'
    id 'war'
    id 'org.springframework.boot' version '3.5.14'
    id 'io.spring.dependency-management' version '1.1.7'
}

group = 'nhn.s.mp'
version = '0.0.1-SNAPSHOT'

bootwar {
    enabled = false
}

war {
    enabled = true
}

java {
    toolchain {
        languageVersion = JavaLanguageVersion.of(21)
    }
}

repositories {
    maven {
        url = uri("http://19.88.120.152:9010/repository/maven-releases/")
    }
}

dependencies {
    implementation 'org.springframework.boot:spring-boot-starter-web:3.5.7'
    implementation 'org.springframework.security:spring-security-config:6.5.7'
    implementation 'org.springframework.boot:spring-boot-starter-security:3.5.10'
    implementation 'org.mybatis.spring.boot:mybatis-spring-boot-starter:3.0.4'
    implementation 'org.springframework.boot:spring-boot-starter-webflux:3.5.14'
    implementation 'org.springframework.boot:spring-boot-autoconfigure:3.5.14'
    implementation 'org.springframework.boot:spring-boot-starter-aop:3.5.14'
    implementation 'org.bgee.log4jdbc-log4j2-log4j2-jdbc-logging:3.5.10'
    implementation 'org.apache.commons:commons-lang3:3.17.0'
    implementation 'org.springframework.boot:spring-boot-starter-test:3.5.10'
    testImplementation 'org.projectlombok:lombok'
    testAnnotationProcessor 'org.projectlombok:lombok'
    annotationProcessor 'org.projectlombok:lombok'
    implementation 'com.google.code.gson:gson:2.10.1'
    implementation 'com.oracle.database.jdbc:ojdbc11:23.3.0.23.09'
    implementation 'com.oracle.ojdbc:ora18n:19.3.0.0'
    /* JWT Session */
    implementation 'io.jsonwebtoken:jwt-api:0.13.0'
    implementation 'io.jsonwebtoken:jwt-jackson:0.13.0'
    implementation 'io.jsonwebtoken:jwt-impl:0.13.0'
    implementation 'org.springframework.boot:spring-boot-starter-security:3.5.10'
    /* ETC */
    implementation fileTree(dir: 'libs', include: ['*.jar'])
}

```

```
all {
    exclude group: 'org.springframework.boot', module: 'spring-boot-starter-logging'
    configureEach {
        exclude group: 'io.netty', module: 'netty-resolver-dns-native-macos'
        exclude group: 'io.netty', module: 'netty-transport-native-epoll'
        exclude group: 'io.netty', module: 'netty-transport-native-kqueue'
    }
}
```

```
Setting.gradle
pluginManagement {
    repositories {
        maven {
            url = uri("http://19.88.120.152:9010/repository/maven-releases/")
            allowInsecureProtocol = true
        }
    }
}
```

```
rootProject.name = 'pdmp'
```

```
Rdw.mp.co.a
```

```
<?xml version="1.0" encoding="UTF-8"?><!DOCTYPE mapper PUBLIC "-//mybatis.org/DTD Mapper 3.0//EN"
<mapper namespace="nhn.is.mp.co.a.dao.mpcoa99999DA0">
    <select id="mpcoa9999950_50" resultType="java.util.HashMap">
        SELECT /*+ INDEX(T1 TB_CR_AH_SALES_TIP_RACT_PK) */ /* mpcoa9999950_50 */
        T1.TRT_BRG
        , T1.TRTM_ENO
        , T1.SALZ_TIP_KDC
        , T1.BAS_DT
        , T1.PRTO_CN
        , T1.INQ_CN
        , T1.INP_CN
        FROM TB_CR_AH_SALES_TIP_RACT T1
        WHERE 1 = 1
        <if test="salzTipkdc != null and salzTipkdc != ''">
            AND T1.SALZ_TIP_KDC = #{salzTipkdc}
        </if>
    </select>
</mapper>
```

```
Application.yml
```

```
spring:
  profiles: local
  active: local
  application:
    name: pdmp
  config:
    import: classpath:exceptionCode.yml
    # CORS 차등 등록 (수동 등록)
  cors:
    allowed-origins:
    allowed-methods:
    allowed-headers:
  datasource:
    jdbc-url: jdbc:log4jdbc:oracle:thin:@19.24.148.173:1521:SBMF CRT
    driver-class-name: net.sf.log4jdbc.sql.jdbcapi.DriverSpy
    username: MFCR
    password: uXPHv0.0Udv6
```

```
spring:
  config:
    activate:
      on-profile: local
jwt:
  secret: "Qw8mx2pl9rtv6NZA4kYh7UCdF1B8e5JSMPR3XW8LncV0HgKe"
  access-token-expiration: 180000
  on-profile: dev
  activate:
    config:
      spring:
        config:
          activate:
            on-profile: local
exceptionCode.yml
nhnjs:
exception:
  FW0001: "{0} 에러 발생"
  FW0002: "TEST Exception"
  FW0003: "{0} exception 은 {1} 문 공의 주체공"
  FW9999: "메기치 않음 공을 사용했습니다. 시스템 관리자에게 문의하세요."
Log4j2.xml
<?xml version="1.0" encoding="UTF-8"?>
<Configuration status="INFO">
  <Properties>
    <property name="time">%d{yyyy-MM-dd HH:mm:ss.SSS}</property>
    <property name="elk_split">|+|</property>
    <property name="custom_split">|</property>
  </Properties>
  <include resource="/home/mfproblemx/architecture/proto/was/mpco/logs/fw/mp/application/<property>" />
  <include resource="/home/mfproblemx/architecture/proto/was/mpco/logs/fw/mp/service/<property>" />
  <property name="FRAMEWORK_LOG_PATH">/home/mfproblemx/architecture/proto/was/mpco/logs/fw/mp/application/<property></property>
  <property name="SERVICE_LOG_PATH">/home/mfproblemx/architecture/proto/was/mpco/logs/fw/mp/service/<property></property>
  <property name="CORE-HEADER">${elk_guid} ${elk_split} ${elk_userid} ${elk_serviceid}</property>
  <property name="BIZ-HEADER">${elk_ip} - ${elk_guid} ${elk_split} ${elk_userid} ${elk_serviceid}</property>
  <property name="IO-HEADER">${elk_ip} - ${elk_guid} ${elk_split} ${elk_userid} ${elk_serviceid}</property>
  <property name="SQL-HEADER">${elk_ip} - ${elk_guid} ${elk_split} ${elk_userid} ${elk_serviceid}</property>
  <property name="IF-HEADER">${elk_split} ${elk_fid} ${elk_split} ${elk_userid} ${elk_serviceid}</property>
  <property name="ERR-HEADER">${elk_ip} ${elk_split} ${elk_guid} ${elk_split} ${elk_serviceid}</property>
  <property name="${elk_ip}" %>{time}%</property>
  <!-- CUSTOM Default -->
  <!-- % : 로그 레벨, %m : 로그 메시지, %n : 줄 바꿈 문자 -->
  <appender name="STDOUT" class="ch.qos.logback.core.ConsoleAppender">
    <filter class="ch.qos.logback.classic.filter.ThresholdFilter">
      <level>INFO</level>
    </filter>
    <layout class="ch.qos.logback.classic.PatternLayout">
      <pattern>%d{yyyy-MM-dd HH:mm:ss.SSS} [%-5p] [%-5sp] %replace{%m}{\n}{&#x2028;}%n</pattern>
    </layout>
  </appender>
  <root>
    <level>INFO</level>
    <appender-ref ref="STDOUT"/>
  </root>
</Configuration>
```



```
</property>
<property name="MONITOR_CUSTOM">[{$time}] [%-5p] [%C.%M:%L] %replace{%m}{\n}{&#x2028;}\n
```

```
<!-- PATTERN -->
<!-- CORE -->
<property name="CORE_LOG_PATTERN">[ CORE ]{$ek-split} ${CORE_HEADER}
</property>
<!-- BIZ -->
<property name="BIZ_LOG_PATTERN">[ BIZ ]{$ek-split} ${BIZ_HEADER} ${BIZ_CUSTOM}</property>
<!-- SQL -->
<property name="SQL_LOG_PATTERN">[ SQL ]{$ek-split} ${SQL_HEADER} ${SQL_CUSTOM}</property>
<!-- IF IO -->
<property name="IO_LOG_PATTERN">[ IO ]{$ek-split} ${IO_HEADER} ${IO_CUSTOM}</property>
<!-- IF -->
<property name="IF_LOG_PATTERN">[ IF ]{$ek-split} ${IF_HEADER} ${IF_CUSTOM}</property>
<!-- ERR -->
<property name="ERR_LOG_PATTERN">[ ERR ]{$ek-split} ${ERR_HEADER} ${ERR_CUSTOM}</property>
<!-- MONITOR -->
<property name="MONITOR_LOG_PATTERN">[ MONITOR ]{$ek-split} ${MONITOR_CUSTOM}</property>
<!-- MONITOR_CUSTOM -->
<property name="MONITOR_CUSTOM">[{$time}] [%-5p] [%C.%M:%L] %replace{%m}{\n}{&#x2028;}\n
</property>
</Properties>
```

```
<Appenders>
<!-- CORE -->
<Console name="CORE">
<PatternLayout pattern="%${CORE_LOG_PATTERN}" disableAnsi="false"/>
</Console>
<!-- IO -->
<Console name="IO">
<PatternLayout pattern="%${IO_LOG_PATTERN}" disableAnsi="false"/>
</Console>
<!-- IF -->
<Console name="IF">
<PatternLayout pattern="%${IF_LOG_PATTERN}" disableAnsi="false"/>
</Console>
<!-- BIZ -->
<Console name="BIZ">
<PatternLayout pattern="%${BIZ_LOG_PATTERN}" disableAnsi="false"/>
</Console>
<!-- SQL -->
<Console name="SQL">
<PatternLayout pattern="%${SQL_LOG_PATTERN}" disableAnsi="false"/>
</Console>
<!-- ERR -->
<Console name="ERR">
<PatternLayout pattern="%${ERR_LOG_PATTERN}" disableAnsi="false"/>
</Console>
<!-- MONITOR -->
<Console name="MONITOR">
<PatternLayout pattern="%${MONITOR_LOG_PATTERN}" disableAnsi="false"/>
</Console>
</Appenders>
```

```
<RollingFile name="FRAMEWORK_LOG_FILE"
filePattern="%${FRAMEWORK_LOG_PATH}/sd-framework.log"
PatternLayout pattern="%${CORE_LOG_PATTERN}"
Policies>
<!-- 1. 滚动策略 -->
<SizeBasedTriggeringPolicy size="500MB"/>
</Policies>
<!-- 2. 滚动策略 -->
<DefaultRollingStrategy>
<Delete>
<IfFileName glob="*.log.gz"/>
<IfLastModified age="30d"/>
</Delete>
</DefaultRollingStrategy>
</RollingFile>
```

```
<RollingFile name="SERVICE_LOG_FILE"
filePattern="%${SERVICE_LOG_PATH}/sd-service.log"
PatternLayout pattern="%${BIZ_LOG_PATTERN}"
Policies>
<!-- 1. 滚动策略 -->
<SizeBasedTriggeringPolicy size="500MB"/>
</Policies>
<!-- 2. 滚动策略 -->
<DefaultRollingStrategy>
<Delete>
<IfFileName glob="*.log.gz"/>
<IfLastModified age="30d"/>
</Delete>
</DefaultRollingStrategy>
</RollingFile>
```

```
<!-- 3. 滚动策略 -->
<TimeBasedTriggeringPolicy interval="1" modulate="true"/>
</TimeBasedTriggeringPolicy>
<!-- 4. 滚动策略 -->
<DefaultRollingStrategy>
<Delete>
<IfFileName glob="*.log.gz"/>
<IfLastModified age="30d"/>
</Delete>
</DefaultRollingStrategy>
</RollingFile>
</Appenders>
</Loggers>
```

Log4jdbc, Log4j2.properties
Log4jdbc.spyLogdelegator.name=net.sf.log4jdbc.log.sifaj.sifajspyLogdelegator
Log4jdbc.dump.sql.maxInLength=0
Log4jdbc.auto.load.popular.drivers=false
Log4jdbc.drivers=oracle.jdbc.OracleDriver

```
</Loggers>
</Configuration>

<Logger name="jdbc.connection" level="off" additivity="false">
  <AppenderRef ref="SQL"/>
</Logger>

<Logger name="jdbc.resultset" level="off" additivity="false">
  <AppenderRef ref="SQL"/>
</Logger>

<Logger name="jdbc.audit" level="off" additivity="false">
  <AppenderRef ref="SQL"/>
</Logger>

<Logger name="jdbc.resultsettable" level="off" additivity="false">
  <AppenderRef ref="SQL"/>
</Logger>

<Logger name="jdbc.sqltiming" level="debug" additivity="false">
  <AppenderRef ref="FRAMEWORK_LOG_FILE"/>
  <AppenderRef ref="SERVICE_LOG_FILE"/>
  <AppenderRef ref="SQL"/>
</Logger>

<Logger name="jdbc.sqlonly" level="off" additivity="false">
  <AppenderRef ref="FRAMEWORK_LOG_FILE"/>
  <AppenderRef ref="SERVICE_LOG_FILE"/>
  <AppenderRef ref="SQL"/>
</Logger>

<!-- LOG4JDBC -->
<Logger name="nhis.mp.config.MybatisLogInterceptor" level="debug" additivity="false">
  <AppenderRef ref="SQL"/>
</Logger>

<Logger name="nhis.mp" level="info" additivity="false">
  <AppenderRef ref="BIZ"/>
  <AppenderRef ref="SERVICE_LOG_FILE"/>
  <AppenderRef ref="FRAMEWORK_LOG_FILE"/>
</Logger>

<Logger name="nhis.fw" level="info" additivity="false">
  <AppenderRef ref="CORE"/>
  <AppenderRef ref="FRAMEWORK_LOG_FILE"/>
</Logger>

<Logger name="org.apache" level="off" additivity="false">
  <AppenderRef ref="CORE"/>
  <AppenderRef ref="FRAMEWORK_LOG_FILE"/>
</Logger>

<Logger name="org.springframework" level="info" additivity="false">
  <AppenderRef ref="CORE"/>
  <AppenderRef ref="FRAMEWORK_LOG_FILE"/>
</Root>
<AppenderRef ref="FRAMEWORK_LOG_FILE"/>
<AppenderRef ref="CORE"/>
```

1764706445 장*증 01420

본 문서는 저작권의 보호를 받습니다

- > > pamp
- > > pdmp [boot] [pdmp feature/CSS46155]
- > > src/main/java
- > > src/main/resources
- > > rdw.mp.co.a
- > > mpc0a9999-ORA.xml
- > > application.yml
- > > exceptionCode.yml
- > > log4j2.xml
- > > log4j2.properties
- > > JRE System Library [JavaSE-21]
- > > Project and External Dependencies
- > > bin
- > > docs
- > > docs-exam