

# Data Preprocessing

Kaiqi Zhao

The University of Auckland

# Content

- Data Cleaning
- Missing Data
  - Imputation
- Data Reduction
  - Dimensionality Reduction
  - PCA
  - Feature Selection
- Noisy Data
- Data Transformation and Data Discretization
  - Normalization
  - Discretization
- Imbalanced Data
  - Sampling
  - SMOTE

# Why preprocess?

- Preprocessing means to transform the data before we feed it to a learning algorithm
- Why would we do that?
- What would we for example do?

```

time,CO2,m14.0028,m15.0238,m15.9962,m16.0201,m17.0260,m18.0338,m18.
'12/18/2013 11:46:00',610.208,1.92631,3.97879,1.7699,0.969783,355.
'12/18/2013 11:46:30',609.304,1.90129,4.74365,1.8163,0.905811,359.
'12/18/2013 11:47:00',608.475,1.97128,4.72838,1.97672,0.843545,361
'12/18/2013 11:47:30',607.667,1.78681,4.5312,1.83743,0.8414,358.41
'12/18/2013 11:48:00',606.66,2.07051,4.7177,1.87686,0.984419,358.2
'12/18/2013 11:48:30',605.9,2.05568,4.4257,1.69587,0.997787,361.53
'12/18/2013 11:49:00',605.213,2.14381,4.22846,1.81092,1.08215,360.
'12/18/2013 11:49:30',604.763,2.14666,4.41321,1.62883,0.949994,362
'12/18/2013 11:50:00',604.28,1.72339,4.37108,1.60896,0.864071,361.
'12/18/2013 11:50:30',603.878,1.9908,4.23466,2.12354,1.14864,361.8
'12/18/2013 11:51:00',603.477,1.75594,4.52392,1.98485,1.16035,359.
'12/18/2013 11:51:30',603.094,1.93295,4.35966,1.98952,1.03466,358.
'12/18/2013 11:52:00',602.834,1.66704,3.89078,1.94005,1.13423,360.
'12/18/2013 11:52:30',602.454,2.04784,4.32292,2.03664,0.840845,360
'12/18/2013 11:53:00',601.932,1.94109,4.0525,1.64712,1.10734,355.2
'12/18/2013 11:53:30',601.703,1.69041,4.39691,1.91399,0.989235,356
'12/18/2013 11:54:00',601.434,1.75891,4.41485,1.97739,0.848539,359
'12/18/2013 11:54:30',601.378,1.90523,4.16484,1.6669,1.02649,358.6
'12/18/2013 11:55:00',600.968,1.90005,4.38889,1.83583,0.878652,355
'12/18/2013 11:55:30',600.696,2.09066,4.12527,1.70364,0.851626,363
'12/18/2013 11:56:00',600.447,1.87109,4.50434,1.9375,0.961437,358.
'12/18/2013 11:56:30',600.32,1.90586,4.38532,1.82742,0.969086,358.
'12/18/2013 11:57:00',600.358,1.94303,4.13967,2.14942,1.14285,364.
'12/18/2013 11:57:30',600.469,1.84692,4.45638,1.84505,0.971452,362
'12/18/2013 11:58:00',600.299,1.62961,3.93316,2.06964,0.881806,362
'12/18/2013 11:58:30',600.101,2.00212,4.09161,1.5438,0.964047,362.
'12/18/2013 11:59:00',600.176,1.68476,3.66563,1.81482,1.13721,366.
'12/18/2013 11:59:30',600.318,1.69015,4.09808,1.81106,0.760072,364
'12/18/2013 12:00:00',600.371,1.95708,4.19909,1.89499,1.07517,360.
'12/18/2013 12:00:30',600.341,1.72461,3.94856,2.24348,1.01338,359.
'12/18/2013 12:01:00',600.37,1.74072,3.70107,1.53534,0.811749,360.

```

## In this topic we will...

- Talk about problems that can appear in data
- Introduce strategies to solve these problems
- Talk about feature selection, a very important technique in machine learning

# Major Tasks in Data Preprocessing

- Data cleaning
  - Missing values
  - Noisy data
  - Outliers
- Data reduction
  - Dimensionality reduction
  - Data compression
- Transformation and discretization
  - Normalization
  - Hierarchy generation

# Data Cleaning

# Data Cleaning

- Basic assumption in machine learning?
  - The distributions of the training and test data are the same
- But, real-world data are, in most cases, dirty
- This can lead to problems, if data are
  - **Incomplete** lacking attribute values, certain attributes, or containing only aggregate data
  - **Noisy** containing noise, errors, or outliers
  - **Inconsistent** containing discrepancies in codes or names
  - **Intentially wrong** for example, there are a lot of pictures with a GPS location just a bit west of Africa

# Missing Data




# Incomplete (Missing) Data

- Data are not always available
  - Many tuples have no recorded value for several attributes
  - E.g. customer income in sales data
- Missing data may be due to
  - Equipment malfunction
  - Inconsistent with other recorded data and thus deleted
  - Data not entered due to misunderstanding
  - Certain data may not be considered important at the time of entry
  - Not register history or changes of the data
- Missing data may need to be inferred
  - When, for example?

# What to Consider When Handling Missing Data?

- Why are data missing?
- Three types of missing data (Rubin, D. B., 1974)
  - **Missing completely at random (MCAR)**
    - Completely unrelated to the data
    - Potential problem?

Name	Country	Income
Jane	NZ	\$50k
Kate	NZ	\$75k
Tom	US	\$53k
George	UK	\$64k
Mark	UK	\$77k
Philippe	US	\$80k



Name	Country	Income
Jane	NZ	
	NZ	\$75k
Tom	US	
George		\$64k
	UK	\$77k
Philippe	US	\$80k

Missing data not  
related to the data

# What to Consider When Handling Missing Data?

- Why are data missing?
- Three types of missing data (Rubin, D. B., 1974)
  - Missing at random (MAR)
    - The fact the data are missing is not related to the missing attribute itself, but to some other attributes in the data set
    - Potential problem?

Name	Country	Income
Jane	NZ	\$50k
Kate	NZ	\$75k
Tom	US	\$53k
George	UK	\$64k
Mark	UK	\$77k
Philippe	US	\$80k




Name	Country	Income
Jane	NZ	\$50k
Kate	NZ	\$75k
Tom	US	\$53k
George	UK	
Mark	UK	
Philippe	US	\$80k

Missing income  
report from UK

# What to Consider When Handling Missing Data?

- Why are data missing?
- Three types of missing data (Rubin, D. B., 1974)
  - Missing not at random (MNAR)
    - The fact the data are missing is related to the missing attribute itself
    - Potential problem?

Name	Country	Income
Jane	NZ	\$50k
Kate	NZ	\$75k
Tom	US	\$53k
George	UK	\$64k
Mark	UK	\$77k
Philippe	US	\$80k




Name	Country	Income
Jane	NZ	
Kate	NZ	\$75k
Tom	US	
George	UK	
Mark	UK	\$77k
Philippe	US	\$80k

People with income less than \$70k might refuse to provide their income details

# How to Handle Missing Data – Imputation


- Ignore the tuple



- Usually done when the class label is missing (classification)
- Not effective when the fraction of missing values varies considerably

# How to Handle Missing Data – Imputation

- Fill in the missing data manually



- Tedious and sometimes infeasible

# How to Handle Missing Data – Imputation

- Fill in automatically
  - A global constant

$X$						$X'$				
sunny	warm	Mon	May	...		sunny	warm	Mon	May	...
cloudy	?	?	July	...		cloudy	missing	missing	July	...
sunny	cold	?	?	...		sunny	cold	missing	missing	...
...	...	...	...	...		...	...	...	...	...
overcast	cold	Sat	June	...		overcast	cold	Sat	June	...

- E.g. " missing"
- A new class

# How to Handle Missing Data – Imputation

- Fill in automatically
  - The attribute mean

$X$						$X'$				
12	2	22	38	...	→	12	2	22	38	...
11	?	?	90	...		11	12	38	90	...
2	23	?	?	...		2	23	38	30	...
...	...	...	...	...		...	...	...	...	...
9	11	54	23	...		9	11	54	23	...

- A very commonly used method
- Changes relationship with other variables  $\Rightarrow$  bias in data



# How to Handle Missing Data – Imputation


- Fill in automatically
  - The attribute mean of the samples belonging to the same class

$X Y$							$X' Y$					
12	2	22	38	...	1	→	12	2	22	38	...	1
11	?	?	90	...	0		11	12	38	90	...	0
2	23	?	?	...	1		2	23	38	30	...	1
...	...	...	...	...	...		...	...	...	...	...	...
9	11	54	23	...	0		9	11	54	23	...	0

- Might change relationship with other variables other than class  $\Rightarrow$  bias in data

# How to Handle Missing Data – Imputation

- Fill in automatically
  - The most probable value



- Inference-based such as decision tree, linear regression, Bayesian formula, nearest neighbour,...

# More on Imputation

- Matrix decomposition approaches
  - Decompose matrix using, for example, Singular Value Decomposition (SVD)
    - Decompose the data matrix  $X$  such that  $X = U\Lambda V$
    - Create imputed matrix  $X'$  by multiplying  $U \times \Lambda \times V$

$$\begin{array}{ccc}
 M & U & \Lambda & V \\
 \begin{bmatrix} x_{11} & \cdots & x_{1d} \\ \vdots & \ddots & \vdots \\ x_{n1} & \cdots & x_{nd} \end{bmatrix} & \approx & \begin{bmatrix} u_{11} & \cdots & u_{1k} \\ \vdots & \ddots & \vdots \\ u_{n1} & \cdots & u_{nk} \end{bmatrix} & \begin{bmatrix} \lambda_{11} & \cdots & 0 \\ \vdots & \ddots & \vdots \\ 0 & \cdots & \lambda_{kk} \end{bmatrix} & \begin{bmatrix} v_{11} & \cdots & v_{1d} \\ \vdots & \ddots & \vdots \\ v_{k1} & \cdots & v_{kd} \end{bmatrix} \\
 n \times d & & n \times k & k \times k & k \times d
 \end{array}$$

Minimize the Sum of Squared Errors

$$\min_{U, \Lambda, \Sigma} \sum_{x_{ij} \in X} (x_{ij} - [U\Lambda V]_{ij})^2$$

# Even More on Imputation

- EM imputation
  - Expectation Maximization
  - Use other variables to impute the values (Expectation)
  - Check if value is most probable (Maximization)
- Multiple imputation (e.g., MICE)
  - 1. Impute missing values using appropriate model (for example using classifier / regression model to predict the missing value)
  - 2. Repeat the step multiple times (3-5)
  - 3. Carry out required full analysis of data (e.g. build classifier and evaluate)
  - 4. Average the results (predictions or evaluation)
- So what is the best approach?

# Preprocessing and Evaluation

- So now we know a preprocessing example
- Where would you put the preprocessing step in the evaluation?
- For example, for imputation:
  - Impute the values before splitting in train and test?
  - Impute the values in the training set — then how about the test set?