
Who Is The Best Manager
in Premier League

CHANGYE LI

4880276

INDEPENDENT RESEARCH, FIRST DRAFT

03/17/2016

Contents

1	Introduction	2
1.1	Background	2
1.2	Methods	3
2	Data Collection	3
3	Model Description	4
3.1	Definitions	4
3.2	Notations	5
3.3	Algorithms	5
4	Algorithms Implementations	6
4.1	Fuzzy Preference Relation Matrix	6
4.2	Fuzzy Consistent Matrix	7
4.3	Weight Matrix	7
5	Data Analysis	8
5.1	Pilot Analysis	9
5.2	The Best Manager Who Coached At Least One Season in All Time . . .	9
5.3	The Best Current Premier League Manager	10
5.4	The Best Premier League Manager Who Managed At Most Three Seasons	11
6	Summary	12
	References	13

1 Introduction

Football (soccer) is one of the most popular and valued sport in the world. In order to win more titles, football clubs do not only seek for high level players but also experienced managers. To improve the performances, clubs are increasingly looking for technical and scientific methods to evaluate players and managers' performances. On the website *WhoScored*, players are rated objectively and effectively based on their performances. The higher ratings the players get, the more valued the players are and higher level the players are at. Unfortunately, there are no such ratings for managers. Therefore, building up an objective and effective system to evaluate the performances of managers is highly demanded.

In this paper, I will use mathematical methods to evaluate managers' performances by calculating fuzzy preference relation matrix and fuzzy consistent matrix. Unlike other studies that are based on human judgment, fuzzy set theory will provide an objective and effective method to rank managers' performances.

1.1 Background

Premier League is not only one of the most famous and popular professional football league all over the world, but also stands for the top of English football league system. In Premier League, 20 teams will play 38 matches each and the team who has the highest scores will win the league. The levels of managers are becoming critical to raise probability of winning championships. Premier League clubs are looking forward to hiring high quality manager in order to win more titles in the league. For example, after they sacked Brendan Rodgers, Liverpool hired Jürgen Klopp, who is a former winner of the Bundesliga title. Also, in next season (2016-2017), Manchester City will hire Pep Guardiola, the manager who is considered as the best all over the world, in order to win more titles.

1.2 Methods

General speaking, there are three methods to evaluate managers' performances. Two of them are subjective and another one is objective. Some previous studies focused on subjective results, such as questionnaires for athletes to judge coaches (Rushall & Wiznuk, 1985) and interviewing with coaches (Cassidy, Potrac, & McKenzie, 2006). Moreover, some clubs' executive boards focus more on rebuilding up a team, such as working with youngsters, judging player potential and ability, and team management. Therefore, managers who are more likely to be a "Tinker" are hired to take over or rebuild a team, thus Louis Van Gaal, Claudio Ranieri and Carlo Ancelotti are hired by different clubs. Both of these methods focus on human judgement and they are subjective. Thus the third method will use traditional evaluation factors, such as Winning Percentage, Title Won, Manager of Year and Manager of Month, to evaluate managers' performances.

Although the statistics is listed, unlike football players, managers don't have any "score" or ratings like those on *WhoScored* or an evaluation system to build up a "score", so a quantitative score is highly needed in order to rank managers' performances. However, factors that count for rebuilding up a team are hard to be quantitative, so in this paper I will choose traditional factors, namely Winning Percentage, Title Won, Manager of Year and Manager of Month, to evaluate Premier League managers' performances. Also, a fuzzy consistent matrix will be applied to determine the weight of factors and evaluate and rank the performance of Premier League managers. The product of calculated weight and selected factors will be the final score to rank managers' performances.

In other words, in this paper I will use mathematical methods to evaluate managers' performances by calculated score rather than complete human judgment.

2 Data Collection

All data is collected from the official Premier League website and relevant Wikipedia pages. All relevant Wikipedia pages refer to related the manager profile page on the official Premier League website.

Also, the performances of Premier League managers are decided by league performances only. In other words, team performances in UEFA Europa League, UEFA Champions League, Community Shield, FA Cup and League Cup are not included.

3 Model Description

3.1 Definitions

According to Barzilai (1998), Kandasamy, Smarandache and Ilanthenral,(2007), Ismail and Mors (1991), Wang and Chen (2005), the definitions of fuzzy set theory are defined as following:

1. Fuzzy matrix $F = (f_{ij})_{m \times m}$ is a rectangular array of fuzzy numbers, where fuzzy number can be defined by the proper linguistic scale (For example, high, medium and low) and fall between $[0, 1]$.
2. $F = (f_{ij})_{m \times m}$ denotes the matrix that has m categories, and each i and j represent a different category in the matrix.
3. For fuzzy matrix F , if $f_{ij} + f_{ji} = 1$, then this matrix is defined as fuzzy reciprocal matrix. If $f_{ij} = f_{ik} - f_{jk} + 0.5$ for any $k \in [1, 2, \dots, m]$, then the matrix is fuzzy consistent matrix.
4. If $f_{ij} = 0.5$, then element i and j are equally important. If $0 \leq f_{ij} \leq 0.5$, then element j is more important than i . If $0.5 \leq f_{ij} \leq 1$, then element i is more important than j .
5. The smaller f_{ij} is, the more important element j is than i .
6. The larger f_{ij} is, the more important element i is than j .
7. Fuzzy preference relation matrix is the matrix that shows the preference among factors based on previous three rules.

3.2 Notations

1. In a fuzzy preference relation matrix, j refers to the indexes of row elements, and i refers to the indexes of column elements.
2. Each sum of row in fuzzy preference is defined as $c = \sum_{k=1}^m f_{ik}$ where $i \in [1, 2, \dots, m]$, and c is row vector.
3. There are m factors in total. In this paper, $m = 4$.
4. No.Manager of Month is notated as NoMM.
5. Win Percentage is notated as WP.
6. Title Won is notated as TW.
7. No.Manager of Year is notated as NoMY.

3.3 Algorithms

Based on literature mentioned earlier, a fuzzy preference relation matrix and fuzzy consistent matrix should be calculated in order to find the weight matrix of each factors. Lucheng, Xin and Wenguang (2010), Chan, Chan and Tang, (2000) developed algorithms to calculate these matrices. They pointed out that fuzzy consistent matrix and fuzzy set theory are introduced to deal with the vagueness of human thought.

1. Each entity of fuzzy consistent matrix is defined as $r_{i,j} = \frac{c_i - c_j}{2m} + 0.5$, where r is a $m \times m$ square matrix.
2. Each entity of fuzzy consistent matrix should be normalized as $s_{i,j} = \frac{r_{i,j}}{d_j}$, where d is the sum of each row of r . At this stage, d is a row vector and s is a $m \times m$ matrix.
3. The weight of factors is defined as $w = \frac{k_i}{\sum_{i=1}^m k}$, where k is the product of each element in each row of s . At this stage, k is a row vector and w is a $m \times m$ matrix.
4. *weight* is a row vector that contains the diagonal elements of w . Each element of *weight* is the weight of corresponding factor.

4 Algorithms Implementations

4.1 Fuzzy Preference Relation Matrix

In order to transform vague human thought into relative precise estimators, Chan recommended to convert these linguistic terms to fuzzy numbers. Therefore, a fuzzy multi-criteria decision-making is considered as the best solution to convert human thought into estimators and related weights in the evaluating model.

Chan also points out several steps to build up a fuzzy preference relation matrix, which is the matrix consists of preferences of each factor. Factors that are selected in previous section should be rated respectively by a set of linguistic scale. By looking at official Premier League data, only 4 manager won the Manager of Year without winning a title of that season, which means **Title Won** is highly related to the Manager of Year, so I set **No.Manager of Year** to medium. Moreover, the higher win percentage will lead to more points, therefore there would be higher possibility to win the title. Thus I set **Win Percentage** as high. **No.Manager of Month** is another important factor to evaluate managers' performance. The better managers will win more Manager of Month, so I set it to medium. The most important factor is **No.Title Won** since the better manager will win more titles in his career. In this case, each factor has its own scale as shown following:

Table 1: Scale Selection

Variable Name	Linguistic Scale
No. Title Won	Very Important
Win Percentage	High
No. Manager of Month	Medium
No. Manager of Year	low

Therefore, we can get fuzzy preference relation matrix as following:

Table 2: Fuzzy Preference Relation Matrix

	NoMM	WP	TW	NoMY
NoMM	0.5	0	0	1
WP	1	0.5	0	1
TW	1	1	0.5	1
NoMY	0	0	0	0.5

4.2 Fuzzy Consistent Matrix

Based on the calculation above, the fuzzy consistent matrix can be defined as following:

```
> fr = matrix(c(0.5, 0, 0, 1, 1, 0.5, 0, 1, 1, 1, 0.5, 1, 0, 0, 0, 0.5),
+             nrow = 4, ncol = 4, byrow = TRUE)
> rownames(fr) = c('NoMM', 'WP', 'TW', 'NoMY')
> colnames(fr) = c('NoMM', 'WP', 'TW', 'NoMY')
> c = rowSums(fr)
> r = matrix(0, 4, 4)
> m = 4
> for (i in 1:4) {
+   for (j in 1:4) {
+     r[i, j] = (c[i] - c[j]) / (2 * m) + 0.5
+   }
+ }
> rownames(r) = c('NoMM', 'WP', 'TW', 'NoMY')
> colnames(r) = c('NoMM', 'WP', 'TW', 'NoMY')
> print(r)
```

	NoMM	WP	TW	NoMY
NoMM	0.500	0.375	0.250	0.625
WP	0.625	0.500	0.375	0.750
TW	0.750	0.625	0.500	0.875
NoMY	0.375	0.250	0.125	0.500

4.3 Weight Matrix

Chan also points out that a normalization for fuzzy consistent matrix is needed in order to determine the weight. A weight matrix of each factor is defined as following:

```
> d = rowSums(r)
> s = matrix(0, 4, 4)
```



```

> for (i in 1:4) {
+   for (j in 1:4) {
+     s[i ,j] = r[i ,j]/(d[j])
+   }
+ }
> colnames(s) = c('NoMM', 'WP', 'TW', 'NoMY')
> rownames(s) = c('NoMM', 'WP', 'TW', 'NoMY')
> k = apply(s, 1, prod) ** (1/4)
> w = matrix(0, 4, 4)
> for (i in 1:4) {
+   w[i, ] = k[i]/sum(k)
+ }
> colnames(w) = c('NoMM', 'WP', 'TW', 'NoMY')
> rownames(w) = c('NoMM', 'WP', 'TW', 'NoMY')
> weight = c(0, 0, 0, 0)
> for (i in 1:4) {
+   weight[i] = w[i, i]
+ }
> print(weight)

[1] 0.2168543 0.2853963 0.3527301 0.1450192

```

So after calculation, the weight of No.Manager of Month, Win Percentage, Title Won and No.Manager of Year is 0.2168543, 0.2853963, 0.3527301 and 0.1450192 respectively.

5 Data Analysis

In this section, the factor weight which is calculated in previous section will be applied to official Premier League data in order to determine who is the best manager.

5.1 Pilot Analysis

At the very beginning of data analysis, I decide to analysis on all data in order to find some improvements.

```
> score = rep(0, nrow(df3))
> score = as.vector(score)
> for (i in 1:179) {
+   score[i] = df3[i, 6] * weight[1] + df3[i, 4] * weight[2]
+   + df3[i, 8] * weight[3] + df3[i, 7] * weight[4]
+ }
> df3['SCORE'] = score * 100 ## make it easier to compare.
> result = df3[with(df3, order(-SCORE)),]
> head(result)
```

	ID	MANAGER.x	MATCHES	WIN	PRESENT	NoMM	NoMY	TW	SCORE
1	1	Pat Rice	3	100	0	0	0	0	2853.963
2	2	Jim Barron	1	100	0	0	0	0	2853.963
3	3	Eddie Newton	1	100	0	0	0	0	2853.963
6	6	Alex Ferguson	810	65	0	27	11	13	2440.583
11	11	Arsène Wenger	743	58	1	15	3	3	1980.580
5	5	José Mourinho	212	66	0	3	3	3	1948.672

The result above shows that Pat Rice is the best Premier League Manager in all time. However, the first three managers only coached very short time, which means there should be an improvement of data selection, thus the restrictions of candidates should be applied. In this case, the matches that candidates coached should be at least one season, that is, matches should be greater or equal to 38.

5.2 The Best Manager Who Coached At Least One Season in All Time

This time, applicable candidates should manage the team at least one season.

```

> df4 = subset(df3, MATCHES >= 38)
> score1 = rep(0, nrow(df3))
> score1 = as.vector(score)
> for (i in 1:114) {
+   score1[i] = df4[i, 6] * weight[1] + df4[i, 4] * weight[2]
+   + df4[i, 8] * weight[3] + df4[i, 7] * weight[4]
+ }
> df3['SCORE'] = score1 * 100
> result1 = df4[with(df4, order(-SCORE)),]
> head(result1)

```

	ID	MANAGER.x	MATCHES	WIN	PRESENT	NoMM	NoMY	TW	SCORE
6	6	Alex Ferguson	810	65	0	27	11	13	2440.583
11	11	Arsène Wenger	743	58	1	15	3	3	1980.580
5	5	José Mourinho	212	66	0	3	3	3	1948.672
8	8	Manuel Pellegrini	105	63	1	4	0	1	1884.739
9	9	Carlo Ancelotti	76	63	0	4	0	1	1884.739
10	10	Roberto Mancini	133	62	0	2	0	1	1812.828

In this refined result, Sir. Alex Ferguson is the best Premier League manager in all time. However, in this result, only Arsène Wenger and Manuel Pellegrini are still the managers of Premier League team.

5.3 The Best Current Premier League Manager

```

> df5 = subset(df3, PRESENT == 1)
> score2 = rep(0, nrow(df5))
> score2 = as.vector(score2)
> for (i in 1:20) {
+   score2[i] = df5[i, 6] * weight[1] + df5[i, 4] * weight[2]
+   + df5[i, 8] * weight[3] + df5[i, 7] * weight[4]

```

```

+ }
> df5['SCORE'] = score2 * 100
> result2 = df5[with(df5, order(-SCORE)),]
> head(result2)

```

	ID	MANAGER.x	MATCHES	WIN	PRESENT	NoMM	NoMY	TW	SCORE
11	11	Arsène Wenger	743	58	1	15	3	3	1980.580
8	8	Manuel Pellegrini	105	63	1	4	0	1	1884.739
7	7	Guus Hiddink	25	64	1	0	0	0	1826.536
13	13	Rafael Benitez	255	55	1	6	0	0	1699.792
14	14	Claudio Ranieri	176	53	1	3	0	0	1577.657
18	18	Louis Van Gaal	67	49	1	0	0	0	1398.442

The result above shows that the rank of current Premier League managers. As the manager who lead Arsenal for 20 years, Arsène Wenger is no doubly the best current manager in Premier League. Moreover, in this result, most of managers managed the team more than three seasons.

5.4 The Best Premier League Manager Who Managed At Most Three Seasons

This time, applicable candidates should managed at least half season and at most three seasons, which means, matches should be greater or equal to 19, and less or equal to 114.

```

> df6 = subset(df3, MATCHES >= 19 & MATCHES <= 114)
> score3 = rep(0, nrow(df6))
> score3 = as.vector(score3)
> for (i in 1:89) {
+   score3[i] = df6[i, 6] * weight[1] + df6[i, 4] * weight[2]
+   + df6[i, 8] * weight[3] + df6[i, 7] * weight[4]
+ }

```

```

> df6['SCORE'] = score3 * 100
> result3 = df6[with(df6, order(-SCORE)),]
> head(result3)

```

	ID	MANAGER.x	MATCHES	WIN	PRESENT	NoMM	NoMY	TW	SCORE
8	8	Manuel Pellegrini	105	63	1	4	0	1	1884.739
9	9	Carlo Ancelotti	76	63	0	4	0	1	1884.739
7	7	Guus Hiddink	25	64	1	0	0	0	1826.536
12	12	Felipe Scolari	25	56	0	0	0	0	1598.219
15	15	Andre Villas-Boas	81	52	0	2	0	0	1527.432
18	18	Louis Van Gaal	67	49	1	0	0	0	1398.442

For the managers who managed at most three seasons, Both Manuel Pellegrini and Carlo Ancelotti rank first. Both of them share the same winning percentage. Moreover, Manuel Pellegrini is the best manager who managed at most three seasons.

6 Summary

Based on the results in previous sections, statistics and score show that Sir. Alex Ferguson is the best manager of Premier League in all time. Arsène Wenger is the best current manager of Premier League. Moreover, for the managers who managed less than three seasons, both Manuel Pellegrini and Carlo Ancelotti rank the first. In addition, Manuel Pellegrini is the best current Premier League manager who managed less than three seasons.

References

- Barzilai, J. (1998). Consistency measures for pairwise comparison matrices. *Journal of Multi-Criteria Decision Analysis*, 7(3), 123–132.
- Cassidy, T., Potrac, P., & McKenzie, A. (2006). Evaluating and reflecting upon a coach education initiative: The code¹ of rugby. *Sport Psychologist*, 20(2), 145.
- Chan, F., Chan, M., & Tang, N. (2000). Evaluation methodologies for technology selection. *Journal of Materials Processing Technology*, 107(1), 330–337.
- Ismail, H. N., & Morsi, N. N. (1991). Fuzzy rank of a fuzzy matrix. *Fuzzy sets and systems*, 41(2), 243–249.
- Kandasamy, W. V., Smarandache, F., & Ilanthenral, K. (2007). *Elementary fuzzy matrix theory and fuzzy models for social scientists*. Infinite Study.
- Lucheng, H., Xin, L., & Wenguang, L. (2010). Research on emerging technology selection and assessment by technology foresight and fuzzy consistent matrix. *Foresight*, 12(2), 77–89.
- Rushall, B., & Wiznuk, K. (1985). Athletes' assessment of the coach—the coach evaluation questionnaire. *Canadian journal of applied sport sciences. Journal canadien des sciences appliquees au sport*, 10(3), 157–161.
- Wang, T.-C., & Chen, Y.-H. (2005). A new method on decision-making using fuzzy linguistic assessment variables and fuzzy preference relations. In *The 9th world multi-conference on systemics, cybernetics and informatics (wmsci 2005)*.