ARDUINO

ARDUINO DUE

STORE.ARDUINO.CC/DUE



- Ground
- Power
- LED
- Internal Pin
- SWD Pin
- Digital Pin
- Analog Pin
- Other Pin
- Microcontroller's Port
- Default

⚠ **TOTAL DC OUTPUT** current per I/O lines is 130mA

VIN 6-20 V input to the board.

The ADC's channel 15 is not available because connected to the ATSAM3X8E temperature sensor

To check the maximum currents applicable per pins please see the datasheet at STORE.ARDUINO.CC/ARDUINO-DUE

ARDUINO.CC

Last update: 4/09/2020

This work is licensed under the Creative Commons Attribution-ShareAlike 4.0 International License. To view a copy of this license, visit http://creativecommons.org/licenses/by-sa/4.0/ or send a letter to Creative Commons, PO Box 1866, Mountain View, CA 94042, USA.

ARDUINO

ARDUINO DUE

STORE.ARDUINO.CC/DUE



- Ground
- Power
- LED
- Internal Pin
- SWD Pin
- Digital Pin
- Analog Pin
- Other Pin
- Microcontroller's Port
- Default
- Analog
- Communication
- Timer
- Interrupt
- Memory

TOTAL DC OUTPUT current per I/O lines is 130mA

VIN 6-20 V input to the board

The ADC's channel 15 is not available because connected to the ATSAM3X8E temperature sensor

To check the maximum currents applicable per pins please see the datasheet at STORE.ARDUINO.CC/ARDUINO-DUE

ARDUINO.CC

Last update: 4/09/2020

This work is licensed under the Creative Commons Attribution-ShareAlike 4.0 International License. To view a copy of this license, visit http://creativecommons.org/licenses/by-sa/4.0/ or send a letter to Creative Commons, PO Box 1866, Mountain View, CA 94042, USA.

ARDUINO

ARDUINO DUE

STORE.ARDUINO.CC/DUE



Ground
Power
LED
Internal Pin
SWD Pin

Digital Pin
Analog Pin
Other Pin
Microcontroller's Port
Default

Analog
Communication
Timer
Interrupt
Memory

TOTAL DC OUTPUT current per I/O lines is 130mA

VIN 6-20 V input to the board

The ADC's channel 15 is not available because connected to the ATSAM3X8E temperature sensor

To check the maximum currents applicable per pins please see the datasheet at STORE.ARDUINO.CC/ARDUINO-DUE

ARDUINO.CC

Last update: 4/09/2020

This work is licensed under the Creative Commons Attribution-ShareAlike 4.0 International License. To view a copy of this license, visit http://creativecommons.org/licenses/by-sa/4.0/ or send a letter to Creative Commons, PO Box 1866, Mountain View, CA 94042, USA.

ARDUINO



Digital pins D22-D53

ARDUINO DUE

STORE.ARDUINO.CC/DUE



- Ground
- Power
- LED
- Internal Pin
- SWD Pin
- Digital Pin
- Analog Pin
- Other Pin
- Microcontroller's Port
- Default
- Analog
- Communication
- Timer
- Interrupt
- Memory

⚠ **TOTAL DC OUTPUT** current per I/O lines is 130mA

VIN 6-20 V input to the board

The ADC's channel 15 is not available because connected to the ATSAM3X8E temperature sensor

To check the maximum currents applicable per pins please see the datasheet at STORE.ARDUINO.CC/ARDUINO-DUE

ARDUINO.CC

Last update: 4/09/2020

This work is licensed under the Creative Commons Attribution-ShareAlike 4.0 International License. To view a copy of this license, visit http://creativecommons.org/licenses/by-sa/4.0/ or send a letter to Creative Commons, PO Box 1866, Mountain View, CA 94042, USA.

Digital pins D22-D53



- Ground
- Power
- LED
- Internal Pin
- SWD Pin
- Digital Pin
- Analog Pin
- Other Pin
- Microcontroller's Port
- Default
- Analog
- Communication
- Timer
- Interrupt
- Memory

TOTAL DC OUTPUT current per I/O lines is 130mA

VIN 6-20 V input to the board

The ADC's channel 15 is not available because connected to the ATSAM3X8E temperature sensor

To check the maximum currents applicable per pins please see the datasheet at STORE.ARDUINO.CC/ARDUINO-DUE

This work is licensed under the Creative Commons Attribution-ShareAlike 4.0 International License. To view a copy of this license, visit http://creativecommons.org/licenses/by-sa/4.0/ or send a letter to Creative Commons, PO Box 1866, Mountain View, CA 94042, USA.

ARDUINO

ARDUINO DUE

STORE.ARDUINO.CC/DUE



- Ground
- Power
- LED
- Internal Pin
- SWD Pin
- Digital Pin
- Analog Pin
- Other Pin
- Microcontroller's Port
- Default
- Analog
- Communication
- Timer
- Interrupt
- Memory

TOTAL DC OUTPUT current per I/O lines is 130mA

VIN 6-20 V input to the board

The ADC's channel 15 is not available because connected to the ATSAM3X8E temperature sensor

To check the maximum currents applicable per pins please see the datasheet at STORE.ARDUINO.CC/ARDUINO-DUE

ARDUINO.CC

Last update: 4/09/2020

This work is licensed under the Creative Commons Attribution-ShareAlike 4.0 International License. To view a copy of this license, visit http://creativecommons.org/licenses/by-sa/4.0/ or send a letter to Creative Commons, PO Box 1866, Mountain View, CA 94042, USA.

ARDUINO DUE

STORE.ARDUINO.CC/DUE



- Ground
- Power
- LED
- Internal Pin
- SWD Pin
- Digital Pin
- Analog Pin
- Other Pin
- Microcontroller's Port
- Default

TOTAL DC OUTPUT current per I/O lines is 130mA

VIN 6-20 V input to the board.

The ADC's channel 15 is not available because connected to the ATSAM3X8E temperature sensor

To check the maximum currents applicable per pins please see the datasheet at STORE.ARDUINO.CC/ARDUINO-DUE

ARDUINO.CC

Last update: 4/09/2020

This work is licensed under the Creative Commons Attribution-ShareAlike 4.0 International License. To view a copy of this license, visit http://creativecommons.org/licenses/by-sa/4.0/ or send a letter to Creative Commons, PO Box 1866, Mountain View, CA 94042, USA.