

CCS6224

Network Security


Lecture 4
Securing the Local Area Network

π


Outline

- › Introduction to Endpoint Security
 - Host-Based protection
- › Layer 2 Security Threats
 - CAM Table Attack & Mitigation
 - VLAN Attack & Mitigation
 - DHCP Attack & Mitigation
 - ARP Attack & Mitigation
 - Address Spoofing Attack & Mitigation
 - STP Attack & Mitigation

Securing LAN Elements



Endpoint Security



Securing Endpoints in the Borderless Network


Post malware attack questions:

- Where did it come from?
- What was the threat method and point of entry?
- What systems were affected?
- What did the threat do?
- Can I stop the threat and root cause?
- How do we recover from it?
- How do we prevent it from happening again?

Host-Based Protection:

- Antivirus/Antimalware
- SPAM Filtering
- URL Filtering
- Blacklisting
- Data Loss Prevention (DLP)

Antimalware Protection



Spam Filtering



URL Filtering

Add Rule ? x

Name: ☒ Enabled Insert: into Mandatory

Action:

Time Range:

Zones Networks VLAN Tags Users Applications Ports **URLs** SGT/ISE Attributes Inspection Logging Comments

Categories and URLs

Search for a URL

Category: **URLs**

- Custom-URL-object-Example
- Custom-SI-object-URL-List
- URL Attackers
- URL Banking_fraud
- URL Bogon
- URL Bots
- URL CnC
- URL Cryptomining
- URL Dga


Selected URLs (0)

any

Blacklisting



Data Loss Prevention (DLP)




The screenshot displays the 'List of Devices' window in the Endpoint Protector application. The window features a sidebar with navigation options like Dashboard, Device Control, and eDiscovery. The main area contains a table with columns for Device Name, Device Type, Description, VID, PID, Serial Number, Device Code, Last User, Last Computer, and Last Seen. The table lists various devices, including USB storage devices and HP LaserJet printers, with their respective details and last seen timestamps.

Device Name	Device Type	Description	VID	PID	Serial Number	Device Code	Last User	Last Computer	Last Seen
USB Storage Device	USB Storage Device	100%	120x	5800	6708A7AEC702705	30AB			2016-08-08 11:57:21
_SUVH00327120G	USB Storage Device	_SUVH00327120G-KINGSTON	4853	708	1234567890123	C841			2016-08-08 14:28:01
HP LaserJet 200 color MFP M276 PCL 6	Local Printers	HP LaserJet 200 color MFP M276 PCL 6/HP	0	0	PSN_1C402AF013FA2-47C3-WFDC-62C8AF020A	FC28			2017-08-03 12:00:00
HP LaserJet 200 color MFP M276 PCL 6	Local Printers	HP LaserJet 200 color MFP M276 PCL 6/HP	0	0	PSN_10F383037-A2D3-4844-81C9-191C3A838303	1A71			2016-05-18 14:38:01
UTSWHP LaserJet 200 color MT	Local Printers	UTSWHP LaserJet 200 color MT	0	0	UTSWHP LaserJet 200 color MT	1913			2017-08-18 16:10:01
ViewHP LaserJet 200 color MFP M276 PCL 6	Local Printers	ViewHP LaserJet 200 color MFP M276 PCL 6/HP	0	0	PSN_1F5DA8B0C-15A4-4D2C-8345-DB43239119A5	5E48			2017-10-08 10:03:12
ViewHP LaserJet 200 color MFP M276 PCL 6	Local Printers	ViewHP LaserJet 200 color MFP M276 PCL 6/HP	0	0	PSN_1F5DA8B0C-15A4-4D2C-8345-DB43239119A5	5E48			2017-10-08 10:03:12
ViewHP LaserJet 200 color MFP M276 PCL 6	Local Printers	ViewHP LaserJet 200 color MFP M276 PCL 6/HP	0	0	PSN_14E10223-587A-4276-B40D-D66B7D4AC375	AB87			2017-08-08 17:08:02
ViewHP LaserJet 200 color MFP M276 PCL 6	Local Printers	ViewHP LaserJet 200 color MFP M276 PCL 6/HP	0	0	ViewHP LaserJet 200 color MFP M276 PCL 6	F8F1			2017-08-18 11:22:01
0006H0_DEVICE_SYSTEM_KEYBOARD\H0_DEVICE_UP	USB Storage Device	0006H0_DEVICE_SYSTEM_KEYBOARD\H0_DEVICE_UP\0001_U	45x	792	HID_VID_540EAPID_0170A9E1_01B8M_000H0_VID_44BCEDID_0170A9E1_00H0_VID_44BCEDID	A21C			2016-04-18 21:34:11


DLP provides services and protections:

- Detailed logging and forensic evidence gathering
- User/Administrator notification
- Real time prevention and blocking
- Quarantine of confidential data


Cisco Network Access Control




Cisco NAC Functions



Cisco NAC Components



Layer 2 Security Threats



Switch Attack Categories




CAM Table Attack


Basic Switch Operation

```
S1# show mac-address-table
      Mac Address Table
-----
Vlan    Mac Address      Type    Ports
----    -
1       0001.9717.22e0    DYNAMIC Fa0/4
1       000a.f38e.74b3    DYNAMIC Fa0/1
1       0090.0c23.ceca    DYNAMIC Fa0/3
1       00d0.ba07.8499    DYNAMIC Fa0/2
Sw1#
```



CAM Table Operation Example



CAM Table Attack




Intruder Runs Attack Tool




Fill CAM Table

CAM Table Attack



Switch Floods All Traffic

Attacker Captures Traffic



CAM Table Attack Tools


```
macof -i eth1
36:a1:48:63:81:70 15:26:8d:4d:28:f8 0.0.0.0.26413 > 0.0.0.0.49492: S 1094191437:1094191437(0) win 512
16:e8:8:0:4d:9c da:4d:bc:7c:ef:be 0.0.0.0.61376 > 0.0.0.0.47523: S 446486755:446486755(0) win 512
18:2a:de:56:38:71 33:af:9b:5:a6:97 0.0.0.0.20086 > 0.0.0.0.6728: S 105051945:105051945(0) win 512
e7:5c:97:42:ec:1 83:73:1a:32:20:93 0.0.0.0.45282 > 0.0.0.0.24898: S 1838062028:1838062028(0) win 512
62:69:d3:1c:79:ef 80:13:35:4:cb:d0 0.0.0.0.11587 > 0.0.0.0.7723: S 1792413296:1792413296(0) win 512
c5:a:b7:3e:3c:7a 3a:ee:c0:23:4a:fe 0.0.0.0.19784 > 0.0.0.0.57433: S 1018924173:1018924173(0) win 512
88:43:ee:51:c7:68 b4:8d:ec:3e:14:bb 0.0.0.0.283 > 0.0.0.0.11466: S 727776406:727776406(0) win 512
b8:7a:7a:2d:2c:ae c2:fa:2d:7d:e7:bf 0.0.0.0.32650 > 0.0.0.0.11324: S 605528173:605528173(0) win 512
e0:d8:1e:74:1:e 57:98:b6:5a:fa:de 0.0.0.0.36346 > 0.0.0.0.55700: S 2128143986:2128143986(0) win 512
```

Topic 6.2.3: Mitigating CAM Table Attacks



Mitigating CAM Table Attacks

Countermeasure for CAM Table Attacks



Port Security

```
S1(config)# interface f0/1
S1(config-if)# switchport port-security
Command rejected: FastEthernet0/1 is a dynamic port.
S1(config-if)# switchport mode access
S1(config-if)# switchport port-security
S1(config-if)# end
S1#
```

Enabling Port Security

Verifying Port Security

```
S1# show port-security interface f0/1
Port Security           : Enabled
Port Status             : Secure-shutdown
Violation Mode          : Shutdown
Aging Time              : 0 mins
Aging Type              : Absolute
SecureStatic Address Aging : Disabled
Maximum MAC Addresses   : 1
Total MAC Addresses     : 0
Configured MAC Addresses : 0
Sticky MAC Addresses    : 0
Last Source Address:Vlan : 0000.0000.0000:0
Security Violation Count : 0
S1#
```

Port Security Options

```
S1(config)# interface f0/1
S1(config-if)# switchport port-security ?
aging      Port-security aging commands
mac-address Secure mac address
maximum    Max secure addresses
violation  Security violation mode
<cr>

S1(config-if)# switchport port-security
```

Enabling Port Security Options

Setting the Maximum Number of Mac Addresses

```
Switch(config-if)
```

```
switchport port-security maximum value
```

Manually Configuring Mac Addresses

```
Switch(config-if)
```

```
switchport port-security mac-address mac-address {vlan | {access | voice}}
```

Learning Connected Mac Addresses Dynamically

```
Switch(config-if)
```

```
switchport port-security mac-address sticky
```


Port Security Violations

Security Violation Modes:

- Protect
- Restrict
- Shutdown

Security Violation Modes

Violation Mode	Forwards Traffic	Sends Syslog Message	Increases Violation Counter	Shuts Down Port
Protect	No	No	No	No
Restrict	No	Yes	Yes	No
Shutdown	No	Yes	Yes	Yes

Port Security Aging

Switch(config-if)

```
switchport port-security aging {static | time time| type {absolute | inactivity}}
```


Parameter	Description
static	<ul style="list-style-type: none">• Enable aging for statically configured secure addresses on this port.
time time	<ul style="list-style-type: none">• Specify the aging time for this port.• The range is 0 to 1440 minutes.• If the time is 0, aging is disabled for this port.
type absolute	<ul style="list-style-type: none">• Set the absolute aging time. All the secure addresses on this port age out exactly after the time (in minutes) specified and are removed from the secure address list.
type inactivity	<ul style="list-style-type: none">• Set the inactivity aging type. The secure addresses on this port age out only if there is no data traffic from the secure source address for the specified time period.

Port Security with IP Phones




```
S1(config)# interface f0/1
S1(config-if)# switchport mode access
S1(config-if)# switchport port-security
S1(config-if)# switchport port-security maximum 3
S1(config-if)# switchport port-security violation shutdown
S1(config-if)# switchport port-security aging time 120
S1(config-if)#
```

SNMP MAC Address Notification




VLAN Hopping Attacks




VLAN Hopping Attacks

- Trunk ports have access to all VLANs by default
- Used to route traffic for multiple VLANs across the same physical link (generally between switches)
- Encapsulation can be 802.1q or ISL
- An end station can spoof as a switch with ISL or 802.1q
- The station is then a member of all VLANs

VLAN Double-Tagging Attack




Step 1 – Double Tagging Attack




Step 2 – Double Tagging Attack

Step 3 – Double Tagging Attack




Mitigating VLAN Hopping Attacks




- A double-tagging VLAN hopping attack is unidirectional, works only if the attacker and the trunk port are in the same native VLAN
- To mitigate the hopping attack, the best way is to make sure the native VLAN of the trunk port(s) is different than any users' ports
- Do not use VLAN1 for anything

DHCP Function



- Server dynamically assigns IP address on demand
- Administrator creates pools of addresses available for assignment
- Address is assigned with lease time
- DHCP delivers other configuration information in options

DHCP Starvation Attack




- › Gobbler/DHCPx looks at the entire DHCP scope and tries to lease all of the DHCP addresses available in the DHCP scope
- › This is a Denial of Service (DoS) attack using DHCP leases

Mitigating DHCP Starvation Attack

- › Gobbler uses a new MAC address to request a new DHCP lease
- › Restrict the number of MAC addresses on a port
- › Will not be able to lease more IP address then MAC addresses allowed on the port
- › In the example the attacker would get one IP address from the DHCP server

```
Cisco IOS
switchport port-security
switchport port-security maximum 1
switchport port-security violation restrict
switchport port-security aging time 2
switchport port-security aging type inactivity
```

Rogue DHCP Server Attack



What can the attacker do if he is the DHCP server?


IP Address: 10.10.10.101
Subnet Mask: 255.255.255.0
Default Routers: 10.10.10.1
DNS Servers: 192.168.10.4, 192.168.10.5
Lease Time: 10 days

Here Is Your Configuration

- What do you see as a potential problem with incorrect information?
 - Wrong default gateway—Attacker is the gateway
 - Wrong DNS server—Attacker is DNS server
 - Wrong IP address—Attacker does DOS with incorrect IP

Mitigating Rogue DHCP Server Attack

Configuring DHCP Snooping



Configuring DHCP Snooping Example

DHCP Snooping Reference Topology



Configuring a Maximum Number of MAC Addresses

```
S1(config)# ip dhcp snooping
S1(config)#
S1(config)# interface f0/1
S1(config-if)# ip dhcp snooping trust
S1(config-if)# exit
S1(config)#
S1(config)# interface range f0/5 - 24
S1(config-if-range)# ip dhcp snooping limit rate 6
S1(config-if-range)# exit
S1(config)#
S1(config)# ip dhcp snooping vlan 5,10,50-52
S1(config)#
```

Configuring DHCP Snooping Example

Verifying DHCP Snooping

```
S1# show ip dhcp snooping
Switch DHCP snooping is enabled
DHCP snooping is configured on following VLANs:
5,10,50-52
DHCP snooping is operational on following VLANs:
none
DHCP snooping is configured on the following L3 Interfaces:

Insertion of option 82 is enabled
  circuit-id default format: vlan-mod-port
  remote-id: 0cd9.96d2.3f80 (MAC)
Option 82 on untrusted port is not allowed
Verification of hwaddr field is enabled
Verification of giaddr field is enabled
DHCP snooping trust/rate is configured on the following Interfaces:


Interface                Trusted    Allow option    Rate limit (pps)
-----
FastEthernet0/1          yes       yes             unlimited
  Custom circuit-ids:
FastEthernet0/5          no        no              6
  Custom circuit-ids:
FastEthernet0/6          no        no              6
  Custom circuit-ids:
<output omitted>
```

View the DHCP snooping database


```
S1# show ip dhcp snooping binding
MacAddress      IpAddress      Lease(sec)  Type           VLAN  Interface
-----
00:03:47:B5:9F:AD 192.168.10.10 193185     dhcp-snooping 5     FastEthernet0/5
```

ARP Function

- › Before a station can talk to another one
 - it must do an ARP request to map the IP address to the MAC address
 - This ARP request is broadcast
 - All computers on the subnet will receive and process the ARP request
 - the station that matches the IP address in the request will send an ARP reply



ARP Spoofing and ARP Poisoning Attack



Mitigating ARP Attacks


Configuring Dynamic ARP Inspection

- › Uses the DHCP snooping binding table information
- › Check the mac address and IP address fields to see
 - if the ARP from the interface is in the binding
 - if not, traffic is blocked

sh ip dhcp snooping binding					
MacAddress	IpAddress	Lease(sec)	Type	VLAN	Interface
00:03:47:B5:9F:AD	10.120.4.10	193185	dhcp-snooping	4	FastEthernet3/18

π

Configuring DHCP Snooping Example



Configuring Dynamic
ARP Inspection

```
S1(config)# ip dhcp snooping
S1(config)#
S1(config)# ip dhcp snooping vlan 10
S1(config)# ip arp inspection vlan 10
S1(config)#
S1(config)# interface fa0/24
S1(config-if)# ip dhcp snooping trust
S1(config-if)# ip arp inspection trust
S1(config-if)#
```



Configuring DHCP Snooping Example

Checking Source, Destination, and IP

```
S1(config)# ip arp inspection validate ?
dst-mac  Validate destination MAC address
ip       Validate IP addresses
src-mac  Validate source MAC address

S1(config)# ip arp inspection validate src-mac
S1(config)# ip arp inspection validate dst-mac
S1(config)# ip arp inspection validate ip
S1(config)#
S1(config)# do show run | include validate
ip arp inspection validate ip
S1(config)#
S1(config)# ip arp inspection validate src-mac dst-mac ip
S1(config)#
S1(config)# do show run | include validate
ip arp inspection validate src-mac dst-mac ip
S1(config)#
```


Address Spoofing Attack



- › Attacker sends packets with the incorrect source MAC address
- › If network control is by MAC address, the attacker now looks like the Server

Mitigating Address Spoofing Attack

Configuring IP Source Guard



IP Source Guard Reference Topology

Configuring IP Source Guard

```
S1(config)# interface range fastethernet 0/1 - 2
S1(config-if-range)# ip verify source
S1(config-if-range)# end
S1#
```

Checking IP Source Guard

```
S1# show ip verify source
```

Interface	Filter-type	Filter-mode	IP-address	Mac-address	Vlan
F0/1	ip	active	192.168.10.10		10
F0/2	ip	active	192.168.10.11		10


```
S1#
```

- › We can use the DHCP snooping binding table information

`ip verify source dhcp-snooping-vlan`


- › Operates just like dynamic ARP inspection, but it looks at every packet, not just ARP packet

STP Basics




- › STP is used to maintain loop-free topologies in a redundant layer 2 architecture
- › 4-key steps involved
 1. Elect root bridge
 2. Elect root port
 3. Elect designated port
 4. Block all remaining ports

STP Manipulation Attacks




Spoofing the Root Bridge


Successful STP Manipulation Attack




Mitigating STP Attacks



Configuring PortFast




Configuring BPDU Guard



π

Configuring Root Guard



Configuring Loop Guard

