

## 實現拖曳功能



### 1. 需要拖曳控件, 設定在長按時開始拖曳

```
dragView.setOnLongClickListener {  
    val dragData = ClipData.newPlainText("drag_data", "data")  
  
    // 拖動時的陰影  
    val dragShadowBuilder = View.DragShadowBuilder(it)  
  
    // 開始拖放  
    it.startDragAndDrop(dragData, dragShadowBuilder, it, 0)  
    it.visibility = View.INVISIBLE  
  
    true  
}
```



## 2.對要拖曳到的地方設定 onDragListener 監聽器

```
destinationFrameLayout.setOnDragListener { view, dragEvent ->
    when(dragEvent.action) {
        DragEvent.ACTION_DRAG_STARTED -> {
            // 當拖曳進入目標時的處理
            true
        }
        DragEvent.ACTION_DRAG_EXITED -> {
            // 當拖曳離開目標時的處理
            true
        }
        DragEvent.ACTION_DROP -> {
            // 當放下時的處理

            // 得到當時正在拖放的 View
            val v = dragEvent.localState as View

            // 將正在拖曳的 View 添加到目的地
            val destination = view as FrameLayout
            val myView = myView(this)

            // 得到拖曳結束時 x, y 座標
            myView.x = dragEvent.x
            myView.y = dragEvent.y

            destination.addView(myView)

            v.visibility = View.VISIBLE
            true
        }
        DragEvent.ACTION_DRAG_ENDED -> {
            // 拖曳結束
            true
        }
        else -> false
    }
}
```