

播放音頻



1.加入音頻

在 res -> New Directory 命名為 raw -> 把音頻加入 raw 中

2.創建 MediaPlayer 對象

```
private lateinit var mediaPlayer: MediaPlayer

override fun onCreate(savedInstanceState: Bundle?) {

    mediaPlayer = MediaPlayer.create(this, R.raw.htmlthesong)
    mediaPlayer.isLooping = true
}
```

3.開始播放音頻

```
mediaPlayer.start()
```

// start() 開始播放

4.在 app 結束時停止播放

```
override fun onPause() {
    mediaPlayer.pause()
    super.onPause()
}
```

```
override fun onStop() {
    mediaPlayer.stop()
    super.onStop()
}
```

```
override fun onDestroy() {
    mediaPlayer.release()
    super.onDestroy()
}
```

```
// 設置為 50% 音量 左右聲道
mediaPlayer?.setVolume(0.5f, 0.5f)
```

```
// 背景音樂
val bgmPlayer = MediaPlayer.create(this, R.raw.bgm)
bgmPlayer.isLooping = true
bgmPlayer.start()

button.setOnClickListener {
    val sfxPlayer = MediaPlayer.create(this, R.raw.click_sound)
    sfxPlayer.start()

    // 缺點: MediaPlayer 結束後必須手動釋放, 否則會佔用記憶體
    sfxPlayer.setOnCompletionListener {
        it.release()
    }
}
```