

Class 3

！ 非運算號

```
val isPass = false
if (!isPass) {
    println("not pass!")
}
```

字符串方法

```
val name = "Dennis"
```

```
name.length           // 6
name.toLowerCase()     //dennis
name.toUpperCase()     //DENNIS
```

```
val str = " Hello, World! "
str.trim()             // "Hello, World!"
```

&& 和 ||

```
val isAgree = false
val name = "Dennis"

if (isAgree && name.length > 5) { }    // false

if (isAgree || name.length > 5) { }    // true
```

數組

```
val pets = arrayOf("dog", "cat", "canary")
```

```
println(pets[0])           // dog
```

```
println(pets.size)        // 3
```

```
val pets = arrayOf("dog", "cat", "canary")
```

```
for (element in pets) {
```

```
    println(element)
```

```
}
```

while 循環

```
var bicycles = 0
```

```
while (bicycles < 50) {
```

```
    bicycles++
```

```
    println(bicycles)
```

```
}
```

break 循環

```
var bicycles = 0
```

```
while (bicycles < 50) {
```

```
    bicycles++
```

```
    println(bicycles)
```

```
    if (bicycles == 25) {
```

```
        break
```

```
    }
```

```
}
```

while 循環數組

```
val pets = arrayOf("dog", "cat", "canary")
```

```
var i = 0;
while(i < pets.size) {
    println(pets[i])
    i++
}
```

隨機數

```
val number = (1..10).random()
```

When

```
val results = 2
val value = when (results) {
    1 -> "One"
    2 -> "Two"
    3 -> "Three"
    else -> "Unknown number"
}
println(value)    // Two
```