The School

כמה מילים על העבודה שלי:

1. בניתי את המערכת כך שלא יהיה ניתן למחוק את ה-owner או לשנות את התפקיד שלו.
2. לגבי סיסמאות, רק owner יוכל לשנות סיסמא לכל סוגי המשתמשים, ומשתמש מסוג manager יוכל לשנות סיסמא רק ל-sales, זה הגיוני יותר לדעתי.

Description	Method +Path	Request/Response		
Login	http://localhost/the-school/back/api/loginA-PI.php GET	**Request:** { user: string password: string } **Response:** {User Id : integer, user Name: string, permission: string, image: string, status: Boolean }		
Logout	http://localhost/the-school/back/api/logoutA-PI.php LOGOUT	**Request:** --- **Response:** string		
Get Student Details by id *Get Course Details by id*	http://localhost/the-school/back/api/api.php GET	**Student** **Request:** { Ctrl: string id: integer } **Response:** { Id: integer Name: string Phone: string email: string image: string }	**Course** **Request:** { Ctrl: string id: integer } **Response:** { Id: integer Name: string Description: string image: string }	
Get all Admins/ *Get all Courses/* *Get all Students/*	http://localhost/the-school/back/api/api.php GET	**Admin** **Request:** { Ctrl: string } **Response:** [{ id: integer name: string Course description: string image: string },{…}]	**Student** **Request:** { Ctrl: string } **Response:** [{ Id: integer Name: string Phone: string email: string image: string },{…}]	**Course** **Request:** { Ctrl: string } **Response:** [{ Id: integer Name: string Phone: string email: string role: string roleid: integer image: string },{…}]
Delete Student/ *Delete Course/* *Delete Admin*	http://localhost/the-school/back/api/api.php DELETE	**Request:** { [ctrl]: String [id]: integer } **Response:** Response: Boolean		

Description	Method +Path	Request/Response		
Update Admin / *Update Student/* *Update Course*	http://localhost/the-school/back/api/loginA-PI.php PUT	**Admin**	**Student**	**Course**

		Request:
		{
		ctrl: String
		id: integer
		name: String
		phone: String
		email: String
		image: String
		password:String
		roleid: integer
		}
		
		Response:
		Boolean
			Request:
			{
			ctrl: String
			id: integer
			name: String
			phone: String
			email: String
			image: String
			courses:[integer]
			}
			
			Response:
			Boolean
				Request:
				{
				ctrl: String
				id: integer
				name: String
				description:
				String
				}
				
				Response:
				Boolean

New Admin / *New Student/* *New Course*	http://localhost/the-school/back/api/api.php POST	**Admin**	**Student**	**Course**

		Request:
		{
		ctrl: String
		name: String
		phone: String
		email: String
		image: String
		password:String
		roleid: integer
		}
		
		Response:
		Boolean
			Request:
			{
			ctrl: String
			name: String
			phone: String
			email: String
			image: String
			courses:[integer]
			}
			
			Response:
			Boolean
				Request:
				{
				ctrl: String
				name: String
				description:
				String
				}
				
				Response:
				Boolean

send Imege *to server before* *crop*	http://localhost/the-school/back/api/fileAPI.php POST	**Request:** form-data{ name: string; filename: string Content-Type: string} **Response:** [resulte-Boolean, file name-string]		
send Imege *to server after* *crop*	http://localhost/the-school/back/api/cropAPI.php POST	**Request:** crop sizes { start x: integer start y: integer width: integer heigth: integer name: image_name} **Response:** Boolean		