

Module-3

- i) Implement a Q-learning algorithm for a simple grid world environment. Explain how the Q-values are updated and analyze the convergence behaviour of your implementation.

Q-learning is a model free reinforcement learning algorithm used to learn the optimal action-value function for an environment. It allows an agent to learn by interacting with the environment and updating Q-values based on rewards received.

Implementation:

```
import numpy as np, random

Q = np.zeros((16, 4))
alpha = 0.1
gamma = 0.9
epsilon = 0.1

def step(s, a):
    r, c = divmod(s, 4)
    if a == 0 and r > 0: r -= 1
    if a == 1 and r < 3: r += 1
    if a == 2 and c > 0: c -= 1
    if a == 3 and c < 3: c += 1
    ns = r * 4 + c
    reward = 1 if ns == 15 else 0
    return ns, reward

for _ in range(500):
    s = 0
    while s != 15:
        a = random.randint(0, 3) if random.random() < epsilon
        else np.argmax(Q[s, :])
```

$ns, r = \text{step}(s, a)$

$Q[s, a] += \alpha * (r + \gamma \max_{a'} Q[ns, a'] - Q[s, a])$

$s = ns$

Q-value update:

Q-values are updated using:

$$Q(s, a) = Q(s, a) + \alpha (r + \gamma \max_{a'} Q(s', a') - Q(s, a))$$

- The term $r + \gamma \max_{a'} Q(s', a')$ is the target value
- α controls how fast learning happens

Convergence behaviour:

- Q-values gradually stabilize after multiple episodes
- The learned policy becomes the shortest path to goal.
- Because the grid world is small and deterministic, Q learning converges to the optimal Q^* .

2)

Develop a deep q-network (DQN) to solve a basic control problem (eg. Cartpole). Discuss how the neural network approximates the Q function & evaluate its performance to standard q-learning.

A DQN uses a neural network to approximate the Q function instead of Q-table, allowing it solve environments with continuous state spaces like Cartpole.

Implementation:

```
import gym, torch, torch.nn as nn, torch.optim as optim
import random, numpy as np
```

```
from collections import deque
```

```
env = gym.make("Cartpole-v1")
```

```
class DQN(nn.Module):
```

```
    def __init__(self):
```

```
        super().__init__()
```

```
self.net = nn.Sequential(nn.Linear(4, 64), nn.ReLU(), nn.Linear(64, 2))
```

```
def forward(self, x):  
    return self.net(x)
```

```
q_net = DQN()
```

```
target_net = DQN()
```

```
target_net.load_state_dict(q_net.state_dict())
```

```
optimizer = optim.Adam(q_net.parameters(), lr=1e-3)
```

```
memory = deque(maxlen=20000)
```

```
gamma = 0.99
```

```
epsilon = 1.0
```

```
def select_action(state):
```

```
    if random.random() < epsilon:
```

```
        return env.action_space.sample()
```

```
    with torch.no_grad():
```

```
        return q_net(torch.FloatTensor(state)).argmax().item()
```

```
for episode in range(200):
```

```
    s = env.reset()
```

```
    done = False
```

```
    while not done:
```

```
        a = select_action(s)
```

```
        s2, r, done, _ = env.step(a)
```

```
        memory.append((s, a, r, s2, done))
```

```
        s = s2
```

```
    if len(memory) > 1000:
```

```
        batch = random.sample(memory, 64)
```

```
        s_b, a_b, r_b, s2_b, d_b = zip(*batch)
```

with torch.no_grad():

target = r_b + gamma * target_net(s2_b).max(1, keepdim=True)[0] + (1 - d_b)

q_values = q_net(s_b).gather(1, a_b)

loss = nn.MSELoss()(q_values, target)

optimizer.zero_grad()

loss.backward()

optimizer.step()

if episode % 10 == 0:

target_net.load_state_dict(q_net.state_dict())

epsilon = max(0.05, epsilon * 0.97)

The NN takes the 4 dimensional cartpole state & outputs 2 Q-values & backpropagation minimizes:

$$(r + \gamma \max Q_{\text{target}}(s') - Q(s, a))^2$$

Performance vs Standard Q-learning:

- Standard Q-learning requires a discrete state space fails on Cart pole.
- DQN learns directly from continuous states & typically solves Cartpole within 200-300 episodes
- DQN also provides smoother and more stable learning.

3) Design an experiment to compare double DQN with vanilla DQN on a provided environment & Interpret the differences in their learning curves & stability.

Double DQN vs Vanilla DQN

- Environment: CartPole-v1
- Models compared: a) Vanilla DQN b) Double DQN

Both use: same neural network, replay buffer, batch size, optimizer, ϵ greedy schedule & training steps

Only difference : target calculation.

Vanilla DQN target :

with `torch.no_grad()` :

`target = r + gamma * target_net(s2).max(1, keepdim=True)[0] * (1 - done)`

Double DQN target :

with `torch.no_grad()` :

`a_max = online_net(s2).argmax(1, keepdim=True)`

`target = r + gamma * target_net(s2).gather(1, a_max) * (1 - done)`

Learning Curve:

DQN :-

- Learns quickly at first
- Shows spikes & drops
- Sometimes collapses after good performances

Double DQN:

- Slightly slower start
- Much smoother learning
- Higher & more stable final reward.

Interpretation:-

Double DQN provides more stable training and better long-term performances bcz it uses the online network to choose the action and the target network to evaluate it. This experiment shows that double DQN \rightarrow DQN.

4) Extend the Q learning agent to use a dueling network architecture. Analyze how this architecture improves the agent's policy learning.

A dueling network is an improvement and standard Q-networks, instead of predicting Q-values directly, it

splits the network into value and Advantage streams:

$$Q(s, a) = V(s) + A(s, a) - \max_a A(s, a)$$

Implementation:

```
import torch.nn as nn
import torch

class DuelingDQN(nn.Module):
    def __init__(self, state_dim, action_dim):
        super().__init__()
        self.shared = nn.Sequential(nn.Linear(state_dim,
                                                128),
                                    nn.ReLU(),)
        self.value = nn.Sequential(nn.Linear(128, 1))
        self.adv = nn.Sequential(nn.Linear(128, action_dim))
    def forward(self, x):
        h = self.shared(x)
        V = self.value(h)
        A = self.adv(h)
        return V + A - A.max(dim=1, keepdim=True)[0]
```

How it improves Policy learning:

- Learns State value Independently
- Advantage Stream Learns Action Differences
- Faster and more stable learning
- Better policy in Hard states

A dueling network improves Q-learning by separating state value and action advantage, resulting in:
faster policy learning.

5. Use the concepts of multi step learning & hierarchical learning propose and implement an improvement to a basic RL agent. Discuss the effects.

Improve a basic Q-learning agent by adding:

1. n-step learning and hierarchical choice

1. Add n-step buffer + return

```
n_step_buffer.append((s, a, r, s_next, done))
```

```
if len(n_step_buffer) == n or done:
```

```
    R = 0
```

```
    for i, (_, _, ri, _, di) in enumerate(n_step_buffer):
```

```
        R += (gamma ** i) * ri
```

```
        if di: break
```

```
    s0, a0, _, _, d0 = n_step_buffer[0]
```

```
    s_n = n_step_buffer[-1][3]
```

```
    replay_buffer.append((s0, a0, R, s_n, d0))
```

```
    n_step_buffer.pop()
```

```
    target = R + (gamma ** n) * max Q(s_n, n) * (1 - done)
```

Hierarchical option selection:

```
if steps_left == 0:
```

```
    option = random.choice([0, 1])
```

```
    steps_left = k
```

```
if option == 0:
```

```
    action = argmax Q(s)
```

```
else:
```

```
    action = random_action()
```

```
steps_left -= 1
```

n-step learning:-

Faster reward propagation \rightarrow quicker learning

Lower variance than 1-step TD \rightarrow more stable updates.

— hierarchical learning:-

High level decision ~~to~~ reduce action noise \rightarrow smoother behaviour.

Improves generalization to longer horizon tasks.