temi FOURCAST Specs

	Parameter	Values
Weight	Self weight	91.4kg
Mechanical	Robot Dimension	148H*50W*50D cm
	Lidar height (emitter)	23.8cm
	Hubwheel diameter	15cm
	Castor wheel diameter	7.5cm
Payload	Bottom tray max payload	12kg
	Bottom tray size	D54 x 40.5cm
	Middle tray max payload	10kg
	Middle tray size	D54 x 40.5cm
	Top tray max payload	D54 x 40.5cm
	Top tray size	8kg
	Top shelf max payload	2kg
	Top shelf size	D36cm
Mapping	Max map size	15000-20000m²
	No. of locations	1000
Camera Parameters	5MP	2592*1944
Floor-Conditions	Max Step climbing	0.5cm
	Max Slope angle	3°
	Max gap crossing	4cm

robo solutions

temi

THE PERSONAL ROBOT

	Parameter	Values
Movement	Max Linear speed	1m/s
	Spin Radius	0cm
	Location accuracy	<10cm
Display Parameters	Dimensions	38.6"
	Backlight Type	LED
	Resolution	1920*562
	Display Size (mm)	941(H) x 275.5(V)
	Brightness	300cd/m²
	Refresh Rate	60Hz
	Parameters for Advertisement Projection	Full Screen: 1920*540px Dual Screen Split: (960*540px) + (960*540px) Triple Screen Split: (540*540px) + (840*540px) + (540*540px)
Projection Parameters	Display Size (mm)	510*310mm
	Projection Distance	360-680mm
	Resolution	960x540
	Lumens	300 Lumens
	Parameters for Interactive Game Projection Area	960*540px
Sensing	Height obs detection range	12-150cm
	Ground obs detection range	2-150cm
	Min ground obs height	2cm
	Min Cliff detection height	2cm
	Lidar range	0-40m
Floor Touch Sensing Parameters	Resolution	Depth Resolution: 640x480@25 fps, 640x400@25fps, 320x240@30fps, @60fps, 320x200@30fps, @60fps, etc. RGB Resolution: 1280x800@30fps, 640x400@30fps, etc. Simulation Depth and RGB Output: 640x400 depth + 720p color@25fps

temi FOURCAST Specs

	Parameter	Values
HW Interface + Remote Access	CPU	RK3576, featuring quad-core Cortex-A72 and quad-core Cortex-A53, with a maximum clock frequency of up to 2.2GHz
	GPU	OpenGL ES 1.1, 2.0, and 3.2, OpenCL 2.0 and Vulkan 1.1
	NPU	NPU computing power up to 6 TOPS, supporting mixed operation of INT4/INT8/INT16/FP16/BF16/TF32
	OS	Android 14
	Memory	8+64GB
	WiFi/BT/SIM	Wifi 2.4GHz/5GHz, Bluetooth 5.0, Supports 4G
	Android USB Port	For connecting external USB flash drivers
	SDK	See guidebook
	WEB-Center	Temi Center
Home Base	External dimensions	278H*332W*232L mm
	Weight	3.6Kg
	Rated Input	AC100 ~ 240V 15A Max
	Rated Output	DC 29.4V 20A
Packaging	External Dimensions	112*104*75cm
	Packaging Weight	45Kg
	Gross Weight (Machine + Packaging)	136.4Kg
Storage Conditions	Environment	Indoor Environment
	Humidity Range	15-65%
	Recommended Humidity	<60%
	Temperature Range	0-45°C
	Recommended Temperature	25°C
	Sunlight	Avoid direct sunlight

robo solutions

temi

THE PERSONAL ROBOT

	Parameter	Values
Chassis Battery	External Dimension	80H*190W*200L mm
	Weight	3.5Kg
	Battery Life	4-5h
	Charging Time	5h
	Cell Type	Li-Ion
	Output Range	19-20.16V
	Capacity	20.8 Ah
	Charging Voltage	29.4V
	Lifespan	>500 charge cycles* *Maximum capacity drops to 70% or lower after 800 charge cycles
External Battery	External Dimension	68.5H*224W*423L mm
	Weight	5.6Kg
	Battery Life	4-5h
	Charging Time	5h
	Cell Type	Li-Ion
	Output Range	17.5-29.4V
	Capacity	45 Ah
	Charging Voltage	29.4V
	Lifespan	>500 charge cycles* *Maximum capacity drops to 70% or lower after 800 charge cycles