



UNIFOCUS
WORKFORCE MANAGEMENT

Integration API

Operations Modules – v1.5



TABLE OF CONTENTS

Summary	3
Assumptions	3
Security	3
API Requirements	4
1. Masters	4
2. Registering Service Requests	6
3. Register Multiple Service Requests.....	9
4. Search Service Request	9
5. Search Guest Service Requests	14
6. Search Multiple Service Requests	14
7. Get Attachments for Service Requests	14
8. Update/Close Service Requests	15
9. GuestLookUp.....	17
10. Update Baggage Tag for Reservation.....	18
11. Send Room Events.....	19
12. Send Multiple Room Events	20
13. Search Glitch Information	20
Error codes	31
Appendix	32

SUMMARY

The purpose of this document is to define the various methods by which an external system can:

1. Register jobs.
2. Send automation events.
3. Send Luggage Tags
4. Get Housekeeping status.
5. Get Glitch Information

Since the Unifocus suite handles all Guest requests and manages their workflow, it can also allow external systems to use its exposed HTTPS API to register service requests and complaints.

ASSUMPTIONS

1. External system has been provided with a list of service requests which the Unifocus Suite needs to handle.
2. In case the external system fails to get a response for a particular request due to any technical reason, then the system expects the external system to resubmit the request again. The number of retries should be configurable in the external system.
3. Both the systems will maintain the same location IDs (Unique Room numbers) for each location.
4. External system has been provided with a Property ID, Public Key and Private Key.
5. Base URL has been provided.

SECURITY

1. There will be one public key and one private key shared between the vendor and KC.
2. A Signature will be generated and will be sent as a header of request.
3. Signature Algorithm: - Public key + request method + encoded request URI + UNIX time
4. Create one string by concatenating Public Key, request method, encoded request URI & UNIX time.
5. Generate hash of above string by using private key and HMACSHA256 algorithm.
6. Send signature in header of request in the following format.
X-Knowcross-Access": "Public Key: Signature Base64 String: UNIX time"
7. A sample C# code is attached in Appendix.

API REQUIREMENTS

1. Masters

API allows the external system to fetch the master data.

URL: [/Master/GetAllPropertyMaster?PropertyId={propertyID}](#)

Method: Get

Header: "X-Knowcross-Access": "Generated Signature"

Response: [

```
{
  "Key": "4147_ENG",
  "Location": [
    {
      "Id": 107926,
      "Description": "0303 - Balcony",
      "LocationTypeCode": "M"
    },
    {
      "Id": 107966,
      "Description": "0303 - Bathroom",
      "LocationTypeCode": "M"
    }
  ],
  "CallCategories": [
    {
      "Id": 19523,
      "Description": "Ac-Engineering"
    },
    {
      "Id": 11956,
      "Description": "Air Conditioning - FM&E"
    }
  ],
  "CallDescriptions": [
    {
      "Id": 145984,
      "CategoryId": 12024,
      "Description": "(Ird) - Order",
      "Priority": 1,
```



```
        "ComplainType": 2,
        "IsDel": false
    },
    {
        "Id": 233906,
        "CategoryId": 19523,
        "Description": "Ac not working",
        "Priority": 3,
        "ComplainType": 2,
        "IsDel": false
    }
],

"ComplainTypes": [
    {
        "Id": 3,
        "Name": "Complaint"
    },
    {
        "Id": 4,
        "Name": "Maintenance"
    },
    {
        "Id": 1,
        "Name": "Query"
    },
    {
        "Id": 2,
        "Name": "Service Request"
    }
],
"PropertyID": 4147,
"LanguageCode": "ENG",
"LastUpdate": "2020-06-09T17:28:58.0057962+00:00",
"LastUpdate_String": "6/9/2020 5:28:58 PM +00:00"
}
]
```

Parameters	Descriptions
Property Masters	Array of Property Masters objects, each containing following
PropertyID	PropertyId for this master object, provided by Unifocus.
LanguageCode	All descriptions will be for this language
Location	Array of Locations objects, with following attributes
Id, Description	Unifocus Id of location & it's description (name)
LocationTypeCode	"M" (public location) or "R" (guest room)
CallCategories	Array of call categories, with following attributes
Id, Description	Unifocus Id of Call Categories & it's description (name)
CallDescriptions	Array of call Descriptions, with following attributes
Id, Description	Unifocus Id of Call descriptions & it's description (name)
CategoryId	Parent Call Category Id
Priority	Default Priority of the Job
ComplainType	Type of Complain
IsDel	Is Description deleted
ComplainTypes	Array of Complain Types available in the platform

2. Registering Service Requests

The Service request API allows the external system to submit their service requests to the system. The Unifocus suite doesn't have any limitation in terms of the number of services which are supported by this interface, as long as the service request is mapped in the system. No Special characters are allowed in the remarks parameter.

URL: </Complain/RegisterCall>

Method: Post

Header: "- X-Knowcross-Access": "Generated Signature"

Body: [



```
{
  "PropertyId": 0,
  "LocationId": 0,
  "CategoryId": 0,
  "CallDescriptionsId": 0,
  "Priority": 0,
  "IsGuestCall": true,
  "Remarks": "string",
  "Attachments": [
    {
      "FileName": "string",
      "Base64String": "string",
      "ApplicationId": 0
    }
  ],
  "Operation": 1,
  "CurrentStatus": "OPN"
  "ApplicationId": 0,
  "ClosedReasonCode": 0,
  "ReopenTime": "2020-06-09T21:39:40.118Z"
}
```

Parameter	Mandatory	Description
Complains	Y	Array of Complain Objects as defined below. Multiple Complains can be registered using the same request
PropertyId	Y	Property Id for which complain has to be registered
LocationId	Y	Location Id for which complain has to be registered
CategoryId	Y	Category Id of selected complain description
CallDescriptionsId	Y	Id of selected complain
Priority	Y	Priority of complain

		1-Normal 2-Urgent 3-Extra Urgent 4-Crisis
IsGuestCall	Y	Whether complain has to be registered for the guest at location
Remarks	N	Remarks for the call if needed, max length 1000 characters. No special characters allowed
Attachments	N	List of attachment objects, each attachment object is defined by FileName, a base64 representation of the image & a string identifying the source application. Per request, maximum size for attachment is 10Mb
Operation	Y	For Register, Operation = 1 For Register & close, Operation = 2 For Register & Park, Operation = 3
currentStatus	Y	For Register, currentStatus = OPN For register and immediate closure, currentStatus = CLS For register and park, currentStatus = PRK
ApplicationId	N	A string identifying the source application, provided by Unifocus
ClosedReasonCode	Mandatory id "Operation" value is not 1	Integer identifying reason when complain is to be parked (when service request needs to be handled later on as defined by 'ReopenTime')

ReopenTime	Mandatory id "Operation" value is 3	If complain has to be parked, this field defines its reopening time (UTC timestamp)
------------	-------------------------------------	---

Response: This is same as defined below in section 4 – Search Service Request

3. Register Multiple Service Requests

Multiple Service Requests can be generated using a single http call, as defined above, the request body takes an array of complain request objects.

4. Search Service Request

This Service request API allows the external system to fetch the status of their service request from the Unifocus Suite.

Master Data Reference

Please note that service-related master data such as call categories, call descriptions, and location IDs should be retrieved from /integrationapi/master/GetAllPropertyMaster endpoint. These values will be required to filter or interpret service request records correctly.

Request Parameters

The endpoint allows flexible filtering to support multiple scenarios, including filtering by status, priority, complaint ID, and other criteria. A sample request body is provided below. The corresponding status and priority code masters are listed in the request object table for reference. The maximum supported PageSize is 25. To retrieve additional records beyond this limit, increment the pageNumber value accordingly.

URL: </Complain/SearchComplain>

Method: Post

Header: "- X-Knowcross-Access": "Generated Signature"

Body: {
 "ComplainId": 0,
 "Properties": [
 0
],
 "StatusCode": "string",
 "Locations": [
 0
],
 "LoggedBy": [
 0
]
}



```
],  
  "ApplicationId": string,  
  "IsGuestCall": true,  
  "Priority": 1,  
  "PageNumber": 0,  
  "PageSize": 0,  
  "OrderBy": "string"  
}
```

Request Object:

Parameter	Mandatory	Description
ComplainId	N	Lookup a service request by its ComplainId
PropertyID	Y	Array of PropertyId in which the search has to be done
StatusCode	N	Search requests by StatusCodes: OPN: Open Jobs PRK: Parked Jobs USN : Unassigned Jobs SNL : Staff Not logged In Jobs CLS : Closed Jobs
Locations	N	List of LocationIds for which search has to be done
LoggedBy	N	Search by logger's Id
IsGuestCall	N	Filter if service request was registered for guest
Priority	N	Filter by Priority: 1-Normal 2-Urgent 3-Extra Urgent 4-Crisis
ApplicationId	N	Filter by source application
PageNumber	N	Set the page number which has to be fetched

PageSize	N	Set the page size of request
OrderBy	N	Order the result set by particular attribute: "ReportedAt", "LastUpdate", "DisplayCallNo asc", "DisplayCallNo desc", "Priority"

Response: {

```

    "TotalRecords": 1,
    "CurrentPage": 1,
    "Result": [
      {
        "ComplainId": 6069212,
        "DisplayCallNo": 132,
        "MRT": 20,
        "CurrentStatus": "OPN",
        "IsReset": false,
        "NoOfAttachments": 0,
        "LastActionTime": "2020-06-09T13:42:56.007Z",
        "ClosedAt": null,
        "CallDescriptionsId": 145931,
        "LocationId": 111426,
        "LocationTypeCode": "R",
        "IsGuestCall": false,
        "LoggedBy": 0,
        "LastUpdate": "2020-06-09T13:42:56.007Z",
        "CategoryId": 12017,
        "ComplainTypeId": 2,
        "ComplainTypeName": "Service Request",
        "IsRemarkAdded": true,
        "LastRemarks": "Job Triggered By Check-In",
        "PropertyId": 4147,
        "Priority": 1,
        "TotalResetTime": 0,
        "ParkReopenTime": null,
        "Attachments": [],

```

```

    "CalculatedFinishDate": "2020-06-09T14:02:56.007Z",
    "ApplicationId": null,
    "AssignToName": "abc27217 def27217",
    "CallDescription": "Room - Booking Request",
    "LocationName": "1001",
    "RegisteredAt": "2020-06-09T13:42:56.007Z"
  }
],
"HasError": false,
"Errors": null
}

```

Parameters	Descriptions
TotalRecords	Total number of records found
CurrentPage	Page number for current response
HasError	Are there any errors for current request
Errors	List of errors, if any
Result	List of Complains, each object has the following fields
ComplainId	Id for the complain
DisplayCallNo	Display number for the complain
MRT	Maximum Resolution Time as per complain description (in seconds)
CurrentStatus	Current status code of the complain, values can be : OPN, PRK, CLS, SNL, USN
IsReset	Was the service request reset
TotalResetTime	Duration by which the request was reset (in seconds)
NoOfAttachments	Number of attachments with the complain
LastActionTime	When was last action taken (UTC)



CallDescriptionsId	Description Id for the registered complain
ClosedAt	If CurrentStatus is CLS, then when was the complain closed.
LocationId	LocationId for the complain
LocationTypeCode	Type of location: Public or Guest Room
IsGuestCall	If complain was registered for a guest
LoggedBy	Id of the logger
LastUpdate	When was complain last updated (UTC)
CategoryId	Id for the description's category
ComplainTypeId	Type of complain
ComplainTypeName	Description of complain type
LastRemarks	Last remarks added to the complain
PropertyId	Property Id to which this complain is registered at
Priority	Priority of the complain
ParkReopenTime	If current status is PRK, then reopen time of the complain (UTC)
Attachments	List of attachments: Each attachment object has following attributes
ComplainId	ComplainId to which this attachment is associated with
CallRegAttachmentId	Id for the attachment, this will be used to fetch the actual attachment using API provided in section 2.7 (Get Attachments for Service Request)
FileName	Filename of the attachment (includes extension)
ApplicationId	A string identifying the source application, provided by Unifocus

IsDeleted	If attachment has been deleted
ApplicationId	A string identifying the source application, provided by Unifocus
LocationName	Description of the location where this complain was registered
AssignToName	Name of the staff to which this complain is assigned
RegisteredAt	When was the complain registered (UTC)

5. Search Guest Service Requests

Guest Service requests can be searched by setting the "IsGuestCall" flag to true in the request when searching for service requests (as defined in section 4 - Search Service Request)

6. Search Multiple Service Requests

Complain Search API request return a list of complains that match the filters provided in the search request.

7. Get Attachments for Service Requests

URL: </Complain/GetAttachmentComplain?CallRegAttachmentId={CallRegAttachmentId}>

Method: Get

Header: "- X-Knowcross-Access": "Generated Signature"

Response: {
 "ComplainId": 0,
 "FileName": "string",
 "Base64String": "string",
 "CallRegAttachmentId": 0,
 "IsDeleted": true,
 "ApplicationId": 0,
 }

Parameter	Description
Attachments	List of attachments: Each attachment object has following attributes
ComplainId	ComplainId to which this attachment is associated with

CallRegAttachmentId	Id for the attachment, this will be used to fetch the actual attachment using API provided in section 2.7 (Get Attachments for Service Request)
Base64String	Base64 representation of the attachment
FileName	Filename of the attachment (includes extension)
ApplicationId	A string identifying the source application, provided by Unifocus
IsDeleted	If attachment has been deleted

Alternatively, the below endpoint can be used to retrieve the attachments using the CallRegAttachmentId."

URL: </complain/GetComplainAttachmentStream?CallRegAttachmentId={CallRegAttachmentId}>

Method: Get

Header: "- X-Knowcross-Access": "Generated Signature"

Response : (attachment)

8. Update/Close Service Requests

URL: </Complain/UpdateComplain>

Method: Post

Header: "- X-Knowcross-Access": "Generated Signature"

Body: {
 "ComplainId": 0,
 "PropertyId": 0,
 "Operation": 2,
 "ClosedReasonCode": 0,
 "CurrentStatus": "CLS",
 "LastActionRemarks": "string",
 "ApplicationId": 0,
 }

Parameter	Mandatory	Description
-----------	-----------	-------------

ComplainId	Y	Id of the complain which has to be closed.
PropertyId	Y	Property Id to which this complain belongs to.
Operation	Y	For Closing a service request, Operation = 2 For Parking a service request, Operation = 3 For updating only the remarks of the service request, Operation = 7
ClosedReasonCode	Y	Code for closing a service request, provided by Unifocus.
CurrentStatus	Y	"CLS" = To close the service request. "PRK" = To park the service request. "OPN" = Just to update remarks while keeping the request opened.
Remarks	N	To update the main remarks when updating the complaint, max length 1000 characters. No special characters allowed.
LastActionRemarks	N	Any remarks to be added when closing/updating the complain, max length 1000 characters. No special characters allowed.
ApplicationId	N	A string identifying the source application, provided by Unifocus.

Sample request to park the service request:

```
{
  "ComplainId": 1315185,
  "PropertyId": 3038,
  "CurrentStatus": "PRK",
```



```
"Operation": 3,  
"ReopenTime": "2025-08-26T05:35:45.643Z",  
"ClosedReasonCode": 1910  
}
```

Sample request payload to update only the remarks of the service request:

```
{  
  "ComplainId": 1321754,  
  "PropertyId": 3038,  
  "CurrentStatus": "OPN",  
  "Operation": 7,  
  "Remarks": "TEST UPDATED REMARKS"  
}
```

Response: Response format will be same as Complain Search (as defined in section 4 - Search Service Requests)

9. GuestLookUp

API allows to verify the guest reservation.

URL: /Guest/GuestLookup

Method: Post

Header: "X-Knowcross-Access": "Generated Signature"

Body: {
 PropertyId: number, // mandatory
 ReservationStatus: number, // mandatory
 FirstName: string, // optional, minLength = 3
 LastName: string, // optional, minLength = 3
 LocationDescription: string, // optional, minLength = 3
 PMSReservationId: string// optional
}

Response:

```
{  
  
  HasError: false,  
  Errors: [{  
    ErrorCode: 0,  
    ErrorMessage: "string",  
  }],  
}
```

```
Result: [{
  PropertyId: number,
  GuestId: number,
  FullName: string,
  LocationDescription: string,
  LocationId: number,
  ReservationStatus: number,
  PMSReservationId: string,
  DepartureDate: "2020-12-14T10:07:47.484Z",
  ArrivalDate: "2020-12-14T10:07:47.484Z",
  Pax: number,
  VIPCode: string,
}],
}
```

10. Update Baggage Tag for Reservation

URL: [/Guest/UpdateBaggageTag](#)

Method: Post

Header: "- X-Knowcross-Access": "Generated Signature"

Body: {

```
PropertyId: number, // mandatory
PMSReservationId: string, // either pms reservationId or guestId is
required
GuestId: number, // either pms reservationId or guestId is required
BaggageTagValue: string // mandatory, added by vendor
}
```

Response: {

```
HasError: false,
Errors: [{
  ErrorCode: 0,
  ErrorMessage: "string",
}],
Result: "SUCCESS"
}
```

Request & Response objects

Parameters	Descriptions
PropertyID	Property Id for guest

GuestID	Guest profile ID received from PMS
FullName	Full name of guest
FirstName	First name of guest
LastName	Last name of guest
LocationDescription	Room number assigned to guest
LocationID	Unique id for the room number
ReservationStatus	Reservation status for the guest 1- Arrival 2- In-house 3- Checked out
PMSReservationID	PMS reservation id for guest
DepartureDate	Departure date for guest
ArrivalDate	Arrival date for guest
PAX	Number of people
VIPCode	VIP level of guest
BaggageTagValue	Baggage tag issued for guest

11. Send Room Events

URL: </Automation/PublishEvent>

Method: Post

Header: "- X-Knowcross-Access": "Generated Signature"

Body: {
 "Events": [
 {
 "PropertyId": 0,
 "IntegrationId": 0,
 "EventType": "string",
 "EventState": true,
 "LocationId": "string",
 "EventTimeStamp": "2021-04-30T11:38:11.036Z"
 }
]
}

Parameter	Mandatory	Description
PropertyId	Y	Property Id to which this complain belongs to
IntegrationID	N	Integration id provided by Unifocus
EventType	Y	DND or MUR
EventState	Y	1/true or 0/false shall be sent for DND/MUR on and off respectively
LocationId or Location	Y	LocationId or actual Location for the event
EventTimeStamp	Y	Time stamp at which event was generated.

12. Send Multiple Room Events

Multiple room events can be sent using a single call, as defined above, the request body takes an array of request object.

13. Search for Glitch Information

This endpoint allows external system to retrieve glitch-related data stored in the Unifocus platform for integration purposes. Access control remains the same as existing API endpoints, where tokens and signatures must be generated prior to calling the API.

Master Data Reference

Please note that glitch-related master data such as glitch categories, glitch descriptions, and location IDs should be retrieved from the existing `/integrationapi/master/GetAllPropertyMaster` endpoint. These values will be required to filter or interpret glitch records correctly.

Request Parameters

The endpoint supports flexible filtering based on multiple use cases. Below are sample request bodies for different scenarios. The maximum `PageSize` is 25, and records beyond this limit should be fetched by incrementing `PageNumber`.

URL: `/integrationapi/glitch/Glitch_Search`

Method: POST

Header: `"- X-Knowcross-Access": "Generated Signature"`

Request Body samples:

Scenario	Sample Request Body
Default with Page Size and Page Number	{ "PropertyId": 4124, "PageSize": 25, "PageNumber": 1 }
Only Open Glitches	{ "PropertyId": 4124, "PageSize": 25, "PageNumber": 1, "Status": 1 }
Only Closed Glitches	{ "PropertyId": 4124, "PageSize": 25, "PageNumber": 1, "Status": 0 }
With Unifocus Glitch Number	{ "PropertyId": 4124, "PageSize": 25, "PageNumber": 1, "GlitchCallNo": 5 }
With Glitch Number and Status	{ "PropertyId": 4124, "Status": 0, "PageSize": 25, "PageNumber": 1, "GlitchCallNo": 5 }
With PMS Profile ID	{ "PropertyId": 4124, "PMSProfileId": "60290", "PageSize": 25, "PageNumber": 1 }
With Investigations	{ "PropertyId": 4124, "HasInvestigation": true, "PageSize": 25, }



	<pre>"PageNumber": 1 }</pre>
With Recovery	<pre>{ "PropertyId": 4124, "HasRecovery": true, "PageSize": 25, "PageNumber": 1 }</pre>
With Both Investigation and Recovery	<pre>{ "PropertyId": 4124, "HasInvestigation": true, "HasRecovery": true, "PageSize": 25, "PageNumber": 1 }</pre>
By Departments (Multiple Supported)	<pre>{ "PropertyId": 4124, "Departments": [12031,11448], "PageSize": 25, "PageNumber": 1 }</pre>
By Glitch Descriptions (Multiple Supported)	<pre>{ "PropertyId": 4124, "GlitchDescriptions": [123814,123821], "PageSize": 25, "PageNumber": 1 }</pre>
By Glitch Categories (Multiple Supported)	<pre>{ "PropertyId": 4124, "GlitchCategories": [6159,6166], "PageSize": 25, "PageNumber": 1 }</pre>
By Guest Name Search	<pre>{ "PropertyId": 4124, "GuestName": "HARDCODED SLSH", "PageSize": 25, "PageNumber": 1 }</pre>
With Attachments	<pre>{ "PropertyId": 4124, "HasAttachment": true, "PageSize": 25, }</pre>

	"PageNumber": 1 }
--	----------------------

Request objects:

Request Parameter	Description
PropertyId	Unique identifier for the property. Mandatory for all requests.
PageSize	Number of records per page. Maximum value per page is 25.
PageNumber	Page number for paginated results. Used to fetch records beyond the first page.
Status	Filter glitches by status. 1 = Open, 0 = Closed.
GlitchCallNo	Glitch display number as visible on the Unifocus platform frontend.
PMSProfileId	Profile ID of the guest from PMS. Used to filter glitches linked to a specific guest.
HasInvestigation	Boolean flag. If true, retrieves glitches with investigations recorded.
HasRecovery	Boolean flag. If true, retrieves glitches with recovery recorded.
Departments	Array of department IDs to filter glitches assigned to specific departments.
GlitchDescriptions	Array of description IDs to filter glitches with specific descriptions.
GlitchCategories	Array of category IDs to filter glitches by specific categories.
GuestName	Guest name or partial name string for search. Supports partial matches.
HasAttachment	Boolean flag. If true, retrieves glitches that have attachments linked.

Response:

Below is a sample response for the Glitch Information endpoint. Key fields include:

- **GlitchId**: Unique identifier for the glitch record.
- **GlitchCallNo**: Display number for the glitch as shown in Unifocus frontend.
- **PMSProfileId**: Guest profile ID from PMS linked to the glitch.
- **Actions/GlitchActionType**: 'INV' represents investigation, 'REC' represents recovery.
- **AuditLog**: Tracks all investigation, recovery, and attachment activities.
- **GuestInfo**: Contains guest details such as name, profile ID, and contact information.



UNIFOCUS

```
{
  "TotalRecords": 1,
  "CurrentPage": 1,
  "Result": [
    {
      "PropertyId": 4124,
      "GlitchId": 156108,
      "GlitchRegistrationType": 1,
      "GlitchStaffId": null,
      "GlitchGuestId": 26882534,
      "Details": "",
      "IsOpen": true,
      "GuestTemperamentId": null,
      "LogTime": "2025-09-08T03:39:12.07Z",
      "LoggedBy": 25242,
      "GlitchIncidentDt": "2025-09-08T03:39:05.843Z",
      "GlitchCallNo": 18,
      "UpdatedById": 25242,
      "IsDel": false,
      "LastUpdate": "2025-09-08T03:55:21.437Z",
      "IncidentLocationId": 246023,
      "DepartmentId": 12031,
      "DescriptionId": 123814,
      "TritonReservationId": 15927602,
      "ClosedDate": null,
      "AttachmentCount": 1,
      "IsEverReOpen": false,
      "IsEverClosed": false,
      "IsEverEdited": false,
      "RecoveryCount": 1,
      "InvestigationCount": 1,
      "NoOfGlitches": 10,
      "TotalRecoveryCost": 1,
      "IsAudited": false,
      "CategoryId": 6164,
      "AverageGSR": null,
      "Version": 1403708572,
      "NoOfStays": 0,
      "CheckInDate": "2025-09-01T18:53:54Z",
      "CheckOutDate": "2025-09-10T19:53:54Z",
      "LocationId": 246023,
      "RoomRate": 0,
      "Company": null,
    }
  ]
}
```




UNIFOCUS

```
"Booking": null,
"PMSProfileId": "60291",
"GlitchStaff": [],
"Attachments": [
  {
    "GlitchId": 156108,
    "FileName": "Media.jpg",
    "Base64String": null,
    "GlitchAttachmentId": 18913,
    "IsDeleted": false,
    "AttachmentDate": "2025-09-07T22:03:13.807Z",
    "AddedBy": 25242
  }
],
"Actions": [
  {
    "GlitchActionId": 361266,
    "GlitchId": 156108,
    "GlitchActionType": "INV",
    "Remarks": "test",
    "ReasonOrRecoveryId": 0,
    "AddedBy": 25242,
    "AddedOn": "2025-09-08T03:52:52.42Z",
    "IsDel": false,
    "IsEdit": false,
    "RecoveryCost": null,
    "AttachCount": 0
  },
  {
    "GlitchActionId": 361267,
    "GlitchId": 156108,
    "GlitchActionType": "REC",
    "Remarks": "TEST",
    "ReasonOrRecoveryId": 1304,
    "AddedBy": 25242,
    "AddedOn": "2025-09-08T03:55:21.427Z",
    "IsDel": false,
    "IsEdit": false,
    "RecoveryCost": 1,
    "AttachCount": 0
  }
],
"AuditLog": [
```



UNIFOCUS

```
{
  "GlitchId": 156108,
  "ColumnName": "Investigation details added",
  "OldValue": null,
  "NewValue": "Remarks: test",
  "Action": "I",
  "ActionTimeStamp": "2025-09-08T03:52:52.427Z",
  "LoggedBy": 25242,
  "Remarks": null
},
{
  "GlitchId": 156108,
  "ColumnName": "Recovery details added",
  "OldValue": null,
  "NewValue": "Recovery option: Airport Transfer. remarks: TEST",
  "Action": "I",
  "ActionTimeStamp": "2025-09-08T03:55:21.43Z",
  "LoggedBy": 25242,
  "Remarks": null
},
{
  "GlitchId": 156108,
  "ColumnName": "Glitch Attachment",
  "OldValue": "",
  "NewValue": "Media.jpg",
  "Action": "U",
  "ActionTimeStamp": "2025-09-08T05:03:13.823Z",
  "LoggedBy": 25242,
  "Remarks": "Glitch Attachment Added"
}
],
"GuestInfo": {
  "GlitchGuestId": 26882534,
  "Title": "Mr",
  "FName": "Test MIDDLE-NAME-HARDCODED",
  "LName": "SLS",
  "FullName": "Mr Test MIDDLE-NAME-HARDCODED SLS",
  "MobileNumber": null,
  "HomeNumber": null,
  "Address": null,
  "Email": null,
  "Vip": null,
  "Lang": ""
}
```

```

    }
  }
],
"HasError": false,
"Errors": null
}

```

Response parameters:

Response Parameter	Description
GlitchId	Unique identifier generated by Unifocus for each glitch record.
GlitchCallNo	Glitch display number generated by Unifocus and visible on the frontend.
PMSProfileId	Profile ID of the guest from PMS linked to the glitch.
Actions/GlitchActionType	Type of action taken on the glitch. 'INV' = Investigation, 'REC' = Recovery.
AuditLog	Tracks investigation, recovery, and other actions with detailed logs.
GuestInfo	It contains guest details such as name and contact information.
Departments	DepartmentId of department linked to the glitch.
GlitchDescriptions	DescriptionID of the glitch description associated with the record.
GlitchCategories	CategoryID assigned to the glitch for classification.

Comprehensive Glitch Response Schema:

The following table enumerates all fields present in the sample response payload, using dot-notation for nested objects and [] to indicate array items. Descriptions are brief and indicative.

Response Field (dot path)	Type	Brief Description
TotalRecords	int	Numeric representation of total records.
CurrentPage	int	Current page information.
Result[].PropertyId	int	Unique identifier for the property.
Result[].GlitchId	int	Unique identifier generated by Unifocus for each glitch record.
Result[].GlitchRegistrationType	int	1= In House Guest Glitch



		2= Checked-Out Guest Glitch 3= Pre-Arrival Guest Glitch 5= Staff Glitch 0= Visitor Guest Glitch
Result[].GlitchStaffId	int	Unique identifier as StaffId of hotel staff if glitch is registered under GlitchRegistrationType registrationtype=5.
Result[].GlitchGuestId	int	Unique identifier generated by Unifocus system for each guest profile.
Result[].Details	str	Remarks entered while registering glitch.
Result[].IsOpen	bool	Boolean flag to identify the glitch's current status (open or close).
Result[].GuestTemperamentId	NoneType	Unique identifier to capture the guest's temperament.
Result[].LogTime	str	Date/time stamp.
Result[].LoggedBy	int	StaffID of the staff who registered the glitch.
Result[].GlitchIncidentDt	str	Date/time stamp of the incident date.
Result[].GlitchCallNo	int	Glitch display number generated by Unifocus and visible on the frontend
Result[].UpdatedById	int	StaffID of the staff who updated the glitch.
Result[].IsDel	bool	Boolean flag to state the deletion status of glitch.
Result[].LastUpdate	str	Date/time stamp according to the last changes made.
Result[].IncidentLocationId	int	Location Id of the incident location for which glitch is registered.
Result[].DepartmentId	int	DepartmentID linked to the glitch

Result[].DescriptionId	int	DescriptionID of the glitch description associated with the record.
Result[].TTNReservationId	int	Unique identifier of guest's reservation generated by Unifocus.
Result[].ClosedDate	NoneType	Date/time stamp when the glitch is marked as closed.
Result[].AttachmentCount	int	Attachment/file count.
Result[].IsEverReOpen	bool	Boolean flag to represent if glitch was ever re-opened.
Result[].IsEverClosed	bool	Boolean flag to represent if glitch was ever closed.
Result[].IsEverEdited	bool	Boolean flag to represent if glitch was ever edited.
Result[].RecoveryCount	int	Recovery action count.
Result[].InvestigationCount	int	Investigation action count.
Result[].NoOfGlitches	int	Total number of glitches recorded against the selected guest.
Result[].TotalRecoveryCost	int	Recovery cost in Numeric amount or value.
Result[].IsAudited	bool	Boolean flag to identify if audit happened.
Result[].CategoryId	int	CategoryID of the glitch category associated with the record.
Result[].Version	int	Versioning information
Result[].NoOfStays	int	Integer value.
Result[].CheckInDate	str	Check-in Date/time stamp.
Result[].CheckOutDate	str	Check-out Date/time stamp.
Result[].LocationId	int	Location Id of the location for which glitch is registered.
Result[].RoomRate	int	Room rate information, if available.
Result[].Company	str	Company information, if available.
Result[].Booking	str	Booking information, if available.



Result[].PMSProfileId	str	Profile ID of the guest from PMS linked to the glitch.
Result[].GlitchStaff[]	Array	List of staff tagged in the glitch.
Result[].Attachments[].GlitchId	int	Unique identifier generated by Unifocus for each glitch record.
Result[].Attachments[].FileName	str	File name of attachment
Result[].Attachments[].Base64String	NoneType	Null/empty value.
Result[].Attachments[].GlitchAttachmentId	int	Attachment Id
Result[].Attachments[].IsDeleted	bool	Boolean flag to state the attachment status.
Result[].Attachments[].AttachmentDate	str	Attachment's Date/time stamp.
Result[].Attachments[].AddedBy	int	StaffId who added the attachment.
Result[].Actions[].GlitchActionId	int	Unique identifier to record the action against Investigations and recovery.
Result[].Actions[].GlitchId	int	Unique identifier generated by Unifocus for each glitch record.
Result[].Actions[].GlitchActionType	str	Type/category of action. INV for investigation and REC for recovery.
Result[].Actions[].Remarks	str	Free-text notes.
Result[].Actions[].ReasonOrRecoveryId	int	Reason or recovery ID.
Result[].Actions[].AddedBy	int	StaffId who performed the recovery actions.
Result[].Actions[].AddedOn	str	Date/time stamp when the recovery actioned.
Result[].Actions[].IsDel	bool	Boolean flag to state the recovery status.
Result[].Actions[].IsEdit	bool	Boolean flag to state the attachment status.
Result[].Actions[].RecoveryCost	int	Recovery cost.
Result[].Actions[].AttachCount	int	Attachment count.
Result[].AuditLog[].GlitchId	int	Unique identifier generated by Unifocus for each glitch record.
Result[].AuditLog[].ColumnName	str	Action name.

Result[].AuditLog[].OldValue	str	Old value against that action.
Result[].AuditLog[].NewValue	str	New value against that action.
Result[].AuditLog[].Action	str	Action type
Result[].AuditLog[].ActionTimeStamp	str	Date/time stamp of action.
Result[].AuditLog[].LoggedBy	int	StaffId who added actioned.
Result[].AuditLog[].Remarks	NoneType	Free-text notes.
Result[].GuestInfo.GlitchGuestId	int	Unique identifier generated by Unifocus for each glitch record.
Result[].GuestInfo.Title	str	Guest's Title
Result[].GuestInfo.FName	str	Guest's First Name
Result[].GuestInfo.LName	str	Guest's Last Name
Result[].GuestInfo.FullName	str	Guest's Full Name
Result[].GuestInfo.MobileNumber	str	Contact info, if any.
Result[].GuestInfo.HomeNumber	str	Contact info, if any.
Result[].GuestInfo.Address	str	Contact info, if any.
Result[].GuestInfo.Email	str	Email address, if any.
Result[].GuestInfo.Vip	str	VIP Code
Result[].GuestInfo.Lang	str	Language Code
HasError	bool	Boolean flag states if the response has error.
Errors	str	Displays error text, if any.

Error codes

Error codes linked with Complain (Service request) Endpoints:

The list below defines the list of tags that can be received in case any of the parameter is invalid or not sent in the request.

Error Tag	Description
ERR_NO_ERROR	Unknown Error
ERR_INVALID_USER_TOKEN	Invalid User Token
ERR_ACCESS_PROPERTY_DENIED	Token not valid for the property
ERR_NOT_AUTHORIZED	Request not authorized
PROPERTY_INTEGRATION_NO_LICENSES_OR_LICENSES_EXPIRED	Integration License Expired
PROPERTY_NO_LICENSES_OR_LICENSES_EXPIRED	Property License Expired

ERR_NOT_FOUND	Not found
ERR_INVALID_REQUEST	Invalid Request
PROPERTY_REQUIRED	Property Required
ERR_SERVER_UNKNOWN_ERR	Unknown Server Error
ERR_GENERIC_ERROR	Validation Error
ERR_INVALID_USERNAME_PASSWORD	Invalid username/password
ERR_INVALID_RESSTATUS	Invalid Reservation Status
ERR_COMPLAIN_INVALID_PRIORITY	Invalid Job Priority
ERR_SELECT_PROPERTY	Property id Missing
ERR_SELECT_CATEGORY	Call/Job Category Missing
ERR_SELECT_DESCR	Call/Job Description Missing
ERR_SELECT_CLOSING_REASON	Invalid Close Reason
ERR_SELECT_PARKING_REASON	Invalid Park Reason
ERR_REQ_REOPEN_TIME_FOR_PARKED_CALL	Reopen Time Missing
ERR_REOPEN_DATE_GEATER_THAN_CURRENT_DATE	Invalid Reopen Date/Time
ERR_COMPLAIN_ID_REQUIRED	Complain Id Missing
ERR_ENTER_REMARKS	Remarks Missing
ERR_INVALID_COMPLAIN_REQUEST	Invalid Complain id
ERR_CALL_ALREADY_CLOSED	Call/Job already closed
ERR_CANNOT_PARK_CLOSED_CALL	Cannot park closed call/job.
ERR_CANNOT_CLOSE_SNL_JOB	Cannot close SNL call/job
ERR_CALL_STATUS_REQUIRED	Invalid Call/Job status
ERR_REMARK_LEN_1000	Invalid Remarks length
ERR_INVALID_LOCATION	Invalid Location
ERR_INVALID_CATEGORY	Invalid call/job category
ERR_INVALID_CALLDESCRIPTION	Invalid call/job description
ERR_INVALID_REASON	Invalid Reason

Appendix

Sample C# Code for Signature generation:


```
string apiBaseAddress = "https://integrationapi.knowcross.com/";  
var request = apiBaseAddress;  
string requestUri = System.Web.HttpUtility.UrlEncode(request.RequestUri.AbsoluteUri.ToLower());  
string requestHttpMethod = request.Method.Method;
```

```
//Calculate UNIX time
```

```
DateTime epochStart = new DateTime(1970, 01, 01, 0, 0, 0, 0, DateTimeKind.Utc);  
TimeSpan timeSpan = DateTime.UtcNow - epochStart;  
string requestTimeStamp = Convert.ToUInt64(timeSpan.TotalSeconds).ToString();  
string signatureRawData = String.Format("{0}:{1}{2}{3}", APIPublicKey, requestHttpMethod,  
requestUri, requestTimeStamp);
```

```
var secretKeyByteArray = PrivateKey.ToByteArray();
```

```
byte[] signature = Encoding.UTF8.GetBytes(signatureRawData);
```

```
using (HMACSHA256 hmac = new HMACSHA256(secretKeyByteArray))
```

```
{
```

```
    byte[] signatureBytes = hmac.ComputeHash(signature);  
    string requestSignatureBase64String = Convert.ToBase64String(signatureBytes);  
    var headrVal = string.Format("{0}:{1}:{2}", APIPublicKey, requestSignatureBase64String,  
requestTimeStamp);
```

```
    request.Headers.Add("X-Knowcross-Access", headrVal);  
    request.Headers.Add("X-Knowcross-ClientID", APIPublicKey);
```

```
}
```

```
ServicePointManager.Expect100Continue = true;
```

```
ServicePointManager.SecurityProtocol = SecurityProtocolType.Tls
```

```
    | SecurityProtocolType.Tls11
```

```
    | SecurityProtocolType.Tls12
```

```
    | SecurityProtocolType.Ssl3;
```

```
// Call API
```

```
response = await base.SendAsync(request, cancellationToken);  
return response;
```

Note: In this document call/job/complain are interchangeably used at different places due to code structure but it denotes the same thing.